WorkForce Enterprise AM-C6000

With the smallest footprint in its class, this more sustainable MFP offers the perfect solution for all your business printing needs.

The WorkForce Enterprise AM-C6000 combines fast performance with low energy consumption. Made with the modern office in mind, the small footprint and modular design allow you to build your device to your exact requirements. And as if that wasn't enough, the innovative technology makes installation and maintenance easy and stress free.

Reliable and improved sustainability

With a simpler, shorter paper path, paper jams can be removed more easily, and the finisher connectivity is improved. This means that service downtimes can be reduced. Through fewer consumables and supplies, it also produces less waste. With low power consumption, the overall environmental impact of printing is cut dramatically.

Efficient maintenance

Fewer replacement parts keep user intervention to a minimum, making day-today maintenance fast and efficient.

Heat-Free Technology

Epson Heat-Free Precision Core Technology requires no heat to warm up when it is switched on or awoken from sleep, which significantly reduces energy consumption. This allows Epson's Heat-Free inkjets to deliver an exceptional fast FPOT compared to laser technology.

Advanced software solution compatibility

A variety of software solutions can be integrated into existing IT infrastructure to improve efficiency. This includes Epson Remote Services (ERS), which offers cloud-based device monitoring and management system that delivers advanced remote diagnostics for Epson business products.

DATASHEET / BROCHURE



KEY FEATURES

High reliability

Simple mechanism for environments where downtime is not an option

- More sustainable Lower power consumption saves energy thanks to Heat-Free technology
- Small footprint Amongst the lowest footprint in its class
- Reduced downtime Simpler, shorter paper path for easier paper jam removal
- Solution compatibility A wide variety of integrated software solutions



PRODUCT SPECIFICATIONS

Maximum Copy Size

A3

TECHNOLOGY	
Printing Method	PrecisionCore™ Micro TFP printhead
Nozzle Configuration	7,230 Nozzles Black, 7,230 Nozzles per Color
Minimum Droplet Size	3.8 pl, With Variable-Sized Droplet Technology
Ink Technology	DURABrite™ Pro
Category	Office Workgroup, Office Departmental
All-in-One Functions	Print, Scan, Copy
PRINT	
Number of colours	4 colour
First Page Out	Monochrome 4.5 Seconds, Colour 4.5 Seconds
-	4 60 pages/min Monochrome, 60 pages/min Colour
Duplex Printing Speed	60 A4 Pages/min Monochrome, 60 A4 Pages/min Colour
ISO/IEC 24734	
Printing Resolution	600 x 2,400 DPI
Recommended Duty Cycle	8,500 - 60,000 pages per month
Colours	Black [Pigment], Cyan [Pigment], Yellow [Pigment], Magenta [Pigment]
Print from	PC, MAC, Cloud, Direct USB, Mobile Device (WiFi Direct)
SCAN	N .
Double-sided scanning	Yes
Scanning Speed	60 ipm (Monochrome, Single-sided, ADF) * Scanning in accordance with ISO/IEC 17991; 60
	ipm (Colour, Single-sided, ADF) * Scanning in accordance with ISO/IEC 17991; 120 ipm (
	Monochrome, Double-sided, ADF) * Scanning in accordance with ISO/IEC 17991; 120 ipm (
	Colour, Double-sided, ADF) * Scanning in accordance with ISO/IEC 17991; 0.4 msec/line (
	Colour, 300 dpi, Flatbed); 0.6 msec/line (Colour, 600 dpi, Flatbed);
Optical Resolution	600 DPI x 1,200 DPI (Horizontal x Vertical)
Optical Resolution (ADF)	600 DPI x 600 DPI (Horizontal x Vertical)
Advanced document	Scan to Email, Scan to FTP, Scan to Network folders, Scan to USB, Computer (Epson
integration	Document Capture Pro)
Maximum scan size	297 mm x 431 mm
Output formats	BMP, JPEG, TIFF, multi-TIFF, PDF, searchable PDF, PDF/A, PNG, Secured PDF
Scanner type	Contact image sensor (CIS)
FAX	
Type of fax	Walk-up black and white and colour fax capability
Fax Transmission Speed	Up to 33.6kbps / Approx. 3 sec/page
Fax speed dials (max)	2,000 names and numbers
Page memory	Up to 550 pages/ 6MB (ITU-T No. 1 chart)
Fax Functions	PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Speed Dial, Fax to Folder, Address
	Book, Fax Preview, Polling Reception
СОРҮ	
Copy resolution (dpi)	600 x 600
Reduction / Enlargement	25 % - 400 %
Maximum number of copies	2,000

WorkForce Enterprise AM-C6000

WHAT'S IN THE BOX

- Information sheet
- Power cable
- User guide
- Initialization Ink Supply Units



PRODUCT SPECIFICATIONS

WorkForce Enterprise AM-C6000

CONNECTIVITY	
Network Printing Protocols	LPR, FTP, IPP, LPD, Port 2501, Port 9100, WSD, IPSec, WSD-Print, IPPS, IS, Bonjour/Airprint,
	SMB 1.0, SMB 2.0, SMB 3.0
Network Management	SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping, SMTP,
Protocols	LLMNR, POP3, IPSec, IEEE 802.1X, ARP, GARP, EAP, ICMP, IGMP, DNS-SD, HTTPS, XMPP,
	SMTPS, LDAP, LDAPS, SNMP 1.0, SNMP 2.0c, SNMP 3.0, SNMP Trap
Network Scanning Protocols	WSD-Scan, FTP, SMB 1.0, SMB 2.0, SMB 3.0
Interfaces	Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T), USB 2.0-A, Wireless LAN IEEE
	802.11a/b/g/n/ac (optional), USB 3.2 Gen 1x1
WLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA2 PSK (AES), WPA2 Enterprise (AES), WPA3-
	SAE(AES)
Network Protocol	TCP, UDP, HTTP, HTTPS, IPv4, IPv6, IPSEC, SSL/TLS
PAPER / MEDIA HANDLING	
Paper Formats	A3 (29.7x42.0 cm), A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), B6, B5, B4, Letter, Executive, C5
	(Envelope), User defined, C4 (Envelope), DL (Envelope), No. 10 (Envelope), C6 (Envelope)
Automatic Document Feed	150 pages
Compatible Paper Weight	52 g/m² - 300 g/m²
Duplex	Yes (A4/A3, plain paper)
Output Tray Capacity	500 Sheets
Paper Tray Capacity	1,150 Sheets Standard, 5,150 Sheets Maximum
Standard paper tray(s)	2 x 500-Sheet paper tray
Optional paper tray(s)	2 x 500-Sheet paper tray, Cabinet
Maximum paper input	5,150
Number of paper trays	2
PAPER FEED MPT	
Paper Input Name	MPT
Paper Formats	A3, A4, A5, B4, B5, B6, C4 (Envelope), C5 (Envelope), DL (Envelope), No. 10 (Envelope), Letter EXE
Custom sizes	EXE Min 55x 140 mm to Max 297x 1,200 mm
Compatible paper weight	52 g/m ² - 300 g/m ²
Paper Capacity 1	150 Sheets of Plain Paper
Paper Capacity 2	10 Envelopes
PAPER FEED C1	
Paper Input Name	C1
Paper Formats	A3, A4, A5, B4, B5, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope), No. 10
	(Envelope), Letter
Custom sizes	Min 85x 140 mm to Max 297x 431.8 mm
Compatible paper weight	52 g/m ² - 300 g/m ²
Paper Capacity 1	500 Sheets of Plain Paper
Paper Capacity 2	150 Postcards
PAPER FEED C2-C4	
Paper Input Name	C2-C4
Paper Formats	A3, A4, A5, B4, B5, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope), No. 10
	(Envelope), Letter
Custom sizes	Min 85x 140 mm to Max 297x 431.8 mm
Compatible paper weight	52 g/m² - 300 g/m²
Paper Capacity 1	500 Sheets of Plain Paper
Paper Capacity 2	150 Postcards
PAPER FEED DUPLEX	
Paper Input Name	Duplex
Custom sizes	Min 139.7x 182 mm to Max 297x 431.8 mm
Compatible paper weight	52 g/m ² - 250 g/m ²
sempationo paper weight	- g g/11



PRODUCT SPECIFICATIONS

WorkForce Enterprise AM-C6000

PAPER FEED LCT			
Paper Input Name	LCT		
Paper Formats	A4, B5, Letter		
Compatible paper weight	60 g/m² - 160 g/m² 3,000 Sheets of Plain Paper		
Paper Capacity 1			
GENERAL			
Energy Use	115 Watt (standalone copying, ISO/IEC 24712 pattern), 1 Watt (sleep mode), 46 Watt (Ready), 0.1 Watt (Power off), TEC 0.25 kWh/week		
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz		
Product dimensions	555 x 620 x 1,214 mm (Width x Depth x Height)		
Product weight	124.3 kg		
Compatible Operating	Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.9.5 or later, Windows		
Systems	10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Server 2012 R2, Windows Server 2016, macOS 11 or later		
Sound Power	Operation: 7.2 B (A)		
Noise	Operation: 57 dB (A)		
Mobile and Cloud printing	Apple AirPrint, Mopria, Epson Smart Panel App, Epson Connect (Email Print, Remote Print		
services	Driver)		
Power supply	100V, 220V, 240V		
Optional extras	Hard Drive, Cover Plus warranty extensions, Wi-Fi unit		
ADDITIONAL FEATURES			
Memory	8,192 MB		
Features	Touchscreen, Direct Print, Direct print from USB, Nozzle Verification Technology		
Panel	Type: Color, Touchscreen, Diagonal: 25.7 cm		
Security Functions	Limit access function with Epson Web Config, Secure confidential printing with PIN code release, IEEE802.1x, Panel Admin Mode		
HDD	320 GB Encrypted AES-256		
OTHER FEATURES			
Emulations	PCL5c, PCL6, PostScript 3, PDF 1.7, ESC/P-R, PCL5e, ESC/Page, ESC/Page-Colour		
Optional Software & Solutions	Epson Device Admin, Epson Net Config, Epson Print Admin, Epson Print Admin Serverless		
Security	TLS, TLS V1.1, TLS V1.2, TLS V1.3, SSL, SNMP V3, IPSec, Document Encryption, Data storage		



SUPPLIES

- Maintenance Box (AM-C4000/5000/6000)
- WorkForce Enterprise AM-C5000/6000 Black Ink
- WorkForce Enterprise AM-C5000/6000 Cyan Ink
- WorkForce Enterprise AM-C5000/6000 Magenta Ink
- WorkForce Enterprise AM-C5000/6000 Yellow Ink

OPTIONAL ACCESSORIES

- Authentication Device Table-P1 C12C937381
- EpsonNet 10/100/1000Base Tx Int C12C934471
- Expansion Board-P1 (OCR unit) C12C936801
- HDD-P1
- C12C936791
- Super G3/G3 Fax Board C12C934491
- Wireless LAN Interface-P1 (2.4GHz) C12C937011
- Wireless LAN Interface-P1 (5GHz) C12C936861

LOGISTICS INFORMATION

SKU	C11CJ91401
EAN code	8715946705712
Country of Origin	Indonesia

WorkForce Enterprise AM-C6000

INK YIELD DATA

C12C937181

C13T08G100 50,000

C13T08G200 30,000

C13T08G300 30,000

C13T08G400 30,000

()

()

()

()

50,000 pages* 30,000 pages*

Approx. page yield based on ISO/IEC 24711/24712 or ISO/ IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit http://www.epson.eu/pageyield

1. - Approx. page yield with the AM C6000. Actual yield will vary depending on images printed and usage conditions. For more information visit www.epson.eu/pageyield.

2. - Fax optional in certain territories at an additional

cost. Please contact your local Epson office for more

3. - Approx. based on internal testing; may vary depending

on the number of copies selected, the output environment, as well as the settings for size, orientation, position of

information.

more information.

* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

4. - Wireless optional in certain territories at an Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway additional cost. Please contact your local Epson office for +47 67 11 37 00

Poland 0-0-800 4911299 (0,16 zl/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 5. -Power consumption based on main body and dual 465-9621 cassette

Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min) Switzerland 022 592 7923

Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

EPSON