

# Data Sheet

## FUJITSU Server PRIMERGY TX1310 M1 Tower Server

### The ideal first server

FUJITSU Server PRIMERGY will give you the servers you need to power any workload and changing business requirements. As business processes expand so does the need for applications. Each has its own resource footprint, so you need a way to optimize your computing to better serve your users. PRIMERGY systems will help you match your computing capabilities to your business priorities with our complete portfolio of expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers, compact and scalable blade systems, as well as hyper-converged scale-out servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, provide more agility in daily operations, and integrate seamlessly to let help you concentrate on core business functions.

Perfect for small and medium businesses as well as branch offices, FUJITSU Server PRIMERGY TX tower systems are robust and cost-efficient servers by providing rock solid reliability. Additionally they are characterized by simple IT operations, low power consumption and quiet operation so that they can be handled by non-technically trained staff and can be used in standard office environments. By the way: Almost all PRIMERGY TX servers can be rack-mounted to offer best flexibility.

#### PRIMERGY TX1310 M1

The Fujitsu PRIMERGY TX1310 M1 is the ideal first server for small and medium-sized businesses. With plenty of RAM and Intel® Xeon® processor support it offers more than enough performance for all classic server tasks, such as file, print, web or office applications. The small tower server is build for reliable 24/7 operation and guarantees data safety by high-end features like ECC memory and an onboard RAID controller. Thanks to the screwless chassis and Fujitsu's Easy Rails for hard

disks the server is easy to service. Moreover, the PRIMERGY TX1310 M1 is incredibly silent making it an excellent choice for any office environment.



# Features & Benefits

Main Features	Benefits
<p><b>Cost effective performance</b></p> <ul style="list-style-type: none"><li>■ Intel® Xeon® E3-1200 v3 product family with up to 4 cores</li><li>■ Up to 32 GB ECC memory (4 DIMMs) and 4 PCIe slots</li></ul>	<ul style="list-style-type: none"><li>■ Provides more than enough performance for small and medium-sized businesses</li><li>■ Ideal for all classic server tasks, such as file, print, web or office applications</li></ul>
<p><b>24/7 reliability at the best price</b></p> <ul style="list-style-type: none"><li>■ Up to 4x 3.5-inch non-hot plug SATA storage drives and support for RDX backup devices</li><li>■ 4 PCIe Gen2/3 slots for e.g. additional LAN or graphics cards</li><li>■ 2x onboard Gigabit LAN</li><li>■ Error-correcting code (ECC) memory</li></ul>	
<p><b>Silent, compact, and easy to service</b></p> <ul style="list-style-type: none"><li>■ Low noise emissions through optimized air flow and Fujitsu's Cool-safe® technology</li><li>■ Compact chassis</li><li>■ Screwless chassis and "Easy Rails" for hard disks</li></ul>	

# Technical details

## PRIMERGY TX1310 M1

Base unit	PRIMERGY TX1310 M1 LFF	PRIMERGY TX1310 M1 Essential Edition
Housing types	Tower	Tower
Storage drive architecture	3.5-inch	3.5-inch
Power supply	Standard	Standard
Product Type	Mono Socket Tower Server	Mono Socket Tower Server

## Mainboard

Chipset	Intel® C226	
Processor quantity and type	Intel® Celeron® processor / Intel® Core™ i3 processor / Intel® Pentium® processor / Intel® Xeon® processor E3-1200 v3 product family	
Mainboard type	D 3219	D 3219-B
Processor quantity and type	1 x Intel® Xeon® processor E3-1200 v6 product family Intel® Celeron® processor Intel® Core™ i3 processor Intel® Pentium® processor	1 x Intel® Celeron® processor Intel® Pentium® processor
Processor notes	Essential Edition does not support Intel® Xeon® and Core i3 processors	

<b>Processor</b>	Intel® Core™ i3-4330 processor (2C/4T, 3.50 GHz, TLC: 4 MB, Turbo: No, Mem bus: 1,600 MHz, 54 W)
	Intel® Pentium® processor G3420 (2C/2T, 3.20 GHz, TLC: 3 MB, Turbo: No, Mem bus: 1,600 MHz, 54 W)
	Intel® Xeon® processor E3-1226v3 (4C/4T, 3.30 GHz, TLC: 8 MB, Turbo: Yes, 1,600 MHz, 84 W)
	Intel® Xeon® processor E3-1246v3 (4C/8T, 3.50 GHz, TLC: 8 MB, Turbo: Yes, 1,600 MHz, 84 W)

Memory slots	4	2
Memory slot type	DIMM (DDR3)	DIMM (DDR3)
Memory capacity (min. - max.)	2 GB - 32 GB	2 GB - 16 GB
Memory protection	ECC	ECC

<b>Memory options</b>	4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1,600 MHz, PC3-12800, DIMM, single rank
	8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1,600 MHz, PC3-12800, DIMM, dual rank

## Interfaces

USB 2.0 ports	4 (4x rear)
USB 3.0 ports	5 (2x front, 2x rear, 1x internal for backup device)
Graphics (15-pin)	1 x VGA (Intel iGfx processor graphics)
Serial 1 (9-pin)	1 x RS232
LAN / Ethernet (RJ-45)	2 x Gbit/s Ethernet

## I/O controller on board

Serial ATA total	6
RAID controller	4 port SATA with RAID 0/1/10 for HDDs
SATA Controller	Intel® C226
LAN Controller	Intel® i217 + Intel® i210 onboard 2 x 10/100/1000 Mbit/s Ethernet PXE-Boot by LAN via PXE-Server, Teaming supported
Trusted Platform Module (TPM)	Infineon / 1.2 (option)

## Slots

PCI-Express 3.0 x8	2 x notched supporting x16 card	2 x notched supporting x16 card
PCI-Express 2.0 x1 (mech. x4)	1 x	0 x
PCI-Express 2.0 x4 (mech. x8)	1 x	0 x

**Drive bays**

Storage drive bay configuration	4x 3.5" easy change SATA
Notes accessible drives	2 (1 bay is occupied by DVD/DVD-RW, 3.5-inch)

**Fan Configuration**

Fan configuration	Silent system fans
Fan notes	Non hot-plug

**Operating panel**

Operating buttons	On/off switch
Status LEDs	Power (green)

**Operating Systems and Virtualization Software**

Certified or supported operating systems and virtualization software	Microsoft® Hyper-V Server 2016
	Microsoft® Windows Server® 2016 Datacenter
	Microsoft® Windows Server® 2016 Standard
	Microsoft® Windows Server® 2016 Essentials
	Microsoft® Windows Storage Server 2016 Standard
	Microsoft® Hyper-V Server 2012 R2
	Microsoft® Windows Server® 2012 R2 Datacenter
	Microsoft® Windows Server® 2012 R2 Standard
	Microsoft® Windows Server® 2012 R2 Essentials
	Microsoft® Windows Server® 2012 R2 Foundation
	Microsoft® Windows Storage Server 2012 R2 Standard
	Microsoft® Hyper-V Server 2012
	Microsoft® Windows Server® 2012 Datacenter
	Microsoft® Windows Server® 2012 Standard
	Microsoft® Windows Server® 2012 Essentials
	Microsoft® Windows Server® 2012 Foundation
	Microsoft® Windows Storage Server 2012 Standard
	Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Windows Server® 2008 R2 Foundation
	SUSE® Linux Enterprise Server 12
	SUSE® Linux Enterprise Server 11
	Red Hat® Enterprise Linux 7
	Red Hat® Enterprise Linux 6
	Red Hat® Enterprise Linux 5
Oracle® Linux 7	
Oracle® Linux 6	
Oracle® VM 3	

Operating system release link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfb3230473">http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfb3230473</a>
-------------------------------	---

Operating system notes	Support of other Linux derivatives on demand Red Hat® certification starting with version 5.9 / 6.4.
------------------------	---

**Server Management**

Standard	ServerView Suite - Deploy SV Installation Manager
Option	ServerView Suite - Integrate Integration pack for Fujitsu ManageNow® solution

**Dimensions / Weight**

Floor-stand (W x D x H)	175 x 419 x 395 mm
-------------------------	--------------------

<b>Dimensions / Weight</b>	
Weight	up to 14 kg
<b>Environment</b>	
Operating ambient temperature	10 - 35 °C
Operating temperature note	ETSI 300 019-2-3 Class 3.1
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=589915e9-1bf8-40f7-8ba4-7cac9371f2f0">http://docs.ts.fujitsu.com/dl.aspx?id=589915e9-1bf8-40f7-8ba4-7cac9371f2f0</a>
Noise emission	According to ISO9296
Sound pressure (LpAm)	23 dB(A) (idle)/ 24 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	4.0B (idle)/ 4.0B (operating)
Noise notes	Noise emissions depends on operation modes, system configuration and ambient temperature.
<b>Electrical values</b>	
Power supply configuration	1 x standard power supply
Active power (max. configuration)	209 W
Apparent power (max. configuration)	211 VA
Heat emission (max. configuration)	752.4 kJ/h (713.1 BTU/h)
Rated current max.	3.5A (100 V) / 1.5 A ( 240 V)
Active power note	To estimate the power consumption of different configurations use the Power Calculator of the System Architect: <a href="http://configurator.ts.fujitsu.com/public/">http://configurator.ts.fujitsu.com/public/</a>
Power supply	250W standard, 90% (Gold efficiency), 100-240V, 50 / 60Hz
<b>Compliance</b>	
Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronical equipment)
Germany	GS
Europe	CE
USA/Canada	CSA us ULc/us FCC Class A
Japan	VCCI:V3 Class A + JIS 61000-3-2
South Korea	KC
China	CCC (planned)
Australia/New Zealand	C-Tick (AS / NZS CISPR 22 Class A)
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

## Components

<b>Backup Drives</b>	RDX Drive, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 3.0
<b>Optical drives</b>	Blu-ray Disc™ Triple Writer, (6x BD-ROM; 8x DVD; 24x CD), slimline, SATA I DVD-ROM, (16xDVD; 48xCD), half height, SATA I DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I

<b>Hard disk drives</b>	HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, non hot plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, 512e, non hot plug, 3.5-inch, economic
	HDD SATA, 6 Gb/s, 7,200 rpm, 512e, non hot plug, 3.5-inch, economic
	HDD SATA, 6 Gb/s, 3 TB, 7,200 rpm, non hot plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, non hot plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, non hot plug, 3.5-inch, business critical
<b>Communication, Network</b>	Ethernet Ctrl. 1 x 1 Gbit/s PCIe 1.1 x1 RJ45 ( Intel® )
	Ethernet Ctrl. 1 x 1 Gbit/s PCIe 2.1 x1 RJ45 ( Intel® )
	Ethernet Ctrl. 2 x 1 Gbit/s PCIe 2.1 x4 RJ45 ( Intel® )
<b>Graphics add on cards</b>	NVIDIA® NVS™ 315, PCIe x16, 2x DVI/VGA
<b>Warranty</b>	
<b>Warranty period</b>	1 year
<b>Warranty type</b>	Onsite Service (depending on country)
<b>Warranty Terms &amp; Conditions</b>	<a href="http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM">http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM</a>
<b>Product Support Services - the perfect extension</b>	
<b>Support Pack Options</b>	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time 24x7, 4h Onsite Response Time
<b>Recommended Service</b>	24x7, Onsite Response Time: 4h
<b>Service Lifecycle</b>	5 years after end of product life
<b>Service Weblink</b>	<a href="http://www.fujitsu.com/fts/products/product-support-services/">http://www.fujitsu.com/fts/products/product-support-services/</a>

# More information

## Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY TX1310 M1, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about Fujitsu PRIMERGY TX1310 M1, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
<http://www.fujitsu.com/primergy>

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
©2016 Fujitsu Technology Solutions GmbH

## Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

**Contact**  
FUJITSU LIMITED

Website: [www.fujitsu.com](http://www.fujitsu.com)  
2017-08-18 INT-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
©2016 Fujitsu Technology Solutions GmbH