

# 3 ft DVI to VGA Active Converter Cable – DVI-D to VGA Adapter – 1920x1200

Product ID: DVI2VGAMM3



The DVI2VGAMM3 3ft active DVI to VGA converter cable lets you connect your DVI video source directly to a VGA monitor or projector, with no additional adapters or cables required.

## **Reduce Cable Clutter**

Using precise cable lengths reduces excess cable clutter and ensures a tidy, professional installation with a monitor at your workstation or a projector in your classroom or boardroom.

The DVI2VGAMM3 is 3 feet (0.9 meters) in length, and part of a complete DVI to VGA adapter cable line, featuring two other cables at <u>6 feet(DVI2VGAMM6)</u> and <u>10 feet(DVI2VGAMM10)</u>, enabling you to choose a customized cable length for your installation.

# **Avoid Hassle**

Don't be fooled by analog DVI adapters that work with a DVI-I port. They won't work with your digital DVI signal, and won't even fit into a DVI-D port.

www.startech.com 1 800 265 1844



# **Data Sheet**

The DVI2VGAMM3 is an end-to-end cable adapter solution that connects directly from your digital DVI-D computer to your VGA monitor or projector in one simple cable, saving you the hassle of combining a DVI to VGA adapter with a bulky VGA cable, perfect for connecting a DVI-equipped POS computer or kiosk to a touch screen monitor that only supports VGA.

Plus, unlike most digital DVI to VGA adapters which require a power outlet to convert the video signal, the DVI2VGAMM3 doesn't need external power in most installations. For added convenience and compatibility with low-powered DVI video cards, the DVI2VGAMM3 features an optional integrated USB power source (USB cable not included), making it perfect for boardroom or classroom projectors that require a simple installation, that may need to work with more than one computer system.

## **Save Money**

In the past converting digital DVI to VGA was a difficult and expensive task that often resulted in upgrading to a DVI-D display. Avoid upgrade costs by connecting your DVI-D video source to your existing VGA display using the DVI2VGAMM3. Plus, because the adapter cable supports video resolution up to 1920x1200 you can rest assured you can use your existing VGA monitor or projector while maintaining high-definition video quality.

The DVI2VGAMM3 is backed by a 3-year StarTech.com warranty and free lifetime technical support.

www.startech.com 1 800 265 1844



# **Data Sheet**

#### Certifications, Reports and Compatibility





− C € F©

#### Applications

- Connect a DVI-D computer to your classroom or boardroom projector
- Use in your boardroom or workstation for installation requiring 3 feet of cable
- Install in your at home workstation to make your DVI-D computer compatible with your VGA monitor
- Connect a DVI-D cable or satellite set top box to your home theater projector or television
- Connect a DVI-D point-of-sales computer or kiosk to a VGA touch screen

#### Features

- Reduce clutter with short 3ft adapter cable
- Avoid the hassle of additional adapters or cables with a built in cable connecting a digital DVI video source directly to a VGA monitor or projector
- Save upgrade cost by connecting your DVI computer to a VGA monitor or projector
- Supports video resolutions up to 1920x1200
- Active Digital DVI (DVI-D) to VGA conversion
- Adapter and cable in one, with 1x male DVI connector and 1x male VGA connector
- Plug-and-play installation

www.startech.com 1 800 265 1844

# StarTechcom

Hard-to-find made easy\*

# **Data Sheet**

	Warranty	3 Years
Hardware	Active or Passive Adapter	Active
	Adapter Style	Cable Adapters
	Audio	No
	AV Input	DVI-D
	AV Output	VGA
	Chipset ID	Chrontel - 7101A
Performance	Maximum Analog Resolutions	1920 x 1200
	Maximum Cable Length	35.4 in [900 mm]
	Maximum Digital Resolutions	PC resolutions up to 1920 x 1200 @ 60 Hz
Connector(s)	Connector A	1 - DVI-D (25 pin) Male Input
	Connector B	1 - VGA (15 pin, High Density D-Sub) Male Output
	Connector Type(s)	1 - USB Micro-B (5 pin) Male
Power	Power Source	USB-Powered
Environmental	Humidity	40%-85%RH
	Operating Temperature	0°C to 60°C (32°F to 140°F)
	Storage Temperature	-10°C to 70°C (14°F to 158°F)
Physical Characteristics	Cable Length	35.4 in [900 mm]
	Product Height	0.6 in [1.5 cm]
	Product Length	35.4 in [90 cm]
	Product Width	1.6 in [40 mm]
	Weight of Product	2.5 oz [70 g]
Packaging Information	Package Height	0.9 in [23 mm]
	Package Length	8.7 in [22 cm]
	Package Width	7.9 in [20 cm]
	Shipping (Package) Weight	3.1 oz [88.6 g]

Product appearance and specifications are subject to change without notice.