


PowerShot SX540 HS

Capture and share every adventure with 50x zoom

Effortless fun and expert control combine in this 50x zoom, connected bridge camera that takes you on an imaging journey to create and share stunning photos and movies. Ideal for holidays and special occasions.



- Get closer or shoot ultra-wide with 24mm, 50x optical zoom. Enjoy superb shots in any light and capture spontaneous action
- Shoot realistic Full HD 60p movies and keep footage steady at full zoom or running with Advanced Dynamic Image Stabilizer
- With Wi-Fi*, NFC and Image Sync it's simple to connect to your smart device, shoot remotely and share or back up your creations
- Just point and shoot with Hybrid Auto and Creative Shot for fantastic results or take full creative control
- Enjoy steadier shots and comfortable shooting with the ergonomic grip. Easily keep track of subjects with Zoom Framing Assist

* Wi-Fi connectivity and features vary by model and region.

Product Range



PowerShot SX60 HS



PowerShot SX540 HS



PowerShot SX420 IS

PowerShot SX60 HS
PowerShot SX540 HS
PowerShot SX420 IS

Technical Specifications

IMAGE SENSOR

Type	1/2.3 type back-illuminated CMOS
Effective Pixels	Approx. 20.3 M ⁽¹⁴⁾
Total Pixels	Approx. 21.1 M
Colour Filter Type	Primary Colour

IMAGE PROCESSOR

Type	DIGIC 6 with iAPS technology
------	------------------------------

LENS

Focal Length	4.3 – 215.0 mm (35 mm equivalent: 24 – 1200 mm)
Zoom	Optical 50x ZoomPlus 100x Digital Approx. 4x (with Digital Tele-Converter approx. 1.6x or 2.0x and Safety Zoom ⁽¹¹⁾). Combined Approx. 200x

Maximum f/number

Construction	13 elements in 10 groups (3 UD lenses and 1 double-sided aspherical lens)
--------------	---

Image Stabilisation	Yes (lens shift-type), approx. 3-stop ⁽¹³⁾ . Intelligent IS with 5-axis Enhanced Dynamic IS
---------------------	--

FOCUSING

Type	TTL
AF System/ Points	AiAF (Face Detection / 9-point), 1-point AF (fixed to centre)
AF Modes	Single, Continuous, Servo AF/AE ⁽⁶⁾ , Tracking AF
AF Point Selection	Size (Normal, Small)
AF Lock	Yes
AF Assist Beam	Yes
Manual Focus	Yes, plus MF Peaking
Closest Focusing Distance	0 cm (W) from front of lens in Macro

EXPOSURE CONTROL

Metering modes	Evaluative (linked to Face Detection AF frame), Centre-weighted average, Spot (Centre)
AE Lock	Yes
Exposure Compensation	+/- 2 EV in 1/3 stop increments Enhanced i-Contrast for automatic dynamic range correction
ISO sensitivity	AUTO, 80, 100, 200, 400, 800, 1600, 3200 AUTO ISO: 80 - 1600

SHUTTER

Speed	1 – 1/2000 sec. (factory default) 15 – 1/2000 sec. (total range – varies by shooting mode)
-------	---

WHITE BALANCE

Type	TTL
Settings	Auto (including Face Detection WB), Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom. Multi-area WB correction available in Smart Auto

COLOUR MATRIX

Type	sRGB
------	------

LCD MONITOR

Monitor	7.5 cm (3.0") TFT, approx. 461,000 dots
Coverage	Approx. 100 %
Brightness	Adjustable to one of five levels. Quick-bright LCD

FLASH

Modes	Auto, Manual Flash On / Off, Slow Synchro
Slow Sync Speed	Yes. Fastest speed 1/2000 sec.
Red-Eye Reduction	Yes
Flash Exposure Compensation	+/- 2 EV in 1/3 stop increments. Face Detection FE. Safety FE, Smart Flash Exposure
Flash Exposure Lock	Yes
Manual Power Adjustment	3 levels with internal flash
Built-in Flash Range	50 cm – 5.5 m (W) / 1.3 m – 3.0 m (T)
External Flash	Canon High Power Flash HF-DC2

SHOOTING

Modes	Smart Auto (58 scenes detected), Program AE, Shutter priority AE, Aperture priority AE, Manual, Hybrid Auto, Live View Control, Creative Shot, SCN (Sport, Portrait, Smart Shutter (Smile, Wink Self-Timer, FaceSelf-Timer), Handheld Night Scene, Low Light, Fireworks), Creative Filters (Fish-eye Effect, Miniature Effect, Toy Camera Effect, Soft Focus, Monochrome, Super Vivid, Poster Effect), Movie
Modes in Movie	Smart Auto (21 scenes detected), Standard, Program AE, Portrait, Miniature Effect, Monochrome, Super Vivid, Poster Effect, Fireworks, Short Clip, iFrame Movie
Photo Effects	My Colors (My Colors Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter Skin Tone, Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)
Drive modes	Single, Auto Drive, Continuous, Continuous with AF, Self-Timer
Continuous Shooting	Approx. 5.9 shots/s with AF: Approx. 4.4 shots/s with Live View: Approx. 4.5 shots/s (all speeds are until memory card becomes full) ⁽³⁾⁽⁴⁾⁽¹²⁾

RECORDING PIXELS / COMPRESSION

Image Size	4:3 - (L) 5184 x 3888, (M) 2592 x 1944, (M1) 3648 x 2736, (M2) 2048 x 1536, (S) 640 x 480 16:9 - (L) 5184 x 2912, (M1) 3648 x 2048, (M2) 1920 x 1080, (S) 640 x 360 3:2 - (L) 5184 x 3456, (M1) 3648 x 2432, (M2) 2048 x 1368, (S) 640 x 424 1:1 - (L) 3888 x 3888, (M1) 2736 x 2736, (M2) 1536 x 1536, (S) 480 x 480
Compression	Resize option available in playback Superfine, Fine
Movies	(Full HD) 1920 x 1080, 59.94 / 29.97 fps, (HD) 1280 x 720, 29.97 fps, (L) 640 x 480, 29.97 fps Miniature Effect (HD, L) 6 fps, 3 fps, 1.5 fps Hybrid Auto Movie (HD) 29.97 fps iFrame Movie (Full HD) 29.97 fps Short Clip (HD) 29.97 fps (Full HD & HD) Up to 4 GB or 29 min. 59 sec. ⁽⁷⁾ (L) Up to 4 GB or 1 hour ⁽⁸⁾
Movie Length	

FILE TYPES

Still Image Type	JPEG compression (Exif 2.3 (Exif Print) compliant) / Design rule for Camera File system, Digital Print Order Format (DPOF) Version 1.1 compliant
Movies	MP4 (Video: MPEG4-AVC (H.264), Audio: MPEG-4 AAC-LC (stereo))

DIRECT PRINT

Canon Printers	Canon SELPHY Compact Photo Printers and Canon Inkjet Printers supporting PictBridge
PictBridge	Yes (via USB or Wireless LAN)

OTHER FEATURES

GPS	GPS via mobile (via Canon Camera Connect app with compatible smart devices) Yes, during shooting and playback
Red-Eye Correction	Yes, with Auto Rotate
Intelligent Orientation Sensor	Yes, during playback
Histogram	Approx. 2x – 10x
Playback zoom	Approx. 2, 10 s or Custom
Self Timer	English, German, French, Dutch, Danish, Finnish, Italian, Greek, Norwegian, Portuguese, Russian, Swedish, Spanish, Ukrainian, Polish, Czech, Hungarian, Turkish, Simplified Chinese, Chinese (traditional), Japanese, Korean, Thai, Arabic, Romanian, Farsi, Hindi, Malay, Indonesian, Vietnamese, Hebrew

INTERFACE

Computer	Hi-Speed USB composite connector (Mini-B compatible)
Other	HDMI Mini (Type-C) Connector A/V output, composite connector (PAL/NTSC)
Computer/Other	Wi-Fi (IEEE802.11b/g/n), (2.4 GHz only), with Dynamic NFC support ⁽¹¹⁾

Technical Specifications

MEMORY CARD

Type SD, SDHC, SDXC (UHS Speed Class 1 compatible)

SUPPORTED OPERATING SYSTEM

PC & Macintosh

Windows 10 / 8.1 / 8 / 7 SP1 ⁽¹⁸⁾
Mac OS X 10.9 / 10.10 / 10.11

For Wi-Fi connection to a PC:
Windows 10 / 8.1 / 8 / 7 SP1
Mac OS X 10.9 / 10.10

For Image Transfer Utility:
Windows 10 / 8.1 / 8 / 7 SP1
Mac OS X 10.9 / 10.10 / 10.11

SOFTWARE

Other

CameraWindow DC
Map Utility
Image Transfer Utility

Camera Connect app available on iOS and Android devices

POWER SOURCE

Batteries

Rechargeable Li-ion Battery NB-6LH (battery and charger supplied)

Battery life

Approx. 205 shots
Eco mode approx. 290 shots
Approx. 300 min. playback

ACCESSORIES

Cases / Straps

Soft Case DCC-850
PowerShot Accessory Organizer

Flash

Lens Hood LH-DC60
Filter Adapter FA-DC67A (Compatible with Canon 67mm Filters: Circular Polarizing PL-C B, Protect Filter)

Flash

Canon High Power Flash HF-DC2

Power Supply & Battery Chargers

Battery Charger CB-2LYE

Other

Rechargeable Li-ion Battery NB-6LH
Canon HDMI Cable HTC-100
Canon AV cable AVC-DC400ST
Interface cable IFC-400PCU

PHYSICAL SPECIFICATIONS

Operating Environment

0 – 40 °C, 10 – 90 % humidity

Dimensions (W x H x D)

120.0 x 81.7 x 91.9 mm

Weight

Approx. 442 g (including battery and memory card)

⁽¹⁾ Depending on the image size selected.

⁽³⁾ Under conditions where the flash does not fire.

⁽⁴⁾ Depending on memory card speed / capacity / compression setting.

⁽⁶⁾ Some settings limit availability.

⁽⁷⁾ The following Speed Class memory cards are required for maximum record time: (HD) 1280 x 720 Speed Class 4 or above. (Full HD) 1920 x 1080 Speed Class 6 or above. (iFrame) 1280 x 720 Speed Class 6 or above.

⁽¹¹⁾ Wi-Fi use may be restricted in certain countries or regions. Wi-Fi support varies by device and region. For more information visit www.canon-europe.com/wirelesscompacts

⁽¹²⁾ Sustained continuous shooting function requires compatible SDHC/SDXC UHS Speed Class 1 memory card, total number of frames captured varies depending on shooting subject.

⁽¹³⁾ Values at maximum optical focal length. Cameras whose focal length exceeds 350 mm (35 mm equivalent) are measured at 350 mm.

⁽¹⁴⁾ Image processing may cause a decrease in the number of pixels.

⁽¹⁸⁾ Software applications compatible with Windows 10 in Windows 10 Desktop Mode only.

All data is based on Canon standard testing methods (according to CIPA Standards) except where indicated.

Subject to change without notice.

PowerShot SX540 HS

Capture and share every adventure with 50x zoom

Effortless fun and expert control combine in this 50x zoom, connected bridge camera that takes you on an imaging journey to create and share stunning photos and movies. Ideal for holidays and special occasions.

Sales Start Date: March 2016



Product Details:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
PowerShot SX540 HS black	1067C002	4549292056426	CHF 369.00

Optional Accessories:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
Power Supply			
Battery Pack NB-6LH	8724B001	4960999898952	CHF 68.00
Battery Charger CB-2LYE	2609B001	4960999571676	CHF 88.00
Lens			
Filter Adapter FA-DC67A	4728B001	4960999677187	CHF 48.00
Protect Filter 67mm	2598A001	4960999430973	CHF 78.00
Circular Polarization Filter PL-C B 67mm	2189B001	4960999455778	CHF 198.00
Lens Hood LH-DC60	4727B001	4960999677163	CHF 48.00
Cables			
Interface Cable IFC-400PCU	9370A001	4960999209906	CHF 38.00
HDMI Cable HTC-100	2384B001	4960999530383	CHF 78.00
AV Cable AVC-DC400 ST	4076B001	4960999659275	CHF 28.00
Flash			
High Power Flash HF-DC2	5189B001	4960999782232	CHF 158.00
Cases			
Soft case DCC-850	1872V639	8714574560380	CHF 48.00
Accessory Organizer	0036X433	8714574583167	CHF 28.00

Measurement / Logistic Information:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Gross Weight (kg)
Digital Camera PowerShot SX540 HS BK EU23	1067C002AA	EA	Each	1	177.5	158.5	129.5	0.954
		CT	Carton	6	413	336	215	6.51
		EP	Euro Pallet	200	1200	800	1225	150
			Layers per pallet	5				
			Cartons per layer	5				
			Products per layer	30				

What's in the box?

- Digital Camera PowerShot SX540 HS
- Neck Strap NS-DC11
- Lens Cap (with Strap)
- Battery Pack NB-6LH
- Battery Charger CB-2LYE
- AC Cable
- User Manual Kit

The Canon logo is displayed in its signature red font.