

ThinkPad Yoga 11e (3rd Gen) Platform Specifications

Product Specifications Reference (PSREF)

| | | | | | | | | | | | | |
|-------------------------|---|------------|--------------|----------------|------------------------|-----------------------|--------------|-----------------------|--------------------------------|---|--|---|
| Processor | Intel® Celeron® processor, Intel Pentium® Processor, or 6th Generation Intel Core™ i3 Processor | | | | | | | | Media reader | 4-in-1 reader (MMC, SD, SDHC, SDXC) | | |
| | Processor Number | # of Cores | # of Threads | Base Frequency | Burst Frequency | Cache | Memory Types | Processor Graphics | Ports | Two USB 3.0, HDMI, Ethernet (RJ-45) | | |
| | Cel N3150 | 4 | 4 | 1.6 GHz | 2.08 GHz | 2MB | DDR3L-1600 | Intel HD graphics | Control buttons | Power button, volume control button | | |
| | Cel N3160 | 4 | 4 | 1.6 GHz | 2.24 GHz | 2MB | | Intel HD graphics | Camera | Audio support | HD720p resolution, low light sensitive, fixed focus HD Audio, Realtek® ALC3245 codec / stereo speakers, 2W x 2 / monaural digital microphone, combo audio/microphone jack | |
| | Pen 4405U | 2 | 4 | 2.1 GHz | - | 2MB | | Intel HD graphics 510 | | | | |
| i3-6100U | 2.3 GHz | | | - | 3MB | Intel HD graphics 520 | | | | | | |
| Graphics | Intel HD Graphics, Intel HD Graphics 510, or Intel HD Graphics 520 in processor, supports external digital monitor via HDMI™; supports dual independent display; Max resolution: 1920X1080 (HDMI) @30Hz | | | | | | | | Security | Power-on password, hard disk password, supervisor password, security keyhole | | |
| Chipset | Intel SoC (System on Chip) platform | | | | | | | | Security chip | Trusted Platform Module, TCG 1.2-compliant | | |
| Memory | 2GB, 4GB, or 8GB / PC3-12800 1600MHz DDR3L, one DDR3L SO-DIMM socket | | | | | | | | vPro | None | | |
| Display | 11.6" (295mm) HD (1366x768), glare, LED backlight, IPS 250 nits, 16:9 aspect ratio, 800:1 contrast ratio | | | | | | | | Fingerprint reader | None | | |
| MultiTouch | Yes, support 10 fingers | | | | | | | | Battery | Integrated Lithium Polymer 3-cell (42Wh) | | |
| Hinge | Yoga hinge, 360 degree | | | | | | | | | | Max battery life ¹⁰ | MobileMark® 2014: 11.53 hr |
| Convertible mode | Laptop, tent, stand and tablet | | | | | | | | | | AC adapter | 45-watt AC adapter |
| Pen | Some: Active pen, batteries required | | | | | | | | | | Preload | Some: Windows 10 Home 64 Some: Windows 10 Pro 64 • Lenovo Solution Center • Lenovo Companion • Lenovo Setting • Microsoft Office preloaded; purchase a product key to activate • McAfee® LiveSafe™ (30-day trial) |
| Storage | M.2 Solid State Drive (SSD), SATA 6.0Gb/s | | | | | | | | | | | |
| Optical | None | | | | | | | | Limited warranty ¹² | One of the following, configurable by model: • 1-year depot repair service • 3-year/1-yr battery depot repair service (US only) | | |
| Ethernet | Realtek RTL8111GUS-CG Gigabit Network Connection | | | | | | | | Mil-Spec test | MIL-STD-810G military certification | | |
| WLAN ⁴ | One of the following, configurable by model: • 11ac+BT, Intel Dual Band Wireless-AC 3165, 1x1, M.2 card • 11ac+BT, Intel Dual Band Wireless-AC 7265, 2x2, M.2 card | | | | | | | | Environment | EPEAT™ Gold (US only); ENERGY STAR® 6.1; RoHS-compliant | | |
| Bluetooth™ | Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter | | | | | | | | | | | |
| WWAN | None | | | | | | | | | | | |
| Dimensions ³ | WxDxH: 11.81" x 8.27" x 0.90"; 300mm x 210mm x 22.9mm | | | | | | | | | | | |
| Weight ² | from 3.5 lb (1.59kg) | | | | | | | | | | | |
| Case color | Display cover: Graphite Black or Silver; | | | | Bottom: Graphite Black | | | | | | | |
| Case material | Display cover: PC+40%GF+TPU; | | | | Bottom: PCC | | | | | | | |