
HP EliteBook 820 G3 Notebook PC




Front / Right

- 1. WLAN antennas (2)
- 2. WWAN antennas (2) (select models)
- 3. Internal microphones (2)
- 4. Webcam LED (select models)
- 5. Webcam (select models)
- 6. SIM card slot
- 7. Power connector
- 8. Docking connector
- 9. Ethernet port
- 10. SD Card Slot
- 11. USB 3.0 Port
- 12. Microphone/ headphones combo jack

- 13. Display Port
- 14. USB-C[™] port
- 15. Fingerprint reader (select models)
- 16. Touchpad
- 17. Touchpad buttons (4)
- 18. Indicator LEDs: Wireless Light, Power Light, AC Adapter/Battery Light, Storage Usage Light
- 19. NFC (select models)
- 20. Pointstick
- 21. Power button






Left

- 1. Security lock slot
- 2. VGA port

- 3. USB 3.0 Charging port
- 4. Smart Card Reader



HP EliteBook 840 G3 Notebook PC




Front / Right

- 1. WLAN antennas (2)
- 2. WWAN antennas (2) (select models)
- 3. Internal microphones (2)
- 4. Webcam LED (select models)
- 5. Webcam (select models)
- 6. Wireless on/off button
- 7. Speaker mute button
- 8. SIM card slot
- 9. Power connector
- 10. Docking connector
- 11. Ethernet port
- 12. USB 3.0 port

- 13. SD card slot
- 14. Microphone/ headphones combo jack
- 15. Display Port
- 16. USB-C[™] port
- 17. Fingerprint reader (select models)
- 18. Touchpad
- 19. Touchpad buttons (4)
- 20. Indicator LEDs: Wireless Light, Power Light, AC Adapter/Battery Light, Storage Usage Light
- 21. NFC (select models)
- 22. Pointstick
- 23. Power button






Left

- 1. Security lock slot
- 2. VGA port

- 3. USB 3.0 Charging port
- 4. Smart Card Reader



HP EliteBook 850 G3 Notebook PC



Front / Right


- 1. WLAN antennas (2)
- 2. WWAN antennas (2) (select models)
- 3. Internal microphones (2)
- 4. Webcam LED (select models)
- 5. Webcam (select models)
- 6. Wireless on/off button
- 7. Speaker mute button
- 8. SIM card slot
- 9. Power connector
- 10. Docking connector
- 11. Ethernet port
- 12. USB 3.0 port

- 13. SD card slot
- 14. Microphone/ headphones combo jack
- 15. Display Port
- 16. USB-C[™] port
- 17. Fingerprint reader (select models)
- 18. Touchpad
- 19. Touchpad buttons (4)
- 20. Indicator LEDs: Wireless Light, Power Light, AC Adapter/Battery Light, Storage Usage Light
- 21. NFC (select models)
- 22. Pointstick
- 23. Power button



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Overview



Left

- 1. Security lock slot
- 2. VGA port

- 3. USB 3.0 Charging port
- 4. Smart Card Reader



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Overview

AT A GLANCE

- Stylish, lightweight magnesium and aluminum chassis starts at 18.9 mm thin
- No dongles are needed with built-in VGA, drop-jaw RJ-45 Ethernet port, USB 3.0, USB Type-C[™], and full-size DisplayPort for high resolution support
- Customer serviceable and upgradeable with component accessible design
- Choice of 6th generation Intel® Core™ i7, i5 and i3 processors
- Integrated Intel® HD Graphics 520 or AMD Radeon™ R7 M365X discrete graphics (HP EliteBook 850 option only)
- Optimize your audio experience for remote collaboration with optional HD webcam, dual-microphone array, premium speakers, HP Noise Reduction Software, HP Clear Sound Amp, Audio by Bang & Olufsen
- Improved keyboard experience featuring HP Premium Keyboard with dual-point (10-key numeric keypad available on 850)
- Optional back-lit keyboard keeps you productive in all settings with HP DuraKeys to protect keys from fading
- Ensured durability through MIL-SPEC 810G testing, plus an additional 115,000 hours of reliability testing through HP's Total Test Process¹
- Enhanced security features including TPM1.2/2.0², SmartCard Reader, HP Sure Start self-healing BIOS, HP Client Security, Self-Encrypting storage drives, and optional Fingerprint reader
- HP Touchpoint Manager manageability supported
- LED-backlit displays:
 - o HP EliteBook 820: 12.5" diagonal HD, FHD Non-Touch or FHD Touch
 - o HP EliteBook 840: 14.0" diagonal HD, FHD, QHD Non-Touch or FHD Touch
 - o HP EliteBook 850: 15.6" diagonal HD, FHD, UHD Non-Touch or FHD Touch
- Flexible wireless connectivity options including mobile broadband
- Easily dock with the optional HP UltraSlim Docking Station
- Choice of hard drives up to 1 TB and solid state drives up to 512 GB
- DDR4 memory up to 16 GB for HP EliteBook 820 and up to 32 GB for HP EliteBook 840 and 850
- Preinstall Windows 10, Windows 8.1, Windows 7, FreeDOS 2.0 or NeoKylin 64 versions
 - 1. Testing was not intended to demonstrate fitness for Department of Defense contracts requirements or for military use. Test results are not a guarantee of future performance under these test conditions.
 - 2. This product ships with TPM 1.2 with option to upgrade to TPM 2.0. Upgrade utility is expected to be available by the second half of 2016 via HP Customer Support.

NOTE: See important legal disclosures for all listed specs in their respective features sections.



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Features PRODUCT NAMES

HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

OPERATING SYSTEM

Preinstalled Windows 10 Pro 64¹

Windows 10 Home 64¹ Windows 8.1 Pro 64³ Windows 8.1 64³

Windows 7 Professional 64 (available through downgrade rights from Windows 10 Pro)² Windows 7 Professional 32 (available through downgrade rights from Windows 10 Pro)²

Windows 7 Professional 64³ Windows 7 Professional 32³

FreeDOS 2.0 NeoKylin Linux 64

Web Supported Windows 10 Pro 64¹

Windows 10 Home 64¹ Windows 10 Enterprise 64¹ Windows 8.1 Pro 64¹ Windows 8.1 64¹

Windows 8.1 Enterprise 64¹ Windows 7 Professional 64¹ Windows 7 Professional 32¹ Windows 7 Enterprise 64¹ Windows 7 Enterprise 32¹

- 1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See http://www.microsoft.com.
- 2. This system is preinstalled with Windows 7 Pro software and also comes with a license and media for Windows 10 Pro software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.
- Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately
 purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. See
 http://www.microsoft.com.

PROCESSOR

Intel® Core™ i7-6600U (2.6 GHz, up to 3.4 GHz with Intel® Turbo Boost Technology, 4 MB cache, 2 cores)¹ Intel® Core™ i7-6500U (2.5 GHz, up to 3.1 GHz with Intel®Turbo Boost Technology, 4 MB cache, 2 cores)¹² Intel® Core™ i5-6300U (2.4 GHz, up to 3 GHz with Intel® Turbo Boost Technology, 3 MB cache, 2 cores)¹ Intel® Core™ i5-6200U (2.3 GHz, up to 2.8 GHz with Intel® Turbo Boost Technology, 3 MB cache, 2 cores)¹² Intel® Core™ i3-6100U (2.3 GHz, 3 MB cache, 2 cores)¹²²



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Features

1. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering is not a Measurement of higher performance.

2. Not available with Intel iAMT (*Not available with vPro)

NOTE: Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

CHIPSET

Chipset integrated with processor

INTEL® CORE 15 WITH vPro/Core 17 WITH vPro Technology CAPABLE

Intel® Core i5 with vPro and Core i7 with vPro technology is a selectable feature that is available on units configured with select processors, an Intel Centrino® Advanced-N or Ultimate-N WLAN module and a preinstalled Windows operating system. It provides advances in remote manageability, security, energy efficient performance, and wireless connectivity. Intel® Active Management Technology (iAMT) offers built-in manageability and proactive security for networked notebook PCs, even when they are powered off* or when the operating system is inoperable. It can help identify threats before they reach the network, isolate infected systems, and update PCs regardless of their power state.

*Requires a Windows operating system, network hardware and software, connection with a power source, and a direct (non-VPN) corporate network connection which is either cable or wireless LAN.

NOTE: Some functionality of this technology, such as Intel® Active management technology and Intel Virtualization technology, requires additional 3rd party software in order to run. Availability of future "virtual appliances" applications for Intel vPro technology is dependent on 3rd party software providers. Microsoft Windows required.

GRAPHICS

Integrated

Intel® HD Graphics 520

Discrete

AMD Radeon™ R7 M365X 1GB GDDR5 dedicated (HP EliteBook 850 only)

DISPLAY

HP EliteBook 820 Internal Non-Touch

12.5" diagonal LED backlight HD1 Slim eDP SVA Anti-glare (1366 x 768)

12.5" diagonal LED backlight HD1 Slim eDP SVA Anti-glare (1366 x 768) with camera

12.5" diagonal LED backlight FHD UltraSlim eDP UWVA Anti-glare (1920 x 1080)

12.5" diagonal LED backlight FHD UltraSlim eDP UWVA Anti-glare (1920 x 1080) with camera



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Features

Touch

12.5" diagonal LED backlight FHD UltraSlim eDP UWVA (1920 x 1080) Touch with camera²

HP EliteBook 840

Internal

Non-Touch

14.0" diagonal LED backlight HD1 Slim eDP SVA Anti-glare (1366 x 768)

14.0" diagonal LED backlight HD1 Slim eDP SVA Anti-glare (1366 x 768) with camera

14.0" diagonal LED backlight FHD Slim eDP SVA Anti-glare (1920 x 1080)

14.0" diagonal LED backlight FHD Slim eDP SVA Anti-glare (1920 x 1080) with camera

14.0" diagonal LED backlight QHD UltraSlim eDP + PSR UWVA Anti-glare (2560 x 1440)

14.0" diagonal LED backlight QHD UltraSlim eDP + PSR UWVA Anti-glare (2560 x 1440) camera

Touch

14.0" diagonal LED backlight FHD Slim eDP SVA (1920 x 1080) Touch with camera²

HP EliteBook 850

Internal

Non-Touch

15.6" diagonal LED backlight HD1 Slim eDP SVA Anti-glare (1366 x 768)

15.6" diagonal LED backlight HD¹ Slim eDP SVA Anti-glare (1366 x 768) with camera

15.6" diagonal LED backlight FHD Slim eDP SVA Anti-glare (1920 x 1080)

15.6" diagonal LED backlight FHD Slim eDP SVA Anti-glare (1920 x 1080) with camera

15.6" diagonal LED backlight UHD Slim eDP UWVA Anti-glare (3840 x 2160)

15.6" diagonal LED backlight UHD Slim eDP UWVA Anti-glare (3840x 2160) with camera

Note: The HP EliteBook 850 G3 UHD panel is not compatible with WWAN.

Touch

15.6" diagonal LED backlight FHD Slim eDP SVA (1920 x 1080) Touch with camera²

VGA

Port supports resolutions up to 1920 x 1200 external resolution @60 Hz

DisplayPort

Supports resolutions up to 4096 x 2160 @ 60 Hz

Resolutions are dependent upon monitor capability, and resolution and color depth settings.

Number of Displays supported with Docking

Supports 3 independent displays if used with optional HP Ultraslim Docking Station.³

- 1. HD content required to view HD images.
- 2. Touch panel has chemically-strengthened Corning® Gorilla® Glass 3 top cover.
- 3. Sold separately or as an optional feature.

NOTE: Resolutions are dependent upon monitor capability, and resolution and color depth settings.

STORAGE AND DRIVES

Primary Storage SATA, 2.5" Hard Drives

500 GB 7200rpm Self Encrypting Drive (FIPS-140-2) (Opal 2)



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Features

500 GB 7200rpm Hard Drive 500 GB 7200rpm Self-Encrypting Drive (Opal 2) 1 TB 5400rpm Hard Drive 500 GB Hybrid, 8 GB cache

Mini Card Solid State Drive

M.2 (NGFF) 2280 Solid State Drive
128 GB SATA-3 TLC Solid State Drive
180 GB SATA-3 MLC Solid State Drive
180 GB SATA-3 Self-Encrypting (Opal 2) MLC Solid State Drive
240 GB SATA-3 MLC Solid State Drive
256 GB SATA-3 TLC Solid State Drive
256 GB SATA-3 Self-Encrypting (Opal 2) MLC Solid State Drive
256 GB PCIe-3x4 NVMe Solid State Drive
512 GB SATA-3 TLC Solid State Drive
512 GB SATA-3 Self-Encrypting (Opal 2) MLC Solid State Drive

NOTE: For Solid State Drives or Hard Drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and up to 30 GB (for Windows 8.1 and 10) is reserved for system recovery software.

HP 3D DriveGuard (Windows and Hard Drives only)

The hard drive is mounted directly to the notebook frame, reducing the transmission of shock to the hard drive

Dual Drive Configuration

System can be configured with a hard drive and M.2 SSD drive.¹

1. Not available for the Hybrid Hard Drive and not supported on 820 G3.

MEMORY

Standard

DDR4 PC4-17000 (Transfer rates up to 2133 MT/s) Two SODIMM slots supporting dual-channel memory Both slots are customer accessible / upgradeable

Supports the following configurations

4096 MB Total System Memory (4096 MB x 1) 8192 MB Total System Memory (4096 MB x 2) 8192 MB Total System Memory (8192 MB x 1) 16384 MB Total System Memory (8192 MB x 2) 16384 MB Total System Memory (16384 MB x 1) (HP EliteBook 840 and 850 only) 32768 MB Total System Memory (16384 MB x 2) (HP EliteBook 840 and 850 only)

Maximum HP EliteBook 820

Up to 16 GB

HP EliteBook 840 and 850

Up to 32 GB

Dual-channel



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Features

Maximized dual-channel performance requires SODIMMs of the same size and speed in both memory slots.

NOTE: Improved system performance when memory is added in pairs (dual channel). Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

NETWORKING/COMMUNICATIONS

Wireless

Support for a broad range of secure, integrated wireless LAN and wireless WAN options featuring support for the latest industry standards. Optional Broadband Wireless (WWAN) requires a Windows operating system and is available in select countries as a standard, factory configurable feature only. Integrated Bluetooth® is also available (factory configurable only) and can be combined with any of the supported wireless LAN and wireless WAN options.

Broadband Wireless (WWAN)

HP lt4120 Qualcomm[®] Snapdragon X5 LTE Mobile Broadband Module ^{1,3} HP hs3110 HSPA+ Intel[®] Mobile Broadband Module^{1,2}

Note: The HP EliteBook 850 G3 UHD panel is not compatible with WWAN.

Wireless LAN (WLAN) Via M.2 Minicard

Intel® Dual Band Wireless-AC 8260 802.11 a/b/g/n/ac (2x2) WiFi and Bluetooth® 4.2 combo (vPro)² Intel® Dual Band Wireless-AC 8260 802.11 a/b/g/n/ac (2x2) WiFi and Bluetooth® 4.2 combo (non-vPro)² Intel® Wireless-AC 3165 802.11 a/b/g/n/ac (1x1) WiFi and Bluetooth® 4.0 combo (non-vPro)²

Near Field Communication (NFC)¹

HP Module with NXP NFC Controller NPC100

Support for Miracast

- 1. Sold separately or as an optional feature.
- 2. Wireless access point and Internet service is required and is not included. Availability of public wireless access points limited.
- 3. WWAN module requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

Communications

Intel® Ethernet Connection I219-V 10/100/1000 Ethernet (with Intel® i3-6100U, i5-6200U, and i7-6500U) Intel® Ethernet Connection I219-LM 10/100/1000 Ethernet (with Intel® i5-6300U and i7-6600U)

NOTE: The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

AUDIO/MULTIMEDIA

Audio

Audio by Bang & Olufsen



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Features

HP Clear Sound Amp HP Noise Reduction Software Digital Microphones (Dual Array) 2 Premium Stereo Speakers

Webcam

Optional¹ 720p HD² webcam³

- 1. Sold separately or as an optional feature.
- 2. HD content required to view HD images.
- 3. Internet access required.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

HP Premium Keyboard

The HP spill-resistant keyboard with drain is designed using a thin layer of Mylar film under the keyboard and includes an all-metal keyboard deck for greater rigidity. The 820 has 79/80-key, 840 has 85-86-key, the 850 has 100/101-key compatible keyboard features a full-pitch key layout with desktop keyboard features, such as editing keys, both left and right control and alt keys, and function keys.

US and International key layouts are available. Backlit keyboard with HP DuraKeys available as an option.

Pointing Devices

Glass Touchpad On/Off button Taps enabled as default

Gestures enabled by default - 2 Finger Scrolling, 2 Finger Zoom (Pinch)

Buttons and Function Keys

HP EliteBook 820

F1 - Sleep

F2 - Blank

F3 – Keyboard Backlit toggle

F4 - Display switching

F5 - Brightness Down

F6 - Brightness Up

F7 - Speaker Mute

F8 - Volume Down

F9 - Volume Up

F10 - Mic Mute

F11 - Wireless

F12 - Num Lock

HP EliteBook 840

F1 - Sleep

F2 - Blank

F3 - Keyboard Backlit toggle

F4 - Display switching

F5 - Brightness Down

F6 - Brightness Up



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Features

F7 - Blank

F8 - Volume down

F9 - Volume up

F10 - Mic mute

F11 - Blank

F12 – Num Lock

HP EliteBook 850

F1 - Sleep

F2 - Blank

F3 - Backlit toggle

F4 - Display switching

F5 - Brightness Down

F6 - Brightness Up

F7 - Blank

F8 - Volume down

F9 - Volume up

F10 - Mic mute

F11 - Blank

F12 - Blank

Hidden Function Keys

Fn+R - Break

Fn+S - Sys Rq

Fn+C - Scroll Lock

SOFTWARE AND SECURITY

Preinstalled Software BIOS

HP BIOSphere¹

HP Sure Start

HP DriveLock | HP Automatic DriveLock

HP BIOS Protection²

BIOS Update via Network

Master Boot Record Security

Power On Authentication

Pre-Boot Security

Secure Erase³

Hybrid Boot

Measure Boot

HP SpareKey

Pre-boot Authentication

Multi Media

Cyberlink Power DVD, BD

Cyberlink YouCam BE (Windows 7 only)



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Features

Communication

HP GPS and Location (Windows 7 only)⁵

HP Connection Manager with support for HP Mobile Connect Pro (Windows 7 only)⁶

HP Mobile Connect Pro (Windows 8.1 and Windows 10 only)⁶

Intel® Wireless Display (WiDi) Software for Windows7

Native Miracast Support8

HP Value Add Software

HP 3D DriveGuard (requires Windows)

HP ePrint Driver9

HP Hotkey Support

HP Recovery Manager

HP Recovery Disc Creator

HP Registration App (Windows 8.1 only)

HP Support Assistant

HP Noise Reduction Software

3rd Party

Foxit PhantomPDF Express for HP

Microsoft Products

Buy Office

Bing Search

Skype¹⁰

Manageability

HP Driver Packs¹¹

HP SoftPaq Download Manager (SDM)

HP System Software Manager (SSM)¹¹

HP BIOS Config Utility (BCU)11

HP Client Catalog¹¹

HP CIK for Microsoft SCCM¹¹

HP Image Assistant¹¹

LANDESK Management¹²

For more information on HP Client Management Solutions refer to: http://www.hp.com/go/clientmanagement.

Client Security Software

HP Client Security

- HP Security Manager (including Credential Manager and Password Manager)
- HP Drive Lock
- HP Fingerprint Sensor



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Features

- HP Password Manager
- Absolute Persistence Module⁴
- Power On Authentication

Microsoft Security Essentials¹³ Microsoft Defender

Security

Trusted Platform Module (TPM) 1.2 (Infineon SLB9670). Common Criteria EAL4+ Certified.

Upgradable to TPM 2.0. Convertible to FIPS 140-2 Certified mode. (TPM 2.0 is not available for Win 7 32-bit.)¹⁴

HP Fingerprint Reader (On select models)

For more information on HP Client Security Software Suite, refer to http://www.hp.com/go/clientsecurity.

- 1. Available only on business PCs with HP BIOS.
- 2. May require a manual recovery step if all copies of BIOS are compromised or deleted
- 3. For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88.
- 4. Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: http://www.absolute.com/company/legal/agreements/ computrace-agreement. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.
- 5. GPS access requires an unobstructed path to multiple satellites. Performance may be affected if/when used inside of buildings, bridges or heavily congested metropolitan areas. Requires separately purchased GPS navigation software available from multiple GPS applications.
- 6. HP Mobile Connect Pro is only available on preconfigured devices with WWAN. For geographic availability refer to http://www.hp.com/go/mobileconnect
- 7. Integrated Intel Wi-Di feature is available on select configurations only and requires separately purchased projector, TV or computer monitor with an integrated or external Wi-Di receiver. External Wi-Di receivers connect to the projector, TV or computer monitor via a standard HDMI cable, also sold separately.
- 8. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming media players that also support Miracast. You can use Miracast to share what you're doing on your PC and present a slide show. For more information: http://windows.microsoft.com/en-us/windows-8/project-wireless-screen-miracast
- 9. Requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see http://www.hp.com/go/eprintcenter). Requires optional broadband module. Broadband use requires separately purchased service contract. Check with service provider for coverage and availability in your area. Separately purchased data plans or usage fees may apply. Print times and connection speeds may vary.
- 10. Skype is not offered in China.
- 11. Not preinstalled, however available for download in December 2015 at http://www.hp.com/go/clientmanagement
- 12. Subscription required.
- 13. Opt in and internet connection required for updates.
- 14. Upgrade utility is expected to be available by the second half of 2016 via HP Customer Support.

POWER

HP 45W Smart AC Adapter (Not available for Asia, China and India) HP 45W 2-prong DC jack AC Adapter (Japan only)



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

QuickSpecs

Features

HP 65W Smart AC Adapter (Not available for Asia, China and India; for 840 & 850 only) HP 65W Smart AC Adapter EM (Asia, China and India only)

Power cord is configurable; either 3.2 feet or 6 feet (1.0 or 1.8 meter)
Total length including external AC adapter is 9.2 feet or 12 feet (2.86 or 3.66 meter)

Battery Life

Platform	Other HW Details	Battery	UMA Graphics	Discrete Graphics
HP EliteBook 820 G3	HDD	3-cell (44WHr)	Up to 9 hrs 45 mins	N/A
HP EliteBook 820 G3	SSD	3-cell (44WHr)	Up to 12 hrs 30 mins	N/A
		Standby Time*	193 hrs	N/A
Platform	Other HW Details	Battery	UMA Graphics	Discrete Graphics
HP EliteBook 840 G3	HDD	3-cell (46WHr)	Up to 10 hrs 30 mins	N/A
HP EliteBook 840 G3	SSD	3-cell (46WHr)	Up to 13 hrs 30 mins	N/A
		Standby Time*	223 hrs	N/A
Platform	Other HW Details	Battery	UMA Graphics	Discrete Graphics
HP EliteBook 850 G3	HDD	3-cell (46WHr)	Up to 9 hrs 30 mins	Up to 9 hrs 30 mins
HP EliteBook 850 G3	SSD	3-cell (46WHr)	Up to 12 hrs 30 mins	Up to 12 hrs
		Standby Time*	223 hrs	221 hrs

^{1.} Disclaimer: Windows 10/MM14 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See www.bapco.com for additional details.

Power Conservation

Hibernation Standby ACPI compliance

Battery recharge times

	HP EliteBook 820	HP EliteBook 840 and HP EliteBook 850
Time to 90% Charge (minute) (3-16)	112 ¹	119³
Time to 100% Charge (minute) (3-16)	155²	163 ⁴



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Features

- 1. Recharges your battery up to 90% within 112 minutes when the system is off. Applies to 3-cell 44 Whr battery only. When the PC is powered on, charge time may increase and will vary based on the workload of the notebook PC.
- 2. Recharges your battery up to 100% within 155 minutes when the system is off. Applies to 3-cell 44 Whr battery only. When the PC is powered on, charge time may increase and will vary based on the workload of the notebook PC.
- 3. Recharges your battery up to 90% within 119 minutes when the system is off. Applies to 3-cell 46 Whr battery only. When the PC is powered on, charge time may increase and will vary based on the workload of the notebook PC.
- 4. Recharges your battery up to 100% within 163 minutes when the system is off. Applies to 3-cell 46 Whr battery only. When the PC is powered on, charge time may increase and will vary based on the workload of the notebook PC.

WEIGHTS & DIMENSIONS

HP EliteBook 820

Weight1

Starting at 2.78 lbs (1.26 kg)

(3-cell battery (44WHr), UMA, no FPR, 1 SODIMM, WLAN, M.2 SSD, no camera, no WWAN, Non-Touch panel) Starting at 3.08 lbs (1.39 kg)

(3-cell battery (44WHr), UMA, no FPR, 1 SODIMM, WLAN, M.2 SSD, no camera, no WWAN, FHD Touch)

Dimensions² (w x d x h)

Non-Touch

12.2 x 8.6 x 0.74 in 31 x 21.89 x 1.89 cm

Touch

12.2 x 8.6 x 0.80 in 31 x 21.89 x 2.02 cm

HP EliteBook 840

Weight1

Starting at 3.41 lbs (1.54 kg)

(3-cell battery (46WHr), UMA, no FPR, 1 SODIMM, WLAN, M.2 SSD, no camera, no WWAN, Non-Touch panel) Starting at 3.76 lbs (1.70 kg)

(3-cell battery (46WHr), UMA, no FPR, 1 SODIMM, WLAN, M.2 SSD, no camera, no WWAN, FHD Touch)

Dimensions² ($w \times d \times h$)

Non-Touch

13.3 x 9.3 x 0.74 in 33.8 x 23.7 x 1.89 cm

Touch

13.3 x 9.3 x 0.80 in 33.8 x 23.7 x 2.02 cm

HP EliteBook 850

Weight1

Starting at 4.10 lbs (1.86 kg)

(3-cell battery (46WHr), UMA, no FPR, 1 SODIMM, WLAN, M.2 SSD, no camera, no WWAN, Non-Touch panel)



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Features

Starting at 4.54 lbs (2.06 kg)

(3-cell battery (46WHr), UMA, no FPR, 1 SODIMM, WLAN, M.2 SSD, no camera, no WWAN, FHD Touch)

Dimensions² (w x d x h)

Non-Touch

15.09 x 10.10 x 0.76 in 38.33 x 25.77 x 1.94 cm

Touch

15.09 x 10.10 x 0.82 in 38.33 x 25.77 x 2.08 cm

- 1. Weight varies by configuration and components.
- 2. Height varies depending upon where on the notebook the measurement is made.

PORTS/SLOTS

Ports

(1) USB 3.0 Charging Port (1) USB 3.0 Port (1) USB Basic Type-C DisplayPort VGA RJ-45 / Ethernet Docking connector Headphone/Microphone Combo AC Port

NOTE: Cables are not included.

Slots

External SIM slot SD Media Card Reader Slot Supports SD, SDHC, SDXC

SERVICE AND SUPPORT

Limited 3-year, 1-year or 90-day limited warranty options available, depending on country. Batteries have a default one year limited warranty except for Long Life batteries which will have same 1-year or 3-year limited warranty as the platform. Optional 1 HP Care Pack Services² are extended service contracts which go beyond your standard limited warranties.

- 1. Sold separately or as an optional feature.
- 2. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. Consult the HP Customer Support Center for details. http://h20000.www2.hp.com/bizsupport/TechSupport/ProductRoot.jsp



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Features



SYSTEM UNIT

TBD

DISPLAYS

12.5" diagonal LED backlight HD Slim eDP SVA Anti-glare (1366 x 768) **Outline Dimensions**

291.0 x181.9mm(max) X 3.0(max) mm

 $(W \times H \times D)$

Active Area 276.615mm x 155.52mm

Weight 250g max.

Diagonal Size 12.5"

Surface Treatment AG

Contrast Ratio 300:1 (typ) - AG

Refresh Rate60HzResponse time16ms typ.Pixel Per Inch (PPI)125Brightness220nits

Pixel Resolution Format 1366 x 768 (HD)
Configuration RGB Stripe

Interface eDP 1.2 (1 lane)

LCD Mode TN

Viewing Angle SVA 40/40/15/30

12.5" diagonal LED backlight FHD UltraSlim eDP UWVA Anti-glare (1920 x 1080) **Outline Dimensions**

282.7 x 179.82 (max) x 2.3 (max) mm

(W x H x D)

Active Area 276.48 typ. (W) x 155.52 typ. (H)

Weight 170 max
Diagonal Size 12.5"
Surface Treatment AG

Contrast Ratio 600:1 (typ) - AG

Refresh Rate60HzResponse time25ms typ.Pixel Per Inch (PPI)176Brightness300nits

Pixel Resolution Format 1920 x 1080 (FHD)

Configuration RGB Stripe

Interface eDP 1.3 (2 lane)
LCD Mode IPS/FFS/VA

Viewing Angle UWVA 85/85/85



12.5" diagonal LED backlight FHD UltraSlim eDP UWVA (1920 x 1080) Touch with camera **Outline Dimensions**

282.7 x 179.82 (max) x 2.3 (max) mm

(W x H x D)

Active Area

276.48 typ. (W) x 155.52 typ. (H)

Weight 170 max
Diagonal Size 12.5"
Touch Enabled Yes

TSP Type Capacitive

Surface Treatment AG

Contrast Ratio 600:1 (typ) - AG

Refresh Rate60HzResponse time25ms typ.Pixel Per Inch (PPI)176Brightness300nits

Pixel Resolution Format 1920 x 1080 (FHD)

Configuration RGB Stripe

Interface eDP 1.3 (2 lane)
LCD Mode IPS/FFS/VA

Viewing Angle UWVA 85/85/85

14.0" diagonal LED backlight HD Slim eDP SVA Anti-glare (1366 x 768) **Outline Dimensions**

320.9 x 205.6 (max) x 3.0mm max

 $(W \times H \times D)$

Active Area 309.4 x 173.95
Weight <290 max.
Diagonal Size 14.0"
Surface Treatment AG

Contrast Ratio 300:1 (typ) - AG

Refresh Rate60HzResponse time16ms typ.Pixel Per Inch (PPI)112Brightness220nits

Pixel Resolution Format 1366 x 768 (HD)
Configuration RGB Stripe

Interface eDP 1.2 (1 lane)

LCD Mode TN

Viewing Angle SVA 40/40/15/30



14.0" diagonal LED backlight FHD Slim eDP **SVA Anti-glare** (1920 x 1080)

Outline Dimensions $(W \times H \times D)$

320.9 x 205.6 (max) x 3.0(max) mm

Active Area 308.851x173.73 Weight <270 max 14" **Diagonal Size**

Surface Treatment AG

Contrast Ratio 300:1 (typ) - AG

Refresh Rate 60Hz **Response time** 16ms typ. Pixel Per Inch (PPI) 157 **Brightness** 300nits

Format 1920 x 1080 (FHD) **Pixel Resolution**

Configuration **RGB Stripe**

Interface eDP 1.2 (2 lane)

LCD Mode TN

SVA 40/40/15/30 **Viewing Angle**

14.0" diagonal LED backlight QHD UltraSlim eDP UWVA Anti-glare (2560 x 1440)

Outline Dimensions

 $(W \times H \times D)$

320.4± 0.5 x 198.6±0.5 mm typ. (w/PCB)

Active Area 309.504 mmx 174.096mm

Weight 270g max **Diagonal Size** 14.0" **Surface Treatment** Anti-Glare **Contrast Ratio** 600:1 (typ.) **Refresh Rate** 60Hz Response time 25ms typ. Pixel Per Inch (PPI) 210

Brightness 340 nits typ

Format 2560x1440 **Pixel Resolution** Configuration **RGB**

Interface eDP 1.3 + PSR

LCD Mode IPS

UWVA 85/85/85/85 **Viewing Angle**



14.0" diagonal LED backlight FHD Slim eDP SVA (1920 x 1080) Touch Active Area with camera

Outline Dimensions

320.9 x 205.6 (max) x 3.0(max) mm

 $(W \times H \times D)$

308.851x173.73

Weight

270g max

Diagonal Size Surface Treatment 14" AG

Touch Enabled

Yes

TSP Type

Capacitive

Contrast Ratio Refresh Rate

300:1 (typ) - AG

Response time

TBD

Pixel Per Inch (PPI)

16ms typ.

Brightness

157 300nits

Format

1920 x 1080 (FHD)

RGB Stripe

Pixel Resolution

Configuration

eDP 1.2 (2 lane)

Interface **LCD Mode**

TN

Viewing Angle

SVA 40/40/15/30

15.6" diagonal LED backlight HD Slim eDP SVA Anti-glare (1366 x 768)

Outline Dimensions

 $(W \times H \times D)$

360.0 x 224.3 x 3.2mm max

Active Area Weight **Diagonal Size** 344.2 x 193.5 370q max

Surface Treatment

15.6" AG

Contrast Ratio

300:1 (typ) - AG

Refresh Rate

60Hz

Response time Pixel Per Inch (PPI) 16ms typ.

101

Brightness

220 nit typ

Pixel Resolution

Format

1366 x 768 (HD)

Configuration

RGB Stripe

Interface **LCD Mode** eDP 1.2 (1 lane)

TN

Viewing Angle

SVA 40/40/15/30



15.6" diagonal LED backlight FHD Slim eDP SVA Anti-glare (1920 x 1080) **Outline Dimensions** (W x H x D)

360.0 x 224.3 x 3.2 mm max

Active Area

344.16 x 193.59 mm

Weight 360 max.

Diagonal Size 15.6"

Surface Treatment AG

Contrast Ratio400:1 (typ)Refresh Rate60HzResponse time16ms typ.Pixel Per Inch (PPI)142Brightness300nits

Pixel Resolution

Format 1920 x 1080 (FHD)

Configuration RGB Stripe

Interface eDP 1.2 (2 lane)

LCD Mode TN

Viewing Angle SVA 45/45/25/35

15.6" diagonal LED backlight UHD Slim eDP UWVA Anti-glare (3840 x 2160) **Dimensions (W x H)** 13.62 x 7.59 in (3.6 x 19.4 cm)

Diagonal Size15.6 in (39.6 cm)Weight345 g (max)Surface TreatmentAnti-glareContrast Ratio1000:1 (typ)Refresh Rate60 Hz

Brightness 340 nit typical

Pixel Resolution Pitch 0.090 x 0.090 mm

Format 3840x2160
Configuration RGB Stripe

Backlight LED PPI 282

Viewing Angle 80° Horizontal, ±80° Vertical (minimum)

80/80/80 (Left/Right/Down/Up) (min)



15.6" diagonal LED backlight FHD Slim eDP SVA (1920 x 1080) Touch with Camera **Outline Dimensions**

360.0 x 224.3 x 3.2 mm max

(W x H x D)

Active Area 344.16 x 193.59 mm

Weight 360 max.

Diagonal Size 15.6"

Surface Treatment AG/BV

Contrast Ratio 500:1 (typ) - BV, 400:1 (typ) - AG

Touch Enabled Yes

TSP Type Capacitive
Refresh Rate 60Hz
Response time 16ms typ.
Pixel Per Inch (PPI) 142
Brightness 300nits

Pixel Resolution Format 1920 x 1080 (FHD)

Configuration RGB Stripe

Interface eDP 1.2 (2 lane)

LCD Mode TN

Viewing Angle SVA 45/45/25/35

Note: All display specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

STORAGE AND DRIVES

500 GB 7200rpm Self Encrypting Drive (FIPS-140-2) (Opal 2) **Drive Weight** 0.21 lbs (95 g)

Capacity 500 GB

 Height
 0.28 in (7 mm)

 Width
 2.75 in (69.85 mm)

 Interface
 ATA-8, SATA 3.0

Transfer RateSynchronous (maximum)600 MB/sSeek TimeSingle Track1.5 ms(typical reads, includingAverage12ms

settling) Maximum 18mm-22ms

Cache32GBRotational Speed7200 rpmLogical Blocks976,773,168

Operating Temperature 32° to 140° F (0° to 60° C) [top cover temp]

Features ATA Security; TCG Opal 2.x, FIPS, S.M.A.R.T., NCQ, Ultra DMA ,



500 GB 7200rpm Hard Drive **Drive Weight** 0.20 lbs (92 g)-0.21 lbs (95 g)

 Capacity
 500 GB

 Height
 0.28 in (7 mm)

 Width
 2.75 in (69.85 mm)

 Interface
 ATA-8, SATA 3.0

Transfer Rate Synchronous (maximum) 600 MB/s

Seek Time Single Track 1.5ms-2.0ms
(typical reads, including settling) Maximum 18ms-22ms

Cache32GBRotational Speed7200 rpmLogical Blocks976,773,168

Operating Temperature 32° to 140° F (0° to 60° C) [case temp]

Features ATA Security

500 GB 7200rpm Self- Drive We Encrypting Drive (Opal 2) Capacity

Drive Weight 0.21 lbs (95 g)

Capacity 500GB

 Height
 0.28 in (7 mm)

 Width
 2.75 in (69.85 mm)

 Interface
 ATA-8, SATA 3.0

Transfer Rate Synchronous (maximum) 600 MB/s

Seek Time Single Track 1.5ms
(typical reads, including settling) 42 and 42 and 43 and 44 and 43 and 44 and 44

Maximum 18ms-22ms

Cache32GBRotational Speed7200rpmLogical Blocks976,773,168

Operating Temperature 32° to 140° F (0° to 60° C) [top cover temp]

Features ATA Security; TCG Opal 2.x, S.M.A.R.T., NCQ, Ultra DMA

1 TB 5400rpm Hard Drive **Drive Weight** 0.21 lbs (94 g)- 0.21 lbs (99 g)

Capacity 1TB

 Height
 0.28 in (7.2 mm)

 Width
 2.75 in (69.85 mm)

 Interface
 ATA-8, SATA 3.0

Transfer RateSynchronous (maximum)600 MB/sSeek TimeSingle Track2ms

(typical reads, including Average 12ms-13ms

settling) Maximum 18ms-23ms



CacheUp to 32GBRotational Speed5400rpmLogical Blocks1,953,525,168

Operating Temperature 32° to 140° F (0° to 60° C) [case temp]

Features S.M.A.R.T., NCQ, Ultra DMA

500 GB Hybrid, 8 GB cache
 Drive Weight
 0.21 lb (95 g)

 Capacity
 500 GB

 Height
 0.276 in (7 mm)

 Width
 2.76 in (70.1 mm)

Interface ATA-8, SATA 2.6, 6.0 Gb/s, NCQ

Transfer Rate Synchronous (maximum) 600 MB/s (Drive Capability)

Seek TimeSingle Track2 ms(typical reads, including
settling)Average12 msMaximumNIL ms

Cache64GBRotational Speed5400 rpmLogical Blocks976,773,168

Operating Temperature 32° to 140° F (0° to 60° C) [case temp]

Features ATA Security

128 GB M2 2280 SATA-3

TLC

Solid State Drive

Drive Weight 0.019 lb (8.5 g)-0.022 lb (10 g)

Capacity 128 GB

Height 0.09 in (2.23 mm)- 0.14 in (3.58 mm)

 Width
 0.87 in (22 mm)

 Interface
 ATA-8, SATA 3.0

Performance Maximum Sequential Read Maximum Sequential Write

Up to 540 MB/s Up to 300 MB/s

Logical Blocks 250,069,680

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp] **Features** ATA Security, DIPM; TRIM; DEVSLP

180 GB M2 2280 SATA-3

MLC

Solid State Drive

Drive Weight 0.022 lb (<10 g)

Capacity 180 GB

 Height
 0.09 in (2.23 mm)

 Width
 0.87 in (22 mm)

 Interface
 ATA-8, SATA 3.0

Performance Maximum Sequential Read Maximum Sequential Write

Up to 540 MB/s (Compressible UP to 490 MB/s (Compressible



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Technical Specifications

Performance) Performance)

Logical Blocks 351,651,888

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp] **Features** ATA Security, DIPM; TRIM; DEVSLP

180 GB M2 2280 SATA-3 Self-Encrypting Drive (Opal 2) MLC Solid State Drive **Drive Weight** 0.022 lb (<10 g)

Capacity 180GB

 Height
 0.09 in (2.23 mm)

 Width
 0.87 in (22 mm)

 Interface
 ATA-8, SATA 3.0

Performance Maximum Sequential Maximum Sequential Write

Read

(Compressible Performance)

Logical Blocks 351,651,888

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features ATA Security, TCG OPAL 2.x, DIPM; TRIM; DEVSLP

240 GB SATA-3 MLC Solid Drive Weight

State Drive

 Drive Weight
 0.02 lb (10 g)

 Capacity
 240 GB

 Height
 0.14 in (3.58 mm)

 Width
 0.87 in (22 mm)

 Interface
 ACS-3, SATA 3.2

Performance Maximum Sequential Maximum Sequential Write

Read

Logical Blocks 468,862,128

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp] **Features** ATA Security, DIPM; TRIM; DEVSLP

256 GB 2280 SATA-3 TLC Drive Weight Solid State Drive Canacity

Drive Weight 0.019 lb (8.5 g)- 0.022 lb (10 g)

Capacity 256GB

Height 0.09 in (2.3 mm)- 0.14 in (3.58 mm)

 Width
 0.87 in (22 mm)

 Interface
 ATA-8, SATA 3.0

Performance Maximum Sequential Maximum Sequential Write

Read

Up to 540 MB/s Up to 455 MB/s

Logical Blocks 500,118,192



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Technical Specifications

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp] **Features** ATA Security, DIPM; TRIM; DEVSLP

256 GB M2 2280 SATA-3 Self-Encrypting Drive (Opal 2) MLC Solid State Drive **Drive Weight** 0.02 lb (10 g) **Capacity** 256 GB

Height 0.14 in (3.58 mm)- 0.09 in (2.23 mm)

 Width
 0.87 in (22 mm)

 Interface
 ATA-8, SATA 3.0

Performance Maximum Sequential Maximum Sequential Write

Read

Up to 540 MB/s UP to 460 MB/s

Logical Blocks 500,118,192

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp] **Features** ATA Security; TCG Opal 2.0, DIPM; TRIM; DEVSLP

256 GB PCIe-3x4 NVMe Solid State Drive
 Drive Weight
 0.02 lb (10 g)

 Capacity
 256 GB

 Height
 0.09 in (2.3 mm)

 Width
 0.87 in (22 mm)

 Interface
 PCIe NVMe Gen3X4

Performance Maximum Sequential Maximum Sequential Write

Read

Up to 2,260 MB/s UP to 1,260 MB/s

Logical Blocks 500.118.192

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features ATA Security, TRIM; L1.2

512 GB M2 2280 TLC Solid State Drive **Drive Weight** 0.019 lb (8.5 g)- 0.02 lb (10 g)

Capacity 512 GB

 Height
 0.09 in (2.3 mm)

 Width
 0.87 in (22 mm)

 Interface
 ATA-8, SATA 3.0

Performance Maximum Sequential Maximum Sequential Write

Read

Logical Blocks 1,000,215,216

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp] **Features** ATA Security, DIPM; TRIM; DEVSLP



SECURITY

HP Fingerprint Reader (optional)

Mobile Voltage Operation 3.0V-3.6V

Operating Temperature $14^{\circ} - 167^{\circ}F (-10^{\circ} - 75^{\circ}C)$

Current Consumption

Image

36 mA peak

Low Latency Wait for

Finger

950 uA

Capture Rate 59000 lines/sec

ESD Resistance IEC 61000-4-2 4B (±15KV)

Detection Matrix 200*1 (plus another secondary line)

508 dpi

10*1 mm sensor area

Smart Card Reader

Smart card standard PC/SC 2.0 for Windows smart card standard

Dimensions (L x W x H) 0.41x 0.08 x 0.32 in (10.5 x 2 x 8.2 mm)

Smart Card support ISO 7816 Class A and AB smart cards

Smart Card Interface Smart Card Interface with T = 0 and T = 1 support

Support I2C memory card, SLE4418, SLE4428, SLE4432, SLE4442, SLE4436,

SLE5536, SLE6636, AT88SC1608, AT45D041 card and AT45DB041 card via

external EEPROM

Operating systems No driver is required for this device. Native support is provided by the operating

system.

Power Normal Mode With card present, before being suspended: 40.9 mA

Without card present, before being suspended: 33.16 mA After being suspended with smart card present: 380 μ A After being suspended without smart card present: 380 μ A



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Technical Specifications

Power Saving With card present, before being suspended: 40.6 mA

Without card present: 380 µA

Mode After being suspended with smart card present: 380 μA

Features

Support single slot

Support T0, T1 protocol

 Support I2C memory card, SLE4418, SLE4428, SLE4432, SLE4442, SLE4436,

 SLE5536, SLE6636, AT88SC1608, AT45D041 card and AT45DB041 card via external EEPROM

Support ISO7816 Class A, B and C (5V/3V/1.8V) card

 Implemented as an USB full speed device with bulk transfer endpoint, Mass

· Storage endpoint

Built-in PLL for USB and Smart Card clocks requirement

 Support EEPROM for USB descriptors customization (PID/VID/ iManufacturer/iProduct/Serial Number), Direct Web Page Link, and accessing memory card module.

EEPROM programmable via USB interface

Support software update for memory card module

Support Direct Web Page Link via configuration in external EEPROM

Support short APDU and extended APDU

Compatible with Microsoft USB-CCID driver

Support remote wake up through inserting card/removing card

Support USB selective suspend

 Support Power Saving Mode (Using one pin to select between Normal/PWR Saving Mode)

Support card power over current protection mechanism

Built in resonator.

Support USB LPM (Link Power Management) features.

Embedded clock source.

NETWORKING/COMMUNICATIONS

HP hs3110 HSPA+ Intel® Mobile Broadband Module*

Technology/Operating

HSPA+: 2100 (Band 1), 1900 (Band 2), 1700 (Band 4), 850 (Band 5), 900 (Band 8) MHz

bands E-GPRS: 1900 (Band 2), 1800 (Band 3), 850 MHz (Band 5), 900 (Band 8) MHz

Wireless protocol WCDMA R99, 3GPP Release 5, 6 and 7 UMTS Specification



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Technical Specifications

standards E-GPRS: Class B, Multi-slot class 33, coding schemes CS1 - CS4 and MSC1 - MSC9

GPS Standalone, A-GPS

GPS bands 1575.42 MHz ± 1.023 MHz

Maximum data rates HSPA+: 21.6 Mbps (Download), 5.76 Mbps (Upload)

E-GPRS: 296 kbps (Download), 236.8 kbps (Upload) GPRS: 107 kbps (Download), 85.6 kbps (Upload)

Maximum output power HSPA+: 24 dBm

E-GPRS 1800/1900: 26 dBm E-GPRS 850/900: 27 dBm GPRS 1800/1900: 30 dBm GPRS 850/900: 33 dBm

Maximum output power HSPA+: 24 dBm

E-GPRS 1800/1900: 26 dBm E-GPRS 850/900: 27 dBm GPRS 1800/1900: 30 dBm GPRS 850/900: 33 dBm

Maximum power consumption

HSPA+: 1,100 mA (peak); 800 mA (average)

E-GPRS: 2,800 mA (peak); 700 mA (average)

Form Factor M.2, 3042-S3 Key B

Weight 6 g

Dimensions (Length x Width x Thickness) 1.65 x 1.18 x 0.09 in (42 x 30 x 2.3 mm)

* Mobile Broadband is an optional feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors.

HP lt4120 Qualcomm® Snapdragon™ X5 LTE Mobile Broadband Module

Technology/Operatin LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3),



g bands

1700/2100 (Band 4), 850 (Band 5), 2600 (Band 7), 900 (Band 8),

700 (Band 12 lower), 700 (Band 13 upper), 700 (Band 17 lower),

800 (Band 20), 700 (Band 28).

HSPA+: 2100 (Band 1), 1900 (Band 2), 1700/2100 (Band 4),

850 (Band 5), 900 (Band 8) MHz

EV-DO: 850 (BCO), 1900 (BC1) MHz (Only work with Verizon network)

E-GPRS: 1900 (Band 2), 1800 (Band 3), 850 (Band 5), 900 (Band 8)

MHz

Wireless protocol standards

3GPP Release 10 LTE Specification CAT.4, 20MHz BW WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification

1xEVDO Release 0, A and B.

E-GPRS: Class B, Multi-slot class 12, coding schemes CS1 - CS4

and MSC1 - MSC9

GPS Standalone, A-GPS (MS-A, MS-B and XTRA)

GPS bands 1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz

Maximum data rates LTE: 150 Mbps (Download), 50 Mbps (Upload)

DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload)

HSPA+: 21Mbps (Download), 5.76 Mbps (Upload)

CDMA 1xRTT: 153.6 kbps (Download), 153.6 kbps (Upload)

EVDO Rel.A: 3.1 Mbps (Download), 1.8 Mbps (Upload)

EVDO Rel.B: 14.7 Mbps (Download), 5.4Mbps (Upload)

EDGE: 236.8 kbps (Download), 236.8 kbps (Upload)

GPRS: 85.6 kbps(Download), 85.6 kbps (Upload)

Maximum output power

LTE: 23 dBm

HSPA+: 23.5 dBm



1xRTT/EVD0: 24dBm

E-GPRS 1900/1800: 26 dBm

E-GPRS 900/850: 27 dBm

GPRS 1900/1800: 29.5 dBm

GPRS 900/850: 32.5 dBm

Maximum power consumption

LTE: 1,200 mA (peak); 900 mA (average)

HSPA+: 1,100 mA (peak); 800 mA (average)

1xRTT/EVDO: 1,000 mA (peak); 700 mA (average)

E-GPRS: 2,800 mA (peak); 500 mA (average)

Dimensions (Length x Width x Thickness)

42 x 30 x 2.3 mm

Intel® Dual Band Wireless-N 8260AC 802.11 a/b/q/n (2x2) WiFi + Bluetooth 4.2 Combo Adaptor* (vPro)

Wireless LAN IEEE 802.11a **Standards** IEEE 802.11b IEEE 802.11g IEEE 802.11n

Interoperabilit Wi-Fi certified

Frequency

802.11b/g/n 2.402 - 2.482 GHz

Band

Note: The FCC has declared as of January 1, 2015 products that utilize passive scanning on channel 12/13 and are

capable of transmitting must fully comply with

requirements of 15.247 or otherwise disable those channels

802.11a 4.9 - 4.95 GHz (Japan)

> 5.15 - 5.25 GHz 5.25 - 5.35 GHz 5.47 - 5.725 GHz



^{*} Mobile Broadband is an optional feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products or in all countries.

5.825 - 5.850 GHz

Note: Indonesia only supports 5.725 - 5.825 GHz

(CH149 - CH161)

Antenna Structure 2 transmit; 2 receive (2x2)

Data Rates

802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

802.11b: 1, 2, 5.5, 11 Mbps

802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)

Modulation

Direct Sequence Spread Spectrum CCK, BPSK, QPSK, 16-QAM, 64-QAM

Security¹

- IEEE and Wi-Fi compliant 64 / 128 bit WEP encryption for a/b/g mode only
- AES-CCMP: 128 bit in hardware
- 802.1x authentication
- WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.
- WPA2 certification
- IEEE 802.11i
- Cisco Certified Extensions, all versions through CCX4 and CCX Lite

Sub-channels Multinational support with frequency bands and channels compliant to local regulations

• WAPI

Network

Ad-hoc (Peer to Peer)

Architecture Models Infrastructure (Access Point Required)

Roaming IEEE 802.11 compliant roaming between band Access Points

Output Power²

- 802.11b: +16dBm minimum
- 802.11g: +14dBm minimum
- 802.11a:+14dBm minimum
- 802.11n HT20(2.4GHz): +13dBm minimum
- 802.11n HT40(2.4GHz): +13dBm minimum
- 802.11n HT20(5GHz): +12dBm minimum
 802.11n HT40(5GHz): +12dBm minimum

Transmit: 2.0 Watts (max)

Power Trans **Consumption** Recei

Receive: 1.6 Watts (max)

Idle mode³ (PSP): 180 mW (WLAN Associated)
Idle mode: 60 mW (WLAN unassociated)

Radio off: 30 mW

Power

ACPI and PCI Express compliant power management



Management 802.11 compliant power saving mode

Receiver 802.11b, 1Mbps: -94dBm maximum **Sensitivity**⁴ 802.11b, 11Mbps: -86dBm maximum

802.11g, 6Mbps: -88dBm maximum 802.11g, 54Mbps: -74dBm maximum 802.11a, 6Mbps: -86dBm maximum 802.11a, 54Mbps: -72dBm maximum 802.11n, MCS07: -69dBm maximum 802.11n, MCS15: -66dBm maximum

Antenna Type High efficiency antenna with spatial diversity, mounted in the display enclosure

Two embedded dual band 2.4/5 GHz antennas are provided to the card to

support WLAN MIMO and Bluetooth communications

Form Factor PCI-Express M.2 MiniCard

Dimensions Type 2230 : 2.3 x 22.0 x 30.0 mm

0r

Type 1630: 2.3 x 16.0 x 30.0 mm

Weight Type 2230 : 2.8g

0r

Type 1630: 2g

Operating Voltage

3.3v +/- 9%

Temperature Operating 14° to 158° F (-10° to 70° C)

-40° to 176° F (-40° to 80° C)

Non-operating

Humidity Operating 10% to 90% (non-condensing)

Non-operating 5% to 95% (non-condensing)

Altitude Operating Non-operating 0 to 10,000 ft (3,048 m)

0 to 50,000 ft (15,240 m)

LED Activity LED Off - Radio OFF; Solid LED On - Radio ON

1. Check latest software/driver release for updates on supported security features.



- 2. Maximum output power may vary by country according to local regulations.
- 3. In Power Save Polling mode and on battery power.
- 4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CCK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
- 5. WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows XP. WLAN may also be compatible with certain third-party software supplicants. WLAN supplier IHV extensions required for Cisco Compatible Extensions support for Microsoft Windows Vista.

Intel® Dual Band Wireless- Wireless LAN Standards IEEE 802.11a

N 8260AC 802.11 a/b/g/n

 (2x2) WiFi + Bluetooth 4.2
 IEEE 802.11b

 Combo Adaptor* (non-vPro)
 IEEE 802.11g

 IEEE 802.11n
 IEEE 802.11ac

Interoperability Wi-Fi certified

Frequency Band 802.11b/g/n

2.402 - 2.482 GHz

Note: The FCC has declared as of January 1, 2015 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels

802.11a

- 4.9 4.95 GHz (Japan)
- 5.15 5.25 GHz
- 5.25 5.35 GHz
- 5.47 5.725 GHz
- 5.825 5.850 GHz

Note: Indonesia only supports 5.725 - 5.825 GHz (CH149 - CH161)

Antenna Structure 2 transmit; 2 receive (2x2)

Data Rates 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

802.11b: 1, 2, 5.5, 11 Mbps

802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

802.11n: card will support rates for NSS=1 and NSS=2 for RX and TX for 20



and 40 MHz channels. Short and long guard interval shall be supported.

802.11ac: MCSO ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)

Modulation Direct Sequence Spread Spectrum

BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM

Security¹

 IEEE and Wi-Fi compliant 64 / 128 bit WEP encryption for a/b/g mode only

AES-CCMP: 128 bit in hardware

802.1x authentication

WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.

WPA2 certification

IEEE 802.11i

Cisco Certified Extensions, all versions through CCX4 and CCX Lite

WAPI

Network Architecture

Models

Ad-hoc (Peer to Peer)

Infrastructure (Access Point Required)

Roaming IEEE 802.11 compliant roaming between access points

Output Power²

802.11b:+16dBm minimum
 802.11g:+14dBm minimum
 802.11a:+14dBm minimum

802.11n HT20(2.4GHz): +13dBm minimum
 802.11n HT40(2.4GHz): +13dBm minimum
 802.11n HT20(5GHz): +12dBm minimum
 802.11n HT40(5GHz): +12dBm minimum

802.11ac 80MHz(5GHz): +11dBm minimum

Power Consumption Transmit: 2.0 W (max)

Receive: 1.6 W (max)

Idle mode (PSP): 180 mW (WLAN Associated)
Idle mode: 60 mW (WLAN unassociated)

Radio disabled: 30 mW

Power Management ACPI and PCI Express compliant power management

802.11 compliant power saving mode

Receiver Sensitivity³ 802.11g:-90 dBm (6 Mbps), -89 dBm (9 Mbps), -87 dBm (12 Mbps), -85 dBm

(18 Mbps), -82 dBm (24 Mbps), -79 dBm (36 Mbps), -76 dBm (48 Mbps), -74

dBm (54 Mbps)

802.11b:-95 dBm (1 Mbps), -93 dBm (2 Mbps), -91 dBm (5.5 Mbps), -88 dBm

(11 Mbps)



802.11q:-90 dBm (6 Mbps), -89 dBm (9 Mbps), -87 dBm (12 Mbps), -85 dBm

(18 Mbps), -82 dBm (24 Mbps), -79 dBm (36 Mbps), -76 dBm (48 Mbps), -74

dBm (54 Mbps)

802.11n:-69 dBm (150 Mbps), -66 dBm (300 Mbps)

Antenna type High efficiency antenna with spatial diversity, mounted in the display

enclosure

Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications

Form Factor PCI-Express Half-MiniCard

Dimensions 0.134 x 1.06 x 1.18 in (3.4 x 26.8 x 30 mm)

Weight 3.1g

Operating Voltage 3.3v +/- 9%

Temperature Operating 14° to 158° F (-10° to 70° C)

> -40° to 176° F (-40° to 80° C) Non-operating

Humidity Operating 10% to 90% (non-condensing)

> 5% to 95% (non-condensing) Non-operating

Altitude Operating 0 to 10,000 ft. (3,048 m)

> 0 to 50,000 ft. (15,240 m) Non-operating

LED Activity LED Amber - Radio OFF; LED White - Radio ON

- 1. Check latest software/driver release for updates on supported security features.
- 2. Maximum output power may vary by country according to local regulations.
- 3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

HP Integrated Module with Bluetooth 4.0+EDR Wireless Technology

Bluetooth Specification 4.2+EDR Compliant

Frequency Band 2402 to 2480 MHz

Number of Available 79 (1 MHz) available channels

Channels



Data Rates and Throughput 3 Mbps data rate; throughput up to 2.17 Mbps

Synchronous Connection Oriented links up to 3, 64 kbps, voice channels

Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric or

1306.9 kbps symmetric

Transmit Power The Bluetooth component shall operate as a Class II Bluetooth device with a

maximum transmit power of +4 dBm for BR and EDR

Receiver Sensitivity Better than -20 dBM at 0.1 % raw bit error rate

Power Consumption Peak (Tx) 330 mW

Peak (Rx) 230 mW

Selective Suspend 17 mW

Antenna Internally integrated within module

Range Up to 33 ft. (10 m)

Electrical Interface USB 2.0 compliant

Microsoft Windows Plug and Play compliant

Bluetooth Software

Supported

Broadcom Bluetooth for Windows

Microsoft Windows Bluetooth Software

Link Topology Point to Point, Multipoint Pico Nets up to 7 slaves

Security Full support of Bluetooth Security Provisions

Power Management Microsoft Windows ACPI, and USB Bus Support

Self-configurable to optimize power conservation in all operating modes,

including Standby, Hold, Park, and Sniff

Certifications All necessary regulatory approvals for supported countries, including:

FCC (47 CFR) Part 15C, Section 15.247 & 15.249

ETS 300 328, ETS 300 826

Low Voltage Directive IEC950



UL, CSA, and CE Mark

Bluetooth Profiles
Supported

Serial Port Profile (SPP)¹

Service Discovery Application Profile (SDAP)

Dial-Up Networking (DUN)1,2

Generic Object Exchange Profile (GOEP)^{1,2}

Object Push Profile (OPP)^{1,2} File Transfer Profile (FTP) Synchronization Profile (SYNC)

Hard Copy Cable Replacement (HCRP)^{1,2} Personal Area Networking Profile (PAN)^{1,2} Human Interface Device Profile (HID)^{1,2}

FAX Profile (FAX)

Basic Imaging Profile (BIP)² Headset Profile (HSP) Hands Free Profile (HFP)

Advanced Audio Distribution Profile (A2DP)

- 1. Indicates the profile is supported by Microsoft Windows XP SP2
- 2. Indicates the profile is part of Windows Vista
- * Wireless access point and internet service required. Availability of public wireless access points limited.

Intel Dual Band Wireless- Wireless LAN AC 3160 802.11 ac (1x1) Standards WiFi and Bluetooth 4.0 Combo Adapter (non-vPro)

IEEE 802.11a

IEEE 802.11b IEEE 802.11g

IEEE 802.11n

IEEE 802.11ac

Interoperability Wi-Fi certified

Frequency Band 802.11b/g/n

2.402 – 2.482 GHz

Note: The FCC has declared as of January 1, 2015 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.



Technical Specifications

802.11a/n

- 4.9 4.95 GHz (Japan)
- 5.15 5.25 GHz
- 5.25 5.35 GHz
- 5.47 5.725 GHz
- 5.825 5.850 GHz

Note: Indonesia only supports 5.725 - 5.825 GHz (CH149 - CH161)

Data Rates

- 802.11b: 1, 2, 5.5, 11 Mbps
- 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
- 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
- 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)
- 802.11ac: MCS0 ~ MCS7, (1SS) (20MHz, 40MHz, and 80MHz)

Modulation

Direct Sequence Spread Spectrum

BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM

Security¹

- IEEE and Wi-Fi compliant 64 / 128 bit WEP encryption for a/b/g mode only
- AES-CCMP: 128 bit in hardware
- 802.1x authentication
- WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.
- WPA2 certification
- IEEE 802.11i
- Cisco Certified Extensions, all versions through CCX4 and CCX Lite
- WAPI

Network Architecture Ad-hoc (Peer to Peer)

Models Infrastructure (Access Point Required)

Roaming

IEEE 802.11 compliant roaming between access points

Output Power²

- 802.11b: +16dBm minimum
- 802.11g: +14dBm minimum
- 802.11a: +14dBm minimum
- 802.11n HT20(2.4GHz): +13dBm minimum
- 802.11n HT40(2.4GHz): +13dBm minimum
- 802.11n HT20(5GHz): +12dBm minimum
- 802.11n HT40(5GHz): +12dBm minimum 802.11ac 80MHz(5GHz): +11dBm minimum
- **Power Consumption** Transmit: 2.0 W (max)

Receive: 1.6 W (max)

Idle mode (PSP): 180 mW (WLAN Associated)



Technical Specifications

Idle mode: 60 mW (WLAN unassociated)

Radio disabled: 30 mW

Power Management ACPI and PCI Express compliant power management

802.11 compliant power saving mode

Receiver Sensitivity³ 802.11b, 1Mbps: -94dBm maximum

802.11b, 11Mbps: -86dBm maximum

802.11g, 6Mbps: -88dBm maximum

802.11g, 54Mbps : -74dBm maximum

802.11a, 6Mbps: -86dBm maximum

802.11a, 54Mbps: -72dBm maximum

802.11n, MCS07: -69dBm maximum

802.11n, MCS15: -66dBm maximum

802.11ac, 1SS, MCS-0: -86dBm maximum

802.11ac, 1SS, MCS-9: -61dBm maximum

802.11ac, 2SS, MCS-0: -83dBm maximum

802.11ac, 2SS, MCS-9 : -58dBm maximum

Antenna type High efficiency antenna with spatial diversity, mounted in the display

enclosure

Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications

Form Factor PCI-Express M.2 MiniCard

Dimensions Type 2230 : 2.3 x 22.0 x 30.0 mm

0r

Type 1630: 2.3 x 16.0 x 30.0 mm

Weight Type 2230: 2.8g

0r



Type 1630: 2g

Operating Voltage 3.3v +/- 9%

Temperature Operating 14° to 158° F (-10° to 70° C)

Non-operating -40° to 176° F (-40° to 80° C)

Humidity Operating 10% to 90% (non-condensing)

Non-operating 5% to 95% (non-condensing)

Altitude Operating 0 to 10,000 ft (3,048 m)

Non-operating 0 to 50,000 ft (15,240 m)

Near Field Communications Controller

Dimensions (L x W x H) Module 25 mm by 10 mm by 2.0 mm

Chipset NPC100

System interface I²C

NFC RF standards ISO/IEC 14443 A

ISO/IEC 14443 B ISO/IEC 15693 ISO/IEC 18092

ECMA-340 NFCIP-1 Target and Initiator

ECMA-320 NFCIP-2

NFC Forum Support Tag Type 1, Type 2, Type3 and Type 4, NFCIP-1 and NFCIP-2



Reader (PCD-VCD) Mode(1) ISO/IEC 14443 A

ISO/IEC 14443 B ISO/IEC 15693 MIFARE 1K MIFARE 4K

MIFARE DESFire

FeliCa

Jewel and Topaz cards

Card Emulation (PICC-VICC) Mode(1) ISO/IEC 14443 A

ISO/IEC 14443 B and B'

MIFARE FeliCa

Frequency 13.56 MHz

NFC Modes Supported Reader/Writer, Peer-to-Peer, Card Emulation

Raw RF Data Rates 106, 212, 424, 848 kbps

Operating temperature 0°C to 70°C

Storage temperature -20°C to 125°C

Humidity 10-90% operating

5-95% non-operating

Supply Operating voltage 2.97 to 5.5 Volts

I/O Voltage 1.8V or 3.3V

Power Consumption Mode Power Consumption,
Typical⁽²⁾

(Booster enable, VBAT= 3.3V, VCC_BOOST

= 5V) Polling 7.3 mA

Detected Test Tag Type 1 Total 283.8 mA

Net Module 236.8 mA



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Technical Specifications

Detected Test Tag Type 2 Total 288.8 mA

Net Module 241.8 mA

Detected Test Tag Type 3 Total 287.7 mA

Net Module 240.7 mA

Detected Test Tag Type 4 Total 282.3 mA

Net Module 235.3 mA

Antenna Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna

matching is external to module.

Intel® I219-V Gigabit Network Connection

Ethernet Features 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3

clauses 13-14)

100 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE

802.3 clauses 13-14)

100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE

802.3 clauses 21-30)

1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE

8023. Clauses 40)

Auto-Negotiation (Automatic Speed Selection)
Full Duplex Operation at all Speeds, Half Duplex

operation at 10 and 100 Mbit/s

IEEE 802.1p QoS (Quality of Service) Support

IEEE 802.1q VLAN support

IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32;

configurable)

IEEE 802.3az EEE(Energy Efficient Ethernet)

Jumbo Frame 9K

Auto MDI/MDIX Crossover cable detection

Power ACPI compliant - multiple power modes

Management Energy Detect Low Power Mode(Green Ethernet)

Performance TCP/IP/UDP Checksum Offload (configurable)

Features Protocol Offload(ARP & NS)

Large send offload and Giant send offload

Receiving Side Scaling MACSec Offload (802.3ae)

Intel Non-vPro iSCSI Boot



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Technical Specifications

Manageability Wake-on-LAN from standby and hibernation (Magic

Packet and Microsoft Wake-Up Frame); Wake-on-LAN

from off (Magic Packet only)
PXE 2.1 Remote Boot

Statistics Gathering (SNMP MIB II, Ethernet-like MIB,

Ethernet MIB (802.3x, clause 30))

Comprehensive diagnostic and configuration software

suite

Virtual Cable Doctor for Ethernet cable status

Interface PCI Express 1.1 x1 to fully support ASPM LOs/L1 and

CLKREQ.

NOTE: Intel 82579 PCIe interface is not PCIe compliant. It operates at half of PCIe specification V1.1 (2.5GT/S)

speed.

NIC Device Driver Name Intel 82579LM/82579V Ethernet Network Connection

Intel® I219-LM Gigabit Network Connection **Ethernet Features**

10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-

14)

100 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses

13-14)

100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses

21-30)

1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023.

Clauses 40)

Auto-Negotiation (Automatic Speed Selection)

Full Duplex Operation at all Speeds, Half Duplex operation at 10 and

100 Mbit/s

IEEE 802.1p QoS (Quality of Service) Support

IEEE 802.1q VLAN support

IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)

IEEE 802.3az EEE(Energy Efficient Ethernet)

Jumbo Frame 9K

Auto MDI/MDIX Crossover cable detection

Power ACPI compliant - multiple power modes

Management Energy Detect Low Power Mode(Green Ethernet)

Performance TCP/IP/UDP Checksum Offload (configurable)

Features Protocol Offload(ARP & NS)

Large send offload and Giant send offload

Receiving Side Scaling MACSec Offload (802.3ae)

Intel vPro



iSCSI Boot

Manageability Wake-on-LAN from standby and hibernation (Magic Packet and

Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet

only)

PXE 2.1 Remote Boot

Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB

(802.3x, clause 30))

Comprehensive diagnostic and configuration software suite

Virtual Cable Doctor for Ethernet cable status

Interface PCI Express 1.1 x1 to fully support ASPM LOs/L1 and CLKREQ.

NOTE: Intel 82579 PCIe interface is not PCIe compliant. It operates

at half of PCIe specification V1.1 (2.5GT/S) speed.

NIC Device Driver Name Intel 82579LM/82579V Ethernet Network Connection

AUDIO/MULTIMEDIA

Hardware Implementation CX7501

Function Key Volume

Controls

Volume up, volume down, and mute

Full Duplex Yes

Line in/Line out Yes via dock

Headphone/Microphone

In

Yes combo jack

Integrated Microphone Yes, dual digital microphone array

Audio Output Quality Frequency Response 20 Hz – 20 kHz

Signal to Noise Ratio >85 dB

Total Harmonic

Distortion

0.01%

Noise Floor -110 dB



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Technical Specifications

Play/Record Sampling

Rate(s)

8 kHz – 48kHz

DAC 16, 20 or 24-bit

ADC 16 or 20-bit

Integrated Stereo

Speakers

Power Rating 2 Watts

Impedance 4 Ohms

Power

HP 45W Smart AC Adapter **Dimensions** (H x W x D)

3.74 x 1.57 x 1.04 in (9.5 x 4.0 x 2.65 cm)

 Weight
 0.386 lb (175g) max

 Input
 90 to 265 VAC

Input Efficiency 87.74% at 115Vac and 88.4% at 230Vac

Input frequency range 47 to 63 Hz
Input AC current 1.4 A at 90 VAC

Output Output power 45W

DC output 19.5V

Hold-up time 5 msec at 115 VAC input

Output current limit <8.0A

Connector3 pin/grounded, mates with interchangeable cordsEnvironmental DesignOperating32° to 95° F (0° to 35° C)

temperature

Non-operating (storage) -4° to 185° F (-20° to 85° C)

temperature

Altitude 0 to 16,400 ft (0 to 5,000 m)

Humidity 20% to 95% **Storage Humidity** 10% to 95%

EMI and Safety*CE Mark - full compliance with LVD and EMC directives
*Worldwide safety standards - IEC60950, EN60950, UL

* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC

Class B, CISPR22 Class B, CCC, NOM-1 NYCE.

* MTBF - over 200,000 hours at 25°C ambient condition.

HP 65W Smart Dimensions 4.98 x 1.97 x 1.18 in (12.65 x 5.0 x 3.0 cm)



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC **HP EliteBook 850 G3 Notebook PC**

Technical Specifications

AC Adapter EM

Weight 0.62 lb (290g) max Input 90 to 265 VAC

> **Input Efficiency** 87% min at 115 VAC

Input frequency range 47 to 63 Hz **Input AC current** 1.7 A at 90 VAC

Output **Output power** 65W

DC output 19.5V

Hold-up time 5 msec at 115 VAC input

Output current limit <11.0A

Connector 3 pin/grounded, mates with interchangeable cords

Environmental Design Operating

32° to 95° F (0° to 35° C) temperature

Non-operating (storage)

temperature

-4° to 185° F (-20° to 85° C)

Altitude 0 to 16,400 ft (0 to 5,000 m)

Humidity 20% to 95% **Storage Humidity** 10% to 95%

EMI and Safety Certifications

*CE Mark - full compliance with LVD and EMC directives

* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC

Class B, CISPR22 Class B, CCC, NOM-1 NYCE.

* MTBF - over 200,000 hours at 25°C ambient condition.

HP 3-cell Long

Life Li-Ion (44.5 WHr) – HP Weight EliteBook 820 G3

Dimensions $(H \times W \times L)$

8.30 mm x127.5 mm x 160.25 mm

213q (ATL), 211.1q (SDI) Cells/Type ATL 505295, SDI 505295

Energy Voltage 11.4V

> Amp-hour capacity 3910mAh **Watt-hour capacity** 44.5Wh Operating (Charging) 0~45 C Operating (Discharging) -10~60 C

Non-operating 5~40 C

Fuel Gauge LED NA

Warranty 1000 cycles >65% (at 23°C)

Optional Travel Battery

Available

Cells/Type

Temperature

HP 3-cell Long Life Li-lon (46.5 WHr) – HP Weight EliteBook 840 & 850 G3

Dimensions $(H \times W \times L)$

6.8mm x 102.8mm x 198mm 216.3g (ATL), 217.8g (COS) ATL 506480, COSLIGHT 506480

Energy **Voltage**

11.4V



	Amp-hour capacity	4080mAh
	Watt-hour capacity	46.5Wh
Temperature	Operating (Charging)	0~45 C
	Operating (Discharging)	-10~60 C
	Non-operating 5~40 C	
Fuel Gauge LED	NA	
Warranty	1000 cycles >65% (at 23°C)	

Optional Travel Battery

Available

ENVIRONMENTAL

HP EliteBook 820 G3 Notebook PC

& declarations

Eco-Label Certifications This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- **US ENERGY STAR®**
- US Federal Energy Management Program (FEMP)
- EPEAT <Gold> registered in the United States. See http://www.epeat.net for registration status in your country.

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".

Consumption Energy (in accordance with US ENERGY **STAR®**

method)	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	8.79 W	9.05 W	8.85 W
Normal Operation (Long idle)	6.35 W	6.7 W	6.63 W
Sleep	0.85 W	0.96 W	0.84 W
Off	0.38 W	0.48 W	0.37 W



Technical Specifications

Note:

Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	30 BTU/hr	31 BTU/hr	30 BTU/hr
Normal Operation (Long idle)	22 BTU/hr	23 BTU/hr	23 BTU/hr
Sleep	3 BTU/hr	3 BTU/hr	3 BTU/hr
Off	1 BTU/hr	2 BTU/hr	1 BTU/hr

*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (L _{WAd} , bels)	Sound Pressure (L _{pAm} , decibels)
Typically Configured — Idle	2.8	20
Fixed Disk – Random writes	3.0	21

Longevity and Upgrading

This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:

- 3 USB ports
- 1 PC card slot (type I/II)



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Technical Specifications

- 1 ExpressCard/54 slot
- 1 IEEE 1394 Port
- 2 SODIMM memory slots
- Optional expansion base docking station
- 1 multi-bay II storage port
- Interchangeable HDD

Spare parts are available throughout the warranty period and or for up to "5" years after the end of production.

Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain: Mercury greater the1ppm by weight Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)

Battery type: Lithium

Battery size: 6-cell high capacity Lithium-Ion battery (optional 8 cell available)

Battery type:

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the
 gold> level, see www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 0% post-consumer recycled plastic (by wt.)
- This product is 96.6% recycle-able when properly disposed of at end of life.

Pac	kagın	g Ma	terials
-----	-------	------	---------

External:	PAPER/Corrugated	329.5 g
Internal:	PLASTIC/EPE (Expanded Polyethylene)	38 g
	PLASTIC/Polyethylene low density	14.5 g
	PLASTIC/Polypropylene	3.2 g

The plastic packaging material contains at least 50% recycled content. The corrugated paper packaging materials contains at least 70% recycled content.

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf):



- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a



responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

Hewlett-Packard Corporate **Environmental** Information

For more information about HP's commitment to the environment:

Global Citizenship Report

http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html

Eco-label certifications

http://www8.hp.com/us/en/hp-

information/environment/ecolabels.html

ISO 14001 certificates:

http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755

and

http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf

HP EliteBook 840 G3 Notebook PC

& declarations

Eco-Label Certifications This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- **US ENERGY STAR®**
- EPEAT <Gold> registered in the United States. See http://www.epeat.net for registration status in your country.

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".

Energy Consumption (in accordance with US ENERGY **STAR®** test

115VAC, 60Hz 230VAC, 50Hz 100VAC, 60Hz



Technical Specificat method)	ions		
Normal Operation (Sort idle)	8.12 W	8.66 W	8.39 W
Normal Operation (Long idle)	6.23 W	7.64 W	6.77 W
Sleep	0.86 W	1.0 W	0.84 W
Off	0.37 W	0.49 W	0.37 W

Note:

Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	28 BTU/hr	30 BTU/hr	29 BTU/hr
Normal Operation (Long idle)	21 BTU/hr	26 BTU/hr	23 BTU/hr
Sleep	3 BTU/hr	3 BTU/hr	3 BTU/hr
Off	1 BTU/hr	1 BTU/hr	1 BTU/hr

*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

Declared	Noise	Sound Power	Sound Pressure
Emissions		(L _{wAd} , bels)	(L _{pAm} , decibels)
(in accordance	with		



Technical Specifications ISO 7779 and ISO 9296)

Typically Configured – 2.9 22

Idle

Fixed Disk – Random 3.0 24

writes

Longevity and Upgrading

This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:

- 3 USB ports
- 1 PC card slot (type I/II)
- 1 ExpressCard/54 slot
- 1 IEEE 1394 Port
- 2 SODIMM memory slots
- Optional expansion base docking station
- 1 multi-bay II storage port
- Interchangeable HDD

Spare parts are available throughout the warranty period and or for up to "5" years after the end of production.

Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain: Mercury greater the1ppm by weight Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)

Battery type: Lithium

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the <Gold> level, see www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 0.0% post-consumer recycled plastic (by wt.)
- This product is 95.7% recycle-able when properly disposed of at end of life.

Packaging Materials

External: PAPER/Corrugated

268.8 g



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Technical Specifications

Internal:PLASTIC/EPE (Expanded Polyethylene)91.9 gPLASTIC/Polyethylene low density13.6 gPLASTIC/Polypropylene5.5g

The plastic packaging material contains at least 50.0% recycled content. The corrugated paper packaging materials contains at least 70.0% recycled content.

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)



Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

Hewlett-Packard Corporate Environmental Information For more information about HP's commitment to the environment:

Global Citizenship Report

http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html

Eco-label certifications

http://www8.hp.com/us/en/hp-

information/environment/ecolabels.html

ISO 14001 certificates:

http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755

and

http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf

HP EliteBook 850 G3 Notebook PC



Technical Specifications

& declarations

Eco-Label Certifications This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- **US ENERGY STAR®**
- EPEAT <Gold> registered in the United States. See http://www.epeat.net for registration status in your country.

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".

Energy Consumption (in accordance with US

method)	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	9.06 W	9.98 W	9.6 W
Normal Operation (Long idle)	7.31 W	7.82 W	8.0 W
Sleep	0.76 W	0.89 W	0.75 W
Off	0.44 W	0.56 W	0.43 W

Note:

Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	31 BTU/hr	34 BTU/hr	33 BTU/hr
Normal Operation (Long	25 BTU/hr	27 BTU/hr	27 BTU/hr



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Technical Specifications

idle)

Sleep	3 BTU/hr	3 BTU/hr	3 BTU/hr
Off	2 BTU/hr	2 BTU/hr	1 BTU/hr

*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

Declared Noi Emissions (in accordance wi ISO 7779 and ISO 9296)	(L _{WAd} , bels)	Sound Pressure (L _{pAm} , decibels)
Typically Configured Idle	- 2.9	20
Fixed Disk – Rando writes	om 2.9	21

Longevity and Upgrading

This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:

- 3 USB ports
- 1 PC card slot (type I/II)
- 1 ExpressCard/54 slot
- 1 IEEE 1394 Port
- 2 SODIMM memory slots
- · Optional expansion base docking station
- 1 multi-bay II storage port
- Interchangeable HDD

Spare parts are available throughout the warranty period and or for up to "5" years after the end of production.

Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain: Mercury greater the1ppm by weight Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)

Battery type: Lithium



Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the <qold> level, see www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 0% post-consumer recycled plastic (by wt.)
- This product is 96.1% recycle-able when properly disposed of at end of life.

Dac	kaaina	Mata	.iale
rau	Kauiiiu	Male	Idis

External:	PAPER/Cardboard & misc	360.2 g
Internal:	PLASTIC/EPE (Expanded Polyethylene)	29.8 g
	PLASTIC/Polyethylene low density	13.6 g
	PLASTIC/Polypropylene	6 g

The plastic packaging material contains at least 50% recycled content. The corrugated paper packaging materials contains at least 70% recycled content.

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- · Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances



Packaging Usage

• Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

Hewlett-Packard Corporate Environmental Information For more information about HP's commitment to the environment:

Global Citizenship Report

http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html

Eco-label certifications

http://www8.hp.com/us/en/hp-

information/environment/ecolabels.html

ISO 14001 certificates:

http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU _Product_Design_ISO_14K_Certificate.pdf

and

http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf

Country of Origin



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Technical Specifications

China



Options and Accessories (Sold separately and availability may vary by country.)

Туре	Description	Part #
Batteries	HP Notebook Power Bank	N9F71AA
	HP SN03XL Rechargeable Battery (820 G3)	T7B33AA
	HP CSO3XL Rechargeable Battery (840, 850 G3)	T7B32AA
Cases	HP Essential Top Load Case (up to 15.6")	H2W17AA
	HP Business Backpack (up to 17.3")	H5M90AA
	HP Business Case (up to 15.6")	H5M92AA
Docking	HP 3005pr USB 3.0 Port Replicator	H1L08AA
-	HP UltraSlim Docking Station	D9Y32AA
	HP Display and Notebook Stand II	E8G00AA
	HP Adjustable Dual Display Stand	AW664AA
Input/Output Devices	HP 2.4 GHz Keyboard and Mouse	G1K29AA
	HP Slim Wireless Keyboard and Mouse	T6L04AA
	HP Wireless (Link-5) Keyboard	T6U20AA
	HP Touch to Pair Mouse	H6E52AA
	HP Comfort Grip Wireless Mouse	H2L63AA
	HP USB Travel Mouse	G1K28AA
	HP Slim Bluetooth Mouse	F3J92AA
	HP Ultrathin Wireless Mouse SE	L9V77AA
	HP UC Wired Headset	K7V17AA
	HP UC Speaker Phone	K7V16AA
	HP Conferencing Keyboard	K8P74AA
Adapters	HP Wireless Display Adapter	J1V25AA
	HP USB-C to USB 3.0 Adapter	N2Z63AAA
	HP USB-C to RJ45/USB 3/USB-C	N2Z64AA
	HP DisplayPort to HDMI 1.4 Adapter	F3W43AA
	HP DisplayPort to VGA	F7W97AA
Memory	HP 4GB 2133MHz DDR4 Memory	T7B76AA
	HP 8GB 2133MHz DDR4 Memory	T7B77AA
Power Adapters	HP 65W Slim AC Adapter	H6Y82AA#xxx
	HP 45W Smart AC Adapter	H6Y88AA#xxx
	HP 65W Smart AC Adapter	H6Y89AA#xxx
	HP 90W Slim Combo AC Adapter w/USB	H6Y84AA#xxx
External Drives	HP USB External DVDRW Drive	F2B56AA
Security	HP Docking Station Cable Lock	AU656AA
	HP UltraSlim Keyed Cable Lock	H4D73AA
	HP 12.5" Notebook PC Privacy Filter (non-touch screens)	J6E64AA
	HP 14.1" Notebook PC Privacy Filter (non-touch screens)	J6E65AA
	HP 15.6" Notebook PC Privacy Filter (non-touch screens)	J7H71AA
Displays	HP EliteDisplay E240 23.8-inch Monitor	M1N99AA
	HP EliteDisplay E272Q 27-inch QHD Monitor	M1P04AA
	HP EliteDisplay E240c 23.8-inch Video Conferencing Monitor	M1P00AA
	HP EliteDisplay S140u 14-inch USB Portable Monitor	G8R65AA



HP EliteBook 820 G3 Notebook PC HP EliteBook 840 G3 Notebook PC HP EliteBook 850 G3 Notebook PC

Summary of Changes

Date of change:	Version History:		Description of change:
January 11, 2016	V1 to v2	Updated	Military testing and footnote page 7
			Battery life and stand by time page 17
January 19, 2016	V2 to V3	Updated	Weight for 850 Non-Touch and Touch page 18
January 21, 2016	V3 to v4	Added	Environmental information
March 4, 2016	V4 to v5	Added	Battery recharge times
March 29, 2016	V5 to v6	Updated	Disclaimer for TPM
			Memory up to 32 GB for HP EliteBook 840 and 850
		Changed	1920 x 1080 displays specs
April 6, 2016	V6 to v7	Added	Memory configurations
•			512 GB SATA-3 Self-Encrypting (Opal 2) MLC Solid State Drive
April 7, 2016	V7 to v8	Added	More battery life details

Copyright © 2016 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty.

HP shall not be liable for technical or editorial errors or omissions contained herein. Intel, Core, and Celeron are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a trademark of its proprietor used by HP, INC. under license. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

