

USB-C to 4K HDMI Adapter with USB Power Delivery - 60 Watts - Black

Product ID: CDP2HDUCP



This USB- C^{TM} to 4K HDMI® adapter connects an HDMI display to your laptop or MacBook with USB Type-C. The USB C to HDMI adapter features USB Power Delivery, so you can power your laptop while outputting video, using the same USB-C port. The adapter is also available in white (CDP2HDUCPW), so you can choose an adapter that matches the style of your laptop.

Power and Video in One Port with USB Power Delivery

Smaller and lighter laptops are great for portability but you're left with fewer connectivity ports. This USB-C video adapter supports USB Power Delivery up to 60 watts and features an additional USB-C port, so you can charge your laptop using its USB-C power adapter, even while you output video. Many laptops like Dell XPS and MacBook Pro support charging through your USB-C port with USB Power Delivery, check your specifications to confirm compatibility.



Data Sheet

Enjoy Astonishing Picture Quality with Video Resolutions up to 4K 60Hz

To ensure the UHD quality of your video signal is maintained the USB Type C to HDMI adapter supports HDMI resolutions up to $3840 \times 2160 \ 60$ Hz, including popular high-definition resolutions like 1080p and 720p.

Stylish Connectivity for Your Ultrabook or Any Laptop

This USB C to HDMI converter has an all-black housing and built-in USB-C cable designed to match your Ultrabook or laptop. The adapter is compatible with any device that supports USB-C DP Alt Mode.

The CDP2HDUCP is backed by a 3-year StarTech.com warranty and free lifetime technical support.





Certifications, Reports and Compatibility











Applications

- · Connect to any HDMI display while travelling
- Connect your BYOD laptop to an HDMI display at work, school or home while charging your laptop
- Present on a large HDMI display using your USB-C laptop

Features

- Charge your laptop while connecting an HDMI display using just one USB-C port, with USB Power Delivery
- Get astonishing picture quality with support for UHD video resolutions up to 4K 60Hz
- Make the perfect connection, with a black USB-C adapter that exactly matches the cables for your Ultrabook or laptop



Data Sheet

	Warranty	3 Years
Hardware	AV Input	USB Type-C
	AV Output	HDMI
	Chipset ID	Parade - PS176 VIA/VLI - VL100
Performance	Audio Specifications	7.1 surround sound
	Maximum Digital Resolutions	3840 x 2160 @ 60Hz
	Supported Resolutions	3840 x 2160 @ 60Hz 2560 x 1600 2048 x 1280 1920 x 1200 1920 x 1080 1280 x 720 1680 x 1050 1600 x 900 1440 x 900 1360 x 768 1280 x 800 1280 x 768 Lower resolutions and refresh rates may also be supported
	Video Revision	HDMI 2.0
	Wide Screen Supported	Yes
Connector(s)	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
	Connector B	1 - HDMI (19 pin) Female Output
		1 - USB Type-C (24 pin) USB 3.0 (5Gbps) Female Input
Special Notes / Requirements	System and Cable Requirements	1 - USB Type-C (24 pin) USB 3.0 (5Gbps) Female Input Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter
_	System and Cable Requirements Power Delivery	Your USB-C port must support DisplayPort over USB-C (DP
Requirements		Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter
Requirements Power	Power Delivery	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter 60W
Requirements Power	Power Delivery Humidity	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter 60W 0~90% RH
Requirements Power	Power Delivery Humidity Operating Temperature	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter 60W 0~90% RH 0°C to 40°C (32°F to 104°F)
Power Environmental Physical	Power Delivery Humidity Operating Temperature Storage Temperature	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter 60W 0~90% RH 0°C to 40°C (32°F to 104°F) -20°C to 70°C (-4°F to 158°F)
Power Environmental Physical	Power Delivery Humidity Operating Temperature Storage Temperature Cable Length	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter 60W 0~90% RH 0°C to 40°C (32°F to 104°F) -20°C to 70°C (-4°F to 158°F) 3.9 in [100 mm]
Power Environmental Physical	Power Delivery Humidity Operating Temperature Storage Temperature Cable Length Color	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter 60W 0~90% RH 0°C to 40°C (32°F to 104°F) -20°C to 70°C (-4°F to 158°F) 3.9 in [100 mm] Black



Data Sheet

	Product Width	1.3 in [33 mm]
	Weight of Product	0.8 oz [24 g]
Packaging Information	Package Height	1.3 in [32 mm]
	Package Length	6.9 in [17.4 cm]
	Package Width	5.7 in [14.6 cm]
	Shipping (Package) Weight	0.2 lb [0.1 kg]
What's in the Box	Included in Package	1 - USB-C to HDMI Adapter

Product appearance and specifications are subject to change without notice.