



SPS SAFE Active electrical protectors

SPS SAFE: Multi-outlet power strips for powering and protecting equipment in the office and the home

Salicru's **SPS SAFE** series is a complete range of multi-outlet power strip active electrical protectors, ideal for protecting office and home electronics. Featuring basic 3 and 6-outlet models, the **SPS SAFE 3** and **SPS SAFE 6**, respectively, the **SPS SAFE 7**, model with 7 sockets, EMI/RFI filter and built-in cable collector, and the **SPS SAFE 5+** and **SPS SAFE Master** with 5 sockets and 2 USB chargers for charging electronic devices.

The **SPS SAFE Master** model also features, in addition to the EMI/RFI filter, a master/slave function to achieve significant savings by preventing load 'vampire' consumption in standby.

Features

- Next-generation active electrical protectors.
- Wide range of models (3, 5, 6 and 7 sockets).
- Models with built-in dual USB charger. ⁽¹⁾
- Schuko sockets, orientated for easy connection.
- Possibility of wall mounting.
- Surge control indicator.
- EMI/RFI filter for electrical noise reduction. ⁽²⁾
- On/off switch on all models.
- Financial warranty for protected devices. ⁽²⁾

⁽¹⁾ Safe 5+ and Safe Master
⁽²⁾ Safe 7 and Safe Master



SPS SAFE Range

Applications: Superior electrical protection

Optimum power and protection for: PC, monitor, printer, router, hub/switch, external HDD, telephone, TV/LCD, home cinema, games console, Hi-Fi, decoder, DTT, SAT, DVD, home automation, domestic appliances, etc.



PC



Inkjet printer



HDD/NAS - multimedia



Router



TV



Hi - Fi



Home Cinema



DVD



Video games console



TV Decoder

SPS SAFE 
Active electrical protectors

SPS SAFE 3

- Active electrical protection.
- 3 schuko AC outlets.
- Rocker power switch On/Off.
- All mains dully fixed for easyconnection.
- Wallmounting system.
- Overvoltage control indicator.
- Resettable circuit breaker.
- Outlets with saffety shutters.

SPS SAFE 5+

- Active electrical protection.
- 5 schuko AC outlets.
- 2 ports USB charger 2,1A / 5 VDC.
- Rocker power switch On/Off.
- Overvoltage control indicator.
- Resettable circuit breaker.
- Includes cable-marking plus cable-tie.
- Outlets with saffety shutters.
- Power cord length: 1.8 m.

SPS SAFE 6

- Active electrical protection.
- 6 schuko AC outlets.
- Rocker power switch On/Off.
- All mains dully fixed for easyconnection.
- Wallmounting system.
- Overvoltage control indicator.
- Resettable circuit breaker.
- Outlets with saffety shutters.

SPS SAFE 7

- Electrical protection against overloads, power surges & lightning strikes.
- 7 schuko AC outlets.
- MOV technology.
- EMI/RFI noise filter.
- Cable wrap-organizer device.
- Extra space for great dimension mains.
- Includes cable-marking plus cable-tie.
- Rocker power switch On/Off.
- Overvoltage control indicator.
- Resettable circuit breaker.
- Electrical insurance: 40,000 € ⁽¹⁾

(1) Only European Union countries

SPS SAFE Master

- Smart Master/Slave electrical protection.
- 5 AC outlets.
- One AC outlet is always on.
- 2 ports USB charger 5 VDC.
- Master/Slave function.
- Peripherals auto power on/off .
- EMI/RFI noise filter.
- MOV technology.
- Includes cable-marking plus cable-tie.
- Overvoltage control indicator.
- Resettable circuit breaker.
- Electrical insurance: 60,000 € ⁽¹⁾

(1) Only European Union countries



TECHNICAL SPECIFICATIONS

MODEL	SPS SAFE 3	SPS SAFE 6	SPS SAFE 7	SPS SAFE 5+	SPS SAFE Master
Rated current	10 A				
Rated voltage / frequency	250 V AC / 50 Hz				
Socket type and quantity	3 x Schuko	6 x Schuko	7 x Schuko	5 x Schuko	5 x Schuko
USB charger	No	No	No	2 ports / 2.1 A / 5 VDC	2 ports / 1 A / 5 VDC
Master/slave function	No	No	No	No	Yes
Maximum power dissipation (F-N, N-T and F-T)	238 J	238 J	918 J	306 J	918 J
Maximum peak current	8,000 A	8,000 A	36,000 A	12,000 A	36,000 A
Maximum peak voltage	6,000 V				
Response time	< 1 ns				
EMI/RFI filter (frequency range)	-	-	150 kHz - 100 MHz	-	150 kHz - 100 MHz
On/off switch	Yes				
Possibility of wall mounting	Yes				
Length of power cable	1.5 m	1.5 m	1.8 m	1.5 m	1.8 m
Child protection in the sockets	Yes				
Sockets orientated for easy connection	Yes				
Surge control indicator	Yes				
Safety	IEC-60884-1; EN-61643-11; EN-61643-21				
Quality and Environmental Management	ISO 9001 and ISO 14001				
Code	680BA000001	680BA000003	680BA000006	680BA000002	680BA000005

Information subject to change without notice.