# HP LaserJet Pro MFP 4102dw Printer

## Get blazing fast printing speeds, high-volume scanning, and easy management with LaserJet Pro.

This printer is built for maximum productivity with fast speeds and reliable hardware, delivering effortless everyday use from wherever work happens so you can focus more on your business.





This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

## Highlights

- Instant Ink for Laser available
- HP Wolf Pro security
- Automatic two-sided printing standard
- Fast print speed (40 ppm A4)
- High monthly duty cycle (80,000 pages)
- Dual-band WiFi®, Bluetooth® LE, WiFi® Direct
- 50 sheet ADF with single-pass, two-sided scanning



## Maximum productivity.

- Support your dynamic workteam with this high-speed smart printer, ideal for up to 10 users.
- Step up your workflow with HP Pro-class maximum print speed to meet high-demand environments.  $^{\rm 1}$
- Get productivity in the palm of your hand. Print, scan and get time-saving Shortcuts with HP Smart app.  $^{\rm 2}$

### Seamless management.

- Centralise print management for your enterprise. HP Web Jetadmin makes it easy with its suite of features.  $^{\rm 4}$
- Set up your printers quickly wherever work happens. Cloud connectivity makes it easy for your IT team.
- Access your printers from a single dashboard. Smart Admin guides you through setup and gives IT visibility.  $^{\rm 3}$
- Avoid interruptions with Wi-Fi $^{\circ}$  that intelligently looks for the best connection to stay on-line.  $^{5}$

#### HP Wolf Pro Security.

- Get printer security out of the box. Preconfigured settings mean it's ready when you are.
- Set up your printer security from the dashboard. Smart Admin makes IT configuration and monitoring easy.  $^{\rm 3}$
- Add a layer of security. PIN/pull option authenticates your print jobs only when you're present.
- Set configuration policies and validate settings universally with HP Security Manager.<sup>6</sup>

#### Hassle-free supplies management with Instant Ink.

- Enroll to save on Original HP Toner with Instant Ink. Get toner, delivery and recycling. <sup>7,8,9</sup>
- Never run out of toner with Instant Ink for laser.<sup>10</sup>
- With Instant Ink, get toner automatically delivered to workers or offices all on one consolidated  ${\rm bill.}^9$
- With Instant Ink, you get to select the right plans for each of your printers. Change or cancel at any time.<sup>11</sup>

## Product walkaround

1. Designed for workteams of up to 10 users

- 2. Pre-configured security settings
- 3. Walk-up USB
- 4. Automatic 2-sided printing
- 5. Hi-speed USB ports, built-in Gigabit Ethernet
- 6. Print speeds up to 40 ppm (A4), 350-sheet standard paper capacity



# Accessories, Supplies and Support

Supplies	W1490A HP 149A Black Original LaserJet Toner Cartridge (Average cartridge yields 2,900 standard pages. Declared yield value in accordance with ISO/IEC 19752.)
	W1490X HP 149X High Yield Black Original LaserJet Toner Cartridge (Average cartridge yields 9,500 standard pages. Declared yield value in accordance with ISO/IEC 19752.)
Accessories	D9P29A HP Laser Jet Pro 550-sheet Feeder Tray
Service and Support	U42TZE - HP 3 year Next Business Day Service for LaserJet Pro MFP 410x U42U8PE - HP 1 year Post Warranty Next Business Day Service for LaserJet Pro MFP 410x

# Technical specifications

	-
Model	HP LaserJet Pro MFP 4102dw Printer
Product number	22622F
Functions	Print, copy, scan
Control panel Print	2.7° Color Touchscreen
Print technology	aser
Print speed <sup>1</sup>	Black (A4, normal): Up to 40 ppm ; Black (A4, duplex): Up to 34 ipm
First page out <sup>2</sup>	Black (A4, ready): As fast as 6.3 sec ; Black (A4, sleep): As fast as 8.8 sec
Print resolution	Black (best): Fine Lines (1200 x 1200 dpi) ; Technology: HP FastRes 1200, HP ProRes1200, Economode
Monthly duty cycle	Up to 80,000 pages A4; Recommended monthly page volume: 750 to 4,000
Printer smart software features <sup>3</sup>	Auto duplex and booklet printing, N-up printing, collation, watermarks, install printer driver only, Economode for toner savings, accepts a variety of paper sizes and types
Standard print languages	HP PCL 6, HP PCL 5e, HP postscript level 3 emulation, PDF, URF, Native Office, PWG Raster
Fonts and typefaces Print area	84 scalable TrueType fonts Print margins Top: 4.3 mm, Bottom: 4.3 mm, Left: 4.3 mm, Right: 4.3 mm; Maximum print area: 207.4 x 347.1mm
Duplex printing	Princharguns top, 4-3 min, bottom, 4-3 min, cert, 4-3 min, regit, 4-3 min, Maximum print area. 207.4 × 347.1mm Automatic (default)
Сору	
Copy speed	Black (A4): Up to 38 cpm
Copier specifications	ID Copy, Number of copies; Resize (including 2-Up); Lighter/Darker; Enhancements; Original Size; Binding Margin; Collation; Tray Selection; Two-Sided; Quality (Draft/Normal/Best); Save Current Settings; Restore Factory
	Defaults; Maximum number of copies: Up to 9999 copies; Reduce/Enlarge: 25 to 400%
Scan Scan speed <sup>4</sup>	Normal (A4): Up to 29 ppm/46 ipm (b&w), up to 20 ppm/34 ipm (color) ;Duplex (A4): Up to 46 ipm (b&w), up to 34 ipm (color)
Scan file format	Termine very, up to 25 phine en prince way, up to 26 phine en prince our in colour, up to en prince way, up to 24 phine en prince our in colour.
	Scanner type Flatbed, ADF; Scan technology. Contact image Sensor (CIS); Scan input modes: Front-panel scan, copy, email, or file buttons; HP Scan software; and user application via TWAIN or WIA; Twain version: Version 2.3;
Scanner specifications	Duplex ADF scanning: Yes; Optical scan resolution: Up to 1200 x 1200 dpi Single-pass 2-sided scanning ADF, Scan to cloud (Google Drive and DropBox) Scan to email with LDAP email address lookup, Scan to network folder, Scan to USB, Scan to Microsoft SharePoint®, Scan to computer with
Scanner advanced features Recommended monthly scan	software, Fax archive to network folder, Fax archive to email, Fax to computer, Enable/disable fax, Quick Sets
volume	750 to 4000
Scannable area	Maximum media size (flatbed): 216 x 297 mm ; Minimum media size (ADF): 102 x 152 mm Maximum media size (ADF): 216 x 356 mm
Bit depth/ Grey scale levels	24-bit/256
Fax Fax	No
	NO Auto fax reduction; Auto redialing; Delayed sending; Fax forwarding; TAM interface; Junk barrier; Distinctive ring detection; Cover page; Block fax; Billing codes; Save and load; Fax activity reports; Dial prefix setting; Print fax
Fax smart software features	had far tootking, neurolalang, beayed schaing, nak horizonag, minimentee, sain danner, bisinetive ing decetion, over page, biock nav, billing codes, save and load, nav activity reports, bia prein secting, nin method, sain danner, bisinetive ing decetion, over page, biock nav, billing codes, save and load, nav activity reports, bia prein secting, nin method.
Processor speed	1200 MHz
Connectivity	
Standard	1 Hi-Speed USB 2.0; 1 rear host USB; 1 Front USB port; Gigabit Ethernet LAN 10/100/1000BASE-T network; 802.3az(EEE); 802.11b/g/n / 2.4 / 5 GHZ Wi-Fi radio + BLE
Mobile printing capability	Apple AirPrint <sup>™</sup> ; Mopria <sup>™</sup> Certified; WI-Fi® Direct Printing TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint <sup>™</sup> , Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, AutoIP, AutoIP, Manual), IPv6
Supported network protocold	
Supported network protocols	TCP/II; PV4, PV6, PTIII: TCP-IP (PCT 9) 00 Diffect P006; PV1CW queue support of inj, Apple Amerinic", Mippia, IP-PPTI, Discovery: Sci.; Bonjou, Web Services Social Sci.; PV6 P001; PV4 Boole; Autori; Mariaua, IPV6 (Stateless Link-Local and vis Route; Statelus) Download
Network capabilities	TCP/II; IPV4, IPV6; PTIII: TCP-IP (ptC) 9100 Diffect P000; EPUTdW queue support of inj, Apple Amerini", Minopra, IPP Print, Discovery: Sce, Sonjour, web Services Discovery: The Config. IPV4 (Boole, DetC): Autori; Manuau, IPV6 (Stateles: Link-Local and via Route; Stateley Link-Route; Manuau, IPV6 Yes, via built-in 10/100/1000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X
Network capabilities Hard disk	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No
Network capabilities Hard disk Memory	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X
Network capabilities Hard disk Memory Media handling	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB
Network capabilities Hard disk Memory Media handling Number of paper trays	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum; 512 MB Standard: 512 MB; Maximum; 3
Network capabilities Hard disk Memory Media handling	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.95 to 215.9 x 355.6 mm Supported (metric): Tray 1: 74; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 727 mm); Japanese Postcart, Double Japan Postcard Rotated; Envelope B15; Envelope B5; Envelope B15; Envelope B5; Envelope B15; Custope D1; Custom Size; 4 x 6 in; 5 x 8
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric); Tray 1: A4; A5; A6; B5 (US); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K, (197 x 273 mm); Japanese Positard; Dotated; Envelope # 10; Envelope Monard; Envelope CS; Envelope D (Listorm Size; 4 X 6 in; 5 & Bin; 5 X Bin
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFFICENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4; A5; A6; B5 (US); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Japanese Postcard; Double Japan Postcard Rolated; Envelope #10; Envelope Monarch; Envelope B15; Envelope D1; Custom Size; 4 x 6 in; 5 x Bin; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 U(S); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Custom Size; 4 x 6 in; 5 x Bin; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 Standard input: 100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF) Standard output: 150-sheet output bin Optional Input: Optional third 550-sheet tray
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric); Tray 1: A4; A5; A6; B5 (US); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K, (197 x 273 mm); Japanese Positard; Dotated; Envelope # 10; Envelope Monard; Envelope CS; Envelope D (Listorm Size; 4 X 6 in; 5 & Bin; 5 X Bin
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 512 MB; Maximum: 512 MB Custom (metric): Tray 1: 76 2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Japanese Postcard; Double Japan Postcard Rotated; Envelope #10; Envelope Monard; Envelope Pol; Euxlorm Size; 4 x 6 in; 5 x 8 in; 8
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 21:5 x 355.5 mm; Tray 2.3: 104.9 x 148.59 to 21:5.9 x 355.6 mm; Stary 3: 104.9 x 148.59 to 21:5.9 x 355.6 mm; Stary 3: 104.9 x 148.59 to 21:5.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 21:5.9 x 355.6 mm; Stary 3: A4; A5; A6; B5 UIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 727 mm); Japanese Postcard; Double Japan Postcard Rotated; Envelope #10; Envelope B5; Envelope B5; Envelope C5; Envelope B10; Envelope C5; Envelope B10; Stary Dec) C5; Lost 21:6 x 356 mm; Standard input: 100-sheet tray 1, 250-sheet tray 1: 6K (184 x 260 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Gustom Size; A5-R; 4 x 6 in; B6 UIS) ADF: Letter; Legal; A4; custom sizes 102 x 152 to 21:6 x 356 mm Tray 1: 6 to 200 Jm²; tray 2, optional 550-sheet tray 2: 50 -sheet Automatic Document Feeder (ADF) Standard output: 150-sheet tray 1, 250-sheet tray 1: 750 s 10: 120 Jm² Tray 1: 50 to 200 Jm²; tray 2, optional 50-sheet tray 2: 50 to 120 Jm² Tray 1: Sheets: 100; Envelopes: 10 Tray 2; Sheets: 250 Tray 3; Sheets: 550 (optional) Maximum: Up to 900 sheets (with Optional 550-sheet tray) ADF: Standard, 50 sheets
Network capabilities Hard disk Memory Media handling Number of paper trays Media size Media size Media handling Media ungiht Input capacity Output capacity	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.4 x 260 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Loss (198 x 220 mm); 16K (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (198 x 220 mm); Loss (198 x 200 mm); Loss (198 x 200 mm);
Network capabilities Hard disk Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download         Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X         No         Standard: 512 MB; Maximum: 3         Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels;         Custom (metric): Tray 1: 76.2 × 127 to 21:5.9 × 355.6 mm; Tray 2, 3: 104.9 × 148.95 to 215.9 × 355.6 mm Supported (metric); Tray 1: 7.42, 45; nd; 5.4 KG; 105 (DIS); Oficio (216 × 340 mm); 16K (195 × 270 mm); 16K (184 × 260 mm); 16K (195 × 270 mm); 16K (184 × 260 mm); 16K (195 × 270 mm); 16K (184 × 260 mm); 16K (195 × 270 mm); 16K (184 × 260 mm); 16K (195 × 270 mm); 16K (184 × 260 mm); 16K (195 × 270 mm); 16K (195 × 270 mm); 16K (195 × 270 mm); 16K (197 × 273 mm); Loganese Postcard; Double Japan Postmard Rotated; Prevelope B5; Envelope B5; Envelope C5; Envelope D12, Custom Size; 4 × 6 in; 5 × 8 in; S taimers, tray 2 & 8 tray 3: A4; A5, A6; B5 (US); Oficio (216 × 340 mm); 16K (195 × 270 mm); 16K (194 × 260 mm); 16K (195 × 270 mm); 16K (194 × 260 mm); 16K (195 × 270 mm); 16K (194 × 260 mm); 16K (195 × 270 mm); 16K (194 × 260 mm); 16K (195 × 270 mm); 16K (197 × 273 mm); Loustom Size; 45 - R; 4 × 6 in; 56 (US) A0E-Letter; Legal; A4; custom Size 102 × 152 to 216 × 356 mm         Standard input: 100-sheet tray 1, 250-sheet tray 3: 60 to 120 g/m²         Tray 1: 60 to 200 g/m²; tray 2, optional 550-sheet tray 3: 60 to 120 g/m²         Tray 1: Sheets: 100; Envelopes: 10 to 1
Network capabilities Hard disk Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Starported (metric): Tray 1: 76.4 x 260 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Loss (198 x 220 mm); 16K (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (197 x 273 mm); Loss (198 x 220 mm); Loss (198 x 220 mm); Loss (198 x 200 mm); Loss (198 x 200 mm);
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 × 127 to 21:5.9 × 355.6 mm; Tray 2, 3: 104.9 × 148.95 to 215.9 × 355.6 mm Supported (metric): Tray 1: 74; A5; A6; B5 (JIS); Oficio (216 × 340 mm); 16K (195 × 270 mm); 16K (184 × 260 mm); 16K (197 × 727 mm); Japanese Postcard; Double Japan Postcard Rotated; Envelope #10; Envelope B5; Envelope B5; Envelope B5; Envelope B5; Custope B5; Envelope B10; Custom Size; 4 × 6 in; 5 × 81m; Statement; Tray 2 & 8 Tray 3: A4; A5; A6; B5 (JIS); Oficio (216 × 340 mm); 16K (195 × 270 mm); 16K (184 × 260 mm); 16K (197 × 273 mm); Laganese Postcard; Double Japan Postcard Rotated; Envelope #10; Envelope B5; Envelopes: Up to 10 envelopes Maximum: Up to 900 sheets (with Optional 550-sheet tray) ADF; Standard; 50 sheets Standard: Up to 150 sheets Envelopes: Up to 10 envelopes Maximum: Up to 500 sheets Standard: Up to 150 sheets Envelopes: Up to 10 envelopes Maximum: Up to 500 sheets Standard: Up to 150 sheets Envelopes: Up to 10 envelopes Maximum: Up to 50 sheets Standard: Up to 150 sheets Envelopes: Up to 10 envelopes Maximum: Up to 150 sheets Windows 10; Windows 10; Windows Client O5; Android; 105; Mobile O5; macO5 10.15 Catalina; macOS 11 Big Sur; m
Network capabilities Hard disk Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heav, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: Ad; A5; A6; B5 (US); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); labarese Portion (197 x 273 mm); Lostom Sizer 4, X 61 m, B6 (US); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); labarese Portion (197 x 273 mm); Lostom Size; 4 x 61 m; B6 (US); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); labarese Portion (197 x 273 mm); Lostom Size; 4 x 61 m; B6 (US); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); labarese Portion (197 x 273 mm); Lostom Size; 4 x 61 m; B6 (US); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); 16K (197 x 273 mm); 16K (197 x 273 mm); Lostom Size; 4 x 61 m; B6 (US); ADF Letter; Legal; 44; custom Size; 4 x 51 to 216 x 340 mm); 16K (197 x 273 mm); 16K (197 x 273 mm); Lostom Size; 105 x 152 to 216 x 350 mm Standard input: 100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF) Standard output; 150-sheet output bin Optional input; Optional third 550-sheet tray Tray 1: Sheets: 100; Envelopes: 10 Tray 2: Sheets: 250 Tray 3: Sheets: 550 (optional) Maximum; Up to 900 sheets (with Optional 550-sheet tray) ADF: Standard, 50 sheets Standard; Up to 150 sheets Envelopes: Up to 10 envelopes Maximum; Up to 150 sheets Windows 11; Windows 10; Windows 7; Windows Client 05; Android; 105; Mobile 05; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Montrey;
Network capabilities Hard disk Hard disk Memory Media handling Number of paper trays Media types Media size Media size Media handling Media weight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 × 127 to 21:5.9 × 355.6 mm; Tray 2, 3: 104.9 × 148.95 to 215.9 × 355.6 mm Supported (metric): Tray 1: 74; A5; A6; B5 (JIS); Oficio (216 × 340 mm); 16K (195 × 270 mm); 16K (184 × 260 mm); 16K (197 × 727 mm); Japanese Postcard; Double Japan Postcard Rotated; Envelope #10; Envelope B5; Envelope B5; Envelope B5; Envelope B5; Custope B5; Envelope B10; Custom Size; 4 × 6 in; 5 × 81m; Statement; Tray 2 & 8 Tray 3: A4; A5; A6; B5 (JIS); Oficio (216 × 340 mm); 16K (195 × 270 mm); 16K (184 × 260 mm); 16K (197 × 273 mm); Laganese Postcard; Double Japan Postcard Rotated; Envelope #10; Envelope B5; Envelopes: Up to 10 envelopes Maximum: Up to 900 sheets (with Optional 550-sheet tray) ADF; Standard; 50 sheets Standard: Up to 150 sheets Envelopes: Up to 10 envelopes Maximum: Up to 500 sheets Standard: Up to 150 sheets Envelopes: Up to 10 envelopes Maximum: Up to 500 sheets Standard: Up to 150 sheets Envelopes: Up to 10 envelopes Maximum: Up to 50 sheets Standard: Up to 150 sheets Envelopes: Up to 10 envelopes Maximum: Up to 150 sheets Windows 10; Windows 10; Windows Client O5; Android; 105; Mobile O5; macO5 10.15 Catalina; macOS 11 Big Sur; m
Network capabilities Hard disk Hard disk Memory Media handling Number of paper trays Media types Media size Media andling Media veght Input capacity Output capacity Output capacity Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download         Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X         No         Standard; 512 MB; Maximum; S12 MB         Standard; 2; Maximum; 3         Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels;         Custom (metric): Tray 1: 76, 2x 127 to 215, 9x 355, 6 mm; Tray 2, 3; 104.9 x 148,59 to 215, 9x 355, 6 mm; Supported (metric) Tray 1: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (194 x 260 mm);         15K (197 x 273 mm); Lapanese Postard; Double Japan Postard Rotated; Envelope PB 15; Envelope B5; Envelope C5; Envelope LC, Starton Szes 102 x 152 to 216 x 356 mm         Standard Input: 100-sheet tray 1, 250-sheet tau tray 2; 50-sheet Automatic Document Feeder (ADF) Standard output: 150-sheet output bin Optional Input: Optional Input: 29 to 103 to 20 fm <sup>2</sup> Tray 1: Sheets: 100; Envelopes: 10 To 7a; 2; Sheets: 250 Tray 3; Sheets: 550 (optional) Maximum; Up to 900 sheets (with Optional 550-sheet tray) ADF; Standard, 50 sheets         Standard: Up to 150 sheets Envelopes: Up to 10 envelopes Maximum; Up to 150 sheets         Windows 11; Windows 10; Windows 70; Windows Client OS; Madriel OS; Mobile OS; macOS 10: 15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; Chrome OS         Windows 8; Windows 70; Windows 7; Windows 7; Windows 10; Mandreid OS; Madriel OS; Mandreid OS hared/UP Provy Agent (Part of HP WebJetAdmin); Printer Administrator Re
Network capabilities Hard disk Hard disk Hernory Media handling Number of paper trays Media types Media size Media size Media handling Media weight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer wanagement Dimensions and weight Printer wight Operating environment	(Stateless Link-Local and via Route, Statefull via DHCPAD, SS. Security and Certificate management; Management; SMIPv1, SMIPv2, SMIPv3, HTTP/HTTPS, Syslog, FTP FW Download         Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X         No         Standard: 512 MB; Maximum: 512 MB         Standard: 2; Maximum: 3         Paper (plain, EccEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels;         Custom (metric): Tray 1: 76, 2x 127 to 215.9 x 355.6 mm State(Rotated: Envelope Monarch: Envelope BS; Envelope DL; Custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4, 54, 66; B5 (UIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Custom Size; A5 - R 4 x 6 in; 56 (UIS) ADF. Letter; Legal; A4; custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4, 54, 66; B5 (UIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Custom Size; A5 - R 4 x 6 in; 56 (UIS) ADF. Letter; Legal; A4; custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4, 54, 260 mm); 16K (197 x 273 mm); Custom Size; A5 - R 4 x 6 in; 56 (UIS) ADF. Letter; Legal; A4; custom Size; A1 x 8 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4, 54, 66; B5 (UIS) ADF. Letter; Legal; A4; custom Size; A5 - R 1 x 6 in; 50 coloral Maximum: 0 to 020 g/m²; tray 2, optional 550 - sheet tray 3: 60 to 120 g/m²         Tray 1: 60 to 200 g/m²; tray 2, optional 550 - sheet tray 3: 60 to 120 g/m²         Tray 1: 60 to 200 g/m²; tray 2, optional 550 - sheet tray 3: 60 to 120 g/m²         Windows 10; Windows 7; Windows 7; Windows 7; Modows Client 05; Android; IOS; Mobile OS; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; Chrome 05
Network capabilities Hard disk Hard disk Memory Media handling Number of paper trays Media size Media size Media andling Media usight Input capacity Output capacity Output capacity Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SMMPv1, SNMPv2, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download         Yes, via bult-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X         No         Standard: 512 MB; Maximum: 512 MB    Standard: 512 MB; Maximum: 512 MB     Standard: 512 MB; Maximum: 512 MB        Standard: 512 MB; Maximum: 512 MB    Standard: 512 NB; Maximum: 512 NB, Statement; Tray 2, 3: 104 9; 134 8; 59 to 215 9; x 355.6 mm; Supported Intett/2; Tray 1: A4; A5; A6; IDS; Oficio [216 x; 340 mm]; 16K (195 x 270 mm); 16K (194 x 260 mm]; 16K (197 x 273 mm); Lapanese Postcard; Double Jopan Postcard Rotated; Envelope H10; Envelope Monard; Envelope G5; Envelope C12; Envelope E12; Lostom Size; 4, 6 in; 5 x 81 m; Statement; Tray 2, 81 Tray 3: A4; A5; A6; B5 (UIS); Oficio [216 x; 340 mm]; 16K (195 x 270 mm); 16K (194 x 260 mm]; 16K (195 x 270 mm); 16K (194 x 273 mm); Lapanese Postcard; Double Jopan Postcard Rotated; Envelope H10; Envelope Monard; Envelope G5; Envelope C12; Euvelope E12; Lostom Size; 4, 6 in; 5 x 81 m; Statement; Tray 2, 81 Tray 3: A4; A5; A6; B5 (UIS); Oficio 125 a 240 mm]; 16K (195 x 270 mm); 16K (195
Network capabilities Hard disk Hard disk Hemory Media handling Number of paper trays Media types Media types Media size Media handling Media veight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimm system requirements Software included Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslag, FTP FW Download         Yes, via bullt-in 10/1000/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X         No         Standard, S12 MB; Maximum; S12 MB    Standard, S12 MB; Maximum; S12 MB     Standard, S12 MB; Maximum; S12 MB     Standard, S12 MB; Maximum; S12 MB        Standard, S12 MB; Maximum; S12 MB     Standard, S12 MB; Maximum; S12 MB        Standard, S12 MB; Maximum; S12 MB     Standard, S12 MB; Maximum; S12 MB        Standard, S12 MB; Maximum; S12 MB       Standard, S12 MB; Maximum; S12 MB       Standard, S12 MB; Maximum; S12 MB       Standard, S12 MB; Maximum; S12 MB       Standard, S12 MB; Maximum; S12 MB       Standard, S12 MB; Maximum; S12 MB       Standard, S12 MB; Maximum; S12 MB       Standard, S12 MB; Maximum; S12 MB       Standard, S12 MB; Maximum; S12 MB       Standard, S12 MB; Maximum; S12 MB       Standard, S12 MB; Maximum; S12 MB; S20 Control, Ietterhead, preprinted, prepunched, recycled, rough): envelope S1; Envelope C5; Envelope D1; Custom S2e; 45 x 61; KS (S1); S10; Etol S12 S12 S1 x 352 KB m3; S
Network capabilities Hard disk Hard disk Memory Media handling Number of paper trays Media size Media size Media andling Media usight Input capacity Output capacity Output capacity Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions	(Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download         Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1 X         No         Standard: 512 MB, Maximum: 512 MB    Standard: 512 MB, Maximum: 512 MB     Standard: 512 MB, Maximum: 512 MB     Standard: 512 MB, Maximum: 512 MB        Custom (metric)     Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2: 3: 104.9 x 148,59 to 215.9 x 355.6 mm    Standard: 512 MB, Maximum: 512 MB        Standard: 512 MB, Maximum: 512 MB     Custom (metric) Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2: 3: 104.9 x 148,59 to 215.9 x 355.6 mm    Standard Input: 100-sheet tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2: 3: 104.9 x 148,59 to 215.9 x 355.6 mm Supported (metric). Tray 1: Aki; A5 (A6; B5 (US); Ofticio (216 x 340 mm); 16K (195 x 270 mm); 16K (195 x 250 mm; 104.7 x 23 mm); Los (104 x 260 mm); 16K (195 x 250 mm; 178 y 2: A 45 in g 50 KB) ADD (195 KB) (Los (104 x 260 mm); 16K (195 x 250 mm; 178 y 2: A 45 in g 50 KB) ADD (195 KB) (Los (216 x 340 mm); 16K (195 x 250 mm; 196 KI 198 x 250 mm; 196 KI 198 x 250 mm; 196 KI 198 x 250 mm; 198 KI 19
Network capabilities Hard disk Hard disk Hemory Media handling Number of paper trays Media types Media types Media size Media handling Media veight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimm system requirements Software included Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics	IStatess Link-Local and via Router, StateJuli via DICPNoE, SSL. Security and Certificate management; Management; SMMPV1, SMMPv2, SMMPv3, HTTP/HTTPS, Syslog, FTP FW Download         Yes, via buli-in 0/100/100008ase-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X         No         Standard: S12 MB; Maximum; S12 MB
Network capabilities Hard disk Hard disk Memory Media handling Number of paper trays Media types Media types Media size Media andling Media andling Media andling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics Power	IStatess Link-Local and via Route; Statefull via DHCPv6), SS. Security and Certificate management: SNMPv1, SNMPv2, SNMPv2, SNMPv3, HTTP/HTTPS, Syslag, FTP FW Download         Ves: via built-in 10/100/10008ase-TX Ethernet; Gigabit: Auto-crossover Ethernet; Authentication via 802.1X         No         Standard: S12 MB. Maximum: 31         Paper (galan: CeEFFICIENT Light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels;         Custom fnett/b; Tray: 1:76.2 × 127 no 215.9 x355.6 mm; Tray 2.3: 10.49 × 148.5 bit 215.9 × 355.6 mm. Stapported (mrekite) Tray: 1:44,54 AS; AS; DS (DS; Olicio (216 × 340 mm); 16K (119 × 270
Network capabilities Hard disk Hard disk Hernory Media handling Number of paper trays Media types Media size Media size Media handling Media weight Input capacity Output capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology	Stateless Link-Local and va Routes, Stateful via DMCPA0; SSL Security and Certificate management; Management; SNMPv2, SNMPv2, SNMPv2, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download         Yes, via built-in 10100/1000/0008se-FX Ethemet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X         No         Standard: 2 Maximum: 3         Paper (glain: Caline: EFTICENT, Uglin, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough): envelopes: labels:         Classim (metric): Tray 1: 762.x1; 27 tot 21: 58 x3; 55.6 mm; Tray 2: 24: 104.9 x148.59 tot 21: 58 x3; 55.6 mm. Supported (metric): Tray 1: 762.x1; 27 tot 21: 58 x3; 270 mm; 164 (195 x x20 mm); 174 (195 x x20 mm)
Network capabilities Hard disk Hard disk Hemory Media handling Number of paper trays Media types Media size Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible operating systems Software included Printer management Dimensions and weight Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics Power	Stateless Link-Local and va Routes Stateful via DMCPA0; SSL Security and Certificate management; Management; SMMPv1, SMMPv2, SMMPv3, MTP/HTTPS, Syslog, FTP FW Download         Yes via ballich 101/001/1008/sse-TX Ethemet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X         No         Standard: 2, Maximum: 3         Paper (Jain: Carl, Tray: 1: 76.2 x 127 to 21: 56 x 355.6 mm; Tray: 2, 3: 104.9 x 148.55 to 21: 56 x 355.5 mm Supported (Imetric); Tray: 1: 76.2 x 127 to 21: 56 x 355.5 mm; Tray: 2, 3: 104.9 x 148.55 to 21: 55 x 355.5 mm Supported (Imetric); Tray: 1: 76.2 x 127 to 21: 56 x 30.5 mm; Tigk (1184 x 260 mm); 16K (1195 x 270 mm); 16K (1194 x 260 mm); 16K (1195 x 270 mm); 16K (1194 x 260 mm); 16K (1195 x 270 mm); 16K (1194 x 260 mm); 16K (1195 x 270 mm); 16K (1194 x 260 mm); 16K (1195 x 270 mm); 16K (1194 x 260 mm); 16K (1195 x 270 mm); 16K (1195 x 270 mm); 16K (1194 x 260 mm); 16K (1195 x 270 mm); 16K (1195 x 270 mm); 16K (1195 x 270 mm); 16K (1194 x 260 mm); 16K (1195 x 270
Network capabilities Hard disk Hard disk Hemory Media handling Number of paper trays Media types Media size Media size Media handling Media weight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer weight Dimensions and weight Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology	Stateless Link-Local and via Bouter, Stateful via DHCPv6, SS. Security and Certificate management: Management: SNMPv1, SNMPv2, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download         View, via built-in 01/00/10008as-TX Ethernet, Gigabit, Auto-crossover Ethernet, Authentication via 802.1X         No         Standard: 512 MB, Maximum: 312         Paper (plain, EGCEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels:         Custom (metric), Tray: T-R2 x1 271 x2 x1 25 x3 355, mm; Tray 2, 31:04 x148.59 to 215 xx 355, mm. Supported (metric), Tray: T-R4, S6; B5 (US); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (194 x 260 mm); 16K (195 x270 mm); 16K (194 x 260 mm); 16K (195 x270 mm); 16K (194 x 260 mm); 16K (195 x270 mm); 16K (194 x 260 mm); 16K (195 x270 mm); 16K (195 x270 mm); 16K (196 x 270 mm); 16K (197 x270 mm); 16K (197
Network capabilities Hard disk Hard disk Hemory Media handling Number of paper trays Media types Media types Media size Media handling Media veight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer dimensions (W × D × H) Printer weight Dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology Certifications	StateSize Link-Local and Vale Router, StateSitu Vale APECPV6, SS. Security and Certificate management: Management: SNMPV1, SNMPV2, SNMPV3, HTTP/HTTPS, Syslag, FTP FW Download         Ves. via built-in 01/00/10008as-TX Ethernet, Gigabit; Auto-crossover Ethernet, Authentication via 802.1X         No         Standard: 512 M8, Maximum: 3         Paper (Jain, ExcEFFICEN); Light, Heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough), envelopes; Labels;         Custom InterNo: Tray: 17: R2 x1 271 col 25 sy x355 mm; Tray; 2, 3: 104 sy 148.958 to 127 Sy x355 mm; Supported (InterNo: Tray): TAX, A54, B5 (ISS), Officio (2216 x 400 mm); 16K (1194 x 260 mm); 17F (1196 x 200 mm); 16K (1194 x 260 mm); 16K (1194 x 260 mm); 17F (1196 x 200 mm); 16K (1196 x 200 mm); 16K (1196 x 20
Network capabilities Hard disk Hard disk Hernory Media handling Number of paper trays Media types Media size Media size Media handling Media weight Input capacity Output capacity Output capacity Compatible operating systems Gompatible network operating systems Minimum system requirements Software included Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology Certifications Sustainable impact specifications	Stateless Link-Local and via Router, Statelul va BURD+60, SS. Security and Certificate management; NAnagement; SNAMPV2, SNMPV2, SNMPV3, HTTP/HTTPS, Syslog, FTP PM Download         Yes, via built-in 101/001/0008ase-TX: Elternet, Guigblir, Auto-crossover: Elternet; Authentication via 802.1 X         No.         Standard; 512:NB. Maximum; 312:MB         Standard; 512:NB. Maximum; 312:MB         Standard; 2:Maximum; 3         Paper [Jain: CoEFFICIENT, Light, Newy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; Labels;         Custom (metric): Tray: 1:76, 2x 127 to 2:15 x 355.5 mm; Tray; 2:3:104.9 x 104.9 x 104.9 51 0:2:15 x 355.6 mm; Supported (metric): Tray: 1:44, 45; A6; B5 (LIS); Otico (2:16 x 340 mm); 16K (119 x 227 mm); 16K (119 x 227 mm); 16K (119 x 227 mm); 16K (119 x 22.3 mm); 16K (1100 x 20.0 mm); 16K (110 x 20.0 mm); 16K (110 x 20.0 mm);
Network capabilities Hard disk Hard disk Hard disk Memory Media handling Number of paper trays Media types Media types Media size Media handling Media veight Input capacity Output capacity Output capacity Compatible network operating systems Minimum system requirements Software included Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology Certifications	StateSize Link-Local and Vale Router, StateSitu Vale APECPV6, SS. Security and Certificate management: Management: SNMPV1, SNMPV2, SNMPV3, HTTP/HTTPS, Syslag, FTP FW Download         Ves. via built-in 01/00/10008as-TX Ethernet, Gigabit; Auto-crossover Ethernet, Authentication via 802.1X         No         Standard: 512 M8, Maximum: 3         Paper (Jain, ExcEFFICEN); Light, Heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough), envelopes; Labels;         Custom InterNo: Tray: 17: R2 x1 271 col 25 sy x355 mm; Tray; 2, 3: 104 sy 148.958 to 1271 Sy x355 mm; Supported (InterNo: Tray): TAX, A54, B5 (ISS), Officio (2216 x 400 mm); 16K (1194 x 260 mm); 17m 1: 106 x 100 mm); 17m 1: 106 x 100 mm; 17m 1: 106 x 100 mm); 17m 1: 106 x 100 mm); 17m 1: 106 x 100 mm; 17m 1: 106 x 100 mm); 17m 1: 106 x 100 mm); 17m 1: 106 x 100 mm; 17m 2: 100 mm); 17m 1: 106 x 100 mm; 17m 2: 100 mm; 17m 2: 100 mm); 17m 2: 100 mm; 17m 2: 100 mm); 17m 2: 100 mm;
Network capabilities Hard disk Hard disk Hemory Media handling Number of paper trays Media types Media size Media size Media handling Media veight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology Certifications Sustainable impact specifications Country of origin	Statebils Link-Local and Valk Router, Statebil valk DRCPe6, SS. Security and Certificate management; Nangement; SNMPVJ,

#### Footnotes

<sup>1</sup> Measured using ISO/IEC 24734 and excludes first set of test documents. For more information, see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

<sup>2</sup> Requires the HP Smart app download. For details on local printing requirements see http://www.hp.com/go/mobileprinting. Certain features/software are available in English language only, and differ between desktop and mobile applications. Subscription may be required. Internet access required and must be purchased separately. HP account required for full functionality. List of supported operating systems available in app stores. Fax capabilities are for sending a fax only. After 3 months, a monthly fee applies to continue advanced features with HP Smart Pro. For more information, see http://www.hpsmart.com.

<sup>3</sup> Easy setup and manage - Requires use of Smart Admin Dashboard for printer setup and onboarding of users.

<sup>4</sup> HP Web Jetadmin is available for download at no additional charge at hp.com/go/webjetadmin.

<sup>5</sup> Wireless operations are compatible with 2.4 GHz and 5.0 GHz operations only. Learn more at hp.com/go/mobileprinting. Wi-Fi is a registered trademark of Wi-Fi Alliance®. Supports both 5.0 GHz and 2.4 GHz using up to 12 nonoverlapping channels vs only 3 non-overlapping channels for 2.4 GHz only. Supports 5.0 GHz band (up to 150 mbps) vs 2.4 GHz band (up to 72.2 mbps). Internet access required and must be purchased separately.

<sup>6</sup> HP JetAdvantage Security Manager must be purchased separately. To learn more, please visit hp.com/go/securitymanager. <sup>7</sup> Recycling: Through the HP Planet Partners program (where available), recycled plastics are used as raw material and combined with other materials to help make new Original HP cartridges and other everyday products. For

details, see http://www.hp.com/recycle. <sup>8</sup> Save up to 50% on toner (mono) – Based on monthly subscription cost of HP Instant Ink monochrome toner service 1,500 page plan without purchase of additional sets of pages compared to cost per page to print ISO/IEC 24711 pages on most in-class, traditional A4 monochrome toner cartridge printers <€494 and MFPs priced <€672 using original standard-capacity integrated cartridges (toner and drum in one cartridge). Average CPP per country used to determine percent savings claim versus CPP for HP Instant Ink. Sale prices not considered for this study. Printers which only use XL cartridges excluded due to non-standard hardware & supplies model. Keypoint Intelligence September 2021 study commissioned by HP, based on publicly available information as of August 18, 2021. Printers selected by market share in IDC Quarterly Hardcopy Peripherals Tracker – Final Historical 2021Q2. For details: www.keypointintelligence.com/HPInstantInk.

<sup>9</sup> Automatic delivery and consolidated bill: Printers require direct connection to the Internet for program participation. Internet access sold separately.

<sup>10</sup> Never run out: Based on plan usage, Internet connection to eligible HP printer, valid credit/debit card, email address, and delivery service in your geographic area.

<sup>11</sup> Change or cancel: Change or cancel your plan at any time online. If you decide to cancel your HP Instant Ink you can go back to using HP original Standard or XL cartridges. Plan upgrades are effective immediately and the charges will be applied retrospectively or in the next billing cycle, depending on user choice. Plan downgrades and cancellations are effective after the last day of the current billing period. For full details go to hoinstantink.com/terms.

#### Technical specifications disclaimers

<sup>1</sup> Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

<sup>2</sup> Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

<sup>3</sup> Job Storage feature requires a purchase of separate USB flash drive with a minimum of 16 GB capacity.

<sup>4</sup> Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.

<sup>5</sup> Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh).

<sup>6</sup> Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device and 230V for Blue Angel. Please be aware that HP LaserJet Pro 4001 and MFP 4101 series products are ENERGY STAR 3.0 certified in the US and the functionally equivalent HP LaserJet Pro 4003 and MFP 4103 series meet ecolabel energy efficiency limits.

<sup>7</sup> For yield information on the cartridge included with your printer, see http://www.hp.com/go/toneryield. Yield values measured in accordance with ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors.



© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ab-en March 2023

