

Memory Module Specification

KVR400D2R3K2/1G

1GB (512MB 64M x 72-Bit x 2 Pcs.) DDR2-400 CL3 Registered 240-Pin ECC DIMM Kit

DESCRIPTION:

ValueRAM's KVR400D2R3K2/1G is a kit of two 64M x 72-bit (512MB) DDR2-400 CL3 SDRAM (Synchronous **DRAM**) registered ECC memory modules. Total kit capcity is 1GB (1024MB). The components on each module include nine 64M x 8-bit (16M x 8-bit x 4 Bank) DDR2-400 SDRAM in FBGA packages. Each 240-pin DIMM uses gold contact fingers and requires +1.8V. The electrical and mechanical specifications are as follows:

FEATURES:

✓ Clock Cycle Time (tCK) CL=3

Row Cycle Time (tRC)

Refresh to Active/Refresh Command Time (tRFC)

Row Active Time (tRAS)

Single Power Supply of

Power

UL Rating

5ns (min.) / 8ns (max.)

55ns (min.)

40ns (min.) / 70,000ns (max.)

+1.8V (+/-.1V)

2.277 W (operating per module)

94 V - 0

Note: The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 1.250" (31.75mm).




Figure 1: KVR400D2R3K2/1G 240-Pin DIMM