

KVR800D2S6/512
512MB 64M x 64-Bit DDR2-800
CL6 200-Pin SODIMM

DESCRIPTION:

This document describes ValueRAM's 64M x 64-bit (512MB) DDR2-800 CL6 SDRAM (Synchronous **DRAM**) memory module. The components on this module include eight 64M x 8-bit DDR2-800 SDRAM in FBGA packages. This 200-pin SODIMM uses gold contact fingers and requires +1.8V. The electrical and mechanical specifications are as follows:

FEATURES:

☑ Clock Cycle Time (tCK) CL=6	2.5ns (min.) / 8ns (max.)
☑ Row Cycle Time (tRC)	60ns (min.)
☑ Refresh to Active/Refresh Command Time (tRFC)	105ns
☑ Row Active Time (tRAS)	45ns (min.) / 70,000ns (max.)
☑ Single Power Supply of	+1.8V (+/- .1V)
☑ Power	1.224 W (operating)
☑ UL Rating	94 V - 0

Note: The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 30mm.




Figure 1: KVR800D2S6/512 240-Pin SODIMM