

Additional Information – Digital IXUS 980 IS and Digital IXUS 870 IS

Printing

The Digital IXUS 980 IS and Digital IXUS 870 IS feature a dedicated Print menu for quick access to direct print options. Full PictBridge support means users can print directly to any PictBridge compatible printer without the need for a PC. A Print/Share button allows one-touch printing and easy uploads to Windows or Mac systems.

Language

The Digital IXUS 980 IS and Digital IXUS 870 IS feature a user interface that supports 26 languages: English, German, French, Dutch, Danish, Finnish, Italian, Norwegian, Swedish, Spanish, Simplified Chinese, Traditional Chinese, Japanese, Russian, Portuguese, Korean, Greek, Polish, Czech, Hungarian, Turkish, Thai, Arabic, Romanian, Ukrainian and – new for Autumn 2008 - Farsi.

Memory Card Support

In addition to SD, SDHC and MMC memory cards, the Digital IXUS 980 IS and Digital IXUS 870 IS support MMCplus and HC MMCplus card formats. Both cameras are supplied with a 32MB memory card.

Software and CANON iIMAGE GATEWAY¹

The Digital IXUS 980 IS and Digital IXUS 870 IS come bundled with the following Canon Software:

- ZoomBrowser EX 6.2 (Windows), ImageBrowser 6.2 (Macintosh): For organising and editing images, movies and slideshows, or creating and printing digital photo albums.
- PhotoStitch 3.1 (Windows), PhotoStitch 3.2 (Mac): For creating panoramic photos from multiple images.

The bundled software supports Windows Vista (including SP1) / XP SP2 and Macintosh OS X v10.4-10.5. Both cameras support PTP for driverless transfer to Windows XP and Macintosh OS X, along with MTP for image and movie transfers to Windows Vista.

¹ CANON iIMAGE GATEWAY is not available in all European countries. Please see www.cig.canon-europe.com for available countries. Movie upload requires users to download and install the movie upload task, available after registration.

Purchasers of the Digital IXUS 980 IS and Digital IXUS 870 IS are eligible for free membership of CANON iMAGE GATEWAY, 100MB of online 'personal gallery' space for sharing stills and video with family and friends.

Optional Accessories

The Digital IXUS 980 IS and Digital IXUS 870 IS can be combined with the following accessories:

- Soft case (DCC-70) – Digital IXUS 980 IS
- Soft case (DCC-75) – Digital IXUS 870 IS
- Waterproof case (WP-DC27) – Digital IXUS 980 IS
- Waterproof case (WP-DC26) – Digital IXUS 870 IS
- Waterproof Case Weight WW-DC1
- High Power Flash (HF-DC1)
- Digital IXUS metal strap
- Digital IXUS leather strap
- AC Adaptor Kit (ACK-DC30)

Technologies Explained

DIGIC 4

Canon's DIGIC 4 (Digital Imaging Core) image processor manages all of the camera's primary functions to optimize operating efficiency. Advanced image processing algorithms deliver superb image detail and colour reproduction with accurate white balance. High-speed processing results in outstanding responsiveness, rapid auto focus and extended continuous shooting ability. DIGIC 4 also powers advanced Noise Reduction Technology, i-Contrast and Face Detection AF/AE/FE/WB.

Face Detection AF/AE/FE/WB, Face Select & Track and FaceSelf-Timer

Canon's Face Detection AF/AE/FE/WB system automatically detects up to 35 faces within a frame before adjusting focus, exposure, flash and white balance to ensure optimal results. It is able to determine which faces are intended to be the subject, instantly reverting to the partnering 9-point AiAF system if no face is the primary subject. Face Select & Track allows the user to select a particular face to be the main subject of a photograph and track it, for the best possible results. FaceSelf-Timer allows easy group shots by automatically triggering the shutter shortly after a new face has entered the frame.

i-Contrast

Available in either shooting or playback mode, Canon's i-Contrast function analyses the exposure, dynamic range and other image characteristics of a shot, then adaptively increases the gain in dark areas – to produce heightened detail in darker regions, without blowing out correctly-exposed parts of the image. The noise reduction function of DIGIC 4 ensures minimal noise in adjusted areas.

iSAPS

iSAPS (intelligent Scene Analysis based on Photographic Space) automatically optimises key camera settings before every shot. Each scene is analysed and cross-referenced against Photographic Space – a vast in-camera library of photographic data. This enables the camera to make optimal adjustments to auto exposure, auto focus and auto white balance before image capture occurs.

Optical Image Stabilizer

The Digital IXUS 980 IS and Digital IXUS 870 IS use a lens shift-type Image Stabilizer (IS) system to detect and correct slight camera shakes that can cause image blur. Minute vibration gyros detect lens tilting caused by hand shake. These signals – 8,000 per second on the Digital IXUS 980 IS, and 4,000 per second on

the Digital IXUS 870 IS – are processed by a single-chip IS controller, which discriminates between hand shake and unintentional camera movements. Shake signals are sent to the IS unit, which moves one of the lens elements accordingly to deflect the light rays and cancel out the effects of shake. For improved accuracy and responsiveness, the moving lens element is supported on tiny ceramic spheres. In addition to minimising friction, ceramic spheres avoid some of the problems that can affect metal systems, such as thermal expansion and magnetism. The optical IS allows photographers to shoot at shutter speeds up to 4 stops slower (Digital IXUS 980 IS) and 3 stops slower (Digital IXUS 870 IS) with no perceptible increase in image blur due to camera shake.