LG Monitor Guide April 2005



Premium and Style

80 Series

L1780O, L1980O

The 80 Series represent style and cutting edge functionality. With Forte Hinge and Forte Mirror technology the monitor can be turned 360° 80 Series backwards and the screen contents will automatically rotate. Forte Pivot allows the screen to be turned from landscape to portrait and with the slimmest monitor head depth at just 26mm, the monitor can even be folded flat to a height of 52mm. Ideal for business applications or for the consumer who likes to be at the leading edge of technology. Available in 17" or 19" models.



L1740P. L1740B. L1940P. L1940B

The elegant, curved form of the 40 Series is perfect for style conscious individual looking for a design statement. With Flatron f Engine technology, a high contrast ratio, wide viewing angle, low response time and DVI available. Models include 17" or 19".



40 Series

13 Series

13 Series

L1713P. L1913P. L2013P

The 13 Series are designed and equipped to play an integral role in every office. Features include height adjustment, Swivel, Pivot and Tilt functionality. The Ultra narrow bezel design, allows the monitors to be tiled. With Digital input and certified to TCO-03 - with the 13 Series work has never been made easier. Available in 17". 19" or 20" models.

Main LCDs

50 Series

L1550S, L1750H, L1750G, L1750S. L1950H, L1950G, L1950S

With the 50 Series users will enjoy all the benefits of LG's advanced LCD screen technology that eliminates glare, image distortion and screen flicker, 50 Series allowing sharp, comfortable viewing without fatigue. With a fast response time, ultra slim bezel design, LightView function and certified to TCO-03. Available in 15". 17" or 19" models.

30 Series

L1530S, L1730S, L1730B, L1730P, L1930S, L1930B The ergonomic design of the 30 Series makes it perfect for the working environment. With a sophisticated circular stand and streamlined curved 30 Series back, a quick response time, integrated Flatron f Engine technology for high digital picture quality, high contrast ratio and a new standard in brightness, users looking for a balance between design and performance need look no further. Models include 15". 17" and 19" versions.

10 Series

models.

L1510M, L1710M

With integrated speakers these silver monitors are ideal for web based and interactive communication applications. The power block is incorporated into the back of the panel reducing cable clutter and making wall mounting simple and easy. Other features include on touch automatic resizing for intelligent image resizing at the touch of a button as well as LightView function. Available in 15" or 17"



10 Series

15 Series

L1515S, L1715S, L1915S

The 15 Series is the perfect choice for small offices. the home or educational users. With their built-in power adapter for reduced cable clutter and mounting slots, the monitor can be easily wall 15 Series mounted. OSD lock function prevents unwanted changes to the display settings and the Auto Adjustment Function automatically sets image position, phase and pitch. With LG's LightView function users can freely adjust brightness and colour according to their application. Models include 15". 17" or 19" versions.



L172WT, L2323T, L3020T

LG offers multi-purpose all in-one display solutions for a variety of PC and home entertainment uses. With wide screen 15:9 aspect ratio, various AV/TV functions, remote control. TV tuner, and Multimedia speakers available. Models include 17", 23" or 30".





Large LCDs

L3200TF, L3700TF, L4200TF.

Ideal for public information display, a better alternative to plasma in terms of product life, power consumption, noise and glare. With high performance, wide viewing angle, superior resolution and ultra high brightness. Easily wall mountable. Models include 32". 37". 42".46" all with TV tuner.



L4200TF L3700TF



Specifications are subject to change, without prior notice



LG Monitor Guide April 2005

			/ / _								_IN	PUTS			STANE)
						SPONSE TIME	CONTRAST RATIO	/			IIN	015			JANL	ž /
			S S	- /.	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		15			15		æ			\$	J. J
¥				\\displaystarting \text{3.5}	THE STATE OF THE S	\8\\8\\\8\\\\8\\\\\8\\\\\\8\\\\\\\\\\\	The second second			, , , , , , , , , , , , , , , , , , ,	ور ۶	3	٨.	W .	· .	WED IN
5	ĮŽŽ	18 8	\\ \tilde{\pi}	/ <i>8</i>	1948 B.	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	<i>\§</i>	ر کی ا	1	70	MDEO		The state of the s	, Z	Ž,	
5" LCD																
510M	Integrated speakers, Slim bezel, VESA Compliant (standard 75)	15	1024x768	Silver	250cd/m2	16ms	450:1	99	•							
550S NEW	Ultra Slim Bezel design, Lightview, Analogue	15	1024x768	Silver	250cd/m2	16ms	450:1	99	•							
530S	Lightview, VESA Compliant (standard 75), circular stand	15	1024x768	Silver	250cd/m2	16ms	450:1	99	•							
15158	Value Entry Model, Slim Bezel design, Wide viewing angle, Lightview, OSD lock	15	1024x768	Grey	250cd/m2	16ms	450:1	99	•							
7" LCD																
172WT	Wide viewing angle, TV tuner, Video input, Digital input, Inbuilt speaker	17.1	1280x768	Silver	450cd/m2	12ms	600:1		•	•	•				• •	
	Rotate screen, contents automatically rotate, Superior Folding mechanism, Ultra slim, Digital input	17	1280x1024	White/Black/Silver	250cd/m2	8ms	500:1	99	•	•		•		**	•	
740P	Stylish black & white curved design, Fast Response Time, VESA Compliant, Digital Input	17	1280x1024	White/Black/Silver	300cd/m2	12ms	500:1	99	•	•					•	
740B	Stylish black & white curved design, Fast Response Time, VESA Compliant, Analogue Input	17	1280x1024	White/Black/Silver	250cd/m2	12ms	500:1	99	•						•	
	Ultra Slim Bezel design, quick response time, ergonomic design, Lightview, TCO-03	17	1280x1024	Silver	300cd/m2	16ms	500:1	03	•	•		•	•	•	•	
750H NEW	Ultra Slim Bezel design, quick response time, Lightview, Digital, TCO-03, Height adjust	17	1280x1024	Silver	250cd/m2	12ms	500:1	03	•	•			•	•	•	
750G NEW	Ultra Slim Bezel design, quick response time, Lightview, Analogue, TCO-03, Height adjust	17	1280x1024	Silver	250cd/m2	12ms	500:1	03	•				•	•	•	
	Ultra Slim Bezel design, quick response time, Lightview, Analogue, TCO-03	17	1280x1024	Silver	250cd/m2	12ms	500:1	03	•				•		•	
730P	Height adjustment, Lightview, Digital input, Landscape/Portrait, VESA Compliant (standard 100)	17	1280x1024	Silver	300cd/m2	12ms	500:1	03	•			•	•	•	•	
730B	Height adjustment, Lightview, Digital input, VESA Compliant (standard 100), circular stand	17	1280x1024	Silver	250cd/m2	12ms	500:1	99	•	•			•	•	•	
730S	Fast response time, Lightview, VESA Compliant (standard 100), circular stand	17	1280x1024	Silver	250cd/m2	12ms	500:1	99	•				•		•	
710M	Integrated speakers, Slim bezel, VESA Compliant (standard 75) fast response time	17	1280x1024	Silver	250cd/m2	16ms	500:1	99	•				•		• •	
715S	Value Entry Model, Slim Bezel design, Wide viewing angle, Lightview, OSD lock	17	1280x1024	Grey	250cd/m2	16ms	500:1	99	•							
9″ LCD																
980Q NEW	Rotate screen, contents automatically rotate, Superior Folding mechanism, Ultra slim, Digital input	19	1280x1024	White/Black/Silver	250cd/m2	8ms	500:1	99	•	•		•		**	•	
940P	Stylish black & white curved design, High contrast ratio, VESA Compliant, Digital Input	19	1280x1024	White/Black/Silver	300cd/m2	25ms	700:1	99	•	•					•	
940B	Stylish black & white curved design, High contrast ratio, VESA Compliant, Analogue Input	19	1280x1024	White/Black/Silver	250cd/m2	25ms	600:1	99	•						•	
913P NEW	Ultra Slim Bezel design, quick response time, ergonomic design, Lightview, TCO-03	19	1280x1024	Silver	300cd/m2	25ms	700:1	03	•	•		•	•	•	•	
950H NEW	Ultra Slim Bezel design, quick response time, Lightview, Height adjust, Digital, TCO-03	19	1280x1024	Silver	250cd/m2	12ms	500:1	03	•	•			•	•	•	
950G NEW	Ultra Slim Bezel design, quick response time, Lightview, Height adjust, Analogue, TCO-03	19	1280x1024	Silver	250cd/m2	12ms	500:1	03	•				•	•	•	
950S NEW	Ultra Slim Bezel design, quick response time, Lightview, Analogue, TCO-03	19	1280x1024	Silver	250cd/m2	12ms	500:1	03	•				•		•	
930B	Height adjustment, Lightview, Digital input, VESA Compliant (standard 100), TCO-03	19	1280x1024	Silver	250cd/m2	25ms	600:1	03	•	•			•	•	•	
930S	Lightview, VESA Compliant (standard 100), circular stand, Analogue	19	1280x1024	Silver	250cd/m2	25ms	600:1	99	•				•			
9155	Value Entry Model, Slim Bezel design, Wide viewing angle, Lightview, OSD lock	19	1280x1024	Grey	250cd/m2	12ms	500:1	99	•						•	
ARGE L	CD (20"+)															
200AF	Wide viewing angle, Ideal for public display use, Speakers available, VESA 600 Compliant	42	1600x1200	Black	500cd/m2	10ms	1000:1									
	TV function, Wide viewing angle, Ideal for public display use,	TZ	100001200	Diack	Joocu/ IIIZ	101113	1000.1									
, JOH INLW	Optional Speakers & stand, VESA 600 Compliant	37	1366x768	Silver	500cd/m2	8ms	1000:1		•							
200TE NEW	TV function, Wide viewing angle, Ideal for public display use,	3/	13000,700	JIIVEI	JUUCU/IIIZ	01115	1000.1									
ZOOTI INCW	Optional Speakers & stand, VESA 200 Compliant	32	1366x768	Silver	500cd/m2	8ms	1000:1									
020T	Wide viewing angle, Flexible input ports, Ideal for public display use,	JL	15000/00	JIIVCI	Joocu/ IIIZ	OHIS	1000.1									
0201	VESA 200x100 Compliant	30	1280x768	Silver	500cd/m2	12ms	500:1								*	
323T	Wide viewing angle, PIP/POP/PBP technology, Digital input, Remote control, VESA Compliant	23	1280x768	Black	450cd/m2	25ms	400:1		•	•	•					
	mae nemma angle, i ii / i Oi / i Di technology, Digital input, Remote control, YESA Compilant	23	12000/00	Diuck	15000/1112	251113	100.1								الکا کے	

^{*} Optional ** Folding only All LG monitors come with a 3 year on site warranty.

Optical Storage Guide April 2005



Super Multi DVD-Rewriters GSA-4163B, GSA-5163D, GMA-4080N

Award winning Super Multi DVD Rewriters can write, read and erase data on all DVD and CD media formats. They are all formats compatible as they support DVD +R/RW, DVD-R/RW. DVD-RAM. CD-R/RW and are Dual Layer DVD +R up to 8.5G. Available as an internal drive, external drive or internal slim drive for notebooks.



GMA-4080N

Combi GCC-4521B, GCC-4243N


Available as internal or internal slim for notebookCombine the best of CD- Rewriter (CD-R/RW) and DVD-Rom Reader with an LG Combi drive.



GDR-8163B

DVD-Rom GDR-8163B

ads DVD data at an incredible 16x and CD data at 52x. Access has never been so guick and video so clear.



With this CD-Rewriter you can read CD data at 52x and write at 32x. High speed recording is improved with AFT (Anti Flutter Technology).



GCE-8526B

LG's newest DVD-Rom drive	rea
at an incredible 16x and CD	4-

		/>	San			READ MAX SPEED									WRITE MAX SPEED					
MODE	3014	October 100 Company of the Company o	To Suite Sui	#000 000	6	MON.	MON. ONO	Any Ono	4 0,00	ONO.	ONOXO	70,000	THE MAY	8	ONO.	W. ONO.	Olo April	4.00	ONYONO	9 4× 040
GSA-4163B	DVD-RW	Internal Super Multi DVD-Rewriter	True 16x +R/-R / All DVD formats compatible	Beige / Black/Silver	40	16	8	8	10	10	8	5	24	40	5	6	8	16	4	16
GSA-5163D	DVD-RW	External Super Multi DVD-Rewriter	Carry and Burn, DVD+R DL support up to 8.5G	Ivory	40	16	8	8	10	10	8	5	24	40	5	6	8	16	4	16
GMA-4080N	DVD-RW	Slim Super Multi DVD-Rewriter	Slim drive for Notebook PC	Black	24	8	6	6	8	8	4	3	16	24		4	4	8	2.4	8
GCC-4521B	COMBI	CD-RW & DVD-ROM Reader	32 X CD-RW write / 16 X DVD read	Beige / Black/Silver	52	16							32	52						
GCC-4243N	COMBI	Slim CD-RW & DVD-ROM Reader	Slim drive for Notebook PC	Black	24	8							24	24						
GDR-8163B	DVD-ROM	DVD-Rom Multi Reader	Play all DVD formats	Beige / Black/Silver	52	16														
GCE-8526B	CD-RW	CD-Rewriter	52x CD-R, 32 X CD-RW Write	Beige / Black/Silver	52								32	52						

BOOM	8	DATA TRANSF RATE(/s)	/	A CALONO	CCESS (mse		Sell STREET THE SELLING	W * H * D (mm)	WEIGHT (E)		WARRANTY
GSA-4163B	6000 KB	22.16 Mbytes /s	125	145	165	2MB with buffer underrun prevention technology	E-IDE / ATAPI	145 x 184.6 x 41.3	920	Windows98 SE, ME, 2000 Pro, XP Home Edition, Pro	2 yrs
GSA-5163D	6000 KB	22.16 Mbytes /s	125	145	165	2MB with buffer underrun prevention technology	USB 2.0 / IEEE 1394	163.2 x 244.7 x 54	1460	Windows 2000 Pro, XP Home Edition	2 yrs
GMA-4080N	3600 KB	11080 KB	140	160		2MB with buffer underrun prevention technology	Internal E-IDE / ATAPI	128 x 129 x 12.7	180	Window 98SE, ME, 2K Pro, XP Home Edition / Pro	2 yrs
GCC-4521B	7800 KB	21600 KB	100	120		2MB with buffer underrun prevention technology	Internal E-IDE / ATAPI / ULTRA DMA 33	146 x 184.7 x 41.3	900	Window 3.1 (only read),95,98,98SE,2K,ME,NT4.0 or later,XP	2 yrs
GCC-4243N	3600 KB	11080 KB	110	120		2MB with buffer underrun prevention technology	Internal E-IDE / ATAPI	128 x 129 x 12.7	195	DOS 3.1 (only read), Window95 (only read), 98SE, ME, NT, 2K, XP	2yrs
GDR-8163B	7800 KB	22100 KB	98	110		256KB with buffer underrun prevention technology	Internal E-IDE / ATAPI / ULTRA DMA 33	146 x 184.6 x 41.3	780	Window 95,98,2K,ME,NT4.0 or later, XP	2 yrs
GCE-8526B	7800 KB		90			2MB with buffer underrun prevention technology	Internal E-IDE / ATAPI	146 x 184.7 x 41.3	900	Window 95 (only read),98,2K,ME,NT4.0 or later, XP	2 yrs

Suffix Meaning BB Bulk BA Bare Bulk Black bulk Black Bare Bulk BRL Black Retail