

ENERGY STAR® Power and Performance Data Sheet

PRIMERGY RX300 S5; LKN:R3005S0021IN



System Characteristics

Form Factor	2U Rackmount
Available Processor Sockets	2
Available DIMM Slots / Max Memory Capacity	18 / 144GB
ECC and/or Fully Buffered DIMMs	ECC and registered DIMMs
Available Expansion Slots	7 PCIe
Minimum and Maximum # of Hard Drives	0 and 12
Redundant Power Supply Capable?	Yes
Power Supply Make and Model	Delta Electronics, DPS-800GB-3 A
Power Supply Output Rating* (watts)	800W
Minimum and Maximum # of Power Supplies	1 and 2
Input Power Range (AC or DC)	100 - 240V AC
Power Supply Efficiency at Specified Loadings*	84.4%@10%, 89.6%@20%, 92.2%@50%, 90.9%@100%
Power Supply Power Factor at Specified Loadings*	0.819@10%, 0.921@20%, 0.974@50%, 0.989@100%
Operating Systems Supported	Microsoft® Windows Server® 2008 Microsoft® Windows Server® 2003 Novell SUSE Linux Enterprise Server Red Hat Enterprise Linux Citrix® XenServer™ VMware Infrastructure VMware vSphere 4.0
Installed Operating System for Testing	MS Windows Server 2008 Enterprise Edition, SP2

* Note: Power supply information is for a single power supply only

System Configurations

Processor Information	2 x Intel® Xeon® X5550 (4 cores, 2.66GHz)
Memory Information	12GB (6 x 2GB), PC3-10600R DDR3-1333 reg ECC
Internal Storage	1 x 2.5" SATA HDD, 120GB, 5400 RPM
I/O Devices	1 x Intel® 82575EB Dual Port Gigabit Server Adapter
Power Supply Number and Redundancy Configuration	2 installed, (1 redundant)
Management Controller or Service Processor Installed?	Yes
Other Hardware Features / Accessories	8 port SAS RAID Controller with LSI 1068 in PCIe slot

Power Data

Idle Category (1S and 2S only)	Category D: Managed Dual Installed Processor (2P) Servers
ENERGY STAR Idle Power Allowance (1S and 2S only)	186W
Measured Idle Power (watts)	135,3
Power at Full Load* (watts)	262,6
Benchmark / Method Used for Full Load Test	SiSoftware Sandra Engineer 2009.SP3c, .Net Multimedia, Double x1
Test Voltage and Frequency for Idle and Full Load Test	230V / 50Hz
Range of Total Estimated Energy Usage ** (kWh/year)	2370 to 4601
Link to Detailed Power Calculator (if available)	http://ts.fujitsu.com/products/standard_servers/e_efficient.html

* Note: Full load power represents the sustained, average power at 100% load of the given workload, and does not necessarily represent the absolute peak power or the highest average, sustained power possible for other workloads.

** Note: Estimated kWh/year gives the absolute range of energy use a user could expect from continuous operation (24x365) and ranges from 100% Idle usage to 100% full load operation. The calculation also includes typical data center overhead at a ratio of 1 watt of overhead to every 1 watt of IT load (corresponding to a PUE of 2.0). Closer approximations may be found by using established power calculators and specific information about the intended operating environment (e.g., average time at Idle, data center PUE, etc.).

ENERGY STAR Power and Performance Data Sheet

PRIMERGY RX300 S5; LKN:R3005S0021IN



Power and Performance for Benchmark #1

Benchmark #1	Benchmark Used and Type of Workload	SiSoftware Sandra Engineer 2009.SP3c, .Net Multimedia, Double x1
	Avg. Power Measured During Benchmark Run	262,6W
	Benchmark Performance Score	51,27Mpixel/s
	Power Performance Ratio (perf score/avg. power)	0.20Mpixel/s / W
	Link to Full Benchmark Report (Where Available)	N/A

Power and Performance for Benchmark #2 (optional)

Benchmark #2	Benchmark Used and Type of Workload	
	Avg. Power Measured During Benchmark Run	
	Benchmark Performance Score	
	Power Performance Ratio (perf score/avg. power)	
	Link to Full Benchmark Report (Where Available)	

Power Saving Features	Enabled on Shipment	End-User Enabling Required
Processor Dynamic Voltage and Frequency Scaling	X	
Processor or Core Reduced Power States	X	
Power Capping		X
Variable Speed Fan Control Based on Power or Thermal Readings	X	
Low Power Memory States		
Low Power I/O States		
Liquid Cooling Capability		
Other1:		
Other2:		
Other3:		
Other4:		

Power and Temperature Measurement and Reporting

Input Power Available & Accuracy?	Yes, +10% above 200W and +25% until 200W
Input Air Temp Available & Accuracy?	Yes, +/- 3°C
Processor Utilization Available?	Yes
Other Data Measurements Available & Accuracy?	
Compatible Protocols for Data Collection	IPMI
Averaging method and time period	Linear Average calculation / 5 sec.

Thermal Information *

	Minimum	Typical	Maximum
Reference Configurations		2xX5550; 6x2GB, PC3-10600R; 1x120GB, 5400 RPM SATA; 2x800W PSU	
Total Power Dissipation (watts)		235	
Delta Temperature at Exhaust at Peak Temp. (°C)		11	
Airflow at Maximum Fan Speed (CFM) at Peak Temp.		135m ³ /h	
Airflow at Nominal Fan Speed (CFM) at Nominal Temp.		70m ³ /h	

* Thermal information is provided for the minimum, typical and maximum configurations for the model line
References: ASHRAE Extended Environmental Envelope Final August 1, 2008
Thermal Guidelines for Data Processing Environments, ASHRAE, 2004, ISBN 1-931862-43-5
Peak temperature is defined as 35 °C, Nominal Temperature is defined as 18 - 27 °C

Notes

1. Benchmark results stated above reflect results published on 08/07/2009.