

KVR667D2E5/512I

**512MB 64M x 72-Bit DDR2-667
CL5 ECC 240-Pin DIMM**

DESCRIPTION:

This document describes ValueRAM's 64M x 72-bit (512MB) DDR2-667 CL5 SDRAM (**Synchronous DRAM**) ECC "Intel Certified" memory module. The components on this module include nine 64M x 8-bit (16M x 8-bit x 4 Bank) DDR2-667 SDRAM in FBGA packages. This 240-pin DIMM uses gold contact fingers and requires +1.8V. The electrical and mechanical specifications are as follows:

FEATURES:

<input checked="" type="checkbox"/> Clock Cycle Time (tCK) CL=5	3ns (min.) / 8ns (max.)
<input checked="" type="checkbox"/> Row Cycle Time (tRC)	54ns (min.)
<input checked="" type="checkbox"/> Refresh to Active/Refresh Command Time (tRFC)	105ns
<input checked="" type="checkbox"/> Row Active Time (tRAS)	39ns (min.) / 70,000ns (max.)
<input checked="" type="checkbox"/> Single Power Supply of	+1.8V (+/- .1V)
<input checked="" type="checkbox"/> Power	1.701 W (operating)
<input checked="" type="checkbox"/> UL Rating	94 V - 0

Note: The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 1.250" (31.75mm).




Figure 1: KVR667D2E5/512I 240-Pin DIMM