

Philips AVENT DECT baby monitor

SCD498/00

Guaranteed zero interference

With DECT digital technology

This digital technology provides a secured, private connection, because you want to be the only one listening to your baby. Automatically chooses an unused channel and switches as it detects another device using the same channel.

Complete peace of mind

- · Guarantees zero interference from any other device
- Indicates a continuous connection between the two units
- Uses lights to indicate if the baby makes noise

Ultimate mobility in and around the house

- Travel pouch for easy storage
- · Belt clip and neck cord for hands-free convenience
- Rechargeable parent unit for minimum 24 hours of monitoring
- Small, mobile parent unit to freely roam around the house
- 300 m range ensures secure reception in and around the house

Soothing sights and words

- Comforts the baby in the dark with soothing stars
- Provides the ability to allow you to talk to the baby



Highlights

Guaranteed zero interference



Guarantees zero interference from any other device (other baby monitors, cordless phones and cell phones). Provides a secure and private connection using data encryption. You will be the only one who can hear your baby and you only hear your own baby.

Digital signal confirmation



Indicates a continuous connection between the baby and the parent unit with visible and audible link indicators.

Sound level lights

Uses lights to indicate if the baby makes noise, even with volume off.

Travel pouch

Travel pouch for easy storage while traveling.

Belt clip and neck cord

The belt clip and neck cord provide hands-free convenience and mobility: clip the parent unit to your belt or wear it around your neck.

Small, mobile parent unit



Allows you to freely roam around the house due to the small size, but still hear when your baby needs

With a range up to 300 m

With a range up to 300 m you are ensured a secure reception in and around the house.

Starry night-light

Nightlight with soothing stars to comfort your baby.

Parent talkback

Provides the ability to allow you to hear the baby and talk to the baby.

Specifications

Technical specifications

- Operating temperature range: 0 .. 40 °C
- Storage temperature range: -20 .. +60 °C

Tuner/Reception/Transmission

- Frequency band: DECT
- Automatic channel selection
- Number of channels: 120

Convenience

- · Auto out of range warning
- Battery charging indication
- Battery low indication
- Night light
- · Power on indication
- Sound-level lights
- System check: Battery check light, System check alarm, System check light
- Volume control

Accessories

- AC/DC adaptor: 2x 9VDC, 300mA
- Batteries: 2 x AAA NiMH rechargeable
- Belt clip
- Charger: Charging base for parent unit
- DFU/ user manual: Dutch, English, Finnish, French, German, Greek, Italian, Portuguese, Spanish, Swedish, Norwegian, Danish
- · Quick start guide

Power

- Charging time: 8 hour(s)
- Power supply: 230-240 V
- Rechargeable
- Operating time on battery: 24 hour(s)

Logistic data

- FAN F-hox
- F-box dimensions (W \times H \times D): 305 \times 187 \times 135 mm

Development stages

• Stages: 0 - 6 months, 6 - 12 months



Issue date 2010-11-22

Version: 4.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

12 NC: 0000 000 00000

www.philips.com