



**HP Everyday Adhesive Matte Polypropylene is versatile, durable and produces quality prints with excellent colour vibrancy at an everyday price. Ideal for both indoor and outdoor applications.**

**Ideal for retail, POS/POP, Commercial & Signage PSPs, high-volume customers and customers looking for an everyday self-adhesive polypropylene.**

HP Everyday Adhesive Matte Polypropylene is a good quality matte polypropylene material that produces long-lasting prints with outstanding image quality ideal for eye-catching POP and retail displays, and event signage.

HP Everyday Adhesive Matte Polypropylene is easy to use and handle for quick and large production runs, post-print processing and application to many surface types. Get exceptional performance at a low price.

This tear resistant, easy-to-handle HP Everyday Adhesive Matte Polypropylene features a permanent adhesive to ensure secure, reliable mounting. As a result, this media enables easier handling and faster mounting.

# HP Everyday Adhesive Matte Polypropylene

## Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on [www.hp.com/go/designjet/supplies](http://www.hp.com/go/designjet/supplies)

For the latest ICC/media profiles, please visit [www.hp.com/go/designjet/supplies](http://www.hp.com/go/designjet/supplies) (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

## Product specifications

| Weight                                                  | 180 g/m² per ISO 536 Test Method                                                                                                                                                                                                                                                                                                                                            |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
|---------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|------------|-----------|--------|-----------------|--------------|--------|------------------|--------------|--------|------------------|--------------|--------|-----------------|--------------|
| Thickness                                               | 8.9 mil/225 microns per ISO 534 Test Method                                                                                                                                                                                                                                                                                                                                 |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Opacity                                                 | Greater than 96% per ISO 2471 Test Method                                                                                                                                                                                                                                                                                                                                   |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Brightness                                              | Greater than 101 per ISO 2470 Test Method                                                                                                                                                                                                                                                                                                                                   |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Whiteness                                               | Greater than 119 per CIE Ganz 82 Test Method                                                                                                                                                                                                                                                                                                                                |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Lamination                                              | Yes, cold                                                                                                                                                                                                                                                                                                                                                                   |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Finish                                                  | Matte                                                                                                                                                                                                                                                                                                                                                                       |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Tear resistant                                          | 1210 N per ASTM D1004 Test Method                                                                                                                                                                                                                                                                                                                                           |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Tensile strength                                        | 10.3 N per ASTM D882 Test Method                                                                                                                                                                                                                                                                                                                                            |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Adhesive backing                                        | Permanent                                                                                                                                                                                                                                                                                                                                                                   |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Operating temperature                                   | 15 to 35° C                                                                                                                                                                                                                                                                                                                                                                 |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Operating humidity                                      | 20 to 80% RH                                                                                                                                                                                                                                                                                                                                                                |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Fade-resistance (indoor commercial window, pigment ink) | 1 year printed on HP Designjet Z6100 Printer series using HP 91 Viverra Ink Supplies, 1 year printed on HP Designjet 5000/5500 using HP 83 UV Ink Supplies. For details: <a href="http://www.hp.com/go/supplies/printpermanence">http://www.hp.com/go/supplies/printpermanence</a> .                                                                                        |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Fade-resistance (indoor home or office, pigment ink)    | In test                                                                                                                                                                                                                                                                                                                                                                     |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Fade-resistance (outdoor, pigment ink)                  | 6 months printed on HP Designjet Z6100 Printer series using HP 91 Viverra Ink Supplies, 6 months printed on HP Designjet 5000/5500 using HP 83 UV Ink Supplies. For details: <a href="http://www.hp.com/go/supplies/printpermanence">http://www.hp.com/go/supplies/printpermanence</a> .                                                                                    |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Waterfastness                                           | Moderately water-resistant                                                                                                                                                                                                                                                                                                                                                  |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Dry time                                                | 2 minutes (@23°C, 50% RH)                                                                                                                                                                                                                                                                                                                                                   |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Shelf time                                              | 1 year, unopened in original packaging                                                                                                                                                                                                                                                                                                                                      |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Storage temperature                                     | 0 to 40° C                                                                                                                                                                                                                                                                                                                                                                  |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Storage humidity                                        | 5 to 80% RH                                                                                                                                                                                                                                                                                                                                                                 |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Country of origin                                       | Product of China                                                                                                                                                                                                                                                                                                                                                            |                 |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| Ordering information                                    | <table><tr><th>Product Numbers</th><th>Roll sizes</th><th>UPC codes</th></tr><tr><td>CG824A</td><td>914 mm x 22.9 m</td><td>884420179306</td></tr><tr><td>CG825A</td><td>1067 mm x 22.9 m</td><td>884420179313</td></tr><tr><td>CG826A</td><td>1524 mm x 22.9 m</td><td>884420179320</td></tr><tr><td>CG843A</td><td>610 mm x 22.9 m</td><td>884420404118</td></tr></table> | Product Numbers | Roll sizes | UPC codes | CG824A | 914 mm x 22.9 m | 884420179306 | CG825A | 1067 mm x 22.9 m | 884420179313 | CG826A | 1524 mm x 22.9 m | 884420179320 | CG843A | 610 mm x 22.9 m | 884420404118 |
| Product Numbers                                         | Roll sizes                                                                                                                                                                                                                                                                                                                                                                  | UPC codes       |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| CG824A                                                  | 914 mm x 22.9 m                                                                                                                                                                                                                                                                                                                                                             | 884420179306    |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| CG825A                                                  | 1067 mm x 22.9 m                                                                                                                                                                                                                                                                                                                                                            | 884420179313    |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| CG826A                                                  | 1524 mm x 22.9 m                                                                                                                                                                                                                                                                                                                                                            | 884420179320    |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |
| CG843A                                                  | 610 mm x 22.9 m                                                                                                                                                                                                                                                                                                                                                             | 884420404118    |            |           |        |                 |              |        |                  |              |        |                  |              |        |                 |              |

## Warranty

HP large format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the users are unsatisfied with HP large format printing material they should contact their HP reseller.

© Copyright 2009 Hewlett-Packard Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit <http://www.hp.com/go/designjet/supplies>

Published in EMEA 4AA2-3594 EEE

