HP DesignJet T950 36-in Multifunction **Printer**



The world's most efficient A4-A0 printing experience to boost productivity¹



MOST EFFICIENT¹—Save time, get through more jobs

- Pick up your jobs quickly and simply—stacker holds up to 40 pages flat for easy collection.
- Do it all—seamlessly print your A4 jobs with integrated input and output trays, keeping pages sorted by size.
- Move projects forward with fast print speeds, 300-ft roll, and high image quality with HP Flex
- Simplify scan and copy workflows with personalized one-click shortcuts from the front panel.

CONNECTED—Secure and seamless collaboration

- Save time with HP Click—print in fewer steps and avoid reprinting with print preview.
- Protect your printer and data from cyberthreats without any effort thanks to HP Wolf Pro
- Stay on task with HP app³—manage your device and print from virtually anywhere using your mobile or tablet.
- Share drawings and collaborate with colleagues wherever they are with the easy-to-use frontloading scanner.

GO BEYOND—Meet office and environmental needs

- Advance environmental goals—printer is made with at least 35% recycled plastics⁴ and recyclable supplies⁵.
- Invest in a robust and compact plotter that's designed to last.
- Reduce energy and ink waste—auto schedule printer on/off usage and enjoy efficient ink maintenance routines.

For more information, please visit https://www.hp.com/go/designjet-t950-mfp

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

¹ The HP DesignJet T950 is faster than its main competitors: 44% faster than competitor A and 43% faster than competitor B in end-to-end performance, including job preparation with printing software, processing, printing, and collection. Testing performed by Sogeti, April 2023. Detailed test report is available upon request.

Based on test results using A0 size, plain paper, and standard configuration. Stacking capacity is subject to paper type, printed file and ambient conditions.

³ Requires HP app download available at https://www.hp.com/go/mobileprinting. Certain Features are available in English language only and may vary by printer model/country, and between desktop/mobile applications. HP reserves the right to introduce charges for use of functionality facilitated by the HP app. Internet access required and may not be available in all countries. HP account required for full functionality. List of supported

operating systems available in app stores.

⁴ Declared %RCP content is based on the quantity and weight of parts made with RCP resin over the total plastic parts.

⁵ Program availability varies. See https://www.hp.com/go/recycle

Technical specifications

Technical s	specifications
Print	•
Print speed	21 sec/page on A1, 120 A1 prints per hour ¹
Print resolution	Up to 2400 x 1200 optimized dpi
Technology	HP Thermal Inkjet
Margins	Roll: 5 x 5 x 5 x 5 mm
	Sheet: 5 x 5 x 5 x 5 mm
Ink types	Pigment-based (C, M, Y, mK)
Ink drop	6 pl (C, M, Y); 12.6 pl (mK)
Printheads	1 (C, M, Y, mK)
Printhead nozzles	1376 per color; 5504 in total
Line accuracy	±0.1% ²
Minimum line width	0.02 mm (via raster driver)
Max optical density	15 L* min/1.7 D ³
Multifunction capabilities	
Scan speed	Up to 3.81 cm/sec (color, 200 dpi), up to 11.43 cm/sec (grayscale, 200 dpi)
Scan resolution	Up to 600 dpi
Technology	Sheetfed, CIS (Contact Image Sensor), media jam detection sensor, front feed scanning method
Scan format	JPEG, PDF, TIFF
Scan destinations	Scan to email, network, and USB. Scan to cloud, computer, and mobile through HP app.
Maximum scan length	7 m ⁴
Thickness	Up to 0.8 mm
Media	
Handling	Sheet feed, roll feed, front-loading input tray (100 sheet capacity), sheet organizer (50 sheet capacity ⁵), stacker (40 sheet capacity ⁵), automatic horizontal cutter
Roll size	369 to 914 mm
Maximum roll diameter	140 mm
Sheet size	Front-loading input tray: 210 x 279 to 305 x 457 mm Manual feed: 210 x 279 to 914 x 1676 mm
Standard sheets	Input tray: A4, A3 Manual feed: A4, A3, A2, A1, A0
Grammage	60 to 280 g/m² (roll/manual feed); 64 to 220 g/m² (front-loading input tray)
Thickness	Up to 0.3 mm
Applications	Line drawings; Renderings; Presentations; Maps; Posters
Memory	2 GB
Hard disk	None
Job storage	2.7 GB reprint queue
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n
Native print languages	TIFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4
Printing paths	Wi-Fi Direct, remote printing, Apple AirPrint and HP app for Android and iOS devices, Windows and macOS printer drivers, printing support for Chrome OS, print from USB pen drive
Drivers	Raster driver for macOS and Windows, HP-GL/2 driver for Windows
Security features	HP Secure Boot, white listing, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, Semi-permanent-queue Erase, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration and State of the North Research of the North Research State of the North Research Re
Dimensions (W x D x H)	
Printer	1407 x 720 x 967 mm
Shipping	1575 x 630 x 780 mm
Weight	
Printer	71 kg
Shipping	97 kg
What's in the box	HP DesignJet T950 MFP, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord
HP Software and solutions	HP Click for Windows and macOS, HP app for Windows, macOS, Android, and iOS
Remote print enabled	Yes
One-click multi-size printing	Yes
Environmental ranges	
Recycled plastic in printer	36%
Necycleu plastic iii priirtei	51, 4006
Operating temperature	5 to 40℃
	20 to 80% RH
Operating temperature	
Operating temperature Operating humidity	20 to 80% RH
Operating temperature Operating humidity Operating altitude	20 to 80% RH Up to 3000 m
Operating temperature Operating humidity Operating altitude Storage temperature	20 to 80% RH Up to 3000 m
Operating temperature Operating humidity Operating altitude Storage temperature Acoustics	20 to 80% RH Up to 3000 m -25 to 55°C
Operating temperature Operating humidity Operating altitude Storage temperature Acoustics Sound pressure	20 to 80% RH Up to 3000 m -25 to 55°C 42 dB(A) (operating), <16 dB(A) (idle)

Certification

Safety	USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS)
Electromagnetic	Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC)
Environmental	ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements.
Warranty	Two-year limited hardware warranty. Warranty and support options vary by

Ordering information

2Y9H3A	HP DesignJet T950 36-in Multifunction Printer		
Accessories			
7F2C8A	HP DesignJet 36-in Spindle		
CNICOOA	LID Desire let 3 is Core Adestes		

Original HP printing supplies

498N0A	HP 739 DesignJet Printhead Replacement Kit
498N4A	HP 738 130-ml Black DesignJet Ink Cartridge
498N5A	HP 738 130-ml Cyan DesignJet Ink Cartridge
498N6A	HP 738 130-ml Magenta DesignJet Ink Cartridge
498N7A	HP 738 130-ml Yellow DesignJet Ink Cartridge
498N8A	HP 738 300-ml Black DesignJet Ink Cartridge
676M6A	HP 738 300-ml Cyan DesignJet Ink Cartridge
676M7A	HP 738 300-ml Magenta DesignJet Ink Cartridge
676M8A	HP 738 300-ml Yellow Design let Ink Cartridge

Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit https://hp.com/go/OriginalHPinks

Original HP large format printing materials

HP Universal Bond Paper (FSC® certified)⁶ (recyclable)⁷ HP Coated Paper (FSC® certified)⁶ (recyclable)⁷ HP Heavyweight Coated Paper (FSC® certified)⁶ (recyclable)⁷

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U56T9E HP 3-year Next Business Day HW Support U56TBE HP 4-year Next Business Day HW Support U56TCE HP 5-year Next Business Day HW Support

HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more information, please visit http://www.hp.com/go/cpc

¹ Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper

(bond) and Original HP inks. 2 ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Heavyweight Coated roll feed and

humidity, on AO/E printing material in Best or Normal mode with HP Heavyweight Coated roll feed an Original HP inks.

3 With HP Universal Instant Dry Photo Gloss media with Original HP inks.

4 Scanned at 200 dpi using "Long Plot" setting.

5 Based on test results using 80 g/m² plain paper and standard configuration. Capacity is subject to paper type, printed file, and ambient conditions.

6 BMG trademark license code FSC®-C115319, see http://www.fsc.org . HP trademark license code FSC®-C017543, see http://www.fsc.org

7 Can be recycled through commonly available recycling programs.



















35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.

Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 A max







Consumption

Requirements