# 3-Port Metal DIN-Rail Mounting Module for Snap-In Keystone Jacks and Couplers, Silver, TAA

MODEL NUMBER: **N063-003**

Accepts snap-in keystone jacks and couplers to help you manage your DIN-rail network cable application.

## Highlights

- Heavy-duty metal construction ideal for industrial Ethernet network applications
- 3 blank cutouts compatible with all keystone jacks and couplers
- Built-in mounting clip attaches to standard 35 mm DIN rail with no tools needed
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Package Includes

N063-003 Metal DIN-Rail Mounting Module, 3 Ports

## Features

**Organizes a Wide Variety of Ethernet Network Patch Cables in Your DIN-Rail Installation**
This DIN-rail mounting module lets you manage network cable interconnectivity with three blank cutouts, which accommodate all snap-in keystone jacks and in-line couplers. Made from sheet metal with nickel plating, the N063-003 is quick and easy to install on a standard 35-millimeter DIN rail using the built-in mounting clip.

**TAA-Compliant for GSA Schedule Purchases**
The N063-003 is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

# Specifications

| OVERVIEW | |
| --- | --- |
| UPC Code | 037332276889 |
| Technology | Cat5/5e; Cat6; Cat6a |
| **Firmware / Software Docs** | |
| Offset Ports | No |
| **PHYSICAL** | |
| Primary Form Factor | DIN-Rail |
| Color | Silver |
| Material of Construction | SUS304 & SPCC NI PLATE (STEEL) |
| Total Number of Ports | 3 |

| Shipping Dimensions (hwd / in.) | 2.10 x 4.50 x 8.00 |
|---|---|
| Shipping Weight (lbs.) | 0.15 |
| Unit Dimensions (hwd / in.) | 2.120 x 1.940 x 2.380 |

**ENVIRONMENTAL**

| | |
|---|---|
| Operating Temperature Range | -13° to 122°F (-25° to 50°C) |
| Storage Temperature Range | -40° to 158°F (-40° to 70°C) |
| Operating Humidity Range | 10% to 85% RH, Non-Condensing |
| Storage Humidity Range | 10% to 85% RH, (Non-Condensing) |

**CONNECTIONS**

| | |
|---|---|
| Number of Ports | 3 |
| Side A - Connector 1 | (3) KEYSTONE JACK CUTOUT |

**FEATURES & SPECIFICATIONS**

| | |
|---|---|
| All-in-One Kit | No |
| Antibacterial | No |
| IP68 Rated | No |
| IP20 Rated | No |
| Numbered Ports | No |
| DIN Mountable | Yes |
| Keystone Jacks | Yes |
| Built-in Cables | No |
| Color-Coded Connections | No |
| EIA/TIA 2/32 Spacing | No |
| Labeled Ports | No |
| Down-Angled Ports | No |
| Panel Applications | Ethernet |

**STANDARDS & COMPLIANCE**

| | |
|---|---|
| Product Compliance | CE (Europe); REACH; RoHS; UKCA; Trade Agreements Act (TAA) |

**WARRANTY & SUPPORT**

| | |
|---|---|
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

1000 Eaton Boulevard

Cleveland, OH 44122

United States

https://tripplite.eaton.com