

# Product datasheet

Specifications



## APC Symmetra LX Battery Module



SYBT5

EAN Code: 0731304218869

### Overview

**Presentation** Extended run power protection for servers, networks, and telecommunications

### Main

|                           |                          |
|---------------------------|--------------------------|
| Product or component type | Power module             |
| Number of rack unit       | 0U                       |
| Number of cables          | 1.0                      |
| Battery type              | Lead-acid battery        |
| Provided equipment        | Installation guide       |
| Range of product          | Symmetra Battery Systems |

### Batteries & Runtime

|  |                            |
|--|----------------------------|
| Battery location                       | Internal battery           |
| Number of battery blocks per string    | 10                         |
| Number of battery free slots           | 0                          |
| Number of battery filled slots         | 0                          |
| Device mounting                        | Enclosed battery cartridge |
| Battery voltage                        | 120 V                      |
| Number of battery replacement quantity | 1                          |

### Physical

|                |                    |
|----------------|--------------------|
| Height         | 140 mm             |
| Width          | 210 mm             |
| Depth          | 546 mm             |
| Product weight | 29.1 kg            |
| Mounting mode  | Not rack-mountable |
| USB compatible | No                 |

### Conformance

|                        |         |
|------------------------|---------|
| Standards              | UL 1778 |
| Product certifications | CSA     |

### Environmental

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                       |              |
|---------------------------------------|--------------|
| Ambient air temperature for operation | 0...40 °C    |
| Operating altitude                    | 0...10000 ft |
| Relative humidity                     | 0...95 %     |
| Ambient air temperature for storage   | -15...45 °C  |
| Storage altitude                      | 0...4572 m   |
| Storage Relative Humidity             | 0...95 %     |

## Packing Units

|                              |            |
|------------------------------|------------|
| Unit Type of Package 1       | PCE        |
| Number of Units in Package 1 | 1          |
| Package 1 Height             | 27.000 cm  |
| Package 1 Width              | 29.000 cm  |
| Package 1 Length             | 76.000 cm  |
| Package 1 Weight             | 30.500 kg  |
| Unit Type of Package 2       | P12        |
| Number of Units in Package 2 | 8          |
| Package 2 Height             | 75.000 cm  |
| Package 2 Width              | 80.000 cm  |
| Package 2 Length             | 120.000 cm |
| Package 2 Weight             | 256.000 kg |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|  |   |
|--|---|
| Total lifecycle Carbon footprint                       | 103 kg CO2 eq.                                |
| Carbon footprint of the manufacturing phase [A1 to A3] | 93 kg CO2 eq.                                 |
| Carbon footprint of the distribution phase [A4]        | 2 kg CO2 eq.                                  |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 9 540 kg CO2 eq.                              |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 2 kg CO2 eq.                                  |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

### Use Better



### Materials and Substances

|  |  |
|--|--|
| Packaging made with recycled cardboard | Yes  |
| Packaging without single use plastic   | No   |
| EU RoHS Directive                      | <a href="#">Compliant</a>  |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a> |

### Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

### Use Again



### Repack and remanufacture

|                               |   |
|-------------------------------|---|
| Recyclability potential, in % | 66  |
| Take-back                     | No  |
| WEEE Label                    |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Image of product / Alternate images

Alternative

---



