imagePROGRAF TZ-30000 MFP Z36

AN INTEGRATED LARGE FORMAT MULTIFUNCTION PRINTER WITH UNRIVALLED SPEED, OUTSTANDING PRODUCTIVITY AND HIGH EFFICIENCY

Designed for production, CAD and Poster markets looking for fast printing and smart, integrated scanning for high volume prints.





Increased productivity

Print larger media volumes, at up to 4ppm, with accelerated print speeds and instant return from sleep mode

Sophisticated printout solution

High performance stacker up to 100 pages of AO CAD, or even 100 pages of mixed sizes

High-quality scanning

Colortrac SingleSensor technology and smart software in the integrated 36-inch scanner enables advanced scan quality and control, with a more integrated feel and enhanced operability

Continuous printing

Maintain speed throughout print jobs, with hot swap media rolls and hot swap ink tanks features, during printing

Intuitive workflows

Process high volume jobs efficiently with software that offers instructions and minimises misprints

Superb image quality

Produce stunning graphics and high-precision CAD drawings and Posters with Canon's water-resistant, full pigment ink system



PRODUCT RANGE



Canon imagePROGRAF TZ-30000



TECHNICAL SPECIFICATIONS

imagePROGRAF TZ-30000 MFP Z36

SCANNER TECHNOLOGY

Scan Technology SingleSensor Optical Resolution (dpi) 1200dpi Paper path Flat Scan width 36" (914mm) 6" (150mm) Min. scan width 38" (965mm) Document width

Max. scan length

Weight of scanner 7.8Kg

Dimensions W x D x L

1056 x 199 x 118mm 1056 x 251 x 156mm with Doc return guide Compliances

Front/rear exit Rear (front eject via Document Return Guide)

Document handling - Face up/

Document thickness (1)

Scan speed 8-bit grayscale & mono @200dpi (2)

Scan to PC: Scan speed 24-bit color @200dpi (2)

Copy: Scan speed 24-bit color @200dpi (2) Interface USB

Scanner controls Branding/Colour Software Included What's in the box?

System controller

PRINTER TECHNOLOGY

Printer Type Print Technology

Print Resolution Number of Nozzles

Line Accuracy Nozzle Pitch

Ink Droplet Size

Ink Capacity

Ink Type OS Compatability

Printer Languages Standard Interfaces

MEMORY Standard memory

Hard Drive

MEDIA HANDLING

Media Feed and Output

Media Width

Minimum Printable Length

Maximum Printable Length

Maximum Media Roll Diameter Media Core Size

8m (JPEG/PDF), 15.2m (TIFF)

Europe: CE mark Other Countries : CB certification

0.07 - 1.0mm

13ips

3ips

6ips

3.0 (backward compatible to USB2) Stop, Advance, Rewind, LED status

None / Canon black SmartWorks MFP V6

Z36 scanner Suspension mount for printer and system controller mount 2 paper edge guides 3 Document return guides Calibration target Assembly & Start Up Guide USB3 cable (2 meter) Power Supply 15.6" system controller

3:1 Trident power cord - requires 1 local mains cable (not included).

Windows 10 Enterprise LTSC 64 bit. CPU: Intel i3-8100T. SSD: 256GB, RAM: 8GB DDR4. Display: Multi touch 15.6", 1366 x 768, 3 x USB3 & 1 x USB2, 1 x GbE (rear). Power button and 1 x USB3 (Front).

5 Colour 36"

Canon Bubbleiet on Demand 6 colours integrated type (6 chips per print head x 1 print head)

2.400 x 1.200 dpi

15,360 nozzles (MBK 5,120 nozzles, Other Colors 2,560 nozzles each) ±0.1% or less

1,200 dpi x 2 includes Non-firing nozzle detection and compensation system $\,$ 5 pl per colour

Bundled Starter Ink: 330ml (MBK)/160ml (BK, C, M, Y) Sales Ink: 330ml/700ml

Pigment inks: 5 colour MBK/BK/C/M/Y

Microsoft Windows 32 Bit: 7, 8.1, 10 64 Bit: 7, 8.1, 10, Server 2008/R2, Server 2012, Server 2012/R2, 2016, 2019 Apple Macintosh: macOS 10.12.6 - 10.15

HP-GL/2, HP RTL, PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)

USB A Port: USB Memory Direct Print for JPEG/PDF files USB B Port: Built-in Hi-Speed USB 2.0 Ethernet: 10/100/1000 base-T Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b Please refer to user manual how to activate/deactivate the wireless LAN

128GB (Physical memory 2GB) Expansion slot : No 500GB (Encrypted)

Roll Paper: Two Roll, Front-loading, Front Output/Upper

Output
Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever) Roll paper : 203.2mm - 917mm Cut sheet : 203.2mm - 917mm

Roll/Cut: 0.07mm - 0.8mm Roll paper : 203.2mm (Front output), 205mm (Upper output) Cut sheet : 203.2 mm

Roll paper : 18 m (Varies according to the OS and application) Cut sheet : 610 mm

175 mm

Internal diameter of roll core: 2"/3"

Margins Recommended area

Media Feed Capacity

Borderless Printing Width (Roll Only)

Maximum number of delivered prints

Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Roll paper : Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless) : Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet : Top: 3 mm, Bottom: 20 mm, Side: 3 mm

Roll Paper: Two rolls. Automatic switching is possible. Cut Sheet: 1 sheet

Cut Sirect: Si

[Upper Output (Top Delivery Tray)] Longest stacking length: 1397 mm (CAD, 3inch core Uncoated Paper) A0 portrait: 100 sheets ed size stacking is possible. Maximum 100 sheets

(CAD, 2inch core Uncoated Paper) AO portrait: 50 sheets *Mixed size stacking is possible. Maximum 50 sheets. [Front Output (Basket)] 1 sheet (Longest stacking length: 1219.2mm)

POWER AND OPERATING REQUIREMENTS

Power Supply Power Consumption

Operating Environment

Regulations

Environment Certificates DIMENSIONS AND WEIGHT

Physical Dimensions WxDxH (mm) and Weight (Kg)

WHAT'S INCLUDED What's in the Box?

Software Included

OPTIONS Optional Items CONSUMABLES User Replaceable Items AC 100-240V (50-60Hz)

Operation: 157W or less

Sleep mode: 2.2W or less Default setting for the time to enter the Sleep mode: Approx. 5 Minutes Power off: 0.3 W or less

Temperature: 15~30°C, Humidity: 10~80% RH (no dew condensation)

Operation: 52 dB (A) (Plain paper, Standard mode, Line Drawing/Text mode) (Measured on ISO 7779 standard) Standby: 35 dB (A) or less Operation: 7.0 Bels or less (Plain paper, Standard mode, Line Drawing/Text mode) (Measured on ISO 7779 standard)

Europe: CE mark Other Countries : CB certfication TUV. CB

imagePROGRAF TZ-30000 MFP Z36 1581 x 960 x 1281 mm (Basket Closed) 1581 x 1293 x 1281 mm (Basket Opened) Weight: 222 kg

Printer, 1 x print head, 3 inch paper core attachment, 1 set of starter ink tanks, Set up guide, Safety/Standard Environment leaflet, User software CD-ROM (Win), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, 2 x roll holders(spools), Basket, Power Cable

imagePROGRAF TZ Printer Driver and PosterArtist Lite Other software available as Download from Web.

2"/3" Roll Holder: RH2-34

Ink Tank: PFI-340 (330ml), PFI-740 (700ml) Print Head: PF-06 Maintenance Cartridge: MC-30

Thicker documents must be flexible and the paper return guides removed and may require additional support. Some media should be scanned at reduced speeds. It is not possible to guarantee to be able to scan all media types and sizes.

The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times and quoted top speeds will depend on the host performance and are not guaranteed for all media types. Scan times quoted are the maximum for true 200 x 200dpi image capture.Max scan speed for RGB: Copying at 200/300/600dpi = (3/2/2)s. Scanning at 200/300/600dpi = 3/2/8)s. Max scan speed for RGB: Copying at 200/300/600dpi = 13/8.6/4.3ips.

Notes & Recommendations

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ""and *: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended









Canon Inc. canon.com

Canon Europe

canon-europe.com English edition © Canon Europa N.V.,2021

