

Digitally-Signed Secure Firmware USB 3.0 Flash Drive

The Kanguru FlashTrust™ USB 3.0 flash drive is the world's first unencrypted, USB 3.0 flash drive with onboard, trusted firmware to protect against the potential risk of malicious firmware-based attacks. With its RSA-2048 bit, digitally signed and secured firmware, the Kanguru FlashTrust offers consumers and organizations the same level of protection typically reserved for encrypted, high-end flash drives, to unencrypted USB device users.

The Kanguru FlashTrust is perfect for organizations who may not require the need for high-end hardware encryption but are seeking added protection from any type of "badUSB" malware threat. With its handy physical write protect switch, SuperSpeed USB 3.0 interface, and vast storage space options, the FlashTrust is sure to handle the task, providing plenty of room to store, read, and transport your files in record time.

Part Number: WP-KFT3-xG





Physical Write-Protect Switch



SuperSpeed USB 3.0

MODEL NUMBER         WP-KFT3 Series           CAPACITIES         8GB, 16GB, 32GB, 64GB, 128GB, 256GB, 512GB           INTERFACE         USB3.0 Interface (USB 3.2 Gen 1x1)           DATA TRANSFER RATE         Max Read: Up to 300MB/sec*		
INTERFACE  USB3.0 Interface (USB 3.2 Gen 1x1)  Max Read: Up to 300MB/sec* Max Write: Up to 250MB/sec* Windows 10/8/7/Vista/XP** Mac OSX 10.1.5+ Linux (Kernel 2.4.1 and Above, must be mounted) Linux Ubuntu 10+ Red Hat 5+ Open SUSE11+  DATA RETENTION  10 Years or More  OPERATING TEMP  O° C - 70°C  HUMIDITY RANGE  20% - 90%  SHOCK RESISTANCE  1000G Max  VIBRATION  15G Peak to Peak Max  WEIGHT  14g  77.21 mm L x 19.44 mm W x 8.96 mm H	MODEL NUMBER	WP-KFT3 Series
DATA TRANSFER RATE  Max Read: Up to 300MB/sec* Max Write: Up to 250MB/sec*  Windows 10/8/7/Vista/XP** Mac OSX 10.1.5+ Linux (Kernel 2.4.1 and Above, must be mounted) Linux Ubuntu 10+ Red Hat 5+ Open SUSE11+  DATA RETENTION 10 Years or More  OPERATING TEMP 0° C - 70°C  HUMIDITY RANGE 20% - 90%  SHOCK RESISTANCE 1000G Max  VIBRATION 15G Peak to Peak Max  WEIGHT 14g  DIMENSIONS 77.21 mm L x 19.44 mm W x 8.96 mm H	CAPACITIES	8GB, 16GB, 32GB, 64GB, 128GB, 256GB, 512GB
DATA TRANSFER RATE  Max Write: Up to 250MB/sec*  Windows 10/8/7/Vista/XP** Mac OSX 10.1.5+ Linux (Kernel 2.4.1 and Above, must be mounted) Linux Ubuntu 10+ Red Hat 5+ Open SUSE11+  DATA RETENTION 10 Years or More  OPERATING TEMP 0° C - 70°C HUMIDITY RANGE 20% - 90%  SHOCK RESISTANCE 1000G Max  VIBRATION 15G Peak to Peak Max  WEIGHT 14g  DIMENSIONS 77.21 mm L x 19.44 mm W x 8.96 mm H	INTERFACE	USB3.0 Interface (USB 3.2 Gen 1x1)
Mac OSX 10.1.5+ Linux (Kernel 2.4.1 and Above, must be mounted) Linux Ubuntu 10+ Red Hat 5+ Open SUSE11+  DATA RETENTION 10 Years or More  OPERATING TEMP 0° C - 70°C  HUMIDITY RANGE 20% - 90%  SHOCK RESISTANCE 1000G Max  VIBRATION 15G Peak to Peak Max  WEIGHT 14g  DIMENSIONS 77.21 mm L x 19.44 mm W x 8.96 mm H	DATA TRANSFER RATE	•
OPERATING TEMP         0° C - 70°C           HUMIDITY RANGE         20% - 90%           SHOCK RESISTANCE         1000G Max           VIBRATION         15G Peak to Peak Max           WEIGHT         14g           DIMENSIONS         77.21 mm L x 19.44 mm W x 8.96 mm H	OS COMPATIBILITY	Mac OSX 10.1.5+ Linux (Kernel 2.4.1 and Above, must be mounted) Linux Ubuntu 10+ Red Hat 5+
HUMIDITY RANGE         20% - 90%           SHOCK RESISTANCE         1000G Max           VIBRATION         15G Peak to Peak Max           WEIGHT         14g           DIMENSIONS         77.21 mm L x 19.44 mm W x 8.96 mm H	DATA RETENTION	10 Years or More
SHOCK RESISTANCE         1000G Max           VIBRATION         15G Peak to Peak Max           WEIGHT         14g           DIMENSIONS         77.21 mm L x 19.44 mm W x 8.96 mm H	OPERATING TEMP	0° C - 70°C
VIBRATION         15G Peak to Peak Max           WEIGHT         14g           DIMENSIONS         77.21 mm L x 19.44 mm W x 8.96 mm H	HUMIDITY RANGE	20% - 90%
WEIGHT 14g 77.21 mm L x 19.44 mm W x 8.96 mm H	SHOCK RESISTANCE	1000G Max
77.21 mm L x 19.44 mm W x 8.96 mm H	VIBRATION	15G Peak to Peak Max
DIMENSIONS	WEIGHT	14g
	DIMENSIONS	77121 HILL 2X 1711 HILL 11 X 0170 HILL 1

## **FEATURES/BENEFITS**

- Digitally-Signed Secure Firmware (RSA-2048 Bit)
- SuperSpeed USB 3.0 Interface (USB 3.2 Gen 1x1)
- Physical Write-Protect Switch
- Windows "Ready Boost" Compatible
- Simple Driverless Setup
- High-Strength Aluminum Design
- Capacities 16GB 512GB
- Custom Engraving Available

Digitally-Signed Secure Firmware USB 3.0 Flash Drive

<sup>\*\*</sup> In line with Microsoft's End-of-Support announcement for Windows XP™, Kanguru Solutions is ending support for its line of products running on the Windows XP platform.



The Kanguru FlashTrust secure firmware flash Drive is TAA Compliant



<sup>\*</sup> Speeds depending on capacity of model