



TS-131K

CPU	AnnapurnaLabs, an Amazon company Alpine AL214, 4-core, 1.7GHz
-----	---

CPU Architecture	32-bit ARM
------------------	------------

Floating Point Unit	Yes
---------------------	-----

Encryption Engine	Yes
-------------------	-----

System Memory	1GB DDR3
---------------	----------

Maximum Memory	1GB DDR3
----------------	----------

Flash Memory	512 MB (Dual boot OS protection)
--------------	----------------------------------

Drive Bay	1 x 3.5-inch SATA 6Gb/s, 3Gb/s
-----------	--------------------------------

Drive Compatibility	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
---------------------	--

Hot-swappable	Yes
---------------	-----

SSD Cache Acceleration Support	Yes
--------------------------------	-----

Gigabit Ethernet Port (RJ45)	1
------------------------------	---

Wake on LAN (WOL)	Yes
-------------------	-----

Jumbo Frame	Yes
-------------	-----

USB 3.2 Gen 1 port	2
--------------------	---

Form Factor	Tower
-------------	-------

LED Indicators	Power, Status, LAN, USB, HDD1
----------------	-------------------------------

Buttons	Power, Reset, USB Auto Copy
---------	-----------------------------

Dimensions (HxWxD)	169 × 73 × 219 mm
--------------------	-------------------

Weight (Net)	1.19 kg
--------------	---------

Weight (Gross)	2.02 kg
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	36W adapter (12VDC), 100-240VAC
Power Consumption: HDD Sleep Mode	7.29 W
Power Consumption: Operating Mode, Typical	11.62 W
Fan	1 x 50mm, 12VDC
System Warning	Buzzer
Kensington Security Slot	Yes
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	400

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.