
TS 8660C CPNE

12NC: F166527

GTIN (EAN) code: 5054645665273







Product group Built-in Type of control Electronic Type of control Electronic Type of control Settings - Number of gas burners 0 Number of electric cooking zones 4 Number of electric plates 0 Number of radiant plates 0 Number of halogen plates 0 Number of induction plates 4 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Black Electrical connection rating (W) 7200 Gas connection rating (W) 7200 Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 540 Width of the product 551 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3 Automatic programmes	MAIN FEATURES		
Type of control Type of control settings Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of electric warming zones Location of control panel Basic surface material Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) 31,3 Voltage (V) Plug type Roas connection Soloto Gas connection N/A Width of the product Depth of the product Minimum niche height Minch weight (kg) Pug by P. 3 Note depth Note weight (kg) Note one control panel Electronic Electronic O A Black Front Black Electrical connection rating (W) 7200 O Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product 54 Depth of the product 54 Depth of the product 480 Net weight (kg) 9.3	Product group	Hob	
Type of control settings Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) 31,3 Voltage (V) Prequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Depth of the product Minimum niche height Minimum niche width Net weight (kg) Pug by Net weight (kg) P. So O O O O O O O O O O O O O	Construction type	Built-in	
Number of gas burners0Number of electric cooking zones4Number of electric plates0Number of radiant plates0Number of induction plates4Number of electric warming zones0Location of control panelFrontBasic surface materialGlassMain colour of productBlackElectrical connection rating (W)0Gas connection rating (W)0Gas typeN/ACurrent (A)31,3Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)120Plug typeNoGas connectionN/AWidth of the product54Depth of the product54Depth of the product510Minimum niche height28Minimum niche width560Niche depth480Net weight (kg)9.3	Type of control	Electronic	
Number of electric cooking zones4Number of electric plates0Number of radiant plates0Number of induction plates4Number of electric warming zones0Location of control panelFrontBasic surface materialGlassMain colour of productBlackElectrical connection rating (W)7200Gas connection rating (W)0Gas typeN/ACurrent (A)31,3Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)120Plug typeNoGas connectionN/AWidth of the product54Depth of the product54Depth of the product510Minimum niche height28Minimum niche width560Niche depth480Net weight (kg)9.3	Type of control settings	-	
Number of electric plates0Number of radiant plates0Number of halogen plates0Number of induction plates4Number of electric warming zones0Location of control panelFrontBasic surface materialGlassMain colour of productBlackElectrical connection rating (W)7200Gas connection rating (W)0Gas typeN/ACurrent (A)31,3Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)120Plug typeNoGas connectionN/AWidth of the product590Height of the product54Depth of the product510Minimum niche height28Minimum niche width560Niche depth480Net weight (kg)9.3	Number of gas burners	0	
Number of radiant plates0Number of halogen plates0Number of induction plates4Number of electric warming zones0Location of control panelFrontBasic surface materialGlassMain colour of productBlackElectrical connection rating (W)7200Gas connection rating (W)0Gas typeN/ACurrent (A)31,3Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)120Plug typeNoGas connectionN/AWidth of the product54Depth of the product54Depth of the product510Minimum niche height28Minimum niche width560Niche depth480Net weight (kg)9.3	Number of electric cooking zones	4	
Number of halogen plates 0 Number of induction plates 4 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Black Electrical connection rating (W) 7200 Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 590 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3	Number of electric plates	0	
Number of induction plates 4 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Black Electrical connection rating (W) 7200 Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 590 Height of the product 54 Depth of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3	Number of radiant plates	0	
Number of electric warming zones Location of control panel Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Pequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Depth of the product Depth of the product Minimum niche height Minimum niche width Net weight (kg) Poologiass Front Front Glass N/A 0 0 0 0 0 0 0 0 0 0 0 0 0	Number of halogen plates	0	
Location of control panel Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Depth of the product Depth of the product Minimum niche height 28 Minimum niche width Net weight (kg) Net Sasson	Number of induction plates	4	
Basic surface materialGlassMain colour of productBlackElectrical connection rating (W)7200Gas connection rating (W)0Gas typeN/ACurrent (A)31,3Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)120Plug typeNoGas connectionN/AWidth of the product590Height of the product54Depth of the product510Minimum niche height28Minimum niche width560Niche depth480Net weight (kg)9.3	Number of electric warming zones	0	
Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Depth of the product Depth of the product Minimum niche height Miche depth Net weight (kg) Slack Black Bla	Location of control panel	Front	
Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Depth of the product Depth of the product Minimum niche height Associated width Michael Associated width Net weight (kg) 7200 0 0 N/A 31,3 220-240 Frequency (Hz) 50/60 120 No 12	Basic surface material	Glass	
Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 590 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3	Main colour of product	Black	
Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 590 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3	Electrical connection rating (W)	7200	
Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 590 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3	Gas connection rating (W)	0	
Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 590 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3	Gas type	N/A	
Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 590 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3	Current (A)	31,3	
Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Begin to the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) 120 No	Voltage (V)	220-240	
Plug type No Gas connection N/A Width of the product 590 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3	Frequency (Hz)	50/60	
Gas connection N/A Width of the product 590 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3	Length of Electrical Supply Cord (cm)	120	
Width of the product 590 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3	Plug type	No	
Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3	Gas connection	N/A	
Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3	Width of the product	590	
Minimum niche height28Minimum niche width560Niche depth480Net weight (kg)9.3	-	54	
Minimum niche width 560 Niche depth 480 Net weight (kg) 9.3	Depth of the product	510	
Niche depth 480 Net weight (kg) 9.3	Minimum niche height	28	
Net weight (kg) 9.3	Minimum niche width	560	
- ' - '	Niche depth	480	
Automatic programmes Yes	Net weight (kg)	9.3	
	Automatic programmes	Yes	

TECHNICAL FEATURES		
Power on indicator	Yes	
Number of indicators	4	
Type of regulation	Induction	
Type of lid	Without	
Residual heat indicator	Separate	
Main on/off switch	Yes	
Safety device	-	
Timer	Yes	

PERFORMANCES	
Energy input	Electric