

#### SPECIFICATION SHEET

## TM-P20II 2" Wireless Portable Receipt Printer



# The ultra compact and lightweight 2" wireless portable receipt printer.

**Portable and lightweight** — ultra compact, easy for users to wear (belt clip included); helps prevent carry fatigue

**Robust design** — IP54-rated enclosure is water- and dust-resistant; holds up to rigorous use, with a drop rating of 2.1 metres

**Long-lasting battery life** — up to 27 hours on a full charge<sup>1</sup> (battery and USB-C cable included)

**Fast battery charging capability** — fully charges as fast as 3 hours<sup>2</sup> (charger sold separately)

**Versatile connectivity** — wireless connectivity options (Wi-Fi<sup>®</sup> 5 or Bluetooth<sup>®</sup> 5.0) to provide connections to a wide variety of devices and networks

**Exceptional print quality and ultra fast print speed** — quickly produce sharp and crisp text, barcodes and logos at up to 100 mm/sec

Modern design — sleek design suited to complement your business

**Enhance your printing with accessories** — choose from a wide range of optional accessories, such as single or quad battery charger, spare battery, belt strap, shoulder strap and soft carrying case (each sold separately)

World-class service and support — 2-year warranty

Paper Saving Mode — helps reduce cost by decreasing paper usage

POS



Print Method Thermal line printing

Print Resolution Dots/inch: 203 dpi

Print Speed Receipt version: 100 mm/sec (max.)

Barcode UPC-A, UPC-E, JAN13/EAN13, JAN8/EAN8,

GS1 DataBar Omnidirectional, GS1 DataBar Truncated,

Interfaces USB-C (built-in), Wi-Fi 802.11 a/b/g/n/ac (2.4 GHz or

Supported Mobile Operating Systems iOS<sup>®</sup>, Android<sup>™</sup>

Easy Setting SimpleAP, TM Utility, NFC and QR Code

GS1 DataBar Limited, GS1 DataBar Expanded

Symbology, GS-1, Aztec, Datamatrix

Paper Feed Method Friction feed

Roll Diameter (max.) 2.0"/51.0 mm

Core Diameter (min.) 0.71"/18.0 mm

5 GHz band) or Bluetooth 5.0 (Classic + LE)

Print

Fonts

**Print Fonts** 

Font A: 12 x 24, 32 cpl Font B: 9 x 24, 42 cpl (default)

Font C: 9 x 17, 42 cpl

Font E: 8 x 16, 48 cpl

Font D: 10 x 24, 38 cpl

Character Size (W x H)

Font A·15 mm x 30 mm

Font B: 1.12 mm x 3.0 mm

Font C: 1.12 mm x 2.1 mm

Font D: 1.25 mm x 3.0 mm

Font E: 1.0 mm x 2.0 mm

Media Handling

Type Thermal roll paper

Paper Loading Drop-in

Width 2.28"/58 mm

Auto Cutter No

and Windows

Connectivity

Wireless Security Mode

WPA/WPA2-PSK (TKIP/AES) WPA3-SAE (AES) WPA2/WPA3-Enterprise

### TM-P20II 2" Wireless Portable Receipt Printer

#### General Printer Reliability<sup>3</sup> 10 million printing lines IP Rating IP54 plans available Drop Rating 2.1 Metres Charging Available Epson® options: Single-Battery Charging Cradle (OT-SB20II) and Quad-Battery Charging Cradle (OT-CH20II); fully charges as fast as 3 hours<sup>2</sup> Third-party options: USB-C charging devices, wireless charging devices<sup>4</sup> Battery Life 15 hours for Wi-Fi and 27 hours for Bluetooth<sup>1</sup> NV Bit Image Memory NV User: 192KB (max.), NV Graphics: 384KB (max.) Data Buffer Wi-Fi: 4KB, Bluetooth: 64KB Printer Driver ePOS-Print SDK, Windows driver (APD), OPOS, OPOS.NET, JavaPOS (Win), JavaPOS (Linux®), TM Virtual Port Driver Software TM Utility (for iOS and Android), Integrated Utility, What's in the Box TM Bluetooth Connector, Epson WebConfig, Monitoring Tool, Deployment Tool, Firmware Updater Code 39, ITF, CODEBAR (NW-7), Code 93, Code 128, GS1-128, Audible Alert Programmable Buzzer LED Indicators Power LED, Battery LED (x3), Charging LED, **Ordering Information** Bluetooth Connection LED or Wi-Fi Connection LED, Error LED **Printers** 2D Symbol Printing QR Code, Maxi Code, PDF417, Composite Sensors Paper End, Cover Open TM-P20II Wi-Fi Power Source Lithium-ion battery pack, USB-C port TM-P20II Bluetooth **Power Saving Yes Optional Accessories** Temperature -15°C - 50°C (5°F - 122°F) Battery (OT-BY20) Relative Humidity 10% - 90% Belt Strap (OT-BE01) Acoustic Noise Level 53 dB Standards and Approvals EMI FCC Class B, ICES-003 Class B, Shoulder Strap (OT-SH01) Safety standard UL62368-1/CAN/CSA C22.2 No.62368-1 Soft Case (OT-PC20II) Dimensions (W x D x H) 79 x 120 x 46mm Weight 227g Color Epson Black

#### **Eco Features**

Paper Saving Mode Power Saving Mode **RoHS** compliant

#### Warranty

Standard 2-year RTB warranty, with optional extended service

TM-P20II, Battery (OT-BY20), Belt Clip (attached to printer), Starter Roll Paper, USB-C Cable, Documentation

C31CJ99811 C31CJ99801 Mobile Receipt Printers

POS

C32C831093 C32C882321 C32C882331 C32C882341

1 Battery life will vary considerably depending on connectivity (Wi-Fi or Bluetooth), usage and environment, 2 Speed based on charging with Epson genuine battery chargers (OT-SB20II, OT-SB80II, OT-CH20II, OT-CH80II). | 3 Epson's statements about reliability levels are only estimates, based on normal use of the printer using tested media only. See www.epson.com/testedmedia for more information on Tested Media. These reliability statements are not warranties of the media or Epson's printers, and the only warranties for printers are the limited warranty statements for each printer. | 4 Epson cannot guarantee the performance or guality of third-party power adapters.

#### Epson Australia Ptv Ltd

Lvl 1. 3 Talavera Road, Macquarie Park NSW 2113

Specification Sheet | Page 2 of 2

Epson New Zealand Level 1, 7-9 Fanshawe Street Auckland, 1010

www.epson.com.au www.epson.co.nz

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. Android is a trademark of Google LLC. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and other countries. Wi-Fi® is a registered trademark of Wi-Fi Alliance®. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks.

#### Contact: