



## Lexmark CS632dwe

Exceptional performance, secure and sustainable



# Lexmark CS632dwe

With exceptional performance and secure design, the CS632dwe printer delivers enhanced productivity up to 40 ppm\* on A4 paper and toner yields up to 20,000 pages mono\*\*, and up to 11,700 pages colour\*\*. Engineered for long life with environmental certifications and advanced power management, this efficient model offers many sustainability benefits. Fast time to first print, superior print quality and easy-to-use touch screen.

## Secure by design

Lexmark expertise helps customers protect their data, their device and their network. Our security ecosystem is designed to overcome the most complex data challenges. And now we've added the Trusted Platform Module (TPM)\*\*\*, which includes on-board authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint. TPM meets stringent industry and US government security standards including Common Criteria and Federal Information Processing Standard (FIPS).

## Proprietary technology

We own core technology across hardware, firmware, services, and solutions, creating seamless connections designed to reduce the risk of security gaps between your document, your device and your network. Our expertise is our customer's benefit.

## Sustainability

With certifications in Energy Star®, Blue Angel, RoHS, EPEAT® Silver, the CS632dwe is sustainable for today and beyond. Lexmark is an industry leader of recycled content with products using at least 35% PCR content and continual focus on improvement. This line is also engineered for Long Life and designed to last and reduce waste.

## Intelligent Design

Every touch point is designed to withstand high usage while meeting accessibility standards. Steel frames support the device and provide durability to help ensure consistent long-

term performance. Products are designed for long service life with long-life components. Servicing is easy with few tools required.



## Manageability

These IoT-ready devices can be remotely managed, including setup, configuration, consumables management, and diagnostics. Wireless capability gives freedom of access and remote firmware updates make it easy to upgrade to the latest apps and security features. Our mobile printing app makes it easier to monitor and manage your print jobs from remote locations, all from the touch of your phone.

## Ongoing professional product support

From easy installation through a lifetime of producing high volumes of pages, you'll find our devices easy to use and intuitive. Instructional on-product support videos and simple colour-coded guidance for maintenance tasks like changing toner make our device experience world-class. For our managed print customers, we offer a step beyond with predictive analytics for fleet diagnostics that can help Lexmark detect and prevent potential problems before they happen.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

\* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\* Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See [www.lexmark.com/yields](http://www.lexmark.com/yields) for more information. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Programme (LCCP).

\*\*\* The Trusted Platform Module (TPM) is not available in some countries.

# Lexmark CS632dwe



- 1 **Printer with 10.9 cm touch screen**  
318.30 x 455 x 422.50 mm
- 2 **170-Sheet output bin**  
Dimensions included as part of base model
- 3 **Single sheet multipurpose feeder**  
Dimensions included as part of base model
- 4 **250-Sheet tray**  
Dimensions included as part of base model
- 5 **650-Sheet Duo Tray**  
132.1 x 424.2 x 416.6 mm
- 6 **550-Sheet Tray**  
132.1 x 424.2 x 416.6 mm

- 7 **550-Sheet Tray**  
132.1 x 424.2 x 416.6 mm
- 8 **Adjustable Stand**  
521 x 653 x 625 mm
- 9 **Swivel Cabinet**  
263 x 476 x 600 mm

- Standard
- Optional

**P/N** **Hardware**  
50M0067 Lexmark CS632dwe

**P/N** **Supplies**  
75M0W00 Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 30K Waste Toner Bottle  
75M0X10 Lexmark CS632, CX635 Black 20K Toner Cartridge  
75M0X20 Lexmark CS632, CX635 Cyan 11.7K Toner Cartridge  
75M0X30 Lexmark CS632, CX635 Magenta 11.7K Toner Cartridge  
75M0X40 Lexmark CS632, CX635 Yellow 11.7K Toner Cartridge  
75M0Z10 Lexmark CS531, 632, 639, CX532, 635 Black 150K Imaging Kit  
75M0Z50 Lexmark CS531, 632, 639, CX532, 635 4-Color 150K Imaging Kit  
75M0ZK0 Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 Black Return Programme 150K Imaging Kit  
75M0ZV0 Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 4-Color Return Programme 150K Imaging Kit  
75M10C0 Lexmark CS531, 632, CX532, 635 Cyan Return Programme 2K Toner Cartridge  
75M10K0 Lexmark CS531, 632, CX532, 635 Black Return Programme 3K Toner Cartridge  
75M10M0 Lexmark CS531, 632, CX532, 635 Magenta Return Programme 2K Toner Cartridge  
75M10Y0 Lexmark CS531, 632, CX532, 635 Yellow Return Programme 2K Toner Cartridge  
75M1XC0 Lexmark CS632, CX635 Cyan Return Programme 11.7K Toner Cartridge  
75M1XK0 Lexmark CS632, CX635 Black Return Programme 20K Toner Cartridge  
75M1XM0 Lexmark CS632, CX635 Magenta Return Programme 11.7K Toner Cartridge  
75M1XY0 Lexmark CS632, CX635 Yellow Return Programme 11.7K Toner Cartridge

**P/N** **Paper Handling**  
50M7550 550-Sheet Tray  
50M7650 650-Sheet Duo Tray

**P/N** **Memory Options**  
27X0805 500+ GB Hard Disk  
57X9528 Intelligent Storage Drive (ISD)

**P/N** **Application Solutions**  
57X0300 Contact Authentication Device  
57X0301 Contactless Authentication Device (Secondary Alternative)  
82S1203 IPDS License  
82S1204 Bar Code License

**P/N** **Connectivity**  
1021294 USB (2 Metre) Cable  
57X7040 English Keyboard Kit

**P/N** **Furniture**  
3073173 Swivel Cabinet  
40C2300 Adjustable Stand

## Product Specifications

## Lexmark CS632dwe

Printing	
Display	Lexmark e-Task 10.9 cm colour touch screen with audible feedback
Print Speed	Up to: Black: 40 ppm <sup>1</sup> (A4) / Colour: 40 ppm <sup>1</sup> (A4)
Time to First Page	as fast as: Black: 6.5 seconds / Colour: 6.7 seconds
Print Resolution	Black: 1200 x 1200 dpi, 4800 Colour Quality / Colour: 4800 Colour Quality, 1200 x 1200 dpi
Memory	Standard: 1024 MB / Maximum: 1024 MB
Hard Disk	Intelligent Storage Drive available; Magnetic Hard Disk available
Recommended Monthly Page Volume	1,500 - 10,000 pages <sup>2</sup>
Maximum Monthly Duty Cycle	Up to: 125,000 pages per month <sup>3</sup>
Supplies <sup>4</sup>	
Laser Cartridge Yields	up to: 20,000 <sup>5</sup> -page Black Cartridge / up to: 11,700 <sup>5</sup> -page Colour (CMY) Cartridges
Cartridge(s) Shipping with Product	3,000 <sup>5</sup> -page Black Return Program Toner Cartridge <sup>5</sup> , 2,000 <sup>5</sup> -page Colour (CMY) Return Program Toner Cartridges <sup>5</sup>
Paper Handling	
Included Paper Handling	170-Sheet Output Bin, Integrated Duplex, Single sheet multipurpose feeder, 250-Sheet Tray
Optional Paper Handling	650-Sheet Duo Tray, 550-Sheet Tray
Paper Input Capacity	Up to: Standard: 251 pages 75 gsm bond / Maximum: 2001 pages 75 gsm bond
Paper Output Capacity	Up to: Standard: 170 pages 75 gsm bond / Maximum: 170 pages 75 gsm bond
Media Types Supported	Vinyl Labels, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Card Stock & Label Guide.
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki Card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope
General Information <sup>6</sup>	
Standard Ports	Gigabit Ethernet (10/100/1000), MarkNet N8370 802.11 a/b/g/n/ac, Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Specification Hi-Speed Certified port (Type A), USB 2.0 Specification Hi-Speed Certified (Type B)
Noise Level	Operating: 52 dBA (Print)
Specified Operating Environment	Altitude: 0 - 2900 metres / Humidity: 15 to 80% Relative Humidity / Temperature: 10 to 32.2°C (50 to 90°F)
Product Warranty	1-Year Onsite Service
Size / Weight	H x W x D: 318.30 x 455 x 422.50 mm / 20.55 kg
ENERGY STAR Typical Electricity Consumption	TEC: 0.52 kilowatt-hours per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

<sup>1</sup> Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

<sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details. <sup>5</sup> Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. <sup>6</sup> Printers are sold subject to certain license/agreement conditions. See [www.lexmark.com/printerlicense](http://www.lexmark.com/printerlicense) for details.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2023 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).