

Overview

HP Pro x360 435 G10 Notebook PC



Left

1. Internal Microphones (2)	7. World-facing 5MP Camera (Optional)
2. Webcam LED	8. World-facing Camera LED (Optional)
3. HP Privacy Camera	9. Vents
4. Webcam and IR Camera (Optional)	10. SuperSpeed USB Type-A 5 Gbps signaling rate charging Port (USB 3.2 Gen 1)
5. IR Camera LED (Optional)	11. Nano Security Lock Slot (Lock Sold Separately)
6. Clickpad	

Overview



Right

- 1. Speakers
- 2. Power Button
- 3. Power Connector
- 4. SuperSpeed USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)
- 5. SuperSpeed USB Type-A 5 Gbps signaling rate Port (USB 3.2 Gen 1)
- 6. HDMI 2.1 Ports (Cable not included)
- 7. Audio Combo Jack
- 8. MicroSD Card Reader
- 9. Touch Fingerprint Sensor (Select Models)

Overview



Overview

At a Glance

- Preinstalled with Windows 11 versions or FreeDOS
- A stylish and professional convertible adapts with versatile use modes from traditional laptop to tablet, stand and tent
- that enables to create, present and collaborate
- Sleek and durable anodized aluminum top cover and keyboard deck
- Choice of AMD Barcelo™ 7000 series mobile processors, R7, R5 and R3
- Display include your choice of 33.8 cm (13.3") diagonal IPS Wide Viewing Angle, FHD, touch screen with Corning® Gorilla® Glass 5
- Commercial-grade security features including HP Sure Start, HP Sure Sense, HP Client Security, HP Sure Click, Camera Privacy Shutter and optional HP Sure View
- Captures the world around with an optional world facing- camera in the keyboard
- Supports wireless LAN options for connectivity on the go including gigabit data rate Wi-Fi 6E
- Supports fast charging (50% in 30 minutes) with no impact on battery recharge cycles
- Passed MIL-STD 810H tests ¹
- Synchronized hinge allows the EliteBook to ProBook to open to 177° +/- 3° without lifting the keyboard and offers visibility from multiple angles.

1. MIL-STD 810H is not intended to demonstrate fitness of U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

NOTE: See important legal disclosures for all listed specs in their respective features sections.

Technical Specifications

PRODUCT NAME

HP Pro x360 435 G10 Notebook PC

OPERATING SYSTEMS

Preinstalled	Windows 11 Pro ¹ Windows 11 Pro Education ¹ Windows 11 Home - HP recommends Windows 11 Pro for business ¹ Windows 11 Home Single Language - HP recommends Windows 11 Pro for business ¹ Windows 11 Pro (Windows 11 Enterprise or Windows 10 Enterprise available with a Volume Licensing Agreement) ¹ Windows 11 Pro (preinstalled with Windows 10 Pro Downgrade) ^{1,2} FreeDOS
---------------------	---

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

2. This system is preinstalled with Windows 10 Pro software and also comes with a license for Windows 11 Pro software and provision for recovery software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

PROCESSORS

Processor ^{3,4,5}	Cores	Threads	L3 Cache	Max Boost Frequency ⁶	Base Frequency	Pro
AMD Ryzen™ 7 PRO 7730U	8	16	16MB	4.50GHz	2.00GHz	X
AMD Ryzen™ 5 PRO 7530U	6	12	16MB	4.50GHz	2.00GHz	X
AMD Ryzen™ 7 7730U	8	16	16MB	4.50GHz	2.00GHz	
AMD Ryzen™ 5 7530U	6	12	16MB	4.50GHz	2.00GHz	
AMD Ryzen™ 3 7330U	4	8	8MB	4.30GHz	2.30GHz	

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. AMD's numbering is not a measurement of clock speed.

4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

5. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.

6. Max Boost clock frequency performance varies depending on hardware, software and overall system configuration.

Technical Specifications

CHIPSET

Chipset is integrated with processor

GRAPHICS

Integrated

AMD Radeon™ Graphics⁷

Supports

Support HW decode, DX12, HDMI2.1, via HDMI up to 4K@60Hz

[7. HD content required to view HD images.](#)

DISPLAY

Touch

33.8 cm (13.3") diagonal FHD UWVA eDP 1.3+PSR Low Blue Light touch screen with Corning® Gorilla® Glass 5, IPS, Bright View, Narrow Bezel, micro edge, 1000 nits, 72% NTSC with HD + IR camera, HP Sure View Reflect integrated privacy screen (1920 x 1080) with HP Eye Ease ^{7,8,9,10,11}

33.8 cm (13.3") diagonal FHD UWVA eDP BrightView WLED slim touch screen with Corning® Gorilla® Glass 5, 250 nits, 45% NTSC with HD Webcam (1920 x 1080) ^{7,8,9,11}

33.8 cm (13.3") diagonal FHD UWVA eDP BrightView WLED slim touch screen with Corning® Gorilla® Glass 5, 250 nits, 45% NTSC with HD Webcam + IR camera (1920 x 1080) ^{7,8,9,11}

33.8 cm (13.3") diagonal FHD UWVA eDP+PSR BrightView WLED ultra slim touch screen with Corning® Gorilla® Glass 5, Low Power, 400 nits, 72% NTSC with HD Webcam + IR camera (1920 x 1080) with HP Eye Ease ^{7,8,9,11}

33.8 cm (13.3") diagonal FHD UWVA eDP+PSR BrightView WLED ultra slim touch screen with Corning® Gorilla® Glass 5, Low Power, 400 nits, 72% NTSC with HD Webcam (1920 x 1080) with HP Eye Ease ^{7,8,9,11}

Display Size (Diagonal)

13.3"

33.8 cm (13.3")

[7. HD content required to view HD images.](#)

[8. Sold separately or as an optional feature.](#)

[9. Resolutions are dependent upon monitor capability, and resolution and color depth settings.](#)

[10. HP Sure View Reflect integrated privacy screen is an optional feature that must be configured at purchase and is designed to function in landscape orientation.](#)

[11. Actual brightness will be lower with touchscreen or Sure View.](#)

Technical Specifications

DOCKING (Sold Separately)

Docking station model #1	HP Thunderbolt 4 100W G6 Dock
Docking station model #2	HP Thunderbolt 120W G4 Dock
Docking station model #3	HP Thunderbolt 280W G4 Dock
Docking station model #4	HP USB-C Dock G5
Docking station model #5	HP USB-C/A Universal Dock G2
Docking station model #6	HP USB-C G5 Essential Dock

For additional aftermarket options and docking specs please see page 40.

STORAGE AND DRIVES

Primary Storage

2 TB PCIe® NVMe™ TLC 2280 Solid State Drive ¹²
1 TB PCIe® NVMe™ TLC 2280 Solid State Drive ¹²
512 GB PCIe® NVMe™ TLC Solid State Drive ¹²
256 GB PCIe® NVMe™ M.2 SSD ¹²
128 GB PCIe® NVMe™ M.2 SSD ¹²

12. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

MEMORY

Maximum Memory

32 GB DDR4-3200 SDRAM ¹³

Memory

32 GB DDR4-3200 MHz RAM (2 x 16 GB) ¹³
16 GB DDR4-3200 MHz RAM (1 x 16 GB) ¹³
16 GB DDR4-3200 MHz RAM (2 x 8 GB) ¹³
8 GB DDR4-3200 MHz RAM (1 x 8 GB) ¹³
8 GB DDR4-3200 MHz RAM (2 x 4 GB) ¹³
4 GB DDR4-3200 MHz RAM (1 x 4 GB) ¹³

Memory Slots

2 SODIMM

Both slots are accessible/upgradeable by IT or self-maintainers only (CSR-B).

13. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

Technical Specifications

NETWORKING/COMMUNICATIONS

WLAN

Realtek RTL8852CE 802.11ax 2x2 Wi-Fi 6E + Bluetooth® 5.3 Wireless Card ¹⁴

Mediatek RZ616 Wi-Fi 6E + Bluetooth® 5.3 Wireless Card ¹⁴

Qualcomm® Fast Connect 6900 Wi-Fi 6E (2x2) and Bluetooth® 5.2 Wireless Card ¹⁴

Miracast

Native Miracast Support ¹⁵

14. Wi-Fi 6E requires a Wi-Fi 6E router, and Windows 11, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.

15. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

AUDIO/MULTIMEDIA

Audio

Integrated microphone (Dual Array)

Camera

User-facing 720p HD camera ^{7,8}

User-facing 720p HD + IR camera for face authentication with Windows Hello ^{7,8}

World-facing 5MP auto-focus secondary camera ^{7,8}

7. HD content required to view HD images.

8. Sold separately or as an optional feature.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

HP Premium Keyboard, spill resistant with DuraKeys and optional backlit ¹⁶

Function Keys

F1 - Display Switching

F2 - Blank or Privacy

F3 - Brightness Down

F4 - Brightness Up

F5 - Audio Mute

F6 - Volume Down

F7 - Volume Up

F8 - Mic Mute

F9 - Blank or Backlit Toggle

F10 - Insert

F11 - Airplane Mode

F12 - HP Programmable Key

Power Button

Technical Specifications

16. Backlit keyboard is an optional feature.

SOFTWARE AND SECURITY

Preinstalled Software

Software

HP Quick Drop¹⁷

HP PC Hardware Diagnostics Windows

myHP

HP Smart Support¹⁸

HP Services Scan¹⁹

HP Connection Optimizer

HP Hotkey Support

HP Support Assistant²⁰

HP Notifications

HP Privacy Settings

HP Power Manager

Buy Microsoft Office (Sold separately)

Manageability Features

HP Connect²¹

HP Image Assistant Gen5 (download)

HP Manageability Integration Kit (download)²²

HP Client Management Script Library (download)

HP Patch Assistant (download)²³

HP Driver Packs (download)

HP Client Catalog (download)

HP Cloud Recovery²⁴

Security Management

HP Sure Click²⁵

HP Sure Sense²⁶

HP Sure Run²⁷

HP Sure Recover²⁸

HP Sure Start²⁹

HP Tamper Lock

HP Sure Admin³⁰

BIOS

HP BIOSphere Gen6³¹

HP Secure Erase³²

Absolute Persistence Module³³

BIOS Update via Network

HP Wake on WLAN

Secured-Core PC Enable³⁴

TPM 2.0 Embedded Security Chip (Common Criteria EAL4+ Certified) (FIPS 140-2 Level 2 Certified)

HP Fingerprint Sensor³⁵

Technical Specifications

IPv6 Support

Yes

FirstNet Certified:

Yes

The BIOS on this notebook implements ISO/IEC 19678:2015 guidelines (formerly NIST 800-147).

UEFI version: 2.7

Class: Class 3

17. HP Quick Drop requires Internet access and Windows 10 or higher PC preinstalled with HP QuickDrop app and either an Android device (phone or tablet) running Android 7 or higher with the Android HP QuickDrop app, and /or an iOS device (phone or tablet) running iOS 12 or higher with the iOS HP QuickDrop app.

18. HP Smart Support requires HP TechPulse to be installed. For more information about how to enable or to download HP Smart Support, please visit <http://www.hp.com/smart-support>. HP Services Scan is provided thru Windows Update and will check entitlement on each hardware device to determine if an HP TechPulse-enabled service has been purchased, and will download applicable software automatically. HP TechPulse is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP TechPulse follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access with connection to TechPulse portal is required. For full system requirements or to disable this feature, please visit <http://www.hpdaas.com/requirements>

19. HP Services Scan is provided with Windows Update on select products and will check entitlement on each hardware device to determine if an HP TechPulse-enabled service has been purchased, and will download applicable software automatically. HP TechPulse is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP TechPulse follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access with connection to TechPulse portal is required. For full system requirements or to disable this feature, please visit <http://www.hpdaas.com/requirements>. Not applicable in China.

20. HP Support Assistance requires Windows and Internet Access

21. HP Connect is available from the Azure Market Place for HP Pro, Elite, Z and Point-of-Sale PCs managed with Microsoft Endpoint Manager. Subscription to Microsoft Endpoint Manager required and sold separately. Network connection required.

22. HP Manageability Integration Kit can be downloaded from

<http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.

23. HP Patch Assistant available on select HP PCs with the HP Manageability Kit that are managed through Microsoft System Center Configuration Manager. HP Manageability Integration Kit can be downloaded from
<http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.

24. HP Cloud Recovery is available for Z by HP, HP Elite and Pro desktops and laptops PCs with Intel® or AMD processors and requires an open, wired network connection. **NOTE:** You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Details please refer to: <https://support.hp.com/us-en/document/c05115630>.

25. HP Sure Click requires Windows 10 Pro or higher or Enterprise. See https://bit.ly/2PrLT6A_SureClick for complete details.

26. HP Sure Sense is available on select HP PCs with Windows 10 Pro, Windows 10 Enterprise, Windows 11 Pro, or Windows 11 Enterprise OS.

27. HP Sure Run Gen5 is available on select HP PCs and requires Windows 10 and higher.

28. HP Sure Recover Gen5 with Embedded Reimaging is an optional feature which requires Windows 10 and higher must be configured at purchase. You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Network based recovery using Wi-Fi is only available on PCs with Intel Wi-Fi Module

29. HP Sure Start Gen7 is available on select HP PCs and requires Windows 10 and higher

Technical Specifications

30. HP Sure Admin requires Windows 10 or higher, HP BIOS, HP Manageability Integration Kit from <http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store
31. HP BIOSphere Gen6 features may vary depending on the platform and configuration.
32. HP Secure Erase for the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.
33. Absolute firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit: <https://www.absolute.com/about/legal/agreements/absolute/>
34. Secured-Core PC Enable requires an Intel® vPro®, AMD Ryzen™ Pro processor or Qualcomm® processor with SD850 or higher and requires 8 GB or more system memory. Secured-core PC is enabled from the factory.
35. HP Fingerprint sensor is an optional feature that must be configured at purchase.

POWER

Power Supply

- HP Smart 65 W USB Type-C® adapter ³⁶
- HP Smart 65 W EM External AC power adapter ³⁶
- HP Smart 65 W External AC power adapter ³⁶
- HP Smart 45 W USB Type-C™ adapter ³⁶
- HP Smart 45 W External AC power adapter ³⁶

Battery

- HP Long Life 3-cell, 42 Wh Li-ion polymer^{37,38}
- Supports HP Fast Charge ³⁹

Power Cord

- 3-wire plug - 1m ³⁶
- 2-wire plug - 1m ³⁶

Battery Life

Up to 15 hours and 15 minutes with 42whr battery (HP Long Life 3-Cell, 42 Whr Polymer, UMA graphic, AMD R7 Pro, display set to 200 nits, 2*4G memory, 256 GB SSD) ⁴⁰

Battery Weight

- HP Long Life 3-cell - 42 Wh Polymer - .42 lb
- HP Long Life 3-cell - 42 Wh Polymer - 190 g

36. Availability may vary by country.

37. Battery is internal and not replaceable by customer. Serviceable by warranty.

38. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

39. Recharges your battery up to 50% within 30 minutes when the system is off or in standby mode. Power adapter with a minimum capacity of 65 watts is required. After charging has reached 50% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.

Technical Specifications

40. Windows 10 MM18 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See www.bapco.com for additional details.

WEIGHTS & DIMENSIONS

Product Weight

Starting at 3.19 lb ⁴¹

Starting at 1.45 kg ⁴¹

Product Dimensions (W x D x H)

12.15 x 8.78 x 0.71 in

30.85 x 22.29 x 1.79 cm

Packaging Dimensions (W x D x H) ⁴²

12"-15" boxes (305mm height): 1200mm x 1000mm x 1080mm

16"-17" boxes (345mm height): 1200mm x 1000mm x 1200mm

41. Weight will vary by configuration. Does not include power adapter.

42. Product packaging size varies based on options chosen. Please contact your HP representative for your packaging size details.

PORTS/SLOTS

1 AC Power 1 HDMI ⁴³

1 Headphone/microphone combo jack

2 SODIMM

2 SuperSpeed USB Type-A 5 Gbps signaling rate charging Port (USB 3.2 Gen 1)

1 SuperSpeed USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)

Expansion Slots

1 micro SD

43. HDMI cable sold separately

Technical Specifications

SERVICE AND SUPPORT

1-year and 3-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.⁴⁴

44. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit www.hp.com/go/cpc. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

Technical Specifications

SYSTEM UNIT

Stand-Alone Power Requirements

(AC Power)

Nominal Operating Voltage	19V
Average Operating Power	
Integrated graphics	AMD
Discrete Graphics	N/A
Max Operating Power	UMA<45W

Temperature

Operating	32° to 95° F (0° to 35° C)
Non-operating	-4° to 140° F (-20° to 60° C)

Relative Humidity

Operating	10% to 90%, non-condensing
Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature

Shock

Operating	40 G, 2 ms, half-sine
Non-operating	200 G, 2 ms, half-sine

Random Vibration

Operating	0.75 grams
Non-operating	1.50 grams

Altitude (unpressurized)

Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)

Planned Industry Standard

Certifications

Regulatory Model Number	HSN-I54C
CSA/UL 62368-1	Yes

CSA	Yes
-----	-----

ENERGY STAR®	Certified ⁴⁵
--------------	-------------------------

EPEAT®	EPEAT® Gold in the United States ⁴⁶
--------	--

FCC/ICES/CISPR/VCCI	Yes
---------------------	-----

CE MARKING	Yes
------------	-----

GS Mark	No
---------	----

Related commodity should comply with ISO 9241 Standards.

China CCC/SRRC	Yes
----------------	-----

Taiwan BSMI/NCC	Yes
-----------------	-----

Korea KCC/KC/KES	Yes
------------------	-----

Ukraine NSoC/TEC	Yes
------------------	-----

EAEU Compliance	Yes
-----------------	-----

Saudi Arabian Compliance	Yes
--------------------------	-----

TCO	Yes
-----	-----

WW RoHS	Yes
---------	-----

Low Blue Light	Yes
----------------	-----

Technical Specifications

45. Configurations of the HP Pro 435 x360 G10 Notebook PC that are ENERGY STAR® qualified are identified HP Pro 435 x360 G10 Notebook PC ENERGY STAR on HP websites and on <http://www.energystar.gov>.

46. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit <http://www.epeat.net> for more information.

DISPLAYS

1. Actual brightness will be lower with touchscreen or HP Sure View.

NOTE: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

13.3 in FHD (1920 x 1080) UWVA Low Blue Light sRGB NB2Y 1000 eDP 1.3+PSR 100 PrivacyG4 Plus flat LCD Panel	Outline Dimensions (W x H x D)	299.060 x 185.550 (max)
	Active Area	293.760 x 165.240 (typ)
	Weight	210 (max)
	Diagonal Size	13.3 (inch)
	Surface Treatment	Bright View glass
	Touch Enabled	Yes ¹
	Contrast Ratio	1500:1 (typ)
	Refresh Rate	60 Hz
	Brightness	1000 nits ¹
	Pixel Resolution - Format	1920 x1080 (FHD)
	Backlight	WLED
	Pixel Resolution	RGB
	Color Gamut Coverage	sRGB 100%
	Color Depth	8
	Viewing Angle	UWVA 85/85/85/85
	Low Blue Light	Yes
	Power Consumption (W, EBL@ 150nits max/ 200nits max)	N/A

Panel LCD 13.3 inch FHD (1920x1080) WLED UWVA 45percent cg 250nits eDP 1.2 w/o PSR slim NWBZ	Outline Dimensions (W x H)	300.56 x 187.77 mm (max) (w/ PCB & w/o bracket)
	Active Area	293.76 x 165.24 mm (typ.)
	Weight	260 g (max)
	Diagonal Size	13.3 inch
	Surface Treatment	Bright View glass
	Touch Enabled	Yes ¹
	Contrast Ratio	600:1 (typ.)
	Refresh Rate	60 Hz
	Brightness	250 nits ¹
	Pixel Resolution - Format	1920 x 1080 (FHD)
	Backlight	LED
	Pixel Resolution	RGB Stripe

Technical Specifications

Color Gamut Coverage	45%
Color Depth	6
Viewing Angle	UWVA 85/85/85/85
Low Blue Light	No
Power Consumption (W, EBL@ 150nits max/ 200nits max)	2.40 (max)/ NA

Panel LCD 13.3 inch FHD (1920x1080) WLED UWVA 72percent cg 400nits eDP 1.4+PSR2 ultraslim LP NWBZ

Outline Dimensions (W x H)	299.06 x 185.54 mm (max)
Active Area	293.76 x 165.24 mm (typ.)
Weight	170 g (max)
Diagonal Size	13.3 (inch)
Surface Treatment	Bright View glass
Touch Enabled	Yes ¹
Contrast Ratio	1200:1 (typ.)
Refresh Rate	60 Hz
Brightness	400 nits ¹
Pixel Resolution - Format	1920 x 1080 (FHD)
Backlight	LED
Pixel Resolution	RGB Stripe
Color Gamut Coverage	NTSC 72%
Color Depth	8
Viewing Angle	UWVA 85/85/85/85
Low Blue Light	No
Power Consumption (W, EBL@ 150nits max/ 200nits max)	1.09 (max)/ 1.30 (max)

Technical Specifications

STORAGE AND DRIVES

For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

SSD 128GB 2230 PCIe NVMe Value	Form Factor	M.2 2230
	Capacity	128 GB
	NAND Type	Value
	Interface	PCIe NVMe Gen4X4
	Minimum Sequential Read	2000 MB/s ± 10%
	Minimum Sequential Write	600 MB/s ± 10%
	Logical Blocks	250,069,680
	Features	Pyrite 2.0; TRIM; L1.2

SSD 256GB 2280 PCIe NVMe Value	Form Factor	M.2 2280
	Capacity	256 GB
	NAND Type	Value
	Interface	PCIe NVMe Gen3X4 or Gen4X4
	Minimum Sequential Read	2000 MB/s ± 10%
	Minimum Sequential Write	900 MB/s ± 10%
	Logical Blocks	500,118,192
	Features	Pyrite 2.0; TRIM; L1.2

SSD 512GB 2280 PCIe-4x4 NVMe Three Layer Cell	Form Factor	M.2 2280
	Capacity	512GB
	NAND Type	TLC
	Interface	PCIe NVMe Gen4X4
	Minimum Sequential Read	6400 MB/s ± 10%
	Minimum Sequential Write	3500 MB/s ± 10%
	Logical Blocks	1,000,215,215
	Features	Pyrite 2.0; TRIM; L1.2

1TB 2280 PCIe-4x4 NVMe Three Layer Cell	Form Factor	M.2 2280
	Capacity	1TB
	NAND Type	TLC
	Interface	0.02 lb (10 g)
	Minimum Sequential Read	PCIe NVMe Gen4X4
	Minimum Sequential Write	6400 MB/s ± 10%
	Logical Blocks	5000 MB/s ± 10%
	Operating Temperature	2,000,409,264
	Form Factor	Pyrite 2.0; TRIM; L1.2

Technical Specifications

2TB 2280 PCIe-4x4 NVMe	Form Factor	M.2 2280
Three Layer Cell	Capacity	2TB
	NAND Type	TLC
	Interface	PCIe NVMe Gen4X4
	Minimum Sequential Read	6400 MB/s ± 10%
	Minimum Sequential Write	5000 MB/s ± 10%
	Logical Blocks	4,000,797,360
	Features	Pyrite 2.0; TRIM; L1.2

Technical Specifications

NETWORKING/COMMUNICATIONS

Realtek RTL8852CE	Wireless LAN Standards	IEEE 802.11a
802.11ax 2x2 Wi-Fi 6E +		IEEE 802.11b
Bluetooth® 5.3 Wireless		IEEE 802.11g
Card (802.11ax 2x2, supporting gigabit data rate)¹		IEEE 802.11n
		IEEE 802.11ac
		IEEE 802.11ax
		IEEE 802.11d
		IEEE 802.11e
		IEEE 802.11h
		IEEE 802.11i
		IEEE 802.11k
	Interoperability	Wi-Fi certified
	Frequency Band	<ul style="list-style-type: none">• 802.11b/g/n/ax2.402 – 2.482 GHz• 802.11a/n/ac/ax5.15 – 5.25 GHz5.25 – 5.35 GHz5.47 – 5.725 GHz5.825 – 5.850 GHz5.955 – 6.415 GHz6.435 – 6.515 GHz6.535 – 6.875 GHz6.895 – 7.115 GHz
	Data Rates	<ul style="list-style-type: none">• 802.11b: 1, 2, 5.5, 11 Mbps• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps• 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)• 802.11ac : MCS0 ~ MCS9, (20MHz, 40MHz, ,80MHz & 160MHz)• 802.11ax : MCS0 ~ MCS11, (20MHz, 40MHz, ,80MHz & 160MHz)
	Modulation	Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
	Security²	<ul style="list-style-type: none">• IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only• AES-CCMP: 128 bit in hardware• 802.1x authentication• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.• WPA2 certification• WPA3 (personal) certification• IEEE 802.11i• WAPI• EAP
	Network Architecture	Ad-hoc (Peer to Peer)
	Models	Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power³	<ul style="list-style-type: none">• 802.11b : +17dBm minimum• 802.11g : +16dBm minimum• 802.11a : +17dBm minimum

Technical Specifications

	<ul style="list-style-type: none">• 802.11n HT20(2.4GHz) : +14dBm minimum• 802.11n HT40(2.4GHz) : +13dBm minimum• 802.11n HT20(5GHz) : +14dBm minimum• 802.11n HT40(5GHz) : +13dBm minimum• 802.11ac VHT80(5GHz) : +10dBm minimum• 802.11ac VHT160(5GHz) : +10dBm minimum• 802.11ax HE40(2.4GHz) : +12dBm minimum• 802.11ax HE80(5GHz) : +10dBm minimum• 802.11ax HE160(5GHz) : +10dBm minimum• 802.11ax HE80(6GHz) : +10dBm minimum• 802.11ax HE160(6GHz) : +10dBm minimum
Power Consumption	<ul style="list-style-type: none">• Transmit mode :2.5 W• Receive mode :2 W• Idle mode (PSP) 180 mW (WLAN Associated)• Idle mode :50 mW (WLAN unassociated)• Connected Standby/Modern Standby: 10mW• Radio disabled: 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity⁴	<ul style="list-style-type: none">• 802.11b, 1Mbps : -93.5dBm maximum• 802.11b, 11Mbps : -84dBm maximum• 802.11a/g, 6Mbps : -86dBm maximum• 802.11a/g, 54Mbps : -72dBm maximum• 802.11n, MCS07 : -67dBm maximum• 802.11n, MCS15 : -64dBm maximum• 802.11ac, MCS0(VHT80) : -84dBm maximum• 802.11ac, MCS9(VHT80) : -59dBm maximum• 802.11ac, MCS9(VHT160) : -58.5dBm maximum• 802.11ax, MCS11(HE40) : -57dBm maximum• 802.11ax, MCS11(HE80) : -54dBm maximum• 802.11ax, MCS11(HE160) : -53.5dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	1. Type 2230 : 2.8g 2. Type 126: 1.3g
Operating Voltage	3.3v +/- 9%
Temperature	Operating 14° to 158° F (-10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
Humidity	Operating 10% to 60% (non-condensing) Non-operating 5% to 95% (non-condensing)
Altitude	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)

Technical Specifications

LED Activity	N/A
HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Technology	
Bluetooth Specification	4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
Bluetooth Software Supported	Microsoft Windows Bluetooth Software
Link Topology	
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.407
Power Management Certifications	ETSI 300 328 Low Voltage Directive CE Mark
Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP) BT5.2 ESR9/10 Compliance LE Advertisement Extensions Channel Selection Algo Limited High Duty Cycle Non-Connectable Advertising

Technical Specifications

2Mbps LE
LE Long Range
Windows BT profiles support
BT5.3
Periodic Advertisement interval
Encryption key size control enhancements

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Mediatek RZ616 Wi-Fi 6E Wireless LAN Standards + Bluetooth® 5.3 Wireless Card (802.11ax 2x2, supporting gigabit data rate)¹	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11ax IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11j IEEE 802.11k IEEE 802.11mc IEEE 802.11r IEEE 802.11v IEEE 802.11w
Interoperability	Wi-Fi certified
Frequency Band	<ul style="list-style-type: none">• 802.11b/g/n/ax2.402 – 2.482 GHz• 802.11a/n/ac/ax5.15 – 5.25 GHz5.25 – 5.35 GHz5.47 – 5.725 GHz5.825 – 5.850 GHz5.925 – 7.125 GHz
Data Rates	<ul style="list-style-type: none">• 802.11b: 1, 2, 5.5, 11 Mbps• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps• 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)• 802.11ac : MCS0 ~ MCS9, (20MHz, 40MHz, ,80MHz & 160MHz)

Technical Specifications

Modulation	• 802.11ax : MCS0 ~ MCS11, (20MHz, 40MHz, ,80MHz & 160MHz) Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
Security²	• IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • WPA3 (personal) certification • IEEE 802.11i • WAPI
Network Architecture	Ad-hoc (Peer to Peer)
Models	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power³	<p>2.4GHz (MIMO, typical):</p> <ul style="list-style-type: none">• 802.11b : +18dBm• 802.11g : +16.5dBm• 802.11n/ac/ax (HT20/VHT20/HE20) : +16dBm• 802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm <p>5GHz (MIMO, typical):</p> <ul style="list-style-type: none">• 802.11a : +13dBm• 802.11n/ac/ax (HT20/VHT20/HE20) : +13.5dBm• 802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm• 802.11ac/ax (VHT80/HE80) : +11.5dBm• 802.11ax HE160 : +11.5dBm <p>6GHz LPI mode (MIMO, typical)</p> <ul style="list-style-type: none">• 802.11a : 0dBm• 802.11ax HE20 : +1dBm• 802.11ax HE40 : +4dBm• 802.11ax HE80 : +7dBm• 802.11ax HE160 : +7.5dBm
Power Consumption	<ul style="list-style-type: none">• Transmit mode :2.5 W• Receive mode :2 W• Idle mode (PSP) 180 mW (WLAN Associated)• Idle mode :50 mW (WLAN unassociated)• Connected Standby/Modern Standby: 10mW• Radio disabled: 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity⁴	<p>2.4GHz (SISO):</p> <ul style="list-style-type: none">• 802.11b, 11Mbps : -82dBm maximum• 802.11g, 54Mbps : -71dBm maximum• 802.11n, MCS7 : -64dBm maximum• 802.11ac, MCS9 : -52dBm maximum• 802.11ax, MCS11(HT40): -49dBm maximum <p>5GHz (SISO):</p>

Technical Specifications

Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	1. Type 2230 : 2.8g 2. Type 126: 1.3g
Operating Voltage	3.3v +/- 9%
Temperature	Operating 14° to 158° F (-10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
Humidity	Operating 10% to 60% (non-condensing) Non-operating 5% to 95% (non-condensing)
Altitude	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
LED Activity	N/A
HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Technology	
Bluetooth Specification	4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class 1.5 Bluetooth device with a maximum transmit power of + 14 dBm and 10 dBm for BR and EDR, respectively.
Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
Bluetooth Software	Microsoft Windows Bluetooth Software
Supported Link Topology	

Technical Specifications

Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.407
Power Management	ETS 300 328
Certifications	Low Voltage Directive CE Mark
Bluetooth Software Supported	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP) BT5.2 ESR9/10 Compliance LE Advertisement Extensions Channel Selection Algo Limited High Duty Cycle Non-Connectable Advertising 2Mbps LE LE Long Range Windows BT profiles support BT5.3 Periodic Advertisement interval Encryption key size control enhancements

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Technical Specifications

Qualcomm® Fast Connect Wireless LAN Standards	IEEE 802.11a
6900 Wi-Fi 6E +	IEEE 802.11b
Bluetooth® 5.2 Wireless	IEEE 802.11g
Card (802.11ax 2x2, AMD	IEEE 802.11n
AIM-T AME, supporting	IEEE 802.11ac
gigabit file transfer	IEEE 802.11ax
speeds)	IEEE 802.11d
	IEEE 802.11e
	IEEE 802.11h
	IEEE 802.11i
	IEEE 802.11k
	IEEE 802.11r
	IEEE 802.11u
	IEEE 802.11v
	IEEE 802.11w
Interoperability	Wi-Fi certified
Frequency Band	<ul style="list-style-type: none">• 802.11b/g/n/ax2.402 – 2.482 GHz• 802.11a/n/ac/ax5.15 – 5.25 GHz5.25 – 5.35 GHz5.47 – 5.725 GHz5.825 – 5.850 GHz5.925 – 7.125 GHz
Data Rates	<ul style="list-style-type: none">• 802.11b: 1, 2, 5.5, 11 Mbps• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps• 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)• 802.11ac : MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, ,80MHz & 160MHz)• 802.11ax : MCS0 ~ MCS11, (1SS and 2SS) (20MHz, 40MHz, ,80MHz & 160MHz)
Modulation	Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM, 4096QAM
Security³	<ul style="list-style-type: none">• AES-CCMP: 128 bit in hardware• 802.1x authentication• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.• WPA2 certificationWPA3 (personal/enterprise) certification• IEEE 802.11i
Network Architecture	Wi-Fi Direct in Win10 for peer-to-peer connection.
Models	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	2.4GHz (MIMO, typical): <ul style="list-style-type: none">• 802.11b : +18dBm• 802.11g : +16.5dBm• 802.11n/ac/ax (HT20/VHT20/HE20) : +16dBm• 802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm

Technical Specifications

Power Consumption	5GHz (MIMO, typical): <ul style="list-style-type: none">• 802.11a : +13dBm• 802.11n/ac/ax (HT20/VHT20/HE20) : +13.5dBm• 802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm• 802.11ac/ax (VHT80/HE80) : +11.5dBm• 802.11ax HE160 : +11.5dBm 6GHz LPI mode (MIMO, typical): <ul style="list-style-type: none">• 802.11a : 0dBm• 802.11ax HE20 : +1dBm• 802.11ax HE40 : +4dBm• 802.11ax HE80 : +7dBm• 802.11ax HE160 : +7.5dBm
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity[3]	2.4GHz (SISO): <ul style="list-style-type: none">• 802.11b, 11Mbps : -82dBm maximum• 802.11g, 54Mbps : -71dBm maximum• 802.11n, MCS7 : -64dBm maximum• 802.11ac, MCS9 : -52dBm maximum• 802.11ax, MCS11(HT40): -49dBm maximum 5GHz (SISO): <ul style="list-style-type: none">• 802.11a, 54Mbps : -71dBm maximum• 802.11n, MCS07 : -64dBm maximum• 802.11ac, MCS9 : -52dBm maximum• 802.11ax, MCS11(HE80/HE160): -46dBm maximum 6GHz (SISO): <ul style="list-style-type: none">• 802.11a, 54Mbps : -71dBm maximum• 802.11n, MCS7 : -64dBm maximum• 802.11ac, MCS9 : -52dBm maximum• 802.11ax, MCS11(HE160): -46dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	Type 2230 : 2.3 x 22.0 x 30.0 mm
Weight	Type 2230 : 3g
Operating Voltage	3.3 +/- 0.165v
Temperature	Operating 14° to 140° F (-10° to 60° C) Non-operating -40° to 185° F (-40° to 85° C)
Humidity	Operating 10% to 60% (non-condensing)

Technical Specifications

Altitude	Non-operating 5% to 95% (non-condensing) Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
LED Activity	N/A
HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2 Wireless Technology	
Bluetooth Specification	4.0/4.1/4.2/5.0/5.1/5.2 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class 1.5 Bluetooth device with a maximum transmit power of + 14 dBm and 10 dBm for BR and EDR, respectively.
Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW
Bluetooth Software Supported	Microsoft Windows Bluetooth Software
Link Topology	
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.407
Power Management Certifications	ETSI 300 328 Low Voltage Directive CE Mark
Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)
Security & Manageability	AMD AIM-T AME support with appropriate AMD chipset components

Technical Specifications

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Technical Specifications

POWER

1. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors

AC Adapter 45 Watt nPFC	Dimensions (H x W x D)	3.701 x 1.693 x 1.071 in (9.4 x 4.3 x 2.72 cm)
Standard USB Type C®	Weight	0.44 lb (200 g) max (Not including power cord. Power cord varies by country.)
Straight 1.8m		
	Input	Input Efficiency Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V : 81.5% 9V : 86.7% 12V : 87.41% 15V : 87.8%
		Input frequency range 47 ~ 63Hz
		Input AC current Max. 1.4 A at 90 Vac
Output	Output power	5V/15W 9V/27W 12V/36W 15V/45W
	DC output	5V/9V/12V/15V
	Hold-up time	100% load 5ms at 115 Vac input
	Output current limit	<5.0A
Connector	USB Type C®	
Environmental Design	Operating temperature	32°F to 95°F (0° to 35°C)
	Non-operating (storage) temperature	-4°F to 185°F (-20° to 85°C)
	Altitude	0 to 16,400 ft (0 to 5000m)
	Humidity	20% to 95%
	Storage Humidity	10% to 95%
EMI and Safety Certifications	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.	

Technical Specifications

AC Adapter 45 Watt Smart Dimensions (H x W x D)	3.74 x 1.772 x 1.043 in (9.5 x 4.5 x 2.65 cm)
nPFC Standard Barrel Weight	0.44 lb (200 g) max (Not including power cord. Power cord varies by country.)
4.5mm Right Angle 1.8m	
Input	Input Efficiency 87.74 % at 115 Vac and 88.4 % at 230Vac
	Input frequency range 47 ~ 63 Hz
	Input AC current Max. 1.4 A at 90 Vac
Output	Output power 45W
	DC output 19.5V
	Hold-up time 100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input
	Output current limit <8.0A
Connector	4.5mm Barrel Type
Environmental Design	Operating temperature 32°F to 95°F (0°to 35°C)
	Non-operating (storage) temperature -4°F to 185°F (-20°to 85°C)
	Altitude 0 to 16,400 ft (0 to 5000m)
	Humidity 20% to 95%
	Storage Humidity 10% to 95%
EMI and Safety Certifications	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.

AC Adapter 65 Watt nPFC Dimensions (H x W x D)	3.543 x 2.008 x 1.122 in (9.0 x 5.1 x 2.85 cm)
Standard USB Type C® Weight	0.53 lb (240 g) max (Not including power cord. Power cord varies by country.)
Straight 1.8m	
Input	Input Efficiency Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V : 81.5% 9V : 86.7% 12V : 88% 15V : 88% 20V : 89%
	Input frequency range 47 ~ 63 Hz
	Input AC current 1.6 A at 90 VAC and maximum load
Output	Output power 5V/15W 9V/27W 12V/60W

Technical Specifications

		15V/60W
		20V/65W
Connector	DC output	5V/9V/12V/15V/20V
Environmental Design	Hold-up time	100% load 5ms at 115 Vac input
	Output current limit	<8.0A
EMI and Safety Certifications	USB TYPE C®	
	Operating temperature	32°F to 95°F (0°to 35°C)
	Non-operating (storage) temperature	-4°F to 185°F (-20°to 85°C)
	Altitude	0 to 16,400 ft (0 to 5000m)
	Humidity	20% to 95
	Storage Humidity	10% to 95%
	Eg:	
	*CE Mark - full compliance with LVD and EMC directives	
	* Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1, Class1, SELV;	
	Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE.	
	* MTBF - over 200,000 hours at 25°C ambient condition.	

AC Adapter 65 Watt Smart Dimensions (H x W x D)	4.016 x 2.165 x 1.181 in (10.2 x 5.5 x 3 cm)
nPFC EM Barrel 4.5mm	Weight
	0.58 lb (265 g) max (Not including power cord. Power cord varies by country.)
Input	Input Efficiency
	88.0 % at 115 Vac and 89.0 % at 230Vac
Output	Input frequency range
	47 ~ 63 Hz
Connector	Input AC current
	Max. 1.7 A at 90 Vac
Environmental Design	Output power
	65W
	DC output
	19.5V
	Hold-up time
	100% lod 5ms at 115 Vac input/80% load 10ms at 115 Vac input
	Output current limit
	<11.0A
Operating temperature	32°F to 95°F (0°to 35°C)
Non-operating (storage) temperature	-4°F to 185°F (-20°to 85°C)
Altitude	0 to 16,400 ft (0 to 5000m)
Humidity	20% to 95
Storage Humidity	10% to 95%

Technical Specifications

EMI and Safety Certifications

Eg:

*CE Mark - full compliance with LVD and EMC directives
* Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1, Class1, SELV;
Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE.
* MTBF - over 200,000 hours at 25°C ambient condition.

AC Adapter 65 Watt Smart Dimensions (H x W x D)

3.543 x 2.008 x 1.122 in (9.0 x 5.1 x 2.85 cm)

nPFC Standard Barrel Weight 4.5mm Right Angle 1.8m

0.55 lb (250 g) max (Not including power cord. Power cord varies by country.)

Input

Input Efficiency 88.0 % at 115 Vac and 89.0 % at 230Vac

Input frequency range 47 ~ 63 Hz

Input AC current Max. 1.7 A at 90 Vac

Output

Output power 65W

DC output 19.5V

Hold-up time 100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input

Output current limit <11.0A

Connector

4.5mm Barrel Type

Environmental Design

Operating temperature 32°F to 95°F (0°to 35°C)

Non-operating (storage) temperature -4°F to 185°F (-20°to 85°C)

Altitude 0 to 16,400 ft (0 to 5000m)

Humidity 20% to 95

Storage Humidity 10% to 95%

EMI and Safety Certifications

Eg:

*CE Mark - full compliance with LVD and EMC directives
* Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1, Class1, SELV;
Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE.
* MTBF - over 200,000 hours at 25°C ambient condition.

Technical Specifications

3-cell Long Life Li-Ion (42 WHr)¹	Weight	0.183 kg +/- 10g (0.403 lb)
	Cells/Type	3cell Lithium-Ion Polymer cell / 545974
	Energy	Voltage 11.4V
		Amp-hour capacity 3.75Ah
		Watt-hour capacity¹ 42.75Wh
Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)
	Operating (Discharging)	14° to 140° F (-10° to 60° C)
	Optional Travel Battery	N/A
	Available	

Technical Specifications

AUDIO

HD Stereo Codec	Realtek ALC3247-CG
Audio I/O Ports	Headset: CTIA only and Headphone-out
Internal Speaker Amplifier	ALC 3247 has Embedded Class-D 2W Stereo Amplifier
Multi-streaming Capable	Playback multi-streaming can be enabled in the audio control panel to allow independent audio. Following MSFT Behavior
Sampling	DAC: 48kHz ADC: 44.1k/48kHz
Wavetable Syntheses	NA
Analog Audio	Support 3.5mm Headset: CTIA only and Headphone-out
# of Channels on Line-Out	NA
Internal Speaker	Yes

FINGERPRINT READER

Sensor vendor	Elan P1515E
Sensor type	Capacitive
DPI resolution	508 DPI
Scan area	80 x 80 pixels
False Rejection Rate	<= 3%
False Acceptance Rate	< 1/100K
Mobile Voltage Operation	3.0V to 3.6V
Operating Temperature	14° – 167°F (-10°-75°C)
Current Consumption	35mA (MAX)
Image	
Low Latency Wait For	
Finger	900uA (MAX)
Capture Rate	50 cm/sec
ESD Resistance	IEC 61000-4-2 4B (+15KV)
Detection Matrix	80*2 (Plus another secondary line) / 508 dpi / 4*4 mm sensor area

Technical Specifications

ENVIRONMENTAL DATA

Eco-Label Certifications & declarations	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: <ul style="list-style-type: none"> IT ECO declaration US ENERGY STAR® US Federal Energy Management Program (FEMP) EPEAT® Gold registered in the United States. See http://www.epeat.net for registration status in your country. TCO Certified China Energy Conservation Program (CECP) China State Environmental Protection Administration (SEPA) Taiwan Green Mark Korea Eco-label Japan PC Green label* 		
Sustainable Impact Specifications	<ul style="list-style-type: none"> Product Carbon Footprint (hp.com) 50% recycled metal Low halogen External Power Supply 90% Efficiency Outside Box and corrugated cushions are 100% sustainably sourced and recyclable Molded Paper Pulp Cushion inside box is 100% sustainably sourced and recyclable Bulk packaging available 		
System Configuration	The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".		
Energy Consumption (in accordance with US ENERGY STAR® test method)	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz
Normal Operation (Sort idle)	4.69 W	4.78 W	4.73 W
Normal Operation (Long idle)	1.34 W	1.33 W	1.27 W
Sleep	1.34 W	1.33 W	1.27 W
Off	0.3 W	0.34 W	0.3 W
	NOTE: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.		
Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz
Normal Operation (Short idle)	16.0 BTU/hr	16.3 BTU/hr	16.2 BTU/hr
Normal Operation (Long idle)	4.6 BTU/hr	4.5 BTU/hr	4.3 BTU/hr
Sleep	4.6 BTU/hr	4.5 BTU/hr	4.3 BTU/hr
Off	1.0 BTU/hr	1.2 BTU/hr	1.0 BTU/hr

Technical Specifications

	<p>*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.</p>	
Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (L _{WAd} , bels)	Sound Pressure (L _{pAm} , decibels)
Typically Configured – Idle	2.6	14.4
Fixed Disk – Random writes	2.6	14.5
Optical Drive – Sequential reads	3.4	24.9
Longevity and Upgrading	<p>This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the</p>	
	<p>Spare parts are available throughout the warranty period and or for up to "5" years after the end of production.</p>	
Additional Information	<ul style="list-style-type: none"> This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC. This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC. This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986). This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see www.epeat.net Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043. This product is 95.1% recycle-able when properly disposed of at end of life. 	
Packaging Materials	External:	PAPER/Corrugated 220 g
		PAPER/ Corrugated 41 g
		PAPER/Molded Pulp 50 g
		PAPER/Molded Pulp 49 g
		PAPER/Paper 3 g
	Internal:	PLASTIC/Polyethylene low density - LDPE 14 g
	The plastic packaging material contains at least 0.0% recycled content.	
	The corrugated paper packaging materials contains at least 54.0% recycled content.	
RoHS Compliance	<p>HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.</p> <p>We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.</p> <p>We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the</p>	

Technical Specifications

	<p>scope of the commitment to include further restricted substances as regulations continue to evolve.</p> <p>To obtain a copy of the HP RoHS Compliance Statement, see HP RoHS position statement.</p>
Material Usage	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html):</p> <ul style="list-style-type: none">• Asbestos• Certain Azo Colorants• Certain Brominated Flame Retardants – may not be used as flame retardants in plastics• Cadmium• Chlorinated Hydrocarbons• Chlorinated Paraffins• Bis(2-Ethylhexyl) phthalate (DEHP)• Benzyl butyl phthalate (BBP)• Dibutyl phthalate (DBP)• Diisobutyl phthalate (DIBP)• Formaldehyde• Halogenated Diphenyl Methanes• Lead carbonates and sulfates• Lead and Lead compounds• Mercuric Oxide Batteries• Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.• Ozone Depleting Substances• Polybrominated Biphenyls (PBBs)• Polybrominated Biphenyl Ethers (PBBEs)• Polybrominated Biphenyl Oxides (PBBOs)• Polychlorinated Biphenyl (PCB)• Polychlorinated Terphenyls (PCT)• Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.• Radioactive Substances• Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)
Packaging Usage	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none">• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.• Design packaging materials for ease of disassembly.• Maximize the use of post-consumer recycled content materials in packaging materials.• Use readily recyclable packaging materials such as paper and corrugated materials.• Reduce size and weight of packages to improve transportation fuel efficiency.• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

Technical Specifications

End-of-life Management and Recycling	<p>HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>
HP, Inc. Corporate Environmental Information	<p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</p> <p>Eco-label certifications http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</p> <p>ISO 14001 certificates: http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842 and http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</p>
footnotes	<ul style="list-style-type: none">• Percentage of ocean-bound plastic contained in each component varies by product• Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.• External power supplies, WWAN modules, power cords, cables and peripherals excluded.• 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.• Fiber cushions made from 100% recycled wood fiber and organic materials.• Plastic cushions are made from >90% recycled plastic.• Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams.

COUNTRY OF ORIGIN

China



Options and Accessories (Sold separately and availability may vary by country)

DOCKING (Sold Separately)

Docking station model #1

**Total number of supported displays
(incl. the notebook display)**

Max. resolutions supported

HP Thunderbolt 4 100W G6 Dock

4

(4) 4K @60Hz*
(2) 4K @ 120Hz*
(3) QHD @ 120Hz*
(1) QHD @ 360Hz*

Dock Connectors

HP Quick Connect Support

Technical limitations

1x HDMI 2.1, 2x DisplayPort 1.4, 1x Thunderbolt 4

No

HP Quick Connect not supported on this platform.

*Requires DisplayPort 1.4 support with Display Stream Compression (DSC).

Bluetooth required for HP Quick Connect. HP Quick Connect available on select HP notebooks.

Maximum resolution and display support is dependent on the maximum capability of the notebook.

Thunderbolt Hosts:

Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.

Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz

Non-Thunderbolt hosts:

The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is

(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port

Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.

Docking station model #2

**Total number of supported displays
(incl. the notebook display)**

Max. resolutions supported

HP Thunderbolt 120W G4 Dock

4

Quad 4K @60Hz

Dual 8K single cable@30 for TB hosts or USB-C hosts DP 1.4 with DSC in high res mode

2xDP, 1xHDMI, 1xTB, 1xUSB-C Alt Mode

Maximum resolution and display support is dependent on the maximum capability of the notebook.

Thunderbolt Hosts:

Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.

Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz

Non-Thunderbolt hosts:

The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is

(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port

Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2)

Options and Accessories (Sold separately and availability may vary by country)

5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.

Docking station model #3**Total number of supported displays
(incl. the notebook display)****Max. resolutions supported**

HP Thunderbolt 280W G4 Dock

4

Quad 4K @60Hz

Dual 8K single cable@30 for TB hosts or USB-C hosts DP 1.4 with DSC in high res mode

Dock Connectors**Technical limitations**

2xDP, 1xHDMI, 1xTB, 1xUSB-C Alt Mode

Maximum resolution and display support is dependent on the maximum capability of the notebook.

Thunderbolt Hosts:

Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.

Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz

Non-Thunderbolt hosts:

The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is

(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port

Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.

Docking station model #4**Total number of supported displays
(incl. the notebook display)****Max. resolutions supported**

HP USB-C Dock G5

3

Dual 5K@ 30Hz + (1) 4K UHD (multi-function mode)

1xHDMI, 2xDP

Maximum resolution and display support is dependent on the maximum capability of the notebook.

Highest resolution with dual displays is two 8K@ 60Hz host in High Resolution mode.

Three maximum displays supported are two 5K@ 30 Hz on DP ports plus one 4K UHD@ 30 Hz on HDMI in Multi-function mode

The highest resolution for a non-Thunderbolt host in Multi-function mode is a single 5K dual cable (using both DP ports) + (1) 4K on HDMI port.

Docking station model #5**Total number of supported displays
(incl. the notebook display)****Max. resolutions supported**

HP USB-C/A Universal Dock G2

3

Dual 4K @ 60Hz

Single 5K @ 60Hz

Options and Accessories (Sold separately and availability may vary by country)

Dock Connectors

1xHDMI, 2xDP

Technical limitations

Maximum resolution and display support is dependent on the maximum capability of the notebook.

The best resolution for dual or triple displays is 4K UHD@ 60Hz.

For use with the USB-A adapter that comes in the box the maximum number of displays supported is (2) 4k x 60 Hz on the Type-A Gen 1 connection from the host.

Docking station model #6

HP USB-C G5 Essential Dock

**Total number of supported displays
(incl. the notebook display)**

3

Max. resolutions supported

For hosts that support DisplayPort 1.4 with Display Stream Compression:

3x FHD @ 60 Hz
3x QHD @ 60 Hz
3x 4K @ 60 Hz

For hosts that support DisplayPort 1.3/1.4:

3x FHD @ 60 Hz
3x QHD @ 60 Hz
2x 4K @ 60 Hz

1 x HDMI, 2 x DP

Dock Connectors**Technical limitations**

Video resolution depends on the capability of the host machine. This dock provides up to 65W of power delivery to the host machine.

Options and Accessories (Sold separately and availability may vary by country)

Type	Description	Part Number
Audio	HP Wired USB-A Stereo Headset	428K6AA
	HP Wired 3.5mm Stereo Headset	428K7AA
	HP 365 BT Speaker	567D3AA#ACJ
Video	HP 325 FHD USB-A Webcam	53X27AA
	HP 965 4K USB-A STR Webcam	695J5AA
Cases	HP Prelude G2 15.6 Backpack	1E7D6AA
	HP Prelude G2 15.6 Top Load	1E7D7AA
	HP Prelude Pro Recycled 15.6 Backpack	1X644AA
	HP Prelude Pro Recycled 15.6 Top Load	1X645AA
	HP Renew 14 Laptop Sleeve	2E6U9AA
	HP Renew Business 14.1 Laptop Bag	3E5F9AA
	HP Renew Business 14.1 Laptop Sleeve	3E2U7AA
	HP Renew Business 15.6 Laptop Bag	3E5F8AA
	HP Renew Business 17.3 Laptop Backpack	3E2U5AA
	HP Renew Business 17.3 Laptop Bag	3E2U6AA
	HP Renew Executive 14.1 Laptop Sleeve	6B8Y3AA
	HP Renew Executive 16 Laptop Backpack	6B8Y1AA
	HP Renew Executive 16 Laptop Bag	6B8Y2AA
Digital Pen	HP Slim RECHBL Pen	630W7AA
Pen Accessory	HP Rechargeable Slim Pen Charger	4X491AA#AC3
Docking	HP Thunderbolt 4 100W G6 Dock	9X472UT
	HP Thunderbolt 4 Ultra 180W G6 Dock	9X481UT
	HP Thunderbolt 4 Ultra 280W G6 Dock	AW5M5UT
	HP USB-C 120W G5 Dock	5TW10AA
	HP USB-C/A 120W G2 Universal Dock	5TW13AA
	HP Thunderbolt 120W G4 Dock	4J0A2AA
	HP Thunderbolt 280W G4 Dock	4J0G4AA
Hub	HP 4K USB-C Multiport Hub	6G842AA
	HP Universal USB-C Multiport Hub	50H55AA
	HP USB-C Travel Dock G2	7PJ38AA
	HP USB-C to USB-A Hub	Z6A00AA
Adapter	HP USB-C to RJ45 Adapter G2	4Z527AA

Options and Accessories (Sold separately and availability may vary by country)

	HP USB 3.0 to Gigabit RJ45 Adapter G2	4Z7Z7AA
	HP HDMI to VGA Adapter	H4F02AA
	HP USB-C to DisplayPort Adapter	N9K78AA
	HP USB-C to HDMI 2.0 Adapter	1WC36AA
	HP USB-C to USB 3.0 Adapter	N2Z63AA
	HP USB-C to VGA Adapter	N9K76AA
Keyboard/Combo	HP 125 WD USB Keyboard	266C9AA
	HP 320K WD USB Keyboard	9SR37AA
	HP 355 Compact Multi-Device BT Keyboard	692S9AA
	HP 455 Programmable Wireless Keyboard	4R177AA
	HP 975 USB+BT Dual-Mode Wireless Keyboard	3Z726AA
	HP 155 Wired Mouse and Keyboard Combo	5B8C0AA#ACJ
	HP 225 Antimicrobial Wired Mouse and Keyboard Combo	286K3AA#AB2
	HP 225 Wired Mouse and Keyboard Combo	286J4AA
	HP 235 Wireless Mouse and Keyboard Combo	1Y4D0AA
	HP 655 Wireless Keyboard and Mouse Combo	4R009AA
Mouse	HP Wired Desktop 320MK Mouse and Keyboard	9SR36AA
	HP Wireless Rechargeable 950MK Mouse and Keyboard	3M165AA
	HP 125 USB-A Wired Mouse	265A9AA
	HP 128 USB Laser Wired Mouse	265D9AA
	HP 155 USB-A Wired Mouse	5B8B7AA#ACJ
	HP 320M USB-A Wired Mouse	9VA80AA
	HP 435 Bluetooth 5.0 + Wireless 2.4GHz Multi-Device Wireless Mouse	3B4Q5AA
	HP 715 Rechargeable Multi-Device Bluetooth 5.0 + Wireless 2.4GHz Bluetooth Mouse	6E6F0AA
	HP 925 Ergonomic Vertical Bluetooth 5.0 + Wireless 2.4GHz Wireless Mouse	6H1A5AA
	HP Creator USB-A+Bluetooth 935 Wireless Mouse Black	1D0K8AA
Power	HP USB Premium Wireless Mouse	1JR31AA
	HP USB-A+Bluetooth Multi-Device 635 Wireless Mouse Black	1D0K2AA
	HP USB-A+Bluetooth Travel Bluetooth Mouse	6SP30AA
	HP 45W USB-C LC Dali AC Power Adapter	1MZ01AA
	HP 65W 4.5 mm Smart AC Power Adapter	H6Y89AA
	HP 65W GaN USB-C Laptop Charger	600Q7AA
	HP 65W USB-C Laptop Charger	671R3AA
Commodity	HP 65W USB-C LC AC Power Adapter	1P3K6AA
	HP 90W 4.5 mm Smart AC Power Adapter	H6Y90AA
	HP USB DVD-Writer EXT ODD	F2B56AA

Options and Accessories (Sold separately and availability may vary by country)

HP Nano Keyed Cable Lock	1AJ39AA
HP Nano Master Keyed Cable Lock	1AJ40AA
HP SureKey Standard/Nano/Wedge Cable Lock	6UW42AA
HP Combination Nano Cable Lock	63B28AA
HP Essential Combination Nano Cable Lock	63B31AA

Change Log

Date of change:	Version History:		Description of change:
March 2, 2023	V1 to V2	Updated	Weight and dimensions section
March 9, 2023	V2 to V3	Added	Docking station
March 21, 2023	V3 to V4	Added	Environmental Data
March 30, 2023	V4 to V5	Updated	At a Glance section
April 19, 2023	V5 to V6	Added	Miracast in Networking and Communications section
May 31, 2023	V6 to V7	Updated	Audio and Multimedia section
June 5, 2023	V7 to V8	Updated	Storage and Drives section
June 21, 2023	V8 to V9	Updated	Processors section
July 12, 2023	V9 to V10	Added	WLAN in Networking section
August 1, 2023	V10 to V11	Updated	Environmental Data
September 22, 2023	V11 to V12	Added	Camera description in Camera section
October 3, 2023	V12 to V13	Updated	Frequency bands for Realtek 8852CE in Networking section
February 6, 2024	V13 to V14	Updated	Digital Pen
February 18, 2025	V14 to V15	Removed	Display Section
May 28, 2025	V15 to V16	Updated	Docking Section

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core, Thunderbolt Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.