

# SAFETY DATA SHEET 化学品安全技术说明书

Product: LI-ION BATTERY PACK 产品: 锂离子电池组 Model/type reference: C41N2302 型号: Ratings: 15.48V 4580mAh 73Wh 额定容量 Applicant: Dynapack Electronic Technology (Suzhou) Co., Ltd 申请人: 顺达电子科技(苏州)有限公司 No. 8 Hua-Gang Road, WuJiang Economical and Technological Address: Development Zone, Suzhou city, JiangSu. PRC. 地址: 江苏省苏州市吴江区花港路8号 Report No: P23061301601 报告编号: Effective date: 2023-06-14 生效日期: Revision date: 2023-06-14 修订日期:

> Laboratory: Shenzhen NTEK New Energy Technology Co., Ltd. Room 101, Building C, Fenda Hi-Tech Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

The supplier identified below generated this SDS using the NTEK SDS template. NTEK did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. NTEK makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS.

Jake Gron Jesse Zhang Jake Chen Compiled by (name+ signature) ..: Jesse Zhang Approved by (name+ signature) ..:



# Section 1- Identification of the Substance/Preparation and of the Company/Undertaking

第1部分:化学品及企业标识

Product Identifier 产品信息Product Name 产品名: LI-ION BATTERY PACK 锂离子电池组Model No. 型号: C41N2302Other means of identification 其他信息Synonyms 别名: NoneRecommended use of the chemical and restrictions on use 产品用途Recommended Use 推荐用途: LITHIUM ION BATTERIESUses advised against 限制用途: No information availableDetails of the supplier of the safety data sheet 企业信息Manufacturer's/ Supplier Name: Dynapack Electronic Technology (Suzhou) Co., Ltd

制造商/供应商名称: 顺达电子科技(苏州)有限公司

**Address:** No. 8 Hua-Gang Road, WuJiang Economical and Technological Development Zone, Suzhou city, JiangSu. PRC.

地址: 江苏省苏州市吴江区花港路8号

Telephone number of the manufacturer/supplier 电话: +86-0512-63408688-87145 Emergency Telephone Number (24h) 应急电话(24 小时): +86-0512-63408688-87145 E-mail address 邮箱: Will.Wei@dynapack.com.cn Version number 版本号: V2.0

### Section 2 – Hazards Identification

### 第2部分:危险性概述

#### Classification 危险性类别

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) this product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery. 根据 2012 年职业安全与卫生管理局危险标准(29 CFR 1910.1200),该化学品没有危险。本产品是一种密封电池的物品,因此,除非破裂,根据职业安全与卫生管理局危险标准不需要 MSDS。所示的危险是电池破裂后的危险。

Skin corrosion/irritation 皮肤腐蚀/刺激性	Category 2 2 类
Serious eye damage/eye irritation 严重眼睛损伤	Category 2 2 类
/刺激性	
Skin sensitization 皮肤过敏	Category 1 1 类
Specific target organ toxicity (repeated	Category 1 1 类
exposure) 器官毒性	

#### GHS Label elements, including precautionary statements GHS 标签要素



#### Emergency Overview 紧急情况概述

Signal word 警示词: Danger Hazard Statements 危害说明 Causes skin irritation 皮肤刺激性 Causes serious eye irritation 严重眼睛刺激性 May cause an allergic skin reaction 怀疑引起皮肤过敏

May cause cancer 怀疑致癌



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. 本产品是一种含有化学物质的物品,安全信息供可接触售出物品使用。 Intended use of the product should not result in exposure to the chemical substance This is a battery. In case of rupture: the above hazards exist. 预期的使用产品不会导致化学物质暴露,这是一个电池。如发生破裂:存在上述危险。

Appearance 颜色 Black 黑色 Physical State 物理性状 Solid 固体 Odor 气味 Odorless 无味

Precautionary	Obtain special instructions before use 使用前阅读说明
•	
Statements -	Do not handle until all safety precautions have been read and understood 在阅读和理解
Prevention	了所有的安全预防措施前,不要进行作业。
预防措施	Use personal protective equipment as required 根据需要使用个人防护装备
	Wash face, hands and any exposed skin thoroughly after handling 作业后彻底清洗脸、
	手和任何暴露的皮肤
	Contaminated work clothing should not be allowed out of the workplace 不将受污染的工作服带离工作场所
	Wear protective gloves 戴防护手套
	Do not breathe dust/fume/gas/mist/vapors/spray 请勿吸入粉尘、烟雾、雾、喷雾
	Do not eat, drink or smoke when using this product 在使用本产品时,请勿进食、饮水或
	吸烟
Precautionary	IF exposed or concerned: Get medical advice/attention 如果接触: 立即就医
Statements -	Specific treatment (see supplemental first aid instructions on this label) 具体处理方法(参
Response	见本标签上的补充急救说明)
紧急响应	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing If eye irritation persists: Get medical
	advice/attention 如果进了眼睛:用水小心冲洗几分钟,如果有,摘下隐形眼镜。如果眼睛
	刺激持续存在,请继续冲洗:立即就医
	IF ON SKIN: Wash with plenty of soap and water 如果在皮肤上:用大量的肥皂和酸水清
	h ON ON Wash with picity of soap and watch 如来正反成上, 加大重的記名和嵌水的 洗
	Take off contaminated clothing and wash before reuse 脱下受污染的衣服,清洗后再重复
	使用
	If skin irritation or rash occurs: Get medical advice/attention 如果出现皮肤刺激或皮疹: 立即就医



Precautionary	Store locked up 存放处需加锁
Statements -	
Storage	
安全存储	
Precautionary	Dispose of contents/container to an approved waste disposal plant 经批准的废物处理厂
Statements -	对内容物/容器进行处置
Disposal	
废弃处置	
Hazards not	Not applicable 不适用
otherwise	
classified	
(HNOC)	
未分类危害	
Unknown	-
Toxicity	
未知毒性	
Other	May be harmful if swallowed 如果吞食可能会有害
information	Very toxic to aquatic life with long lasting effects 对水生生物毒性极大,持久影响
其他信息	Repeated or prolonged skin contact may cause allergic reactions with susceptible
	persons 反复或长时间的皮肤接触可能会引起对易感人群的过敏反应
Interactions	No information available. 无可资料
with Other	
Chemicals	
反应物质	

### Section 3 – Composition/Information on Ingredients

第3部分:成分/组成信息

Chemical Name 化学名	CAS Number CAS 编号	Weight-% 重量%	Trade Secret
Cobalt lithium dioxide	12190-79-3	15-40	-
Ethyl propionate	105-37-3	15-40	-
Copper foil	7440-50-8	10-30	-
Aluminum foil	7429-90-5	10-30	-
Graphite	7782-42-5	7-25	-
Ethylene Carbonate	96-49-1	0.1-15	-
Propylene Carbonate	108-32-7	0.1-15	-
Lithium hexafluorophosphate	21324-40-3	0.1-15	-
Polyethylene	9002-88-4	0.1-5	-

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

成分的百分比(浓度)是商业机密,需保密。



### Section 4 – First-aid Measures

### 第4部分:急救措施

General Advice	First aid is upon rupture of sealed battery. 电池破裂时的急救措施。		
通用措施	<b>Eye contact:</b> If symptoms persist, call a physician. Rinse immediately with plenty		
	of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while		
	rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do		
	not rub affected area. 眼部接触:如果症状持续存在,立即就医。立即用足够的水		
	对眼睑下进行冲洗,冲洗至少15分钟。冲洗时要睁大眼睛,如果有,移除隐形眼		
	镜。持续冲洗,不要揉搓受影响的区域。		
	<b>Skin contact:</b> Wash off immediately with soap and plenty of water for at least 1		
	minutes. In the case of skin irritation or allergic reactions see a physician. May		
	cause an allergic skin reaction. 皮肤接触:立即用肥皂和大量的水冲洗干净,至少		
	冲洗 15 分钟,如果出现皮肤刺激或过敏反应,立即就医。可能会引起皮肤过敏反		
	应。		
	Inhalation: Remove to fresh air. If symptoms persist, call a physician. Get		
	medical attention immediately if symptoms occur. 吸入:移至新鲜空气的场所。如		
	果症状持续存在,请立即就医。		
	Ingestion: Do NOT induce vomiting. Rinse mouth immediately and drink plenty of		
	water. Never give anything by mouth to an unconscious person. Call a physician.		
	摄入:不要引起呕吐。立即漱口,多喝水,立即就医。		
	Self-protection of the first aider: Avoid contact with skin, eyes or clothing. Use		
	personal protective equipment as required. Wear personal protective clothing		
	(see section 8). 急救员的自我保护:避免接触皮肤、眼睛或衣服。根据需要使用个		
	人防护装备。穿戴个人防护服(见第8部分)。		
Most important	Most important symptoms and effects: Itching. Coughing and/ or wheezing.		
symptoms and	主要症状和影响是: 瘙痒。咳嗽和/或喘息。		
effects, both acute			
and delayed			
主要症状 <b>,急性</b> 和迟发			
性效应			
Indication of any	Notes to Physician: Treat symptomatically. May cause sensitization of		
immediate medical	susceptible persons. 医生须知:对症治疗。		
attention and			
special treatment			
needed 医疗护理和			
特殊治疗			



### **Section 5 – Fire-fighting Measures**

### 第5部分:消防措施

Suitable extinguishing Media 灭火方法和灭火	Use extinguishing measures that are appropriate to local circumstances and the		
剂	surrounding environment. 使用适合当地环境和周围环境的灭火措施。		
Unsuitable	CAUTION: Use of water spray when fighting fire may be inefficient. 注意:灭火		
extinguishing Media	时使用喷水器可能效率低下。		
不合适的灭火方法和灭			
火剂			
Specific Hazards	Product is or contains a sensitizer. May cause sensitization by skin contact. 产		
arising from the	品或含有一种致敏剂,可能因皮肤接触而引起致敏作用。		
chemical 特殊危害			
Hazardous	Carbon oxides. 碳氧化物。		
<b>Combustion Products</b>			
危险易燃产品			
Explosion Data 爆炸数	Sensitivity to Mechanical Impact: No. 机械冲击灵敏度:不敏感。		
据	Sensitivity to Static Discharge: No. 静电灵敏度:不敏感。		
Protective Equipment	As in any fire, wear self-contained breathing apparatus pressure-demand,		
and precautions for	MSHA/NIOSH (approved or equivalent) and full protective gear. 在任何火灾中,		
firefighters 保护消防人	佩戴自给式呼吸器压力要求、MSHA/NIOSH(批准或同等)和全套防护装备。		
员的防护设备及注意事			
项			

### Section 6 – Accidental Release Measures

第6部分:泄漏应急处理

Personal Precautions,	Personal Precautions: Avoid contact with skin, eyes or clothing. Ensure		
protective equipment,	adequate ventilation. Use personal protective equipment as required. Evacuate		
and emergency	personnel to safe areas. 作业人员注意事项:避免接触皮肤、眼睛或衣服。确保		
procedures 作业人员防	作业场所通风充足,根据需要使用个人防护装备,疏散人员到安全区域。		
护措施、防护设备和应急	Other Information: Refer to protective measures listed in Sections 7 and 8. 其		
处置程序	他信息:参见第7、8部分所列的防护措施。		
Environmental	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage		
Precautions 环境保护	or spillage if safe to do so. 请参见第7部分和第8部分中列出的防护措施。如果安		
措施	全,防止进一步泄漏或溢出。		
Methods and material	Methods for Containment: Prevent further leakage or spillage if safe to do so.		
for containment and	Methods for cleaning up: Pick up and transfer to properly labeled containers.		
cleaning up 泄露化学	清理方法:取出并转移到标签正确的容器中。		
品的收容和清理方法			



### Section 7 – Handling and Storage

### 第7部分:操作处置与存储

Precautions for safe	Handling: In case of rupture. Use personal protection equipment. Avoid contact		
handling 操作处置	with skin, eyes or clothing. Ensure adequate ventilation. Do not breathe		
	dust/fume/gas/mist/vapors/spray. 搬运:如发生破裂。使用个人防护设备。避免		
	接触皮肤、眼睛或衣服。确保通风充足。请勿吸入灰尘、烟雾、气雾、喷雾。		
Conditions for safe	<b>Storage:</b> Keep containers tightly closed in a dry, cool and well-ventilated place.		
storage, including any	Incompatible Products: Strong acids. Strong oxidizing agents. Strong bases.		
incompatibilities 安全	储存:将容器密封在干燥、凉爽、通风良好的地方。不相容的产品:强酸。强氧		
存储的条件	化剂。强大的基础。		

### Section 8 – Exposure Controls and Personal Protection

第8部分:接触控制和个体防护

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Graphite	TWA: 2 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total	IDLH: 1250 mg/m <sup>3</sup>
7782-42-5	respirable fraction all	dust synthetic	TWA: 2.5 mg/m <sup>3</sup> respirable
	forms except graphite	TWA: 5 mg/m³	dust
	fibers	respirable fraction	
		synthetic	
		(vacated) TWA: 2.5	
		mg/m <sup>3</sup> respirable dust	
		natural	
		(vacated) TWA: 10	
		mg/m <sup>3</sup> total	
		dust synthetic	
		(vacated) TWA: 5 mg/m <sup>3</sup>	
		respirable fraction	
		synthetic	
		TWA: 15 mppcf natural	
Aluminum foil	TWA: 1 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total	TWA: 10 mg/m <sup>3</sup> total dust
7429-90-5	respirable fraction	dust	TWA: 5 mg/m <sup>3</sup> respirable
		TWA: 5 mg/m³	dust
		respirable fraction	
		(vacated) TWA: 15	
		mg/m <sup>3</sup> total dust	
		(vacated) TWA: 5 mg/m <sup>3</sup>	

### Control parameters 控制参数

#### Exposure Guidelines 接触指南



		respirable fraction (vacated) TWA: 5 mg/m <sup>3</sup>	
		Aluminum	
Phosphate(1-),	TWA: 2.5 mg/m³ F	TWA: 2.5 mg/m <sup>3</sup> F	-
hexafluoro-, lithium		TWA: 2.5 mg/m <sup>3</sup> dust	
21324-40-3		(vacated) TWA: 2.5	
		mg/m³	
Lithium Cobalt Oxide	TWA: 0.02 mg/m <sup>3</sup>	-	-
(LiCoO <sub>2</sub> )			
12190-79-3			

\*ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health 美国政府工业卫生学家会议-阈值OSHA PEL: 职业安全与健康管理局-允许暴露限 制NIOSH IDLH立即对生命或健康造成危险

#### Other Exposure Guidelines其他接触指南

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters 上诉法院在美国劳联-产联诉。俄亥 俄州, 965 F.2d 962 (1992年第11届)国家接触控制参数见第15部分

Appropriate engineering	Engineering Measures 工程措施:	
controls 工程控制方法	Showers 淋浴设备	
	Eyewash stations 洗眼站	
	Ventilation systems. 通风系统	
Individual protection	Eye/Face Protection: If splashes are likely to occur:. Wear safety	
measures, such as personal	glasses with side shields (or goggles). None required for consumer use.	
protective equipment 个人防 护设备	眼睛/面部保护:如果有可能发生飞溅:佩戴带侧护罩的安全眼镜(或护	
	目镜)。	
	<b>Skin and Body Protection</b> : Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. 皮肤和身体防护: 佩戴防护手套和防护服,长袖衣服,防渗手套。	
	Respiratory Protection: No protective equipment is needed under	
	normal use conditions. If exposure limits are exceeded or irritation is	
	experienced, ventilation and evacuation may be required. 呼吸防护:	
	在正常使用条件下,不需要任何防护设备。如果超过接触限值或出现刺	
	激,可能需要通风和疏散。	
	Hygiene Measures: Handle in accordance with good industrial hygiene	
	and safety practice. Do not eat, drink or smoke when using this product.	
	Take off contaminated clothing and wash before reuse. Avoid contact	
	with skin, eyes or clothing. Wear suitable gloves and eye/face	
	protection.Wash hands before breaks and immediately after handling	



the product. 卫生措施:按照良好的工业卫生和安全规范进行操作,在使用本产品时,请勿进食、饮水或吸烟,取下受污染的衣服,清洗后再重复使用,避免接触皮肤、眼睛或衣服,佩戴合适的手套和眼睛/面部保护措施,在休息前和处理产品后立即洗手。

### **Section 9 - Physical and Chemical Properties**

第9部分:理化特性

	Physical state 物理状态: S	nysical state 物理状态: Solid 固体		
Physical	Appearance 外观: Black and Prismatic 黑色、棱柱形			
Properties	Color 颜色: Black 黑色			
理化特性	Odor 气味: Odorless 无味			
	Odor Threshold 嗅觉阈值:	No information available $\mathcal{F}$	<b></b>	
Chemical Prop	erties 化学特性:			
Property 特性		Values 值	Remarks/ Method 备注	
pH 酸碱度		No data available	None known	
Melting / freezi	ng point 熔点和冰点	No data available	None known	
Boiling point /	boiling range 沸点/沸程	No data available	None known	
Flash Point 闪	点	No data available	None known	
Evaporation Ra	ate 蒸发率	No data available	None known	
Flammability (solid, gas) 易燃性(固体、 气体)		No data available	None known	
Flammability Limit in Air 空气中的易燃性 极限 Upper flammability limit 燃点上限 Lower flammability limit 燃点下限		No data available No data available	-	
Vapor pressure	• 蒸气压力	No data available	None known	
Vapor density	蒸汽密度	No data available	None known	
Specific Gravit	<b>y</b> 比重	No data available	None known	
Water Solubilit	y 水溶性	Insoluble in water	None known	
Solubility in other solvents 其他溶剂中的 溶解度		No data available	None known	
Partition coefficient: n-octanol/water 分 配系数		0.00001	None known	
Autoignition temperature 自燃温度		<b>130</b> ℃	None known	
Decomposition temperature 分解温度		No data available	None known	



Kinematic viscosity 运动粘度	No data available	None known
Dynamic viscosity 动态粘滞度	0.00001	None known
Explosive properties 爆炸特性	No data available	-
Oxidizing Properties 氧化特性	No data available	-

#### Other Information 其他信息

Softening Point 软化温度	No data available
VOC Content (%)	No data available
Particle Size 粒径	No data available
Particle Size Distribution 粒径分布	No data available

### Section 10 - Stability and Reactivity

第10部分:稳定性和反应性

Reactivity 反应性	No data available. 无资料	
Chemical stability 化学稳定性	Stable under recommended storage conditions. 在推荐的储存条件下保持稳定。	
Possibility of Hazardous Reactions 发生危险反应的可能性	None under normal processing. 无	
Hazardous Polymerization 危险聚合	Hazardous polymerization does not occur. 不会发生危险的聚合反应。	
Conditions to avoid 应避免的条件	None known based on information supplied. 无资料	
Incompatible materials 不相容物质	Strong acids. Strong oxidizing agents. Strong bases. 强酸。强氧 化剂	
Hazardous Decomposition Products 危险分解产物	Carbon oxides. 碳氧化物。	

### **Section 11 - Toxicological Information**

第11部分: 毒理学信息

Information on likely route	Information on likely routes of exposure 可能的接触途径			
Product Information 产	Product does not present an acute toxicity hazard based on known or			
品信息	supplied information. In case of rupture:. 如有破裂,根据已知或提供的信息,			
	产品不存在急性毒性危害。			
Inhalation 吸入	Specific test data for the substance or mixture is not available. May cause			
	irritation of respiratory tract. 没有关于该物质或混合物的具体测试数据。可能会			
	引起对呼吸道的刺激。			
Eye Contact 眼部接触	Specific test data for the substance or mixture is not available. Expected to be			
	an irritant based on components. Irritating to eyes. May cause redness,			
	itching, and pain. May cause temporary eye irritation. 没有关于该物质或混合			



	物的具体测试数据。成分可能是刺激物,刺激眼睛,可能会引起发红、瘙痒和			
	疼痛,可能会引起暂时性的眼睛刺激。			
Skin Contact 皮肤接触	Specific test data for the substance or mixture is not available. Expected to be			
	an irritant based on components. Irritating to skin. Prolonged contact may			
	cause redness and irritation. 没有关于该物质或混合物的具体测试数据。成分			
	可能是刺激物,长时间的接触皮肤可能会引起发红和刺激。			
Ingestion 摄取	Specific test data for the substance or mixture is not available. Ingestion may			
	cause irritation to mucous membranes. Ingestion may cause gastrointestinal			
	irritation, nausea, vomiting and diarrhea. 没有关于该物质或混合物的具体测试			
	数据。摄入可能会刺激粘膜,摄入可引起胃肠道刺激、恶心、呕吐和腹泻。			

#### Component Information 组件信息

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite	> 10000 mg/kg ( Rat )	-	-
7782-42-5			

Information on toxicological effects 毒理学作	Symptoms: Erythema (skin redness). May cause
用信息	redness and tearing of the eyes. Itching. Rashes.
	Hives. 症状:出现红斑(皮肤发红),可能会导致眼睛
	发红,皮疹,荨麻疹。
Delayed and immediate effects as well as	Sensitization: May cause sensitization of susceptible
chronic effects from short and long-term	persons. May cause sensitization by skin contact. 敏
exposure 短期和长期接触造成的急慢性影响	感:可能引起易感人群的敏感。皮肤接触致敏。
	Mutagenic Effects: No information available.诱变效
	应:无资料。
	Carcinogenicity: The table below indicates whether
	each agency has listed any ingredient as a carcinogen
	致癌性: 下表显示了每个机构是否已将任何成分列为致
	癌物

Chemical Name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt	A3	Group 2B	-	Х
Oxide				
(LiCoO <sub>2</sub> )				
12190-79-3				

ACGIH (American Conference of Governmental Industrial Hygienists美国政府工业卫生学家会议) A1 - Known Human Carcinogen 己知人类致癌物

A3 - Animal Carcinogen 动物致癌物

IARC (International Agency for Research on Cancer国际癌症研究机构)

Group 1 - Carcinogenic to Humans 人类致癌物

Group 2B - Possibly Carcinogenic to Humans 可能对人类致癌

Group 3 - Not Classifiable as to Carcinogenicity in Humans 非人类致癌物

#### NTP (National Toxicology Program国际毒理学计划)

Known - Known Carcinogen 已知致癌物

OSHA (Occupational Safety and Health Administration of the US Department of Labor美国劳工部职 业安全与健康管理局)



X - Present 呈现

Reproductive Toxicity 生	No information avail	able. 无资料		
が一方である。				
STOT - single exposure	No information available. 无资料			
单次接触				
STOT - repeated	Causes damage to organs through prolonged or repeated exposure. Based			
. exposure 反复接触	on classification criteria from the 2012 OSHA Hazard Communication			
•	Standard (29 CFR 1	910.1200), this product has been determined to cause		
	systemic target orga	an toxicity from chronic or repeated exposure. (STOT		
	RE). 通过长时间或	反复接触对器官造成损害。根据2012年职业安全与卫生管		
	理局危害标准(29CF	R1910.1200)的分类标准,该产品已被确定为慢性或反复		
	接触引起全身靶器官	'毒性。(STOT RE).		
Chronic Toxicity 慢性毒	Contains a known or suspected carcinogen. Avoid repeated exposure.			
性	Prolonged exposure may cause chronic effects. May cause adverse liver			
	effects. 含有已知或	疑似的致癌物。避免反复接触,长期接触可能会导致慢性		
	影响,可能会引起对肝脏的不良反应。			
Target Organ Effects 特	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Central Vascular			
异性靶器官系统毒性	System (CVS).Kidney. Liver. Lungs. Heart. 呼吸系统。眼睛。皮胃肠道(GI)。			
	中央血管系统(CVS)。肾脏与肾脏有关。肝脏肺部。心。			
Aspiration Hazard 吸入危	No information available. 无资料			
害				
Numerical measures of toxic	Numerical measures of toxicity Product Information 毒性、产品信息的数值测量方法			
The values which are on th	The values which are on the right are ATEmix (oral)			
calculated based on chapte	er 3.1 of the GHS	ATEmix (dermal)		
document. 右边的值是根据	GHS文档的第3.1章	ATEmix (inhalation-dust/mist)		
计算出来的	算出来的			

### Section 12 - Ecological Information

第12部分: 生态学信息

#### Ecotoxicity 生态毒性

Very toxic to aquatic life with long lasting effects. 对水生生物毒性极大,具有持久的影响。

Chemical	Toxicity to Algae	Toxicity to Fish 对 <u>鱼</u>	Toxicity to	Daphnia Magna
Name 化学名	对藻类的毒性	类的毒性	Microorganisms	(Water Flea) 水蚤
			对微生物的毒性	(水跳蚤)
-	-	-	-	-

Persistence and Degradability 持久性和降解	No information available. 无资料
性	
Bioaccumulation 生物积累性	No information available 无资料
Other adverse effects 其他不良影响	No information available. 无资料



### Section 13 – Disposal Considerations

第13部分:废弃处置

#### Waste treatment methods 废物处理方法

**Disposal methods** 处置方法: This material, as supplied, is not a hazardous waste according to Federal regulations (40CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements. 根据联邦法规 (40CFR 261), 材料不是危险废物, 如果与危险废物混合或以其他方式接触, 如果添加化学品, 或经过加工改变, 该材料可能成为危险废物, 请参考40 CFR 261, 以确定已改变的材料是否为危险废物。有关其他要求, 请 咨询适当的州、以地区或地方法规。

**Contaminated Packaging:** Dispose of in accordance with federal, state and local regulations. 受污染的包装: 根据联邦、州和地方法规进行处理。

Chemical Name	RCRA	RCRA - D Series Wastes	RCRA - U Series Wastes	OSHA
-	-	-	-	-

#### California Hazardous Waste Codes 141 加州危险废物法规141

This product contains one or more substances that are listed with the State of California as a hazardous waste. 本产品含有一种或多种列入加利福尼亚州列为危险废物的物质。

Chemical Name 化学名	California Hazardous Waste 加州危险废物
Aluminum foil	Ignitable powder
7429-90-5	
Lithium Cobalt Oxide (LiCoO <sub>2</sub> )	Toxic
12190-79-3	

### Section 14 – Transport Information

第14部分:运输信息

The LI-ION BATTERY PACK as stated in Appendix is made in compliance to the requirements stated in the latest edition of the IATA Dangerous Goods Regulations Packing Instruction 965 section I B or 966 section II or 967 section II. 附录中所述的锂离子电池组是符合最新版国际航空运输协会危险品条例包装说明965第IB 或966第 II 或967第 II 节的规定的。

With regard to transport, the following regulations are cited and considered: 关于运输问题,我们引用并考虑了以下规定:

- The International Civil Aviation Organization (ICAO) Technical Instructions, Packing instruction 965 section

I B or 966 section Ⅱ or 967 section Ⅱ (2023-2024 Edition). 国际民用航空组织(ICAO)技术说明,包装说明 965 第 IB 或 966 第 Ⅱ 或 967 第 Ⅱ 节(2023-2024 版)。

- The International Air transport Association (IATA) Dangerous Goods Regulations, Packing instruction 965 section I B or 966 section II or 967 section II (64<sup>th</sup> Edition, 2023). 国际航空运输协会(IATA)危险货物条例,包装说明第 965 第 IB 或 966 第 II 或 967 第 II 节 (第 64 版, 2023)



- Special provision 188 of the International Maritime Dangerous Goods (IMDG) Code (Amendment 40-20 Edition). 《国际海上危险货物(IMDG)规范》(修正案 40-20 版)第 188 条。

- The US Hazardous Materials Regulation 49 CRF (Code of Federal Regulations), sections 173-185 Lithium batteries and cells. 美国危险材料法规 49 CRF(联邦法规法规),第 173-185 节锂电池和电池。

- The UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria 38.3 Lithium batteries. 联合国关于危险货物运输的建议,试验手册和标准38.3锂电池。

These products are properly classified, described, packaged, marked, and labeled, and are in proper condition for transportation according to all the applicable international and national governmental regulations, not limited to the above mentioned. We further certify that the enclosed products have been tested and fulfilled the requirements and conditions in accordance with UN Recommendations (T1 - T8) on the Transport of Dangerous Goods Model Regulations and the Manual of Tests and Criteria. 这些产品经过适当的分类、描 述、包装、标记和标签,并根据所有适用的国际和国家政府法规,符合适当的运输条件,但不限于上述规定。 附件产品已经过测试,并符合联合国关于危险货物运输模型法规的建议(T1-T8)和试验和标准手册的要求和条 件。

#### Test results of the UN Recommendation on the Transport of Dangerous Goods 联合国关于危险货物运 输的建议的测试结果

Manual of Test and Criteria (38.3 Lithium battery) 测试和标准于册(38.3锂电池)				
No. 编号	Test items 测试项目	Test results 测试结果	Remark	
T1	Altitude simulation	Pass	-	
	高空模拟			
T2	Thermal test 热滥用	Pass	-	
Т3	Vibration 震动	Pass	-	
T4	Shock 冲击	Pass	-	
Т5	External short circuit	Pass	-	
	外部短路			
Т6	Crush 挤压	Pass	-	
T7	Overcharge 过充电	Pass	-	
Т8	Forced discharge	Pass	-	
	强制放电			

## Manual of Test and Criteria (38.3 Lithium battery) 测试和标准手册(38.3 细由油)

#### Additional Requirements for air transport 关于航空运输的附加要求:

- 1. Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit. 电芯和电 池必须保护以防止短路,这包括防止与同一包装内的导电材料接触,从而可能导致短路。
- 2. Cells and batteries must be manufactured under a quality management program. 电芯和电池必须按照质 量管理程序进行生产。
- 3. The Watt-hour rating must be marked on the outside of the battery case except those manufactured before 1 January 2009. 除2009年1月1日之前生产的电池外壳外,必须在电池外壳外部标记。
- 4. Cells and batteries must be packed in strong outer packagings. (Applicable to PI 965 only) 电芯和电池必 须用坚固的外包装来包装。(仅适用于PI 965)
- 5. Cells and batteries must be packed in inner packagings that completely enclose the cell or battery. To provide protection from damage or compression to the batteries, the inner packagings must be placed in a strong rigid outer packaging of one of the packaging types shown below. 电芯和电池必须包装在完全包 裹电池或电池的内包装中。为了防止电池损坏或压缩,内包装必须放置在以下所示包装类型之一的坚固的



硬外包装中。

- 6. Each consignment must be accompanied with a document with an indication that 每批货物必须附有一份 文件,其中应表明:
- the package contains lithium ion cells or batteries 该包装盒中包含锂离子电芯或电池;

• the package must be handled with care and that a flammability hazard exists if the package is damaged 包 装必须小心处置,如果包装损坏,则存在易燃危险;

• special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary; and 如果包装损坏,必须遵循特殊程序,必要时包括检查和重新包装;以及

• a telephone number for additional information 要获取更多信息的电话号码.

 Each package must be labelled with a lithium battery handling label (Figure 7.4.H) in addition to the Class 9 hazard label (Figure 7.3.W) and Cargo Aircraft Only label. 除9类危险标签(图7.3.W)和货运飞机专用 标签外,每个包装件都必须标明锂电池处理标签。

Each package must be marked in accordance with the requirements of 7.1.4.1(a) and (b) and in addition the net weight when required by 7.1.4.1(c) must be marked on the package. (Applicable to PI 965 only) 每个包装都必须按照7.1.4.1(a)和(b)的要求进行标记,而且当7.1.4.1(c)要求时的净重必须在包装上进行标记。(仅适用于PI 965)

- 8. Each package must be capable of withstanding a 1.2 m drop test in any orientation without(Applicable to PI 965 and 966 only) 每个包装必须能够承受任何方向的1.2 m的跌落试验(仅适用于PI 965和966)而无下 列情况:
- damage to cells or batteries contained therein; 电芯或电池被损坏;
- shifting of the contents so as to allow battery to battery (or cell to cell) contact; 内容物移动,使电池与电池 (或电芯)接触;
- release of contents 内容物泄露。
- 9. Each package must be labelled with a lithium battery handling label (Figure 7.4.H). (Applicable to PI 966 and 967 only) 每个包装上都必须贴有锂电池处理标签。(仅适用于PI 966和967)
- **10.** A Shipper's Declaration for Dangerous Goods is not required. (Applicable to PI 966 and 967 only) 不需要 托运人的危险货物声明。(仅适用于PI 966和967)
- 11. Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities. 任何准备或提供运输电芯或电池的人必须得 到与其责任相称的关于这些要求的充分指示。
- **12.** The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation. (Applicable to PI 966 only) 设备必须固定在外 包装内,防止移动,并必须配备防止意外激活的有效方法。(仅适用于PI 966)
- **13.** The maximum number of batteries in each package must be the minimum number required to power the equipment plus two spares. (Applicable to PI 966 only) 每个电池包中的最大电池数量必须是为设备供电 所需的最小数量,再加上两个备件。(仅适用于PI 966)
- 14. The words "Lithium ion batteries in compliance with Section II of PI 966" must be included on the air waybill, when an air waybill is used. The information should be shown in the "Nature and Quantity of Goods" box of the air waybill. (Applicable to PI 966 only) 当使用航空运单时,航空运单上必须包含"符合 PI966第II 节规定的锂离子电池"字样。该信息应显示在航空运单的"货物的性质和数量"框中。(仅适用 于PI 966)
- **15.** Maximum net quantity of lithium ion cells must not be more than 5 kg. (Applicable to PI 966 and 967 only) 锂离子电池的最大净用量不得超过5公斤。(仅适用于PI 966和967)
- 16. Equipment must be equipped with an effective means of preventing accidental activation. (Applicable to PI 967 only) 设备必须配备一种防止意外激活的有效方法。(仅适用于PI 967)



- 17. The equipment containing the cells or batteries must be secured against movement within the outer packaging and be packed so as to prevent accidental operation during air transport. (Applicable to PI 967 only) 包含电芯或电池的设备必须确保不在外包装内移动,并进行包装,以防止在空气运输过程中发生意外 操作。(仅适用于PI 967)
- 18. The equipment must be packed in strong outer packagings constructed of suitable material of adequate strength and design in relation to the packaging's capacity and its intended use unless the cell or battery is afforded equivalent protection by the equipment in which it is contained. (Applicable to PI 967 only) 设备必须被包装在坚固的外包装中,用适当的材料构成,与包装的强度和设计有关,除非电池或电池由其包含的设备提供同等的保护。(仅适用于PI 967)
- 19. Where a consignment includes packages bearing the lithium battery handling label, the words "Lithium ion batteries in compliance with Section II of PI 967" must be included on the air waybill, when an air waybill is used. The information should be shown in the "Nature and Quantity of Goods" box of the air waybill. (Applicable to PI 967 only) 如果托运包括带有锂电池处理标签的包装,在使用航空单时,航空单上必须包括"符合PI967第II节的锂离子电池"字样。该信息应显示在航空运单的"货物的性质和数量"框中。(仅适用于PI 967)

### **Section 15 - Regulatory Information**

### 第15部分:法规信息

#### International Inventories 国际清单

TSCA: Complies 符合

DSL: All components are listed either on the DSL or NDSL. 所有组件都已在DSL或NDSL上列出。

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory 美国有毒物质控制法第8节(b)清单 **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List 加拿大国内物质清单/非国 内物质清单

#### US Federal Regulations 美国联邦法规

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372 《1986年超级基金修正案和再授权法案》(Sara)第三章第313条。本产品包含化学品或化学品,符合法案和《联邦法规》第372部分第40条的报告要求

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold
			Values %
Aluminum foil	7429-90-5	10-30	1.0
Lithium Cobalt Oxide	12190-79-3	15-40	0.1
(LiCoO2)			

#### SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water



Act (40 CFR 122.21 and 40 CFR 122.42) 本产品包含以下根据《清洁水法》(40 CFR 122.21和40 CFR 122.42) 规定的污染物管理的物质

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
-	-	-	-	-

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) 所提供的 材料包含根据《综合环境反应赔偿和责任法》(CERCLA)(40CFR302)规定的一种或多种危险物质

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Aluminum foil	-	-	-
7429-90-5			

#### <u>US State Regulations 美国州法规</u>

#### **California Proposition 65**

This product does not contain any Proposition 65 chemicals

本产品不含任何65号提案的化学品。

#### U.S. State Right-to-Know Regulations 美国各州的知情权条例

Chemical Name	New	Massachusetts	Pennsylvania	Rhode	Illinois
	Jersey			Island	
Graphite	Х	Х	Х	-	-
7782-42-5					
Ethylene carbonate	-	Х	Х	-	-
96-49-1					
Aluminum foil		Х		Х	
7429-90-5					
Lithium Cobalt Oxide	Х	-	Х	Х	Х
(LiCoO <sub>2</sub> )					
12190-79-3					

#### International Regulations 全球法规

#### Mexico 墨西哥

#### National occupational exposure limits 国家职业暴露限值

Component	Carcinogen Status	Exposure Limits
Graphite	-	Mexico: TWA= 2 mg/m <sup>3</sup>
7782-42-5 (7-25%)		
Aluminum foil	-	Mexico: TWA= 10 mg/m <sup>3</sup>
7429-90-5 (10-30%)		

Mexico - Occupational Exposure Limits - Carcinogens

#### Canada 加拿大

#### WHMIS Hazard Class WHMIS危险等级

Non-controlled



### **Section 16 - Other Information**

第16部分:其他信息

I	NFPA	Health Hazards 1	Flammability 0	Instability 1	Physical and
ł	HMIS	Health Hazards 4	Flammability 0	Physical Hazard 1	Chemical Hazards -
					Personal Protection X

Revision Note 修订说明: No information available 无

#### <u>Disclaimer 免责声明</u>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### --End of Safety Data Sheet--