

SFP-10G-BX-U-I

10GBase-BX-U SFP+ BiDi Transceiver

Hot Pluggable, +3.3V, Tx1270nm/ Rx1330nm, SMF, LC 10km, DOM, Industrial Temperature

FEATURES

- Supports 9.95 to 11.3Gb/s bit rates
- Hot-Pluggable
- Single LC for Bi-Directional Transmission
- Built-in 1270/1330 WDM Filter
- Uncooled 1330nm or 1270nm CWDM DFB Laser.
- SMF links up to 10km
- 2-wire interface for management specifications compliant with SFF-8472 digital diagnostic monitoring interface
- Power Supply: +3.3V
- Power consumption < 1.5W
- Industrial operating temperature range: -40 to 85°C
- RoHS compliant, Lead free

APPLICATIONS

- 10GBASE-LR/LW Ethernet
- SONET OC-192 / SDH
- 10G Fibre Channel

DESCRIPTION

ATGBICS SFP-10G-BX-U-I is a very compact 10Gb/s optical transceiver module for serial optical communication applications at 10Gb/s. The SFP-10G-BX-U-I converts a 10Gb/s serial electrical data stream to 10Gb/s optical output signal and a 10Gb/s optical input signal to 10Gb/s serial electrical data streams. The high speed 10Gb/s electrical interface is fully compliant with SFI specification.

The high performance Tx1330nm/Rx1270 DFB transmitter and high sensitivity PIN receiver provide superior performance for Ethernet applications at up to 10km links. The SFP+ Module IS compliant with SFF-8431, SFF-8432 and IEEE 802.3ae 10GBASE-LR. Digital diagnostics functions are available via a 2-wire serial interface, as specified in SFF-8472. The fully SFP compliant form factor provides hot pluggability, easy optical port upgrades and low EMI emission.

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Min.	Typical	Max.	Units
Storage Temperature	T _s	-40		+85	°C
Supply Voltage	V _{CCT, R}	-0.5		4	V
Relative Humidity	RH	0		85	%

RECOMMENDED OPERATING ENVIRONMENTS

Parameter	Symbol	Min	Typical	Max	Unit
Case operating Temperature	T _s	-40		+85	°C
Supply Voltage	V _{CCT, R}	+3.135		+3.465	V
Supply Current	I _{cc}			350	mA
Power Dissipation	P _D			1.5	W

ELECTRICAL CHARACTERISTICS (V_{cc} = 3.135 to 3.465 Volts)

Parameter		Symbol	Min	Typical	Max	Unit	Note
TRANSMITTER							
Differential input voltage swing			180		700	mVpp	1
Transmit Disable Input	H	V _{IH}	2.0		V _{cc} +0.3	V	
	L	V _{IL}	0		0.8	V	
Transmit Enable Output	H	V _{OH}	2.4		V _{cc} +0.3	V	
	L	V _{OL}	0		0.4	V	2
Input Differential Impedance		Z _{in}	80	100	120	Ohms (Ω)	
RECEIVER							
Differential output voltage swing			300		850	mVpp	3
LOS Output	H	V _{OH}	2.4		V _{cc} +0.3	V	2
	L	V _{OL}	0		0.4	V	
Output Differential Impedance		Z _{on}	80	100	120	Ω	

Note:

1. TD+/- are internally AC coupled with 100Ω differential termination inside the module.
2. Tx Fault and Rx LOS are open collector outputs, which should be pulled up with 4.7k to 10kΩ resistors on the host board. Pull up voltage between 2.0V and V_{cc}+0.3V.
3. RD+/- outputs are internally AC coupled and should be terminated with 100Ω (differential) at the user SERDES.

OPTICAL PARAMETERS (V_{cc} = 3.135 to 3.465 Volts)

Parameter		Symbol	Min	Typical	Max	Unit	Ref.
TRANSMITTER							
Bit Rate		BR	9.9		11.3	Gb/s	
Optical Wavelength	SFP-10G-BX-U-I	λ	1260	1270	1280	nm	
	SFP-10G-BX-U-I		1320	1330	1340		
Average output power		P _o	-6		0	dBm	
Optical Extinction Ratio		ER	3.5			dB	
Spectral width		$\Delta\lambda$			1	nm	
Side Mode Suppression Ratio		SMSR	30			dB	
Optical Eye Mask			Compliant with IEEE802.3ae				
RECEIVER							
Bit Rate		BR	9.9		11.3	Gb/s	
Optical Wavelength	SFP-10G-BX-U-I	λ	1320	1330	1340	nm	
	SFP-10G-BX-U-I		1260	1270	1280		
Receiver Sensitivity		Sen			-15	dBm	1
Maximum Input Power		P _{MAX}	0			dBm	
LOS De-Assert		LOS _D			-15	dBm	
LOS Assert		LOS _A	-25			dBm	
LOS Hysteresis		LOS _H	0.5		4	dB	

Note:

1. Measured with a PRBS of $2^{31}-1$ at 1×10^{-12} BER and 3.5 dB extinction ratio.

TIMING CHARACTERISTICS

Parameter	Symbol	Min.	Typical	Max.	Unit
TX_Disable Assert Time	t _{off}			10	us
TX_Disable Negate Time	t _{on}			1	ms
Time to Initialize Include Reset of TX_FAULT	t _{int}			300	ms
TX_FAULT from Fault to Assertion	t _{fault}			100	us
TX_Disable Time to Start Reset	t _{reset}	10			us
Receiver Loss of Signal Assert Time	T _{A,RX_LOS}			100	us
Receiver Loss of Signal Deassert Time	T _{d,RX_LOS}			100	us
Rate-Select Change Time	t _{ratesel}			10	us
Serial ID Clock Time	t _{serial-clock}			100	kHz

PIN ASSIGNMENT




Diagram of Host Board Connector Block Pin Numbers and Name

PIN FUNCTION DEFINITIONS

Pin No	Name	Function	Notes
1	VeeT	Module transmitter ground	1
2	Tx Fault	Module transmitter fault	2
3	Tx Disable	Transmitter Disable; Turns off transmitter laser output	3
4	SDL	2 wire serial interface data input/output (SDA)	
5	SCL	2 wire serial interface clock input (SCL)	
6	MOD-ABS	Module Absent, connect to VeeR or VeeT in the module	2
7	RS0	Rate select0, optionally control SFP+ receiver. When high, input data rate >4.5Gb/s; when low, input data rate <=4.5Gb/s	
8	LOS	Receiver Loss of Signal Indication	4
9	RS1	Rate select0, optionally control SFP+ transmitter. When high, input data rate >4.5Gb/s; when low, input data rate <=4.5Gb/s	
10	VeeR	Module receiver ground	1
11	VeeR	Module receiver ground	1
12	RD-	Receiver inverted data out put	
13	RD+	Receiver non-inverted data out put	
14	VeeR	Module receiver ground	1
15	VccR	Module receiver 3.3V supply	
16	VccT	Module transmitter 3.3V supply	
17	VeeT	Module transmitter ground	1
18	TD+	Transmitter inverted data out put	
19	TD-	Transmitter non-inverted data out put	
20	VeeT	Module transmitter ground	1

Notes:

1. The module ground pins shall be isolated from the module case.
2. This pin is an open collector/drain output pin and shall be pulled up with 4.7k-10kΩ to Host_Vcc on the host board.
3. This pin shall be pulled up with 4.7k-10kΩ to VccT in the module.
4. This pin is an open collector/drain output pin and shall be pulled up with 4.7k-10kΩ to Host_Vcc on the host board.

SFP MODULE EEPROM INFORMATION AND MANAGEMENT

The SFP modules implement the 2-wire serial communication protocol as defined in the SFP-8472. The serial ID information of the SFP modules and Digital Diagnostic Monitor parameters can be accessed through the I²C interface at address A0h and A2h. The memory is mapped in Table 1. Detailed ID information (A0h) is listed in Table 2. And the DDM specification at address A2h. For more details of the memory map and byte definitions, please refer to the SFF-8472, “Digital Diagnostic Monitoring Interface for Optical Transceivers”. The DDM parameters have been internally calibrated.




Table 1. Digital Diagnostic Memory Map (Specific Data Field Descriptions)

EEPROM SERIAL ID MEMORY CONTENTS (A0h)

Data Address	Length (Byte)	Name of Length	Description and Contents
BASE ID FIELDS			
0	1	Identifier	Type of Serial transceiver (03h=SFP)
1	1	Reserved	Extended identifier of type serial transceiver (04h)
2	1	Connector	Code of optical connector type (07=LC)
3-10	8	Transceiver	10G Base-LR
11	1	Encoding	64B/66B
12	1	BR, Nominal	Nominal baud rate, unit of 100Mbps
13-14	2	Reserved	(0000h)
15	1	Length (9um)	Link length supported for 9/125um fibre, units of 100m
16	1	Length (50um)	Link length supported for 50/125um fibre, units of 10m
17	1	Length (62.5um)	Link length supported for 62.5/125um fibre, units of 10m
18	1	Length (Copper)	Link length supported for copper, units of meters
19	1	Reserved	
20-35	16	Vendor Name	SFP vendor name: ATGBICS
36	1	Reserved	
37-39	3	Vendor OUI	SFP transceiver vendor OUI ID
40-55	16	Vendor PN	Part Number: SFP-10G-BX-U-I
56-59	4	Vendor rev	Revision level for part number
60-62	3	Reserved	
63	1	CCID	Least significant byte of sum of data in address 0-62
EXTENDED ID FIELDS			
64-65	2	Option	Indicates which optical SFP signals are implemented (001Ah = LOS, TX_FAULT, TX_DISABLE all supported)
66	1	BR, max	Upper bit rate margin, units of %
67	1	BR, min	Lower bit rate margin, units of %
68-83	16	Vendor SN	Serial number (ASCII)
84-91	8	Date code	ATGBICS Manufacturing date code
92-94	3	Reserved	
95	1	CCEX	Check code for the extended ID Fields (addresses 64 to 94)
VENDOR SPECIFIC ID FIELDS			
96-127	32	Readable	ATGBICS specific date, read only
128-255	128	Reserved	Reserved for SFF-8079

Table 2 – EEPROM Serial ID Memory Contents

DIGITAL DIAGNOSTIC MONITOR CHARACTERISTICS


Data Address	Parameter	Accuracy	Unit
96-97	Transceiver Internal Temperature	±3.0	°C
100-101	Laser Bias Current	±10	%
100-101	Tx Output Power	±3.0	dBm
100-101	Rx Input Power	±3.0	dBm
100-101	VCC3 Internal Supply Voltage	±3.0	%

REGULATORY COMPLIANCE


The SFP-10G-BX-U-I complies with international Electromagnetic Compatibility (EMC) and international safety requirements and standards (see details in Table following).

Electrostatic Discharge (ESD) to the Electrical Pins	MIL-STD-883E Method 3015.7	Class 1(>1000 V)
Electrostatic Discharge (ESD) to the Single LC Receptacle	IEC 61000-4-2 GR-1089-CORE	Compatible with standards
Electromagnetic Interference (EMI)	FCC Part 15 Class B EN55022 Class B (CISPR 22B) VCCI Class B	Compatible with standards
Laser Eye Safety	FDA 21CFR 1040.10 and 1040.11 EN60950, EN (IEC) 60825-1,2	Compatible with Class 1 laser product.

RECOMMENDED CIRCUIT



Recommended Host Board Power Supply Circuit



Recommended High-speed Interface Circuit

MECHANICAL DIMENSIONS (UNIT: mm)

