HP DesignJet T630 36-in Printer 2025 edition



The world's smallest plotters¹-intuitive and responsibly designed.



*Product image may differ from actual product

INTUITIVE-Easy, effortless printing

- Simplify printing with the new HP Click Print solutions—save time with real-print preview.²
- Print multi-size A4/A to A0/E projects automatically, without manually switching the media source.
- Print your jobs and manage your plotter virtually anywhere, anytime with the HP app.

RESPONSIBLY DESIGNED-Reduce energy and plastic use

- Save 65% energy⁴ with the printer on/off auto scheduler and enjoy efficient ink maintenance routines⁵.
- Minimize plastic waste by more than 50% with a new molded fiber packaging and removal of most plastic bags.
- Made with at least 40% recycled plastic⁷ and the first HP large format printer containing recycled metal.⁸
- Certified by UL ECOLOGO®.9 Registered in EPEAT Gold and achieves EPEAT Climate+¹⁰.

OPTIMIZED-Fits the way you work

- Save space with the world's smallest plotters¹ designed to fit your office, including a built-in stand.
- Avoid waiting by the printer with printing as fast as 30 seconds per A1/D plot.¹¹
- Protect your printer from cyberthreats with HP Wolf Essential Security.
- Get high-quality results—HP Bright Office Inks deliver better line accuracy¹² and up to 34% more gamut.¹³

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

Messaging Footnotes

¹Based on competitive comparison of operational footprint. Test performed by Sogeti and commissioned by HP in May 2024. ²HP One-click printing with HP Click software. HP Click software is only compatible with Original HP ink supplies. Applicable to PDF, JPEG, TIFF, DWF, and HP-GL/2 files. ³Requires HP Smart app download available at https://www.hp.com/go/mobileprinting. Certain features are available in English language only, and may vary by printer model/country, and between desktop/mobile

applications. HP reserves the right to introduce charges for use of functionality facilitated by the HP app. Internet access required and may not be available in all countries. HP account required for full functionality. List of supported operating systems available in app stores. ⁴The percentage reductions in energy consumption are based on tests conducted by HP, 2024. Data based on the implementation of auto-scheduled on/off usage in various printer models, measured on a monthly basis. ⁵Use up to 96% less ink for routine maintenance vs. competitor. Based on HP internal testing, June 2024, comparing the HP DesignJet T200 Printer series and Canon iPF TM printer series in terms of ink used during

⁶The HP Design. Jet T200/T600 Series 2025 Edition plotter uses polystyrene-free packaging with molded pulp cushions made from recycled fiber-based material. The plastic reduction is expressed as a percentage of the

total packaging plastic weight. The reduction varies depending on the printer model, with at least a 53% reduction in the new 36-inch model and at least a 72% reduction in the new 24-inch model, compared to the previous T200/T600 models.

Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled content is based on the definition set in the EPEAT standard for imaging equipment, IEEE 1680.2. ⁸Incorporation of a minimum of 5% of certified recycled metal, expected to be implemented in units manufactured after April 1st, 2025. Recycled metal is expressed as a percentage of the total weight of the metal

¹⁰ Design Jet 160 14021 definitions for metal. This number is the minimum and may vary slightly due to manufacturing processes and material availability. ⁹UL ECOLOGO® Certified HP 712 inks meet a range of stringent human health and environmental considerations. For certifications, see http://www.ul.com/gg ¹⁰ The T200/T600 is EPEAT Gold in the U.S. and Canada and has achieved EPEAT Climate+. See https://www.epeat.net for registration status and tier levels by country. ¹¹ The HP Design Jet T630 2025 Edition 36-in delivers A1/D prints in 30 seconds.

¹² Better line accuracy based on test commissioned by HP and performed by Sogeti in June, 2024. Clear lines based on the number of line breaks found in 2 mm of line. On vertical and diagonal 1px RGB (160,160,160) lines. Printed on Oce 75 g plain paper using equivalent fast print modes. For output produced with HP DesignJet T200 Printer series, Canon iPF TM printer series and Canon iPF TC-20. Test performed under the same conditions

in all printers measuring with QEA PIAS II digital microscope tool. ¹³ Up to 34% more color gamut based on test commissioned by HP and performed by Sogeti in June 2024, of gamut volume comparing prints from the HP DesignJet T200 Printer series, Canon iPF TM printer series, Canon iPF TC-20 and Epson SC-T3100 on Oce 75gsm plain paper using equivalent fast/draft print modes.

For more information, please visit http://www.hp.com/go/designjett630











Technical specifications

| Print | | | Android Default Print Service, Printing support for ChromeOS, Email printing |
|--|---|---|---|
| Print speed | 30 sec/page on A1, 76 A1 prints per hour ¹ | Remote print enabled | Yes |
| Print resolution | Up to 2400 x 1200 optimised dpi | One-click multi-size printing | Yes |
| Technology | HP Thermal Inkjet | | |
| Margins (roll) | 5 x 5 x 5 mm | Drivers | Raster driver for macOS and Windows, HP-GL/2 driver for Windows, HP Click Driver for Windows 11 |
| Margins (sheet) | 5 x 5 x 5 x 17 mm (manual feed); 5 x 5 x 5 x 5 mm (input tray) | Firmware Code Signature Validation; Automo HTTPS Redirect enabled by default; SNMPv1, default; SNMPv3 disabled by default; Write p HP Cartridge Security; Unique password; Dis | HP Wolf Essential Security: Secure boot with HW root of trust; |
| Ink types | Dye-based (C, M, Y); pigment-based (K) | | Firmware Code Signature Validation; Automatic FW Updates; HTTPS Redirect enabled by default; SNMPv1/2 read-only by |
| Print Cartridges/Bottle, Number | 4 (C, M, Y, K) cartridges | | default; SNMPv3 disabled by default; Write-protected memory; HP Cartridge Security; Unique password; Disable USB ports; TL 1.2; 802.1x; IPv4 & IPv6 Compatibility; CA/JD Compatibility |
| Print cartridge/bottle volume delivered | e 80 ml (K); 38 ml (K); 29 ml (C, M, Y) per cartridge | Dimensions (W x D x H) | |
| Page Yield | 20 ml of ink yields 101 A1 pages, taking into account maintenance routines ² | Product | 1317 x 605 x 932 mm |
| | | Shipping | 1470 x 575 x 590 mm |
| Ink drop | 5.5 pl (C, M, Y); 12 pl (K) | Weight | |
| Printheads | 1 (cyan, magenta, yellow, black) | Product | 34.7 kg |
| Printhead nozzles | 1376 | Shipping | 56 kg |
| Line accuracy | ±0.1% ³ | Included | |
| Minimum line width | 0.02 mm | What's in the box | HP DesignJet T630 36-in Printer, printer stand, automatic sheet feeder, printhead, introductory ink cartridaes, spindle, auick |
| Max optical density | 8 L* min/2.10 D ⁴ | | reference guide, setup poster, power cord |
| Media | · · · · · · · · · · · · · · · · · · · | HP Software and solutions | HP Click App for Windows and macOS, HP Click Driver for Windows 11, HP app for Windows, macOS, Android and iOS |
| Applications | Line drawings; Presentations; Renderings | Environmental ranges | |
| Handling | Sheet feed, roll feed, automatic sheet feeder, media bin, automatic horizontal cutter | Operating temperature | 5 to 40°C |
| Rolls | Media rolls: 1; Roll size: 279 to 914 mm; Maximum roll weight: 6.2 kg; Maximum roll diameter: 100 mm; | Operating humidity | 20 to 80% RH |
| | | Operating altitude | Up to 3000 m |
| Maximum media width | 914 mm | Storage temperature | -25 to 55°C |
| Sheet size | Auto sheet feeder: 210 x 279 to 330 x 482 mm; manual feed: 210 x 279 to 914 x 1897 mm | Recycled plastic in printer Acoustics | 40% |
| Standard sheets | Auto sheet feeder: A4, A3; manual feed: A4, A3, A2, A1, A0 | Sound pressure | Printing: 42 dB(A) (operating), <16 dB(A) (idle) |
| Recommended Grammage | 60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (auto sheet | Sound power | Printing: 5.8 B(A) (operating), <0 dB(A) (idle) |
| | feeder) | Power | |
| Thickness | Up to 0.3 mm | Consumption | <35 W (printing), <5.6 W (ready), <2.1 W (sleep), <0.2 W (off) |
| Media types | Bond and coated paper (bond, coated, heavyweight coated, plain, bright white, blueprint), technical paper (natural tracing), film (clear, matte), photographic paper (satin, gloss, semigloss, polypropylene), self-adhesive (adhesive, polypropylene) | Requirements | Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1200 mA max |
| | | Certification | |
| Embedded controller | | Safety | USA and Canada (CSA certified); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA); Singapore (PSB); China (CCC); Argentina (IRAM); India (BIS); Mexico (NYCE) |
| Memory | 1GB | | |
| Hard disk | None | | |
| Native print languages | HP-GL/2, HP-RTL, CALS G4, JPEG, URF | Electromagnetic | Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC/RED Directives), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class B product: Korea (KCC) ENERGY STAR; WEEE; EU RoHS; EAEU RoHS; REACH; ErP; EPEAT |
| Connectivity | | | |
| Interfaces | Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0, Wi-Fi 802.11a/b/g/n, Wi-Fi Direct | Environmental | |
| Printing paths | HP Click App, HP Click Driver, HP app, Windows and MacOS printer drivers, HP-GL/2 driver for Windows, Apple AirPrint, | | Climate+Gold; UL Ecologo |
| | | Warranty | One-year limited hardware warranty |

Ordering information

| Product | | Original HP large format printing materials |
|--|---|--|
| 5HB11D Accessories | HP DesignJet T630 36-in Printer 2025 edition | Q1396A HP Universal Bond Paper (FSC* certified) ⁵ (recyclable) ⁶ 610 mm x 45.7 m C6019B HP Coated Paper (FSC* certified) ⁵ (recyclable) ⁶ 610 mm x 45.7 m |
| B3O37A HP DesignJet 36-in Spindle Original HP printing supplies | | C6029C HP Heavyweight Coated Paper (FSC[®] certified)⁵ (recyclable)⁶ 610 mm x 30.5 m Ear the entire HD Large Format Drinting Materials portfolio plages app. |
| 3ED58A 3ED67A 3ED68A 3ED69A 3ED70A 3ED70A 3ED71A 3ED77A 3ED79A Use Original | HP 713 DesignJet Printhead Replacement Kit HP 712 29-ml Cyan DesignJet Ink Cartridge HP 712 29-ml Magenta DesignJet Ink Cartridge HP 712 29-ml Yellow DesignJet Ink Cartridge HP 712 38-ml Black DesignJet Ink Cartridge HP 712 30-ml Black DesignJet Ink Cartridge HP 712 3-pack 29-ml Cyan DesignJet Ink Cartridge HP 712 3-pack 29-ml Magenta DesignJet Ink Cartridge HP 712 3-pack 29-ml Yellow DesignJet Ink Cartridge HP 712 3-pack 29-ml Yellow DesignJet Ink Cartridge HP 712 3-pack 29-ml Yellow DesignJet Ink Cartridge | For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com. Service and Support U18JSE HP 2y Next Business Day support for DesignJet T630-36 U18JTE HP 3y Next Business Day support for DesignJet T630-36 U18JVE HP 4y Next Business Day support for DesignJet T630-36 U18JWE HP 5y Next Business Day support for DesignJet T630-36 HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more information, please visit http://www.hp.com/go/cpc |
| experience contraction downtime. The | ese critical components are designed and engineered together as an ese critical components are designed and engineered together as an | |

optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit https://hp.com/go/OriginalHPinks

Specification Footnotes ¹Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (bond) and Original HP inks. Actual performance may vary based on a variety of conditions, including but not limited to network configuration. ²Calculation done taking into account two nermal prior based of the state of th

² Calculation done taking into account two normal printhead cleanings and ink on an A1 CAD drawing with black and colour lines and a pixel coverage of 5.2%. ³ ±01% of the specified vector length or ±0.2 mm (whichever greater) at 23°C, 50-60% relative humidity, on A0 printing material in Best or Normal mode with HP Heavyweight Coated roll feed and Original HP inks. ⁴ With HP Premium Instant Dry Photo Gloss media with Original HP inks. ⁵ BMG trademark license code FSC*-C115319, see http://www.fsc.org. HP trademark license code FSC*-C017543, see http://www.fsc.org.

⁶ Can be recycled through commonly available recycling programs.

© Copyright 2025 HP Development Company, LP. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

February 2025 ie-en

