



5m USB 3.0 Active Extension Slim

5m USB 3.0 Extension of a USB Type A port of your computer

Description

5 metre USB 3.0 Active Extension Repeater Lead Supports transfer rates up to 5Gbps For even greater distances simply connect up to 5 cables in series USB Power Adapter cable included 2 year warranty

The Lindy USB 3.0 Active Extension Cable uses built-in active electronics to extend the cable length of a USB 3.0 device by an additional 5m whilst continuing to support data transfer rates of up to 5Gbps. With its USB A male and USB A female connector it allows Type A devices such as storage devices, webcams and other Type A devices to be connected at longer distances to PCs, laptops and tablets, while also ensuring flexible positioning.

Up to 5 USB 3.0 Active Extensions Slim can be chained together. In addition, a maximum of 5 of the different cable lengths of these USB 3.0 Active Extensions Slim can be combined with each other. The only exception is the 15m version No. 43404: as it has 2 chipsets, a maximum of 3 other USB 3.0 Active Extensions Slim can be combined with it.

The Lindy USB 3.0 active extension Slim is supplied with power via the USB bus, but also has a DC socket for connecting a power supply unit for devices with high power requirements or if you want to connect several cables in series.

The Lindy USB 3.0 Active Extension Cable is compatible with all USB Type A equipped computers. With plug and play functionality, this extension cable can be installed quickly and with minimum fuss, ideal for both professional and first time users. The cable's unique and slim design allows installation in narrow surroundings - an advantage over other active USB leads which use bulky connectors.

Information about USB 3.0, 3.1 & 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface. USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps. USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Technical details

Connectors

Connector A: USB Type A Male Connector B: USB Type A Female Power: 2.5/0.7mm DC Connector Housing Material: PVC

Connector Plating: Nickel plated **Pin Construction: Copper** Pin Plating: Gold Dimensions (approx.) WxDxH: USB A Male: 41.1x16.5x9.5mm (1.61x0.64x0.37in) USB A Female: 67.5x22x13.5mm (2.65x0.86x0.53in) **Cable Construction** Length: 5m (16.4ft) Standard: USB 3.2 / 3.1 Gen 1 / 3.0 Colour: Black Type: Round Jacket Diameter: 6.5mm (0.26in) Jacket Material: PVC Conductor Material: Tinned Copper Conductor Gauge: 26AWG+26AWG+21AWG Shielding: 75% Tinned Copper Specifications Supported Bandwidth: 5 Gbps Nominal Attenuation: <23.0Db@2.5GHz (USB 3.0), <5.8Db@200MHz (USB 2.0) Minimum Bend Radius: 80mm (3.14in) Operating Temperature: 0°C to 40°C (32°F - 104°F) Storage Temperature: -10°C to 60°C (14°F - 140°F) Transmission Medium: Twisted Pair Transmission Technology: USB 3.2 / 3.1 Gen 1 / 3.0 **Miscellaneous** Packaging Type: Polybag Packaging Dimensions: 236x255mm (9.29x10.04in) Net Weight: 0.42kg (0.93lb) Gross Weight: 0.46kg (1.01lb) Warranty (Years): 2 Product Compliance: CE, FCC, RoHS & REACH, CP65 **Packaging Content** 5m USB 3.0 Active Extension Slim 1.5m USB 2.0 Type A to 2.5mm DC Cable **Purchasing Information** No.: 43401 EAN: 4002888434010 This product is also available in other lengths 43400 - 3m (9.84ft) 43401 - 5m (16.4ft) 43402 - 8m (26.25ft) 43403 - 10m (32.81ft) 43404 - 15m (49.21ft)

```
© LINDY 2024
```