

REPAIRABILITY INDEX CALCULATION AND PRESENTATION OF THE PARAMETERS WHICH ALLOWED TO ESTABLISH IT	<i>Laptop</i>
---	---------------

Date of calculation	2025/3/16
Producer's or importer's name or trademark	ASUS
Producer or importer adress	115, Li-Te Rd., Peitou, Taipei 112, Taiwan
Producer's or importer's model identifier	CR1104FTA

This "FINAL_SCORE" tab in English is purely indicative. In order to meet regulatory obligations, only the "NOTE_FINALE" tab in French (see the next tab) is to be sent. Note: The results are automatically reported in the French tab.

(see the next tab) is to be sent. Note: The results are automatically reported in the 1 form tab.

Criteria	Sub-criteria	Score of subcriterion /10	Weighting factor of subcriterion	Score of criterion /20	Total criteria scores /100
CRITERION 1 : DOCUMENTATION	1.1 Availability of the technical documentation and other documentation related to user and maintenance instructions	10.0	2	20.0	87.3
CRITERION 2 : DISASSEMBLY, ACCESSIBILITY, TOOLS, FASTENERS	2.1 Ease of disassembly parts from List 2*	9.3	1	18.8	
	2.2 Necessary tools (List 2)	10.0	0.5		
	2.3 Fasteners characteristics parts from List 1** and List 2	9.0	0.5		
CRITERION 3 : AVAILABILITY OF SPARE PARTS	3.1 Availability over time parts from List 2	8.3	1	17.4	
	3.2 Availability over time parts from List 1	8.3	0.5		
	3.3 Delivery time parts from List 2	10.0	0.3		
	3.4 Delivery time parts from List 1	10.0	0.2		
CRITERION 4 : PRICE OF SPARE PARTS	4. Ratio between price of parts from list 2 to the price of the product	5.5	2	11.0	
CRITERION 5 : SPECIFIC CRITERION	5.1 Information about type of updates	10.0	1	20.0	
	5.2 Free remote assistance	10.0	0.5		
	5.3 Possibility to reset softwares	10.0	0.5		
Reparability index on 10					8.7

* list 2: list of a maximum of 3 to 5 spare parts (depending on the category of equipment concerned) whose broken or malfunctioning parts are the most frequent;

** list 1: list of a maximum of 10 other spare parts (depending on the category of equipment concerned) whose good condition is necessary for the operation of the equipment.