# RF 16-28mm F2.8 IS STM EPIC VIEWS. STABLE SHOTS



The RF 16-28mm F2.8 IS STM is a small, light, ultra-wide-angle 16-28mm zoom with a fast f/2.8 aperture and 5.5-stop<sup>1</sup> image stabilisation that's ideal for travel and landscapes. For both stills and video, it performs brilliantly.



f/2.8 aperture

**Image Stabilisation** 

Aspheric and UD elements

Leadscrew STM motor

Customisable focus / control ring









## Fast, bright, and responsive

See more detail in low light thanks to a wide aperture that inspires a more creative approach to your subject. Shoot at f/2.8 to add depth and extra dimension to your images.



## Ultra wide-angle views

Capture wide-angle views effortlessly thanks to a 16-28mm ultra-wide-angle zoom range that lets you get more into a scene. The Canon RF 16-28mm F2.8 IS STM lens offers a sweet spot in performance and practicality with an angle of view that inspires creativity.



## A lens built for travelling light

When luggage space is limited, the RF 16-28mm F2.8 IS STM makes a clever choice for travel. Retract the zoom to 91mm for great portability thanks to the lens' innovative design. And at 445g (approx.) you can leave it on the camera all day.



## High quality results that set you apart

Enjoy superb image quality thanks to two aspheric elements and four UD lenses with Super Spectra coatings for incredible clarity. A fast Leadscrew (STM) motor delivers rapid, smooth, and near-silent focusing for both stills and video.



## Creative features with a practical edge

Capture striking star-like highlights with a nine-blade aperture and, with 5.5-stops<sup>1</sup> of optical image stabilisation, shoot and film handheld to be more innovative on the move, even in low-light.





RF 15-30mm F4.5-6.3 IS STM



RF 16-28mm F2.8 IS STM



RF 14-35mm F4L IS USM



RF 15-35mm F2.8L IS USM



### **TECHNICAL SPECIFICATIONS**

| OPTICAL<br>FEATURES/SPECIFICATIONS                                |                                    |  |  |  |  |
|---|------------------------------------|--|--|--|--|
| Image size  | Full Frame                         |  |  |  |  |
| Angle of view   | 98°-65°                            |  |  |  |  |
| (horizontal, vertical, diagonal)                                  | 74°10'-46°                         |  |  |  |  |
| Lens construction   | 108°10'-75°                        |  |  |  |  |
| (elements/groups)   | 16/13                              |  |  |  |  |
| Special optics  | 4x UD                              |  |  |  |  |
|   | 1x Gmo Aspheric                    |  |  |  |  |
| No. of diaphragm blades   | 1x Replica Aspheric<br>9           |  |  |  |  |
| Minimum aperture  | 22                                 |  |  |  |  |
| Closest focussing distance (m)                                    | 0.25 (at 16mm)                     |  |  |  |  |
| of oscal rocussing distance (in)                                  | 0.2 (at 28mm)                      |  |  |  |  |
| Maximum magnification (x)   | 0.11 (at 16mm)                     |  |  |  |  |
| Control Ring  | 0.26 (at 28mm)<br>combined / focus |  |  |  |  |
| Image stabilizer OIS <sup>1</sup>                                 | 5.5                                |  |  |  |  |
| Image stabilizer IBIS x OIS                                       | 8                                  |  |  |  |  |
| AF actuator   | -                                  |  |  |  |  |
|   | STM                                |  |  |  |  |
| Coatings  | Super Spectra                      |  |  |  |  |
| Fluorine  | No                                 |  |  |  |  |
|   |                                    |  |  |  |  |
| PHYSICAL SPECIFIC ATIONS<br>Dust/moisture resistance <sup>3</sup> | Yes                                |  |  |  |  |
| Filter diameter (mm)  | 67                                 |  |  |  |  |
| Max. diameter x length (mm) <sup>2</sup>                          | 76.5 x 91                          |  |  |  |  |
| Weight (g)  | 445                                |  |  |  |  |
| weight (g)  | 440                                |  |  |  |  |
|   |                                    |  |  |  |  |
| AC CESSOR IES   | E 07 II                            |  |  |  |  |
| Lens cap  | E-67 II                            |  |  |  |  |
| Lens hood   | EW-73E                             |  |  |  |  |
| Lens case/pouch   | LP1116                             |  |  |  |  |
| Rear cap  | Lens Dust Cap RF                   |  |  |  |  |
| Extender Compatiblity   | Not compatible                     |  |  |  |  |
|   |                                    |  |  |  |  |

### **RF 16-28mm F2.8 IS STM**

- Footnotes: <sup>[1]</sup> Tested under CIPA-2024 standard (in the yaw/pitch/roll directions in the centre of the image, at maximum focal length, with a specific camera) <sup>[2]</sup> Lens dimensions when in retracted state

Is a substant of the state of t

Canon Inc. canon.com Canon Europe canon-europe.com English edition Canon Europa NV 2025



### EPIC VIEWS. STABLE SHOTS

## RF 16-28mm F2.8 IS STM

The RF 16-28mm F2.8 IS STM is a small, light, ultra-wide-angle 16-28mm zoom with a fast f/2.8 aperture and 5.5-stop<sup>1</sup> image stabilisation that's ideal for travel and landscapes. For both stills and video, it performs brilliantly.

#### Sales Start Date: 14th February 2025



#### **Product details**

| Product Name Mercury Code |            | EAN Code      | Recommended Retail Price               |  |  |
|---------------------------|------------|---------------|--|--|--|
| RF 16-28mm F2.8 IS STM    | 6906C005AA | 4549292241716 | <please fill="" in="" rrp=""></please> |  |  |

#### **Optional accessories**

| Accessory Name   | Mercury Code | EAN Code      | Recommended Retail Price               |
|------------------|--------------|---------------|--|
| LENS CAP E-67 II | 6316B001AA   | 4960999845869 | <please fill="" in="" rrp=""></please> |
| LENS DUST CAP RF | 2962C001AA   | 4549292115604 | <please fill="" in="" rrp=""></please> |
| LENS CASE LP1116 | 2780A001CA   | 4960999470757 | <please fill="" in="" rrp=""></please> |
| LENS HOOD EW-73E | 5814C001AA   | 4549292207422 | <please fill="" in="" rrp=""></please> |



### EPIC VIEWS. STABLE SHOTS

## RF 16-28mm F2.8 IS STM

The RF 16-28mm F2.8 IS STM is a small, light, ultra-wide-angle 16-28mm zoom with a fast f/2.8 aperture and 5.5-stop<sup>1</sup> image stabilisation that's ideal for travel and landscapes. For both stills and video, it performs brilliantly.



#### Measurement / logistic information

| ProductName            | Mercury Code | Pack<br>type | Pack description      | Quantity<br>perpack | Length<br>(cm) | Width<br>(cm) | Height<br>(cm) | Net<br>Weight<br>(kg) | Gross<br>Weight<br>(kg) |
|------------------------|--------------|--------------|-----------------------|---------------------|----------------|---------------|----------------|-----------------------|-------------------------|
| RF 16-28mm F2.8 IS STM | 6906C005AA   | EA           | Each                  | 1                   | 13.7           | 13.7          | 20.3           | 0.519                 | 0.70                    |
|                        |              | СТ           | Carton                | 6                   | 42.75          | 29.1          | 28.9           | -                     | 5.01                    |
|                        |              | EP           | Euro Pallet           | 96                  | 120            | 80            | 128.6          | -                     | 79.16                   |
|                        |              |              | Layers per Pallet     | 4                   |                |               |                |                       |                         |
|                        |              |              | Cartons per Layer     | 4                   |                |               |                |                       |                         |
|                        |              |              | Products per<br>Layer | 24                  |                |               |                |                       |                         |



### EPIC VIEWS. STABLE SHOTS

## RF 16-28mm F2.8 IS STM

The RF 16-28mm F2.8 IS STM is a small, light, ultra-wide-angle 16-28mm zoom with a fast f/2.8 aperture and 5.5-stop<sup>1</sup> image stabilisation that's ideal for travel and landscapes. For both stills and video, it performs brilliantly.



#### What's in the box

RF 16-28mm F2.8 IS STM

- RF 16-28mm F2.8 IS STM Lens
- Lens Cap E-67 II
- Lens Dust Cap RF
- User Manual



