Redefine the everyday

Expand your view in comfort with a spacious, thoughtfully designed 21.5 inches of workspace. Boasting a crisp, smooth screen and a simple yet functional design, this HP Series 3 Pro 21.5" FHD monitor lets you work better all day.



*Product image may differ from actual product

	_	_			
1	0	0	F	ł	Z

Elevate your visual experience

Make your day more productive and enjoyable with an expanded workspace for projects and assignments. This sleek 21.5-inch FHD monitor boasts a quality IPS screen that's visible from any angle and up to 100 Hz refresh rate¹ for sharp images and fluid motion.

Sustainability in action

Built for a better tomorrow

This thoughtfully designed monitor contains at least 85% recycled plastic content in the enclosure, 5% recycled metal, and 20% recycled glass in the panel². Plus, it meets high energy-saving standards with ENERGY STAR® certification and EPEAT® registration.³



HP Eye Ease

Focus in comfort

Stay in the zone without sacrificing eye comfort with a flicker-free screen and HP Eye Ease, an always-on hardware low-blue light filter that doesn't impact color accuracy. Plus, find your perfect angle with a 100 mm height- and tiltadjustable stand.



Clean design

Keep the focus on your screen with a sleek, simple design. Make borders disappear with a 3-sided micro-edge bezel ideal for clean dual-monitor setups and 2 x 2W downfiring speakers built right in. Easily customize settings with the joypad OSD button.







Featuring

IPS Technology

No matter where you stand, IPS technology ensures image accuracy and consistency across wide 178-degrees horizontal and vertical viewing angles.

HP Eye Ease

HP Eye Ease, an always-on, hardware low-blue light filter, helps keep your eyes comfortable throughout the day by reducing blue light without the yellow color shift.

100 Hz Refresh Rate

Experience smooth scrolling, life-like video and clear detail with a 100 Hz refresh rate that provides fluid movement from frame to frame. $^{1}\,$

Height and Tilt Adjust

The 100 mm height- and tilt-adjustable slim stand helps you find the right angle so you can maximize productivity and work comfortably.

Plenty of Ports

This monitor is ready to connect for sharp FHD visuals with multiple ports including 1 x VGA, 1 x HDMI 1.4, and 1 x DisplayPort^M 1.2.^{4,5}

3-Sided Micro-Edge Bezel

See and do more on your screen with a 3-sided micro-edge bezel that maximizes your viewing area for a sleek design and virtually seamless dual-monitor setups.

Built-in 2W Dual Speakers

Listen to music, meetings and more with the built-in, dual 2W downfiring speakers.

Intuitive Joypad OSD Button

Easily configure your monitor settings with the touch of a button. Simply navigate the on-screen menu with the joypad OSD button to adjust brightness and resolution.

Neat Cable Management

Be more productive with a cleaner workspace by removing the clutter of mixed cables with a neat cable management solution.

Easily Personalize and Adjust Your Monitor

Customize your monitor with easy to use, intuitive HP Display Center software that lets you tailor your settings, partition screens, and even dim the screen–all through the host PC.⁶

Remote Management Reimagined

HP Client Management Script Library (CMSL) makes remote manageability easy to use. This powerful solution works seamlessly with Intune/SCCM to manage your display fleet using PowerShell.⁷

Energy Efficient Design

These monitors meet the latest energy efficiency and environmental standards for tech and IT with EPEAT® registration and ENERGY STAR® and TCO certifications.³

Materials that Matter

This thoughtfully designed monitor contains at least 85% recycled plastic content in the enclosure, 5% recycled metal, and 20% recycled glass in the monitor panel. It's all part of our commitment to help protect our shared future.²

Thoughtful Product Packaging

100% of HP paper-based packaging is from recycled or certified sustainable sources.⁸

HP PC Mounting Bracket

Save space and optimize your desk by attaching the B200 or B550 bracket to the monitor stand and your PC.⁹

Works With Chromebook Certified

The Works With Chromebook badge on a device means it's optimized to work with your Chromebook and other Chrome OS devices. Enjoy a seamless experience across Works With Chromebook certified accessories.^{10,11}



Specifications

Lipstyl spucification Second Display size 54.6 cm (2157) ¹ Viewabie diagonal size 215 (54.61 cm) Aspect ratio Field Variable diagonal size Field (1620.1 1060) ¹² Resolution (maximum) FHD (1620.1 1060) ¹² Panel ottype (177.1 10	Display specification	e		
Viewsdie diagonal size 21.5° (54.61 cm) Aspect ratio 16.91 Curvature Flat Native resolution FHD (1920 x 1080 @ 100 Hz) ¹ 640 x 480 @ 60 Hz, 120 x 000 @ 60 Hz, 1000 x 600 @ 60 Hz, 1020 x 768 @ 60 Hz, 1220 x 120 @ 60 Hz, 1220 x 1000 @ 60 Hz, 1220 x 1080 @ 100 Hz, 1220 x 1080 @ 100 Hz, 1220 x 1080 @ 10 Hz, 1020 x 1080 @ 176 Hz, (digital inputs only), 1220 x 1080 @ 176				
Aspect rolls 16:9 ¹ Curvature Flat Netwo resolution FHD (1920 x 1080 @ 100 Hz) ¹ Resolution (maximum) FHD (1920 x 1080 @ 100 Hz) ¹ 640 x 480 @ 60 Hz, 1220 x 400 @ 60 Hz, 1200 x 600 @ 60 Hz, 1200 x 1050 @ 60 Hz, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 60 Hz, 1280 x 1080 @ 60 Hz, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 60 Hz, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 60 Hz, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 60 Hz, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 60 Hz, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 60 Hz, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1980 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs only, 1280 x 1080 @ 100 Hz, (digital inputs onl				
Curveture Flot Native resolution FHD (1920 x 1080) ^{1/2} Resolution (maximum) FHD (1920 x 1080 @ 100 Hz) ¹ Resolutions supported 640 x 480 @ 60 Hz, 720 x 400 @ 70 Hz, 800 x 600 @ 60 Hz; 1024 x 768 @ 60 Hz; 1220 x 120 g 60 Hz; 1220 x 1080 @ 100 Hz; 1220 x 1080 @ 57 Hz (digital inputs only); 1024 x 768 @ 75 Hz (digital inputs only); 1024 x 768 @ 75 Hz (digital inputs only); 120 x 1080 @ 100 Hz; 1220 x 1080 @ 1080 @ 100 Hz; 1220 x 1080 @ 1080				
Nettve resolution FHD (1920 x 1080) ¹² Resolution (maximum) FHD (1920 x 1080 @ 100 Hz) ¹ 640 x 480 @ 60 Hz; 720 x 400 @ 70 Hz; 800 x 600 @ 60 Hz; 1280 x 1720 @ 60 Hz; 1280 x 1024 @ 60 Hz; 7180 x 1024 @ 60 Hz; 7180 x 1020 @ 60 Hz; 1280 x 1020 @ 60 Hz; 6180 x 1050 @ 60 Hz; 1280 x 1020 @ 60 Hz; 6180 x 1050 @ 60 Hz; 1280 x 1020 @ 60 Hz; 6180 x 1050 @ 60 Hz; 1280 x 1020 @ 60 Hz; 6180 x 1020 @ 60 Hz; 6180 x 1020 @ 60 Hz; 1280 x 800 @ 60 Hz Resolutions supported 480 @ 50 Hz; 720 x 400 @ 60 Hz; 1280 x 1020 @ 75 Hz (digital inputs only); 1290 x 1080 @ 100 Hz; (digital inputs only); 1280 x 1080 @ 100 Hz; (digital inputs only); 1280 x 1080 @ 100 Hz; Panel type IPS: LCD ¹ Bazal 3 dided borderless Panel type IPS: LCD ¹ Bazal 3 dided borderless Panel type IPS: LCD ¹ Bazal 3 dided borderless Panel type IPS: LCD ¹ Bazal 3 dided borderless Panel tit depth 8 bit (6 bit + FRO] ¹ Display colors gamut 72% NTSC Referes note (maximum) 100 Hz ¹ Display color gamut 72% NTSC Referes note (maximum) 00 Hz ¹ Display color gamut 72% NTSC Refrightmass 250 fits ¹ </th <td></td> <td></td>				
Resolution (maximum) FHD (1920: 1080 @: 100 Hz) ¹ 640 x 480 @: 60 Hz; 720 x 400 @; 60 Hz; 120 x 768 @; 60 Hz; 120 x 720 @; 60 Hz; 1280 x 1080 @; 100 Hz; 1280 x 1080 @; 60 Hz; 1280 x 1080 @; 60 Hz; 1280 x 1080 @; 60 Hz; 1280 x 1080 @; 100 Hz; 1280 x 1080 @; 75 Hz (digital inputs only); 1280 x 1080				
640 x 490 @ 60 Hz; 720 x 400 @ 70 Hz; 800 x 600 @ 60 Hz; 1200 x 720 @ 80 Hz; 1280 x				
Bezel 3-sided borderless Panel Dit deptit 8 bit (6 bit + FRQ) ¹ Display colors Up to 16.7 million colors supported ^{1,3} Display colors Up to 16.7 million colors supported ^{1,3} Display colors Up to 16.7 million colors supported ^{1,3} Display colors Up to 16.7 million colors supported ^{1,3} Display scan frequency 48.100 Hz (Vertical) ¹ ; 30-115 kHz (Horizontal) ¹ Response time 5ms GtG (with overdrive) ¹ Brightness 250 nits ¹ Contrast ratio 1000.1 (Static) ¹ 8000000.1 (Dynamic) ¹ Pixel per inch (ppl) 0.248 x 0.248 mm ¹ Pixels per inch (ppl) 0.249 pi Viewing angle 178 ^o (Vertical) 178 ^o (Horizontal) Backlight tamp life 30,000 hours Display User Brightness+: Color: Image: Input; Power; Menu; Management; Information; Exit Control Options Moightnesse +: Color: Image: Input; Power; Menu; Management; Information; Exit Control Options No firmware No Low blue Light modes Yes, TÜV certified) Screen treatment Anti-glore Harchness 3H ¹ Haze 25%	Resolutions supported	640 x 480 @ 60 Hz; 720 x 400 @ 70 Hz; 800 x 600 @ 60 Hz; 1024 x 768 @ 60 Hz; 1280 x 720 @ 60 Hz; 1280 x 1024 @ 60 Hz; 1440 x 900 @ 60 Hz; 1600 x 900 @ 60 Hz; 1680 x 1050 @ 60 Hz; 1920 x 1080 @ 60 Hz; 640 x 480 @ 75 Hz (digital inputs only); 800 x 600 @ 75 Hz (digital inputs only); 1024 x 768 @ 75 Hz (digital inputs only); 1280 x 1024 @ 75 Hz (digital inputs only); 1920 x 1080 @ 75 Hz (digital inputs only); 1920 x 1080 @ 100 Hz (digital inputs only); 1280 x 800 @ 60 Hz		
Panel active area 47.61 x 26.78 cm Panel bit depth 8 bit (6 bit + FRQ) ¹ Display color gamut 72% NTSC Refreeh rate (maximum) 100 Hz ¹ Display color gamut 72% NTSC Refreeh rate (maximum) 100 Hz ¹ Display scon frequency 48100 Hz (Vorticol); 30-115 KHz (Horizontal) ¹ Response time 5ms GtG (with overdrive) ¹ Brightness 250 ntts ¹ Contrast ratio 10001 (Static) ¹ 8000001 (Dynamic) ¹ Pixel pitch 0.248 x 0.248 mm ¹ Vewing angle 178' (Vertical) 178' (Horizontal) Backlight type Edge-lit; WLED Backlight type Edge-lit; WLED Backlight type Brightness+; Color: Image; Input; Power; Menu; Management; Information; Exit Management software HP Display Center; HP Client Management Script Library ^{11/2} User updateable No ftmware No Vov bull light modes Yes. HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Screen treatment Anti-glore Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm		·		
Panel bit depth 8 bit (6 bit + FRC) ¹ Display colors Up to 16.7 million colors supported ^{1.3} Display color gomut 72% NTSC Refresh rate (maximum) 100 Hz ¹ Display scon frequency 48100 Hz (Vertical); 30:115 kHz (Horizontal) ¹ Response time 5ms GtG (with overdrive) ¹ Brightness 250 nits ¹ Contrast ratio 1000.1 [Static] 80000001 (Dynamic) ¹ Pixel pitch 0.248 x 0.248 mn ¹ Pixels per inch (ppi) 102 ppi Viewing angle 178" (Vertical) 178" (Horizontal) Backlight top Edge-IIt; WLED Backlight top Edge-IIt; WLED Backlight top Edge-IIt; WLED Backlight top Brightness+; Color; Image; Input; Power; Menu; Management, Information; Exit Management software No Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Uw light modes Yes, HV Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Uw light modes Yes, HV Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Vers Mout 100 x 100 mm Addigree Hardness Streen treatment <t< th=""><td></td><td></td></t<>				
Display colors Up to 16.7 million colors supported ^{1,3} Display color gamut 72% NTSC Refresh rate (mxximum) 100 Hz1 Display scan frequency 48-100 Hz (Vertical) ¹ ; 30-115 kHz (Horizontal) ¹ Response time 5ms GFG (with overdrive) ¹ Brightness 250 nits ¹ Contrast ratio 10001 (Statio) ¹ 80000001 (Dynamic) ¹ Display scan frequency 48-100 Hz (Vertical) ¹ 78" (Morizontal) ¹ Ontrast ratio 1002 nglaticlo ¹ 80000001 (Dynamic) ¹ Display log 78" (Vertical) 178" (Horizontal) Backlight type Edge-lit; WLED Backlight type Edge-lit; WLED Backlight type Edge-lit; WLED Backlight type Brightness+; Color; Image; Input: Power; Menu; Management; Information; Exit Ontrol Options Brightness+; Color; Image; Input: Power; Menu; Management; Information; Exit Management software HP Display Center; HP Client Management Script Library ^{11,2} User updateable No firmware No firmware Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Flicker-free Yes, ITÜV certified) Screent readment Anti-giare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm				
Display color gamut 72% NTSC Refresh rate (maximum) 100 Hz ¹ Display scan frequency 48-100 Hz (Vertical) ¹ ; 30-115 kHz (Horizontal) ¹ Response time 5ms GtG (with overdrive) ¹ Brightness 250 nits ¹ Contrast ratio 1000:1 (Static) ¹ 8000000:1 (Dynamic) ¹ Pixel jtch 0.248 x 0.248 mm ¹ Pixels per inch (ppi) 102 ppi Viewing angle 178° (Vertical) 178° (Horizontal) Backlight type Edge-lit: WLED Backlight type Bedge-lit: WLED Backlight type Brightness+; Color, Image; Input; Power; Menu; Management; Information; Exit Management software HP Display Center; HP Client Management Script Library ^{TL2} User updateable firmware No Monagement software No Screen treatment Anti-glare Hardness 3H ¹ Haze 25% VESA mount 100 x0 nm Adjustability Height adjustment range: 100 mm Tilt: - 5to +23° Speaker output power 2x 2W; Built-In speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) </th <td>-</td> <td></td>	-			
Refresh rate (maximum) 100 Hz ¹ Display scan frequency 48:100 Hz (Vertical) ¹ ; 30:115 kHz (Horizontal) ¹ Response time 5ms GtG (with overdrive) ¹ Brightness 250 ntts ¹ Contrast ratio 1000:1 (Static) ¹ 800000:1 (Dynamic) ¹ Pixel pitch 0.248 x 0.248 mm ¹ Pixels per inch (ppi) 102 ppi Viewing angle 178° (Vertical) 178° (Horizontal) Backlight type Edge-II: WLED Backlight tamp life 30.000 hours Display User Brightness+; Color; Image; Input; Power; Menu; Management; Information; Exit Control Options Brightness+; Color; Image; Input; Power; Menu; Management; Information; Exit Management software HP Display Center; HP Client Management Script Library ^{11/2} User updateable firmware No 100 wblue light modes Flicker-free Yes; HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Soreen treatment Anti-glare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Tilt:- 5 to + 23° Speaker output power Speaker output power 2 x 2 W; Built-in speakers </th <td>• •</td> <td>Up to 16.7 million colors supported^{1,3}</td>	• •	Up to 16.7 million colors supported ^{1,3}		
Display scan frequency 48:100 Hz (Vertical) ¹ :30:115 kHz (Horizontal) ¹ Response time 5ms GCG (with overdrive) ¹ Brightness 250 nits ¹ Contrast ratio 100:01 (Static) ¹ 80:000:01 (Dynamic) ¹ Pixel pitch 0.248 x 0.248 mm ¹ Pixel pitch 0.248 x 0.248 mm ¹ Display sort frequency Kertical) 178° (Horizontal) Backlight type Edge-fit: WLED Backlight type Edge-fit: WLED Backlight lamp life 30:000 hours Display User Brightness+: Color; Image; Input; Power; Menu; Management; Information; Exit Management software HP Display Center; HP Client Management Script Library ¹¹¹² User updateable No Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Screen treatment Ant: glare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Adjustability Height adjustment range: 100 mm Tilt -5 to +23° Speaker output power Special features Works with Chromebook Connectivity and communications 114DMI 14 Port and conn				
Response time 5ms GtG (with overdrive) ¹ Brightness 250 nits ¹ Contrast ratio 10001 (Static) ¹ 8000001 (Dynamic) ¹ Pixel jtch 0.248 x 0.248 mm ¹ Pixels per inch (ppl) 102 ppi Viewing angle 178° (Vertical) 178° (Horizontal) Backlight tamp life 30,000 hours Disploy User Brightness+; Color; Image: Input; Power; Menu; Management; Information; Exit Management software HP Display Center; HP Client Management Script Library ^{11,12} User updateable No fmmware No Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Flicker-free Yes (TÜV certified) Screen treatment Ant: glare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Adjustability Tilt: -5 to +23° Speaker output power 2 x 2 W; Built-in speakers Languages 11(English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications 11HDM 14	Refresh rate (maximum)			
Brightness 250 nits ¹ Contrast ratio 1000:1 (Static) ¹ 800000:1 (Dynamic) ¹ Pixel pitch 0.248 x 0.248 mm ¹ Pixels per inch (ppi) 102 ppi Viewing angle 178° (Vertical) 178° (Horizontal) Backlight type Edge-lit: WLED Backlight lamp life 30.000 hours Display User Brightness+: Color: Image; Input: Power; Menu; Management, Information: Exit Control Options Brightness+: Color: Image; Input: Power; Menu; Management, Information: Exit Management software HP Display Center; HP Client Management Script Library ^{11,12} User updateable No firmware No Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Flicker-free Yes (TÜV certified) Screen treatment Anti-glare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Tilt -5 to +23° Speaker output power Speaker output power 2 x 2 W; Built-In speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features	Display scan frequency	48-100 Hz (Vertical) ¹ ; 30-115 kHz (Horizontal) ¹		
Contrast ratio 1000:1 (Static) ¹ 800000:1 (Dynamic) ¹ Pixel pitch 0.248 x 0.248 mm ¹ Pixels per inch (ppl) 102 ppi Viewing angle 178° (Vertical) 178° (Horizontal) Backlight type Edge-lit; WLED Backlight type Bightness+; Color; Image; Input; Power; Menu; Management; Information; Exit Management software HP Display Center; HP Client Management Script Library ¹¹¹² User updateable No firmware No Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Elicker/free Yes (TÜV certified) Screen treatment Anti-glare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Adjustability Height adjustment range: 100 mm Till: English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Speckal features Works with Chromebook Connectivity and communications 1HDMI14 Port and connectors 1HDMI14 POCP Yes, DisplayPort* and HDMI	Response time	5ms GtG (with overdrive) ¹		
Pixel pitch 0.248 x 0.248 mm ¹ Pixels per inch (ppi) 102 ppi Viewing angle 178° (Vertical) 178° (Horizontal) Backlight tamp life 30,000 hours Display User Brightness+; Color; Image; Input; Power; Menu; Management; Information; Exit Control Options Brightness+; Color; Image; Input; Power; Menu; Management; Information; Exit User updateable No firmware No Low blue light modes Yes, IP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Screen treatment Anti-glare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Adjustability Height adjustment range: 100 mm Tilt:-5 to +23° Speaker output power 2 x 2 W; Built-in speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications 1HDMI 1.4 Port and connectors 1HDMI 1.4 POrt and connectors 1HDMI 1.4 POCP Yes, DisplayPort [™] and HDMI	Brightness	250 nits ¹		
Pixels per Inch (ppi) 102 ppi Viewing angle 178° (Vertical) 178° (Horizontal) Backlight tamp life 30.000 hours Display User Brightness+; Color; Image; Input; Power; Menu; Management; Information; Exit Management software HP Display Center; HP Client Management Script Library ¹¹¹² User updateable firmware No Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Flicker-free Yes (TÜV certified) Screen treatment Antt-glare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Adjustability Height adjustment range: 100 mm Tilt: -5 to +23° Speaker output power 2 x Q: RBuilt-in speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russion) Special features Works with Chromebook Connectivity and communications 1HDMI 1.4 Port and connectors 1HDMI 1.4 HDCP Yes, DisplayPort ^{**} 1.0	Contrast ratio	1000:1 (Static) ¹ 8000000:1 (Dynamic) ¹		
Viewing angle 178° (Vertical) 178° (Horizontal) Backlight lamp life 30,000 hours Display User Brightness+; Color; Image; Input; Power; Menu; Management; Information; Exit Management software HP Display Center; HP Client Management Script Library ^{11/2} User updateable No Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Flicker-free Yes (TÜV certified) Screen treatment Anti-glare Hardness 3H ¹ Haze 25% VESA mount 100 × 100 mm Adjustability Height adjustment range: 100 mm Titl: -5 to +23° Speaker output power 2 x 2 W; Built-in speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications 1HDMI 1.4 Port and connectors 1DisplayPort ^w 1.2 1VGA HDCP Yes, DisplayPort ^w and HDMI	Pixel pitch	0.248 x 0.248 mm ¹		
Backlight type Edge-lit; WLED Backlight lamp life 30,000 hours Display User Brightness+; Color; Image; Input; Power; Menu; Management; Information; Exit Control Options HP Display Center; HP Client Management Script Library ^{11,12} User updateable No firmware No Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Flicker-free Yes (TÜV certified) Screen treatment Anti-glare Hardness 3H-1 Haze 25% VESA mount 100 x100 mm Adjustability Height adjustment range: 100 mm Tilt: -5 to +23° Speaker output power 2 x 2 W; Built-in speakers 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications 1HDMI 1.4 Port and connectors 1HDMI 1.4 HDCP Yes, DisplayPort** and HDMI	Pixels per inch (ppi)	102 ppi		
Backlight lamp life 30,000 hours Display User Control Options Brightness+; Color; Image; Input; Power; Menu; Management; Information; Exit Management software HP Display Center; HP Client Management Script Library ^{11,12} User updateable firmware No Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Flicker-free Yes (TÜV certified) Screen treatment Anti-glare Hardness 3H ¹ Haze 25% VESA mount 100 x100 mm Adjustability Height adjustment range: 100 mm Tilt: -5 to +23° Speaker output power 2x 2 W; Built-in speakers 11 Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications 1HDMI 1.4 Port and connectors 1HDMI 1.4 PDEP Yes, DisplayPort [™] and HDMI	Viewing angle	178° (Vertical) 178° (Horizontal)		
Display User Control Options Brightness+; Color; Image; Input; Power; Menu; Management; Information; Exit Management software HP Display Center; HP Client Management Script Library ^{11,12} User updateable firmware No Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Flicker-free Yes (TÜV certified) Screen treatment Anti-glare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Adjustability Height adjustment range: 100 mm Tilt: -5 to +23° Speaker output power 2 x 2 W; Built-in speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications 1 HDMI 1.4 1 DisplayPort™ 1.2 1 VGA HDCP Yes, DisplayPort™ and HDMI	Backlight type	Edge-lit; WLED		
Control Options Brightness+; Color; Image; Input; Power; Ment; Management; Information; Exit Management software HP Display Center; HP Client Management Script Library ^{11/2} User updateable firmware No Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Flicker-free Yes (TÜV certified) Screen treatment Anti-glare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Adjustability Height adjustment range: 100 mm Tilt: -5 to +23° Speaker output power 2 x 2 W; Built-in speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications 1 HDMI 1.4 1 VGA HDCP Yes, DisplayPort ¹¹¹ and HDMI	Backlight lamp life	30,000 hours		
User updateable firmware No Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Flicker-free Yes (TÜV certified) Screen treatment Anti-glare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Adjustability Height adjustment range: 100 mm Tilt: -5 to +23° Speaker output power 2 x 2 W; Built-in speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications 1 Port and connectors 1 HDCP Yes, DisplayPort™ 1.2 1 VGA				
firmwore NO Low blue light modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹ Flicker-free Yes (TÜV certified) Screen treatment Anti-glare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Adjustability Height adjustment range: 100 mm Tilt: -5 to +23° Speaker output power 2 x 2 W: Built-in speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications Port and connectors 1 HDMI 1.4 1 DisplayPort™ 1.2 1 VGA HDCP Yes, DisplayPort™ and HDMI	Management software	HP Display Center; HP Client Management Script Library ^{11,12}		
Flicker-free Yes (TÜV certified) Screen treatment Anti-glare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Adjustability Height adjustment range: 100 mm Tilt:-5 to +23° Speaker output power 2 x 2 W: Built-in speakers 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications 1 HDMI 1.4 Port and connectors 1 HDMI 1.4 HDCP Yes, DisplayPort™ and HDMI	-	No		
Screen treatment Anti-glare Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Adjustability Height adjustment range: 100 mm Tilt: -5 to +23° Speaker output power 2 x 2 W; Built-in speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications Port and connectors 1 HDMI 1.4 1 DisplayPort™ 1.2 1 VGA HDCP Yes, DisplayPort™ and HDMI	Low blue light modes	Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) ¹		
Hardness 3H ¹ Haze 25% VESA mount 100 x 100 mm Adjustability Height adjustment range: 100 mm Tilt: -5 to +23° Speaker output power 2 x 2 W; Built-in speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications 1 HDMI 1.4 1 DisplayPort™ 1.2 1 VGA HDCP Yes, DisplayPort™ and HDMI	Flicker-free	Yes (TÜV certified)		
Haze 25% VESA mount 100 x 100 mm Adjustability Height adjustment range: 100 mm Tilt: -5 to +23° Tilt: -5 to +23° Speaker output power 2 x 2 W; Built-in speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications 1HDMI 1.4 Port and connectors 1 DisplayPort™ 1.2 / VGA HDCP Yes, DisplayPort™ and HDMI	Screen treatment	Anti-glare		
VESA mount 100 x 100 mm Adjustability Height adjustment range: 100 mm Tilt: -5 to +23° Speaker output power 2 x 2 W; Built-in speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications Port and connectors 1 HDMI 1.4 1 DisplayPort™ 1.2 1 VGA HDCP Yes, DisplayPort™ and HDMI	Hardness	3H ¹		
Adjustability Height adjustment range: 100 mm Tilt: -5 to +23° Speaker output power 2 x 2 W; Built-in speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications Port and connectors 1 HDMI 1.4 1 DisplayPort™ 1.2 1 VGA HDCP Yes, DisplayPort™ and HDMI	Haze	25%		
Adjustability Tilt: -5 to +23° Speaker output power 2 x 2 W; Built-in speakers Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications 1HDMI 1.4 Port and connectors 1 HDMI 1.4 I UsplayPort™ 1.2 1VGA HDCP Yes, DisplayPort™ and HDMI	VESA mount	100 x 100 mm		
Languages 11 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian) Special features Works with Chromebook Connectivity and communications Port and connectors 1 HDMI 1.4 1 DisplayPort™ 1.2 1 VGA HDCP Yes, DisplayPort™ and HDMI	Adjustability			
Connectivity and communications Port and connectors 1 HDMI 1.4 1 DisplayPort™ 1.2 1 VGA HDCP Yes, DisplayPort™ and HDMI	Speaker output power	2 x 2 W; Built-in speakers		
Connectivity and communications Port and connectors 1 HDMI 1.4 1 DisplayPort™ 1.2 1 VGA HDCP Yes, DisplayPort™ and HDMI	Languages			
Port and connectors1 HDMI 1.4 1 DisplayPort™ 1.2 1 VGAHDCPYes, DisplayPort™ and HDMI	Special features	Works with Chromebook		
Port and connectors 1 DisplayPort™ 1.2 1 VGA 1 VGA HDCP Yes, DisplayPort™ and HDMI	Connectivity and cor	nmunications		
	Port and connectors	1 DisplayPort™ 1.2		
Power supply 100 - 240 VAC 50/60 Hz (Internal)	HDCP	Yes, DisplayPort™ and HDMI		
	Power supply	100 - 240 VAC 50/60 Hz (Internal)		



Specifications

Appearance

Appearance		
Product color	Black	
Stand color	Black	
Detachable stand	Yes	
Physical security	Security lock-ready ⁵	
Base area footprint	17.8 x 18.5 cm	
Dimensions without Stand (W x D x H)	48.84 x 5.12 x 29.43 cm (without stand)	
Dimensions with stand (W x D x H)	48.84 x 19.64 x 44.95 cm	
Weight	3.73 kg (with stand); 2.55 kg (without stand)	
Packaged Dimensions (W x D x H)	56.7 x 13.3 x 38.7 cm	
Packaged weight	5.63 kg	

Certification and compliance

Energy efficiency class		
On mode power demand in Standard Dynamic Range (SDR)	11.3 W	
Standby mode power demand	0.2 W	
Energy efficiency	ENERGY STAR [®] certified	
Ecolabels	EPEAT® Gold registered; TCO Certified; TCO Certified Edge	
Sustainable impact specifications	Low halogen; Molded paper pulp cushion inside box is 100% sustainably sourced and recyclable; 85% post- consumer recycled plastic; Contains 20% recycled glass in the monitor panel; At least 5% recycled metal ^{6,7,8,9,10}	
Certifications	Australia MEPS; Bauart; CCC; CE; CECP; CEL; cTUVus; EAC; E-standby (Korea); EUP Lot-5; EUP Lot-6; FCC; ISO 9241- 307; KC (Korean) requirements; KCC (Korean) requirements; NOM (Mexico); PSB for Singapore; RCM; SEPA; S-Mark for Argentina; Taiwan BSMI; VCCI; Vietnam MEPS; Ukraine Energy label; California Energy Commission (CEC); South Africa Energy; EUP Lot 26; Mexico Energy; UAE; TGM; TÜV Flicker free certified; India BIS; Cambodia ISC; NRCS; PSE; TÜV Low Blue Light Hardware Solution certified; Ukraine CoC; Ukraine DOC; CEL Grade 2; CB(62368-1); CB 60950; EMC	
Microsoft WHQL certification	Windows 11; Windows 10	
Environmental	Operating temperature range: 5 to 35°C Non-operating temperature range -40 to 65°C Operating humidity: 20 to 80% RH (non-condensing) Non-operating humidity: 5 - 95% Operating altitude: Up to 5,000 m Non-operating altitude: Up to 12,192 m	
Additional information		
Manufacturer Warranty	HP three-year limited warranty	
What's in the box	Monitor; HDMI cable; Warranty card; Quick Setup Poster; AC power cord ⁴	
Country of origin	Made in China and Vietnam	
Logistic information		
Pallet Dimensions (L x W x H)	Slip sheet: 115.3 x 108 x 233.9 cm (40 ft HQ) Pallet: 115 x 108 x 207.7 cm (20 ft, 40 ft) Pallet: 115 x 108 x 207.7 cm (40 ft HQ)	
Pallet weight	Slip sheet: 545 kg (40 ft HQ) Pallet: 475 kg (20 ft, 40 ft, 40 ft HQ)	
Pallet (layers)	Pallet: 5 layers (20 ft, 40 ft); Slip sheet: 6 layers (40 ft HQ)	
Products per layer	16	
Products per pallet	Pallet: 80; Slip sheet: 96	



Product walkaround



1. Power button

2. Power LED



Joypad OSD button
 Security cable slot
 Power connector

4. DisplayPort™ 1.2 5. HDMI 1.4 port 6. VGA port



Accessories and services (not included)

HP B550 Z Display PC Mounting Bracket	Customize an altogether better solution with the HP PC B550 Mounting Bracket, which lets you attach your Z Mini Workstation directly behind select HP Z displays/Series 7 Pro monitors. ¹ Product number: 16U00AA ¹ Compatible with select HP Z Display, Series 7 Pro, P Series, and Series 3 Pro Monitors. Please check detailed compatibility on accessory datasheet.
HP Business PC Security Lock V3 Kit	Help prevent chassis tampering and secure your PC and display in workspaces and public areas with the affordable HP Business PC Security Lock v3 Kit. Product number: 3XJ17AA
HP B200 PC Mounting Bracket	Create a compact, efficient workspace with the HP B200 PC Mounting Bracket. Simply attach the bracket to the base of your select P G5 Series monitor and easily slide in your select HP Desktop Mini PC ¹ for an optimized space-saving solution that doesn't interfere with port access or tilt adjustment. Product number: 762T5AA ¹ Compatible with select HP P Series and Series 3 Pro Monitors. Please check detailed compatibility on accessory datasheet.
HP Quick Release Single Arm	Enjoy more comfort and space with the HP Quick Release Monitor Arm. Easily mount and quickly release select E-Series G5 ¹ , Series 5 Pro ² , and Series 7 Pro ³ monitors to maximize workday comfort and desk space. Product number: 762U0AA ¹ Compatible with select HP P Series, Series 3 Pro, E Series, Series 5 Pro, and Series 7 Pro monitors. Please check detailed compatibility on accessory datasheet. ² Requires monitor VESA adapter for selected models. Please contact your Sales agent or HP Service for further guidance.



Footnotes

Messaging Footnotes

¹All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower. 100 Hz refresh rate can be supported via HDMI and DisplayPort¹¹ cable connection only. 60 Hz refresh rate with VGA. ² Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 EPEAT¹ standard. Recycled plastic is expressed as a percentage of the total weight plastic. Recycled metal is expressed as a

percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams. Percentage of recycled glass in the monitor panel varies by product. Recycled glass is expressed as a percentage of the total weight of the glass. ³ Based on US EPEAT* registration according to IEEE 1680.1-2018 EPEAT*. EPEAT* status varies by country. Visit www.epeat.net for more information.

⁴ FHD content is required to view FHD images ⁵ Cable included in box varies by region.

⁶ Host PC requires Windows 10 or higher. HP Display Center is available on the Microsoft store. ⁷ HP CMSL is estimated to be available between November 2024 to April 2025. HP CMSL is only supported on 64-bit PowerShell 51 and higher. CMSL Support Windows 10 version 1809 and higher, and Windows 11. Some limitations may apply to legacy displays. Visit support.hp.com to download HP CMSL.

⁸ HP paper and fiber based packaging for PCs, displays, home and office print, and supplies is reported by suppliers as recycled or certified, with a minimum of 97% by volume verified by HP. Packaging is the box that comes with the product and all paper-based materials inside the box. Packaging for personal systems accessories and spare parts is not included.

⁹ Mounting hardware is sold separately, B200 bracket is compatible with all P G5 series, Series 3 Pro and these select mini PCs: Elite Mini 800 G9 UMA sku, Elite Mini 600 G9, Pro Mini 400 G9, Pro Mini 260 G9, EliteDesk 800 G8 UMA sku, EliteDesk 805 G8 UMA sku, EliteDesk 805 G8 UMA sku, EliteDesk 805 G6 UMA sku, ProDesk 600 G6, ProDesk 400 G6, 260 G4 Desktop Mini.

¹⁰ Google tested to meet Chromebook compatibility standards.

¹¹ This product works with devices capable of running the latest version of Chrome OS and has been certified to meet Google's compatibility standards. Google is not responsible for the operation of this product or its compliance with safety requirements. Chromebook and the Works With Chromebook badge are trademarks of Google LLC.

Technical Specifications Footnotes

¹All specifications represent the typical specifications provided by HP's component manufacturers, actual performance may vary either higher or lower

² DisplayPort[™] 1.2 or HDMI 1.4 required to drive panel at its native resolution. The video card of the connected PC must be capable of supporting 1920 x 1080 at 60 Hz with 8-bit color using one HDMI, DisplayPort[™] or VGA. ³ Number of colors through A-FRC technology.

⁴ Included cables may vary by country.

⁵ Lock sold separately.

⁶ ITE Derived Closed Loop Plastic percentage is based on the definition set in the IEEE 1680.1-2018 standard.

⁷ Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams.

⁹ PP paper and fiber based packaging for PCs, displays, home and office print, and supplies is reported by suppliers as recycled or certified, with a minimum of 97% by volume verified by HP. Packaging is the box that

¹⁰ External power supplies, WWAN modules, power cords, cables and peripherals excluded. Service parts obtained after purchase may not be Low Halogen.
 ¹¹ Host PC requires Windows 10. HP Display Center is available on the Microsoft store.

12 HP CMSL is estimated to be available between November 2024 to April 2025. HP CMSL is only supported on 64-bit PowerShell 5.1 and higher. CMSL Support Windows 10 version 1809 and higher, and Windows 11. Some limitations may apply to legacy displays. Visit support.hp.com to download HP CMSL

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. EPEAT* is a registered trademark of Green Electronics Council. ENERGY STAR* is a registered mark owned by the U.S. government. © 2024 Google LLC All rights reserved. Chrome is a trademarks of Google LLC. June 2025

