HP LaserJet Enterprise 8501 Printer series



The ultimate workflow experience

Boost office productivity with fast print speeds and effortless management.





Rely on exceptional performance

- Stay productive and always ready for what's next with upgradeable HP FutureSmart features.²
- Save valuable time. High-quality prints are delivered quickly—with speeds up to 70 ppm.³

Secure what matters¹

- Your work is secure with HP Wolf Security⁴, silently detecting and repairing your printer from cyber attacks.
- Protect your network with the world's first quantum-resistant business printers.⁴
- Protect data stored on your device with the embedded HP Trusted Platform Module. Passwords, keys, and more.

Simplify print management

- Receive an easy-to-install printer at your office. No third-party technician needed.
- Easily maintain on your own—or get assistance from HP Services when you need it.
- Simplify management with long-lasting consumables and parts that minimize intervention.

Reduce your impact with sustainably designed tech

- Our energy efficient designs meet the rigorous criteria of Energy Star and Blue Angel.⁶
- With HP Planet Partners, we offer a convenient way to recycle HP supplies after their use. ⁷
- With every page you print, HP invests in helping to protect, manage, and restore forests.⁸

Product walkaround

- 1. 500-sheet output bin
- 2. Up to 70 ppm
- 3. Automatic, 2-sided printing
- 4. HP Wolf Enterprise Security
- 5. 4.3-in (10.92 cm) color touchscreen
- 6. Power button
- 7. Right door access to the print path
- 8. Hardware Integration Pocket
- 9. Easy access USB port
- 10. 2.180-sheet input



Series at a glance







Model	HP LaserJet Ent 8501dn Prntr	HP LaserJet Ent 8501x Prntr	HP LaserJet Ent 8501x+ Prntr	
Product number	9S187A	AJ7J3A	AQ1E4A	
Print speed	Up to 70 ppm			
Input capacity	Maximum: 1.140 sheets Maximum: 2.180 sheets			
Recommended Monthly Page Volume	60.000			
Control Panel		4.3-in (10.92 cm) color touchscreen		
Finisher	N/A Stapler/Stacker Finisher included			

Accessories, Supplies and Support

Supplies	9U1Q5A HP LaserJet Toner Collection Unit (Average cartridge yields 300,000 standard pages. Declared yield value in accordance with ISP/IEC 19752.)		
	W1760A HP 176A Black Original LaserJet Toner Cartridge (Average cartridge yields 45,000 standard pages. Declared yield value in accordance with ISP/IEC 19752.)		
	W1766A HP 176A LaserJet Black Original Imaging Drum (Average cartridge yields 600,000 standard pages. Declared yield value in accordance with ISP/IEC 19752.)		
ccessories	2NR12A HP Removable Hard Drive Enclosure		
	2TD64A HP Accessibility Kit		
	3JN69A HP Jetdirect 3100w BLE/NFC/Wireless		
	478C2A HP Printing Voice Assistant		
	4QL32A HP Legic Secure USB Reader		
	8FP31A HP Jetdirect LAN Accessory		
	9R1U0A HP JetDirect 3200w Wifi 6 BLE/WL Accy		
	B5L31A HP Foreign Interface Harness		
	Y1G14A HP LaserJet Stapler/Stacker Finisher Staples		
	Y7C05A HP HIP2 Keystroke Reader		
Service and Support	UF8K1E HP 3 year Next Business Day Onsite with DMR Service for LaserJet Enterprise 8501		
	UF8KZE HP 4 year Next Business Day Onsite with DMR Service for LaserJet Enterprise 8501		
	UF8K3E HP 5 year Next Business Day Onsite with DMR Service for Laser Jet Enterprise 8501		
	UFBK4PE HP 1 year Post Warranty Next Business Day Onsite with DMR Service for LaserJet Enterprise 8501		
	UF8K5E HP 3 year Parts Exchange with DMR Service for LaserJet Enterprise 8501 UF8K6E HP 4 year Parts Exchange with DMR Service for LaserJet Enterprise 8501		
	UF8K7E HP 5 year Parts Exchange with DMR Service for LaserJet Enterprise 8501		
	UF8KBPE HP 1 vear Post Warranty Parts Exchange with DMR Service for LaserJet Enterprise 8501		
	U9JT3E HP Installation Service with network configuration for Department Printer (1 unit)		
	UF8L4E HP Maintenance Kit Replacement Service for LaserJet Enterprise 8501 Fuser Kit 110v		
	UF8L5E HP Maintenance Kit Replacement Service for LaserJet Enterprise 8501 Fuser Kit 220v		
Solutions	Security: HP Access Control; HP Security Manager; HP Advance; HP Secure Print and Insights		
	Mobile and universal print: HP Universal Print Driver (UPD)		
	Management: Embedded Web Server		

Technical specifications

Model	HP LaserJet Ent 8501dn Prntr	HP LaserJet Ent 8501x Prntr	HP LaserJet Ent 8501x+ Prntr		
Product number	9S187A	AJ7J3A	AQ1E4A		
Functions	Print				
Control panel	4.3-in (10.92 cm) Color Graphics Display (CGD) with touchscreen; rotating (adjustable angle) display; Speaker				
Print					
Print technology	Laser				
Print speed ³	Black (A4, normal): Up to 70 ppm Black (A4, duplex): Up to 70 ipm Black (A3, normal): Up to 35 ppm				
First page out ⁴	Black (A4, ready): As fast as 5.6 sec Black (A4, sleep): As fast as 12.9 sec (15 min)				
Print resolution	Black (normal): Up to 600 x 600 dpi; Black (fine lines): Up to 1,200 x 1,200 dpi;				
Print technology	Technology : 1,200 x 1,200 dpi (Fine lines); 600 x 600 dpi (Normal); 300 x 300 dpi (Quick view)				
Monthly duty cycle	Up to 250,000 pages A4; Recommended monthly page volume: Up to 60,000				
Printer smart software features	Print preview, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, easy-access USB				
Standard print languages	HP PCL 5e, HP PCL 6, HP Postscript level 3 emulation, PDF (v 1.7), AirPrint™ compatible				
Fonts and typefaces	84 scalable TrueType fonts				
Print area	Print margins Top: 4.23 mm, Bottom: 4.23 mm, Left: 4.23 mm, Right: 4.23 mm; Maximum print area: 311.5 x 448.7 mm				
Duplex printing	Automatic				
Processor speed	1.6 GHz (Quad Core), 1.4 GHz (Dual Core)				
Storage Standard	256 GB SSD				

2 1 1 1	HP LaserJet Ent 8501dn Prntr	HP LaserJet Ent 8501x Prntr	HP LaserJet Ent 8501x+ Prntr		
Product number	9S187A	AJ7J3A	AQ1E4A		
Connectivity	•		-		
Standard	1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Inte (host)	egration Pocket 2nd generation (HIP2); 1 Hi-Speed USB 2.0	(host); 1 SuperSpeed USB 3.0 (device); 1 SuperSpeed USB 3.0		
Optional	HP Jetdirect 3100w BLE/NFC/Wireless Accessory 3JN69A				
Wireless	Optional, enabled with purchase of a hardware accessory				
Mobile printing capability	Apple AirPrint™; Mopria™ Certified; Wi-Fi® Direct Printing; PrinterOn Print				
Supported network protocols	IPv4/IPv6: Apple Bonjour Compatible (Mac OS 10.2.4 or higl MLDv1, ICMPv6; IPv4: Auto-IP, SLP, LLMNR, IGMPv2, BOOTP/	ner), AirPrint, SNMPv1/v2c/v3, HTTP, HTTPS, Port 9100, LPC DHCP WINS, IP Direct Mode, WS Print: HP Web Services), WS Discovery, IPP, Secure-IPP, IPsec/Firewall; IPv6: DHCPv6,		
Hard disk	None	brief, times, in brieder lode, trail limit, in the believes			
Memory	Standard: 6 GB; Maximum: 6 GB				
Media handling	Startagra. 0 db, Hazimani. 0 db				
Number of paper trays	Standard: 3 ; Maximum: Up to 3	Standard: 5 ; Maximum: Up to 5			
Media types	Plain, HP EcoEFICIENT, HP Matte 90 g, Light 60-74 g, Bond,	, Recycled, HP Matte 105 g, HP Matte 120 g, HP Soft Gloss 120 g, Mid-Weight 96-110 g,Heavy 111-130 g, HP Matte 15(220 g, Light Paperboard 221-255 g, Paperboard 256-300 g, Heavy Paperboard, Mono Transparency, Labels, Letterheac			
Media size Media handling	Custom (metric): Tray 1: 98 x 139.7 to 320 x 457.2 mm; Tray 2: 98 x 139.7 to 297 x 390 mm; Tray 3: 140 x 182 to 320 x 457.2 mm; Supported (metric): Tray 1: A3, A4, A4R, A5, A5R, A6, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS), B6 (JIS), 10x15cm, Oficio, 8K, 16k, Postcard (JIS), Postcard (JIS), Envelope 65, Envelope 62, Envelope 62, Envelope 62, Envelope 65, Envelope 61, Tray 3: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k Standard input: 100-sheet multi-purpose tray, 2 x 520-sheet input tray Standard output: 500 sheet	Custom (metric): Tray 1: 98 x 139.7 to 320 x 457.2 mm; Tray 2: 98 x 139.7 to 297 x 390 mm; Tray 3: 140 x 182 to 32 x 457.2 mm; Tray 4: 140 x 182 to 320 x 457.2 mm; Tray 5: 140 x 182 to 320 x 457.2 mm; Supported (metric): Tray 1 A3, A4, A4R, A5, A5R, A6, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS), B6 (JIS), 10x15cm, Oficio, 8K, 16k, Foretope C5, Envelope C6, Envelope D1; Tray 2: A4, A4R, A5, A5R, A6, RA4, B4 (JIS), B6 (JIS), Oficio, 8K, 16k; Tray 4: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 4: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA4, B4 (JIS), B5 (JIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA4, B4 (JIS), B5 (JIS), B5 (JIS), D6 (JIS), B6 (JIS), B6 (JIS), B6 (JI			
Media weight	Tray 1, 2, 3: 60 to 325 g/m²:	Tray 1, 2, 3: 60 to 325 g/m²; Tray 4, 5: 60 to 300 g/m²;	<u>'</u>		
Input capacity	Standard: 100-sheet multi-purpose tray, 2 x 520-sheet input tray Up to 1,140 sheets (Tray 1: up to 100 sheets; Tray 2: up to 520 sheets; Tray 2: up to 520 sheets); Maximum: Up to 1,140 sheets	Standard: 100-sheet multi-purpose tray, 4 x 520-sheet input tray Up to 2,180 sheets (Tray 1: up to 100 sheets; Tray up to 520 sheets; Tray 3: up to 520 sheets; Tray 3: up to 520 sheets; Tray 3: up to 520 sheets); Maximum: Up to 2,1 sheets			
Output capacity	Standard: Up to 500 sheets Envelopes: Up to 40 envelopes Transparencies: Up to 100 sheets Maximum: Up to 500 sheets		Standard: Up to 3,250 sheets Envelopes: Up to 40 envelopes Transparencies: Up to 100 sheets Maximum: Up to 3,250 sheets		
Compatible operating systems	Windows 11; Windows 10; Windows Client OS; Android; iOS	macOS 12 Monterey; macOS 13 Ventura; MacOS v14 Sono	ma; Windows 8.1		
Compatible network operating systems	Windows Server; Linux; Citrix				
Minimum system requirements	Windows: 2 GB available hard disk space, Internet connection Mac: 2 GB available hard drive space; Internet connection or				
Software included	No software solutions are included in the Box only on http:/	/hp.com, https://support.hp.com/			
	Identity management: Kerberos authentication, LDAP authentication, 1000 user PIN codes, Optional HP and 3rd party advanced authentication solutions (e.g., badge readers); Network: IPsec/firewall with Certificate/Pre-shared Key authentication, Supports WIA-10 IPsec configuration Plug-in, 802.1X authentication (EAP-PEAP; EAP-TLS), SNMPv3; HTTPS, Certificates; Data: Storage Encryption, Encrypted PDF & Email, SSL/TLS (HTTPS), Encrypted Credentials; Device: HP Sure Start Secure Boot (BIOS Integrity Checking with self-healing capability), Intrusion Detection (Constant in-device monitoring for attacks), Whitelisting (loads only known good code), HP Memory Shield th , Embedded Trusted Platform Module, H Connection Inspector, Security lock slot, USB port disablement; Security management: Compatible with HP Security Manager, Device Security Syslog Messages processed and accessible in Arcsight and Splunk SIEMS				
Security management	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disablement	nt; Security management: Compatible with HP Security Ma	nager, Device Security Syslog Messages processed and		
	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disablement	ent; Security management: Compatible with HP Security Ma	nager, Device Security Syslog Messages processed and gent (Part of HP WebJetAdmin), Printer Administrator		
Printer management	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disablema accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF	ent; Security management: Compatible with HP Security Ma	nager, Device Security Syslog Messages processed and gent (Part of HP WebJetAdmin), Printer Administrator		
Printer management Dimensions and weight	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disablema accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF	ent; Security management: Compatible with HP Security Ma	nager, Device Security Syslog Messages processed and gent (Part of HP WebJetAdmin), Printer Administrator		
Printer management Dimensions and weight Printer dimensions (W × D × H)	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disablems accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat	ent; Security management: Compatible with HP Security Ma Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy A ion, Utility - Driver, Deployment Utility - Managed Printing A Minimum 585 x 695 x 970 mm; Maximum: 1083.5 x	nager, Device Security Syslog Messages processed and gent (Part of HP WebJetAdmin), Printer Administrator dministrator) Minimum 1293 × 695 × 1050 mm; Maximum: 1677.2 ×		
Printer management Dimensions and weight Printer dimensions (W × D × H) Package dimensions (W × D × H)	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disableme accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat Minimum 585 x 695 x 714 mm; Maximum: 1083.5 x 1197.6 x 736.7 mm	ent; Security management: Compatible with HP Security Ma Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy A ion, Utility - Driver, Deployment Utility - Managed Printing A Minimum 585 x 695 x 970 mm; Maximum: 1083.5 x 1197.6 x 993.2 mm	nager, Device Security Syslog Messages processed and igent (Part of HP WebJetAdmin), Printer Administrator dministrator) Minimum 1293 × 695 × 1050 mm; Maximum: 1677.2 × 1197.6 × 1050 mm		
Printer management Dimensions and weight Printer dimensions (W x D x H) Package dimensions (W x D x H) Printer weight ²	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disableme accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat Minimum 585 × 695 × 714 mm; Maximum: 1083.5 × 1197.6 × 736.7 mm 755 × 850 × 980 mm	ent; Security management: Compatible with HP Security Ma Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy A ion, Utility - Driver, Deployment Utility - Managed Printing A Minimum 585 x 695 x 970 mm; Maximum: 1083.5 x 1197.6 x 993.2 mm 890 x 972 x 1184 mm	nager, Device Security Syslog Messages processed and sigent (Part of HP WebJetAdmin), Printer Administrator dministrator) Minimum 1293 × 695 × 1050 mm; Maximum: 1677.2 × 1197.6 × 1050 mm 1,565 × 972 × 1,207 mm		
Printer management Dimensions and weight Printer dimensions (W x D x H) Package dimensions (W x D x H) Printer weight ² Package weight	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disableme accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat Minimum 585 x 695 x 714 mm; Maximum: 1083.5 x 1197.6 x 736.7 mm 755 x 850 x 980 mm 65.47 kg	ent; Security management: Compatible with HP Security Ma Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy A ion, Utility - Driver, Deployment Utility - Managed Printing A Minimum 585 x 695 x 970 mm; Maximum: 1083.5 x 1197.6 x 993.2 mm 890 x 972 x 1184 mm 93.72 kg	nager, Device Security Syslog Messages processed and sigent (Part of HP WebJetAdmin), Printer Administrator dministrator) Minimum 1293 × 695 × 1050 mm; Maximum: 1677.2 × 1197.6 × 1050 mm 1,565 × 972 × 1,207 mm 133.95 kg		
Printer management Dimensions and weight Printer dimensions (W x D x H) Package dimensions (W x D x H) Printer weight ² Package weight Operating environment	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disableme accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat Minimum 585 x 695 x 714 mm; Maximum: 1083.5 x 1197.6 x 736.7 mm 755 x 850 x 980 mm 65.47 kg 75.87 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH	ent; Security management: Compatible with HP Security Ma Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy A ion, Utility - Driver, Deployment Utility - Managed Printing A Minimum 585 x 695 x 970 mm; Maximum: 1083.5 x 1197.6 x 993.2 mm 890 x 972 x 1184 mm 93.72 kg	nager, Device Security Syslog Messages processed and sigent (Part of HP WebJetAdmin), Printer Administrator dministrator) Minimum 1293 × 695 × 1050 mm; Maximum: 1677.2 × 1197.6 × 1050 mm 1,565 × 972 × 1,207 mm 133.95 kg		
Printer management Dimensions and weight Printer dimensions (W x D x H) Package dimensions (W x D x H) Printer weight ² Package weight Operating environment Storage conditions	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disableme accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat Minimum 585 x 695 x 714 mm; Maximum: 1083.5 x 1197.6 x 736.7 mm 755 x 850 x 980 mm 65.47 kg 75.87 kg	ent; Security management: Compatible with HP Security Ma Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy A ion, Utility - Driver, Deployment Utility - Managed Printing A Minimum 585 x 695 x 970 mm; Maximum: 1083.5 x 1197.6 x 993.2 mm 890 x 972 x 1184 mm 93.72 kg 133.22 kg	nager, Device Security Syslog Messages processed and gent (Part of HP WebJetAdmin), Printer Administrator dministrator) Minimum 1293 × 695 × 1050 mm; Maximum: 1677.2 × 1197.6 × 1050 mm 1,565 × 972 × 1,207 mm 133.95 kg 200.05 kg Acoustic power emissions: 7.4 B(A) (printing mono simple A4 at 70 ppm); Acoustic pressure emissions: 58 B(A)		
Printer management Dimensions and weight Printer dimensions (W x D x H) Package dimensions (W x D x H) Printer weight ² Package weight Operating environment Storage conditions Acoustics ¹ Power	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disableme accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat Minimum 585 x 695 x 714 mm; Maximum: 1083.5 x 1197.6 x 736.7 mm 755 x 850 x 980 mm 65.47 kg 75.87 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 7.1 B(A) (printing mono simplex (printing mono simplex A4 at 70 ppm)	Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WS Pro	nager, Device Security Syslog Messages processed and gent (Part of HP WebJetAdmin), Printer Administrator dministrator) Minimum 1293 × 695 × 1050 mm; Maximum: 1677.2 × 1197.6 × 1050 mm 1,565 × 972 × 1,207 mm 133.95 kg 200.05 kg Acoustic power emissions: 7.4 B(A) (printing mono simple: A4 at 70 ppm); Acoustic pressure emissions: 58 B(A) (printing mono simplex A4 at 70 ppm); Acoustic pressure emissions: 58 B(A) (printing mono simplex A4 at 70 ppm); Acoustic pressure emissions: 58 B(A) (printing mono simplex A4 at 70 ppm)		
Printer management Dimensions and weight Printer dimensions (W x D x H) Package dimensions (W x D x H) Printer weight ² Package weight Operating environment Storage conditions Acoustics ¹ Power Energy savings feature technology	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disablems accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat Minimum 585 × 695 × 714 mm; Maximum: 1083.5 × 1197.6 × 736.7 mm 755 × 850 × 980 mm 65.47 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 7.1 B(A) (printing mono simplex (printing mono simplex A4 at 70 ppm) Requirements: Input voltage: 110 to 127 VAC (+/-10%), 50, dual voltage, power supply varies by part number with # Of Consumption: 1,024.37 watts (printing), 40.08 watts (read, Typical Electricity Consumption (TEG): 1.027 NaWhYleek;	Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WS Pro	nager, Device Security Syslog Messages processed and gent (Part of HP WebJetAdmin), Printer Administrator dministrator) Minimum 1293 × 695 × 1050 mm; Maximum: 1677.2 × 1197.6 × 1050 mm 1,565 × 972 × 1,207 mm 133.95 kg 200.05 kg Acoustic power emissions: 7.4 B(A) (printing mono simple: A4 at 70 ppm); Acoustic pressure emissions: 58 B(A) (printing mono simplex A4 at 70 ppm) z (+/-3 Hz), 7.0 A 100 VAC (+/-10%), 50/60 Hz (+/-3 Hz), (Not		
Printer management Dimensions and weight Printer dimensions (W x D x H) Package dimensions (W x D x H) Printer weight ² Package weight Operating environment Storage conditions Acoustics ¹ Power Energy savings feature technology	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disableme accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat Minimum 585 x 695 x 714 mm; Maximum: 1083.5 x 1197.6 x 736.7 mm 755 x 850 x 980 mm 65.47 kg 75.87 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 7.1 B(A) (printing mono simplex (printing mono simplex A4 at 70 ppm) Requirements: Input voltage: 110 to 127 VAC (+/-10%), 50; dual voltage, power supply varies by part number with #0; Consumption: 1,024.37 watts (printing), 40.08 watts (ready Typical Electricity Consumption (TEC): 1.027 kWh/Week; Power supply type: Internal (Built-in) power supply Power save	Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent, Utility - Driver, Deployment Utility - Managed Printing Aminimum 585 x 695 x 970 mm; Maximum: 1083.5 x 1197.6 x 993.2 mm 890 x 972 x 1184 mm 93.72 kg 133.22 kg A4 at 70 ppm); Acoustic pressure emissions: 55 dB(A) 60 Hz (+/-3 Hz), 12.0 A 220 to 240 VAC (+/-10%), 50/60 Hz (to 240 VAC (to 2	nager, Device Security Syslog Messages processed and agent (Part of HP WebJetAdmin), Printer Administrator dministrator) Minimum 1293 × 695 × 1050 mm; Maximum: 1677.2 × 1197.6 × 1050 mm 1,565 × 972 × 1,207 mm 133.95 kg 200.05 kg Acoustic power emissions: 7.4 B(A) (printing mono simples A4 at 70 ppm); Acoustic pressure emissions: 58 B(A) (printing mono simples A4 at 70 ppm) z (+/-3 Hz), 7.0 A 100 VAC (+/-10%), 50/60 Hz (+/-3 Hz), (Not nual-off);		
Printer management Dimensions and weight Printer dimensions (W × D × H) Package dimensions (W × D × H) Printer weight ² Package weight Operating environment Storage conditions Acoustics ¹ Power Energy savings feature technology Certifications	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security Iock slot, USB port disableme accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat Minimum 585 × 695 × 714 mm; Maximum: 1083.5 × 1197.6 × 736.7 mm 755 × 850 × 980 mm 65.47 kg 75.87 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 7.1 B(A) (printing mono simplex (printing mono simplex A4 at 70 ppm) Requirements: Input voltage: 110 to 127 VAC (+/-10%), 50/dual voltage, power supply varies by part number with # Or Consumption; 1,024.37 watts (printing), 40.08 watts (read), Typical Electricity Consumption (TEC): 1.027 kWh/Week; Power supply type: Internal (Built-in) power supply Power save CISPR 22:2008 (International) - Class A, CISPR 32:2015 (Int 3: 2013+41:2019, EN 55024: 2010+41:2015, EN 55035:20 (Lass A, Other EMC approvals as required by individual collible Angle: EPEAIF equistered: ENERGY STARS certified to	Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent, Utility - Driver, Deployment Utility - Managed Printing Aminimum 585 x 695 x 970 mm; Maximum: 1083.5 x 1197.6 x 993.2 mm 890 x 972 x 1184 mm 93.72 kg 133.22 kg A4 at 70 ppm); Acoustic pressure emissions: 55 dB(A) 60 Hz (+/-3 Hz), 12.0 A 220 to 240 VAC (+/-10%), 50/60 Hz (to 10 de dentifier); 1), 0.86 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main control of the dentifier); 1), 0.86 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main control of the dentifier); 1), 0.86 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main control of the dentifier); 1), 0.86 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main control of the dentifier); 1), 0.86 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main control of the dentifier); 1), 0.86 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main control of the dentifier); 1), 0.86 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main control of the dentifier); 1), 0.86 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main control of the dentifier); 1), 0.86 watts (sleep), 0.11 watts (auto-off), 0.12 watts (auto-off), 0.12 watts (auto-off), 0.13 watts (auto-off), 0.14 watts (auto-off), 0.14 watts (auto-off), 0.15 watts (auto-off), 0.	nager, Device Security Syslog Messages processed and agent (Part of HP WebJetAdmin), Printer Administrator dministrator) Minimum 1293 × 695 × 1050 mm; Maximum: 1677.2 × 1197.6 × 1050 mm 1,565 × 972 × 1,207 mm 133.95 kg 200.05 kg Acoustic power emissions: 7.4 B(A) (printing mono simples A4 at 70 ppm); Acoustic pressure emissions: 58 B(A) (printing mono simples A4 at 70 ppm) z (+/-3 Hz), 7.0 A 100 VAC (+/-10%), 50/60 Hz (+/-3 Hz), (Not nual-off);		
Printer management Dimensions and weight Printer dimensions (W x D x H) Package dimensions (W x D x H) Printer weight ² Package weight Operating environment Storage conditions Acoustics ¹ Power	capability). Intrusion Detection (Constant in-device monitor Connection Inspector, Security Iock slot, USB port disableme accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat Minimum 585 × 695 × 714 mm; Maximum: 1083.5 × 1197.6 × 736.7 mm 755 × 850 × 980 mm 65.47 kg 75.87 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 7.1 B(A) (printing mono simplex (printing mono simplex A4 at 70 ppm) Requirements: Input voltage: 110 to 127 VAC (+/-10%), 50, dual voltage, power supply varies by part number with # 0; Consumption; 1,024.37 watts (printing), 40.08 watts (read) Typical Electricity Consumption (TEC): 1.027 kWh/Week; Power supply type: Internal (Built-in) power supply Power save CISPR 22:2008 (International) - Class A, CISPR 32:2015 (Int 3: 2013+41:2019, EN 55024: 2010+41:2015, EN 55035:20 (Lass A, Other EMC approvals as required by individual coun Blue Angel; EPEAT* registered; ENERGY STAR* certified Blue Angel compliant Yes, Blue Angel DE-UZ 219—only ens	Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent, Utility - Driver, Deployment Utility - Managed Printing Aminimum 585 x 695 x 970 mm; Maximum: 1083.5 x 1197.6 x 993.2 mm 890 x 972 x 1184 mm 93.72 kg 133.22 kg A4 at 70 ppm); Acoustic pressure emissions: 55 dB(A) 60 Hz (+/-3 Hz), 12.0 A 220 to 240 VAC (+/-10%), 50/60 Hz (to 10 dentifier); 1), 0.86 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main tries) ernational) - Class A, EN 55032: 2015 (EU) - Class A, CISPR 117+A11:2020, EN60601-1-2:2015, EMC Directive 2014/30 tries used when using Original HP supplies ic	nager, Device Security Syslog Messages processed and agent (Part of HP WebJetAdmin), Printer Administrator dministrator) Minimum 1293 × 695 × 1050 mm; Maximum: 1677.2 × 1197.6 × 1050 mm 1,565 × 972 × 1,207 mm 133.95 kg 200.05 kg Acoustic power emissions: 7.4 B(A) (printing mono simples A4 at 70 ppm); Acoustic pressure emissions: 58 B(A) (printing mono simples A4 at 70 ppm) z (+/-3 Hz), 7.0 A 100 VAC (+/-10%), 50/60 Hz (+/-3 Hz), (Not nual-off);		
Printer management Dimensions and weight Printer dimensions (W × D × H) Package dimensions (W × D × H) Printer weight ² Package weight Operating environment Storage conditions Acoustics ¹ Power Energy savings feature technology Certifications Sustainable impact specifications	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security Iock slot, USB port disableme accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat Minimum 585 × 695 × 714 mm; Maximum: 1083.5 × 1197.6 × 736.7 mm 755 × 850 × 980 mm 65.47 kg 75.87 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 7.1 B(A) (printing mono simplex (printing mono simplex A4 at 70 ppm) Requirements: Input voltage: 110 to 127 VAC (+/-10%), 50/dual voltage, power supply varies by part number with # Or Consumption; 1,024.37 watts (printing), 40.08 watts (read), Typical Electricity Consumption (TEQ: 1.027 kWh/Week; Power supply type: Internal (Built-in) power supply Power save CISPR 22:2008 (International) - Class A, CISPR 32:2015 (Int 3: 2013+41:2019, EN 55024: 2010+41:2015, EN 55035:20 (Lass A, Other EMC approvals as required by individual consulted Angel; EPEAT* registered; ENERGY STAR®, certified Blue Angel compliant Yes, Blue Angel DE-UZ 219—only ensembles.	Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent, Utility - Driver, Deployment Utility - Managed Printing Aminimum 585 x 695 x 970 mm; Maximum: 1083.5 x 1197.6 x 993.2 mm 890 x 972 x 1184 mm 93.72 kg 133.22 kg A4 at 70 ppm); Acoustic pressure emissions: 55 dB(A) 60 Hz (+/-3 Hz), 12.0 A 220 to 240 VAC (+/-10%), 50/60 Hz (to 10 dentifier); 1), 0.86 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main tries) ernational) - Class A, EN 55032: 2015 (EU) - Class A, CISPR 117+A11:2020, EN60601-1-2:2015, EMC Directive 2014/30 tries used when using Original HP supplies ic	nager, Device Security Syslog Messages processed and agent (Part of HP WebJetAdmin), Printer Administrator dministrator) Minimum 1293 × 695 × 1050 mm; Maximum: 1677.2 × 1197.6 × 1050 mm 1,565 × 972 × 1,207 mm 133.95 kg 200.05 kg Acoustic power emissions: 7.4 B(A) (printing mono simples A4 at 70 ppm); Acoustic pressure emissions: 58 B(A) (printing mono simples A4 at 70 ppm) z (+/-3 Hz), 7.0 A 100 VAC (+/-10%), 50/60 Hz (+/-3 Hz), (Not nual-off);		
Printer management Dimensions and weight Printer dimensions (W x D x H) Package dimensions (W x D x H) Printer weight ² Package weight Operating environment Storage conditions Acoustics ¹ Power Energy savings feature technology Certifications Sustainable impact specifications Replacement cartridges ⁵	capability), Intrusion Detection (Constant in-device monitor Connection Inspector, Security lock slot, USB port disableme accessible in Arcsight and Splunk SIEMs HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat Minimum 585 × 695 × 714 mm; Maximum: 1083.5 × 1197.6 × 736.7 mm 755 × 850 × 980 mm 65.47 kg 75.87 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 7.1 B(A) (printing mono simplex (printing mono simplex A4 at 70 ppm) Requirements: Input voltage: 110 to 127 VAC (+/-10%), 50/dual voltage, power supply varies by part number with # 0/C Consumption: 1,024.37 watts (printing), 40.08 watts (ready Typical Electricity Consumption (TEC): 1.027 kMh/Week; Power supply type: Internal (Built-in) power supply Power save CISPR 22:2008 (International) - Class A, CISPR 32:2015 (Int 3: 2013 + 41:2019, EN 55024; 2010 + 41:2015, EN 55035; 2C class A, Other EMC approvals as required by individual coun Blue Angel; EPEAT® registered; ENERGY STAR® certified Blue Angel; EPEAT® registered; ENERGY STAR® certified Blue Angel; EPEAT® registered; ENERGY STAR® certified Blue Angel compiliant Yes, Blue Angel DE-UZ 219—only ensemble PSC Certified Packaging; 10% post-consumer recycled plast HP 176A Black LJ Toner Cartridge W1760A (ISO Yield 45,00 Installation guide; regulatory flyer; power cords; manual	ent; Security management: Compatible with HP Security Mal Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Agent, Utility - Driver, Deployment Utility - Managed Printing All Minimum 585 x 695 x 970 mm; Maximum: 1083.5 x 1197.6 x 993.2 mm 890 x 972 x 1184 mm 93.72 kg 133.22 kg 133.22 kg 133.22 kg 133.22 kg 14 at 70 ppm); Acoustic pressure emissions: 55 dB(A) for Hz (+/-3 Hz), 12.0 A 220 to 240 VAC (+/-10%), 50/60 Hz (10%), 0.86 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.086 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.12 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.12 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.12 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.12 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.12 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.12 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.12 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.12 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.12 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.12 watts (sleep), 0.11 watts (auto-off), 0.11 watts (main code identifier); 0.12 watts (sleep), 0.11 watts (auto-off), 0.11 watts	nager, Device Security Syslog Messages processed and agent (Part of HP WebJetAdmin), Printer Administrator dministrator) Minimum 1293 × 695 × 1050 mm; Maximum: 1677.2 × 1197.6 × 1050 mm 1,565 × 972 × 1,207 mm 133.95 kg 200.05 kg Acoustic power emissions: 7.4 B(A) (printing mono simples A4 at 70 ppm); Acoustic pressure emissions: 58 B(A) (printing mono simples A4 at 70 ppm) z (+/-3 Hz), 7.0 A 100 VAC (+/-10%), 50/60 Hz (+/-3 Hz), (Not nual-off);		

Footnotes

- ¹ The HP LaserJet Enterprise 8801/8601/8501 printer series is the top-tier model in our HP Enterprise portfolio, featuring the highest print and scan speeds, along with advanced printing solutions for easy print management.
- ² Some features enabled by future HP FutureSmart firmware upgrades may not be available on older devices, if for example, physical product characteristics limit the functionality of the new feature.
- ³ Measured using ISO/IEC 24734, excludes first set of test documents. For more information, see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
- ⁴ HP Security is now HP Wolf Security. Security features vary by platform, please see product data sheet for details. HP's most advanced embedded security features are available on HP Managed and Enterprise devices with HP FutureSmart firmware 4.5 or above. Claim based on HP review of 2024 published features of competitive in-class printers. Only HP offers multiple security features that automatically detect, stop, and recover from attacks with a self-healing reboot in alignment with NIST SP 800-193 guidelines for device cyber resiliency. For a list of compatible products, visit: hp.com/go/PrintersThatProtect. For more information, visit: hp.com/go/PrinterSecurityClaims. HP Security Manager must be purchased separately. To learn more, please visit hp.com/go/securitymanager. Post Quantum Cryptography (PQC): Based on HP's internal analysis of business Printers with preinstalled encryption, authentication, malware protection, and BIOS-level protection with automatic self-healing recovery finding that no other in-class Printers implement a quantum-resistant cryptographic scheme to protect the integrity of the BIOS as of 2025. PQC will be available in Fall'25 with Firmware 25.9.2.2+.
- 5 Use of the HP Trusted Platform Module may require a firmware upgrade.
- ⁶ HP voluntarily designs and tests its printing systems to prevent emissions that exceed Blue Angel and EPEAT eco-label guidelines. Based on US, Canada, India, and Australia EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit www.epeat.net for more information. ENERGY STAR and the ENERGY STAR logo are registered U.S. marks. HP printer, HP paper and Original HP supply Blue Angel DE-UZ 219 Emissions Criteria.
- 7 Program availability varies. For more information, visit hp.com/hprecycle.
- ⁸ HP works collaboratively with our partners including WWF and Conservation International to manage, restore, and protect forests in many countries around the world. With HP, every print—regardless of paper brand—is addressed through HP's Forest Positive Framework to counteract risks of deforestation. To learn more visit hp.com/forestfirst.

Technical specifications disclaimers

- ¹ Acoustic values are subject to change. For current information see http://www.hp.com/support
- ² Including Starter toner cartridge weight
- ³ Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
- ⁴ Based on HP internal evaluation measuring the time from print initiation to page exit. Exact speed varies depending on the system configuration, software application, driver, and document complexity. Additionally, for information of First Page Out measured using ISO/IEC 17629, see hp.com/go/printer claims.
- 5 Approximate average yield based on ISO/IEC 19752. Actual yield varies considerably based on content of printed pages and other factors. For details see http://www.hp.com/go/learnaboutsupplies.



www.blauer-engel.de/uz219



















