

8000T-E Semi-Gloss Piggyback

Semi-gloss paper label with 30% recycled content

For environmentally conscious business owners who need to find solutions that contribute to achieving sustainability targets, Zebra partners with major material suppliers to offer new products and solutions as they come to market. 8000T-E Semi-Gloss Piggyback paper labels have a machine coated, semi-gloss appearance and contain 30% recycled post-consumer waste providing a more sustainable solution without compromising on quality.



Designed for the Toughest Environments and Applications

A multi-layer construction with two layers of adhesive and liner. Labels can be applied to a surface, then later, removed completely or in part from the 'piggyback' liner and re-applied to a second surface. Produces good quality small, detailed barcodes with Zebra 2300 and 2100 ribbons. Minimum application temperature of 5°C and service temperature range from -20°C to 80°C.

Print Confident. Print Quality. Print Zebra.

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce and rigorously pre-test our own line of thermal printing supplies to ensure consistent, optimized performance. We utilize an ISO 9001 certified, 23-point inspection process and consistent materials to ensure reliable performance from order-to-order. No matter when you order your labels, you can count on the same consistent performance.

Sustainability

Contribute to your sustainability goals without compromising on quality with 8000T-E Semi-Gloss Piggyback.

Contribute to your sustainability goals without compromising on quality with 8000T-E Semi-Gloss Piggyback.

For more information, please visit www.zebra.com/supplies

Specifications

Markets and Applications

Material Construction

RM Number	10026936RM
Facestock	Semi-gloss white paper with 30% recycled content 66 microns
Adhesive	Permanent acrylic adhesive 13 microns x 2
Liner	1. 59gsm glassine liner 53 microns 2. 54gsm glassine liner 47 microns
Total thickness +/- 10%	192 microns
Environment	Indoor use; cold temperature compatible

Temperature Performance

Minimum Application Temperature ¹	5°C
Service Temperature Range ²	-20°C to 80°C

Recommended Printers and Settings

Printers	Mid-range and highperformance thermal printers
Ribbons	2300 Wax 2100 High Performance Wax 3400 High Performance Wax Resin 3200 Premium Wax Resin

Adhesive Strength

Corrugate	N/A
Steel	N/A
Polycarbonate	N/A
Polyethylene	N/A

Chemical Resistance

Weak Chemicals	N/A
Moderate Chemicals	N/A
Harsh Chemicals	N/A
Extreme Chemicals	N/A

UL/cUL Certified Materials with this Ribbon

List materials with a common between them	N/A
---	-----

Regulatory and Compliance

Contains 30% post consumer waste recycled material. Adhesive complies with European food regulations EC 1935/2004, EU 10/2011 and BfR Recommendation XIV for direct contact with dry, moist and non-fatty foodstuffs. Adhesive complies with FDA 175.105 for direct contact with dry foodstuffs, or alternatively separated by a functional barrier.

Product Performance and Suitability

Recommended storage conditions	1 year duration when stored at 20° C to 25° C at 40 to 50% RH
Expected life span in application ³	Indoor use, for 1 year+
Sample Part Number	SAMPLE26936

Footnotes

1. When the label is applied, the environment and surface should be above this temperature.
2. Following correct application and appropriate dwell time (usually 24 hrs) the media will withstand this temperature range.
3. Following correct application and appropriate dwell time (usually 24 hrs) we expect, but do not warrant, a life span as indicated.
Specifications are subject to change without notice.

Logistics

- Return Mailing Labels

Warehouse

- Order Picking Labelling

Retail

- Price Labelling

Manufacturing

- Work in Progress Labelling



NA and Corporate Headquarters
+1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
+65 6858 0722
contact.apac@zebra.com

EMEA Headquarters
zebra.com/locations
contact.emea@zebra.com

Latin America Headquarters
zebra.com/locations
la.contactme@zebra.com