HP Color LaserJet Enterprise MFP 8801 Printer series



The ultimate workflow experience

Boost office productivity with blazing-fast print and scan speeds, and effortless management.







Rely on exceptional performance

- Text editing has never been easier. Quickly scan and convert documents to Office formats with Editable OCR.²
- Stay productive and always ready for what's next with upgradeable HP FutureSmart features.³
- Save time with blazing-fast scan speeds up to 300 ipm⁴, and enjoy high-quality prints at speeds up to 60 ppm.⁵

Secure what matters

- Your work is secure with HP Wolf Security, silently detecting and repairing your printer from cyber attacks.⁶
- Protect your network with the world's first quantum-resistant business printers.⁶
- Keep your data safe with the built-in HP Trusted Platform Module⁷. Secure passwords, keys, and more.

Simplify print management

- Receive an easy-to-install printer at your office. No third-party technician needed.
- Easily maintain on your own—or get assistance from HP Services when you need it.
- Simplify management with long-lasting consumables and parts that minimize intervention.


Hit sustainability targets

- Our energy efficient designs meet the rigorous criteria of EPEAT Gold, Energy Star and Blue Angel.⁸
- With HP Planet Partners, we offer a convenient way to recycle HP supplies after their use.⁹
- With every page you print, HP invests in helping to protect, manage, and restore forests.¹⁰

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

Product walkaround

- 1. 300-sheet ADF(Flow models only)
- 2. Flatbed scanner handles sheets up to 11x17-inch (297x432mm)
- 3. Print, scan, copy, fax
- 4. 500-sheet output bin
- 5. 60 ppm
- 6. Automatic, 2-sided color printing
- 7. HP Wolf Enterprise Security
- 8. 10.1-inch color touchscreen
- 9. Power button
- 10. Full size keyboard (Flow models only)
- 11. Right door access to the print path
- 12. Hardware Integration Pocket (for connecting accessories and third-part devices)
- 13. Easy access USB port
- 14. 2,180-sheet input



Series at a glance



Model	HP Color LaserJet Enterprise MFP 8801dn	HP Color LaserJet Enterprise Flow MFP 8801z	HP Color LaserJet Enterprise Flow MFP 8801z+
Product number	9S184A	9S183A	AQ1E2A
Functions	Print, copy, scan, fax(optional)	Print, copy, scan, fax	
Print speed	60 ppm		
Scan speed	Up to 180 ipm	Up to 300 ipm	
ADF capacity	200 sheets	300 sheets	
Input capacity	Maximum: 2,180 sheets		
Advance workflow features	N/A	Advanced Flow Technology	
Finisher	N/A		Stapler/Stacker Finisher included

Accessories, Supplies and Support

Supplies	A91Z4A HP LaserJet Toner Collection Unit (Average cartridge yields 130,000 standard pages. Declared yield value in accordance with ISP/IEC 19798.)
	W2250A HP 225A Black Original Laser Jet Toner Cartridge (Average cartridge yields 45,000 standard pages. Declared yield value in accordance with ISP/IEC 19798.)
	W2251A HP 225A Cyan Original Laser Jet Toner Cartridge (40,000 standard pages in accordance with ISO/IEC 19798)
	W2252A HP 225A Yellow Original LaserJet Toner Cartridge (40,000 standard pages in accordance with ISO/IEC 19798)
	W2253A HP 225A Magenta Original Laser Jet Toner Cartridge (40,000 standard pages in accordance with ISO/IEC 19798)
	W2256A HP 225A Laser Jet Black Original Imaging Drum (Average cartridge yields 300,000 standard pages. Declared yield value in accordance with ISP/IEC 19798.)
	W2257A HP 225A LaserJet CYM Original Imaging Drum (240,000 standard pages in accordance with ISO/IEC 19798.)
Accessories	2NR12A HP Removable Hard Drive Enclosure
Accessones	3JN69A HP Jetdirect 3100w BLE/NFC/Wireless Accessory
	478C2A HP Printing Voice Assistant
	4QL32A HP Legic Secure USB Reader
	7ZAOBA HP MFP 800 Analog Single Fax
	7ZA09A HP MFP 801 Analog Single Fax
	SFP31A HP Jetdirect LAN Accessory
	B5L31A HP Foreign Interface Harness
	X3D03A HP USB Universal Card Reader
	Y1G14A HP Laser Jet Stapler/Stacker Finisher Staples
	Y7C05A HP HIP2 Keystroke Reader
Service and Support	UF8GOE HP 3 year Next Business Day Onsite with DMR Service for Color Laser Jet Enterprise MFP 8801
	UF8G1E HP 4 year Next Business Day Onsite with DMR Service for Color LaserJet Enterprise MFP 8801
	UPSGZE HP 5 year Next Business Day Onsite with DMR Service for Color Laser Jet Enterprise MFP 8801
	UF8G3PE HP 1 year Post Warranty NBD Onsite with DMR Service for Color LaserJet Enterprise MFP 8801 UF8G8E HP 3 year 4 hour Onsite with DMR Service for Color LaserJet Enterprise MFP 8801
	UF8G9E HP 4 year 4 hour Onsite with DMR Service for Color LaserJet Enterprise MFP 8801
	UF8H0E HP 5 year 4 hour Onsite with DMR Service for Color Laberet Enterprise MFP 8801
	UF8H1PE HP 1 year Post Warranty 4 hour Onsite with DMR Service for Color LaserJet Enterprise MFP 8801
	UF8G4E HP 3 year Parts Exchange with DMR Service for Color LaserJet Enterprise MFP 8801
	UF8G5E HP 4 year Parts Exchange with DMR Service for Color Laser Jet Enterprise MFP 8801
	UF8G6E HP 5 year Parts Exchange with DMR Service for Color LaserJet Enterprise MFP 8801 UF8G7PE HP 1 year Post Warranty Parts Exchange with DMR Service for Color LaserJet Enterprise MFP 8801
	U9JT3E HP Installation Service with network configuration for Department Printer (1 unit)
	UF9H2E HP Maintenance Kit Replacement Service for ColorLaserJetEnterpriseMFP8801 Developer(CMYK) Unit Kit
	UF8H3E HP Maintenance Kit Replacement Service for ColorLaserJetEnterpriseMFP8801 Fuser Kit 100v for Japan
	UF8H4E HP Maintenance Kit Replacement Service for ColorLaserJetEnterpriseMFP8801 Fuser Kit 110v
	UF8H5E HP Maintenance Kit Replacement Service for ColorLaserJetEnterpriseMFP8801 Fuser Kit 220v
Solutions	Workflow: HP Capture & Route; Upland Intelligent Capture; Upland Filebound
	Security: HP Access Control; HP Security Manager; HP Advance; HP Secure Print and Insights
	Mobile and universal print: HP Universal Print Driver (UPD)
	Management: Embedded Web Server

Technical specifications

Model				
	HP Color LaserJet Enterprise MFP 8801dn	HP Color LaserJet Enterprise Flow MFP 8801z	HP Color LaserJet Enterprise Flow MFP 8801z+	
Product number	95184A	9S183A	AQ1E2A	
Functions	Print, copy, scan, fax (optional) Print, copy, scan, fax			
Control panel	10.1-in (25.65 cm) Color Graphics Display (CGD) with touchs	screen; rotating (adjustable angle) display; Speaker		
Print				
Print technology	Laser			
Print speed ⁵	Black (A4, normal): Up to 60 ppm Colour (A4, normal): Up to 60 ppm Black (A4, duplex): Up to 60 ipm Colour (A4, duplex): Up to 60 ipm Black (A3, normal): Up to 30 ppm Colour (A3, normal): Up to 30 ppm			
First page out ⁶	Black (A4, ready): As fast as 5.7 sec Colour (A4, ready): As fast as 5.5 sec Black (A4, sleep): As fast as 13.0 sec (15 min) Colour (A4, sleep): As fast as 13.1 sec (15 min)			
Print resolution	Black (normal): Up to 600 x 600 dpi; Black (fine lines): Up to 1,200 x 1,200 dpi; Color (normal): Up to 600 x 600 dpi; Color (fine lines): Up to 1200 x 1200 dpi;			
Print technology	Technology: 1,200 x 1,200 dpi (Fine lines); 600 x 600 dpi (Normal); 300 x 300 dpi (Quick view)			
Monthly duty cycle	Up to 250,000 pages (printer); up to 250,000 pages (copier) A4; Recommended monthly page volume: Up to 60,000			
Printer smart software features	Print preview, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, easy-access USB			
Standard print languages	HP PCL 5c, HP PCL 6, HP Postscript level 3 emulation, PDF (v 1.7), AirPrint™ compatible			
onts and typefaces	84 scalable TrueType fonts			
Print area	Print margins Top: 4.23 mm, Bottom: 4.23 mm, Left: 4.23 mm, Right: 4.23 mm; Maximum print area: 311.5 x 448.7 mm			
Duplex printing	Automatic			
Сору				
Copy speed ²	Black (A4): Up to 60 cpm ; Colour (A4): Up to 60 cpm ; Black	(A4 duplex): Up to 60 ipm : Colour (A4 duplex): Up to 60	inm	
	Black (A4): As fast as 3.2 sec	(14, adpiery, op to oo pin, colour (14, adpiery, 00 to 00	ipin	
First copy out ⁶	Colour (A4): As fast as 3.2 sec			
Copier specifications	Two-sided copying; automatically detect color/monochrome; reduce/enlarge; image adjustments (darkness, contrast, background cleanup, sharpness); optimize text/picture (text, mixed, printed picture, photograph); N-Up; N or Z-ordering; content crientation; collate; booklet; scan mode (book, 2-sided ID); watermark; stamps; image overlay; erase edges; job build; image preview; image shift; paper selection; blank page suppression; automatically straighten; scan to job storage Maximum number of copies: Up to 9999 copies; Reduce/Enlarge: 25 to 400%; Copy resolution, color text and graphics: Up to 600 x 600 dpi; Copy resolution, black text: Up to 600 x 600 dpi	Two-sided copying; automatically detect color/monochrome; reduce/enlarge; image adjustments (darkness, contrast, background cleanup, sharpness); optimize text/picture (text, mixed, printed picture, photograph); N-Up; N or Z-ordering content orientation; collate; booklet; scan mode (book, z-sided ID); watermark; stamps; image overlay; erase edges; jot build; image preview; image shift; paper selection; blank page suppression; automatically straighten; scan to job storage; optimized text/picture (ato); automatic tome; multi-feed detection; document editing; auto paper color removal Maximum number of copies: Up to 9999 copies; Reduce/Enlarge; 25 to 400%; Copy resolution, color text and graphics: Up to 600 x 600 dpi;		
Scan				
	Normal (A4): Up to 90 ipm (B&W), Up to 90 ipm (Color);	Normal (A4): Up to 150 ipm (B8W) up to 150 ipm (Colo	r): Duploy (A4): Up to 300 ipm	
Scan speed ¹	Duplex (A4): Up to 180 ipm	Normal (A4): Up to 150 ipm (B&W), up to 150 ipm (Colo	r); Duplex (44). Op to 300 lpm	
Scan file format ⁴	JPEG; TIFF; MTIFF; XPS; PDF; PDF/A; High-Compression PDF; High-Compression PDF/A; Searchable PDF (OCR); Searchable PDF/A (OCR); High-Compression PDF (OCR); High-Compression PDF/A (OCR); High-Compression Searchable PDF (OCR); High-Compression Searchable PDF/A (OCR)	JPEG; TIFF; MTIFF; XPS; PDF; PDF/A; High-Compression PDF; High-Compression PDF/A; PDF (OCR); PDF/A (OCR); Searchable PDF (OCR); Searchable PDF/A (OCR); High-Compression PDF (OCR); High-Compression PDF/A (OCR); High- Compression Searchable PDF (OCR); High-Compression Searchable PDF/A (OCR); CSV (OCR); HTML (OCR); Open Office XML (.docx, .xlsx, .pptx); RTF (OCR); TEXT (OCR); Unicode TEXT (OCR)		
	Scanner type: Flatbed, ADF; Scan technology: Platen Scanner CCD Digital-CIS; Scan input modes: Front panel applications: Copy; Fax; Scan to Email; Scan to Network Folder; Scan to USB; Scan to Job Storage; Open Extensibility Platform (OXP); Twain version: Version 2.4; Duplex ADF scanning: Yes, single pass duplex scanning; Optical scan resolution: Up to 600 x 600 dpi			
Scanner specifications	USB; Scan to Job Storage; Open Extensibility Platform (OXP)); Twain version: Version 2.4; Duplex ADF scanning: Yes, si	ions: Copy, Fax; Scan to Email; Scan to Network Folder; Scan to ngle pass duplex scanning; Optical scan resolution : Up to 600 >	
	USB; Scan to Job Storage; Open Extensibility Platform (OXP)); Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text	ngle pass duplex scanning; Optical scan resolution : Up to 600 > /picture (auto); scan to multi-destination; automatic tone; auto	
Scanner advanced features	USB; Scan to Job Storage; Open Extensibility Platform (OXP) 600 dpi	; Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; doo page, barcode); watermark; stamps	ngle pass duplex scanning; Optical scan resolution : Up to 600 ; /picture (auto); scan to multi-destination; automatic tone; auto .ument editing; auto paper color removal; job separation (blanl	
Scanner specifications Scanner advanced features Scannable area Bit depth/ Grey scale levels	USB; Scan to Job Storage; Open Extensibility Platform (OXP, 600 dpi Embedded OCR; Automatically straighten	; Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; doo page, barcode); watermark; stamps	ngle pass duplex scanning; Optical scan resolution : Up to 600 x /picture (auto); scan to multi-destination; automatic tone; auto .ument editing; auto paper color removal; job separation (blank	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending	USB; Scan to Job Storage; Open Extensibility Platform (OXP, 600 dpi Embedded OCR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m); Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; dor page, barcode); watermark; stamps eedia size (ADF): 68 × 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan tr to LAN fax; scan to Internet Fax; local address book; SM compression PDF; image adjustments (darkness, contr mixed, printed picture, photograph); content orientation build; image preview; blank page suppression; automat	ngle pass duplex scanning; Optical scan resolution : Up to 600 x /picture (auto); scan to multi-destination; automatic tone; auto :ument editing; auto paper color removal; job separation (blank : 297 x 420 mm DSB drive; scan to SharePoint; scan to FTP; scan to sFTP; scan TP over SSL; automatically detect color/monochrome; high st, background cleanup, sharpness); optimize text/picture (text); ; scan mode (book, 2-sided ID); erase edges; auto page crop; jo ically straighten; embedded OCR; optimize text/picture (auto); ion; multi-feed detection; reverse and retry: document edition;	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending Fax	USB; Scan to Job Storage; Open Extensibility Platform (0XP, 600 dpi Embedded OCR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m 24-bit / 256 Standard: Scan to Email; scan to network folder; scan to USB drive; scan to SharePoint; scan to FTP; scan to SFTP; scan to LAN fax; scan to Internet Fax; local address book; SMTP over SSL; automatically detect color/monochrome; high compression PD; image adjustments (darkness, contrast, background cleanup, sharpness); optimize text/picture (text, mixed, printed picture, photograph); content orientation; scan mode (book, 2-sided ID); erase edges; job build; image preview; blank page suppression; automatically straighten; embedded OCR;); Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; do page, barcode); watermark; stamps eedia size (ADF): 68 × 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan to LAN fax; scan to Internet Fax; local address book; SM compression PDF; image adjustments (darkness, contra mixed, printed picture, photograph); content orientation build; image preview; blank page suppression; automat scan to multi-destination; automatic tone; auto orienta auto paper color removal; job separation (blank page, b)	ngle pass duplex scanning; Optical scan resolution : Up to 600 x /picture (auto); scan to multi-destination; automatic tone; auto :ument editing; auto paper color removal; job separation (blank : 297 x 420 mm DSB drive; scan to SharePoint; scan to FTP; scan to sFTP; scan TP over SSL; automatically detect color/monochrome; high st, background cleanup, sharpness); optimize text/picture (text); ; scan mode (book, 2-sided ID); erase edges; auto page crop; jo ically straighten; embedded OCR; optimize text/picture (auto); ion; multi-feed detection; reverse and retry: document edition;	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending	USB; Scan to Job Storage; Open Extensibility Platform (0XP, 600 dpi Embedded OCR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m 24-bit / 256 Standard: Scan to Email; scan to network folder; scan to USB drive; scan to SharePoint; scan to TP; scan to LAN fax; scan to Internet Fax; local address book; SMTP over SSL; automatically detect color/monochrome; high compression PD; image adjustments (darkness, contrast, background cleanup, sharpness); optimize text/picture (text, mixed, printed picture, photograph); content orientation; scan mode (book, 2-sided ID); erase edges; job build; image preview; blank page suppression; automatically straighten; embedded OCR; Optional, 33.6 kbps (fax modem max speed)	(; Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; do page, barcode); watermark; stamps eedia size (ADF): 68 × 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan te to LAN fax; scan to Internet Fax; local address book; SM compression PDF; image adjustments (darkness, contr mixed, printed picture, photograph); content iorientation build; image preview; blank page suppression; automat scan to multi-destination; automatic tone; auto orienta auto paper color removal; job separation (blank page, b Yes, 33.6 kbps (fax modern max speed)	ngle pass duplex scanning; Optical scan resolution : Up to 600 × /picture (auto); scan to multi-destination; automatic tone; auto :ument editing; auto paper color removal; job separation (blank : 297 x 420 mm b) USB drive; scan to SharePoint; scan to FTP; scan to SFTP; scan TP over SSL; automatically detect color/monochrome; high st, background cleanup, sharpness); optimize text/picture (tex ; scan mode (book, 2-sided ID); erase edges; auto page crop; j icially straighten; embedded OCR; optimize text/picture (lato; icially straighten; icially	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending Fax Fax	USB; Scan to Job Storage; Open Extensibility Platform (OXP, 600 dpi Embedded OCR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m 24-bit / 256 Standard: Scan to Email; scan to network folder; scan to USB drive; scan to SharePoint; scan to FTP; scan to LAN fax; scan to Internet Fax; local address book; SMTP over SSL; automatically detect color/monochrome; high compression PDF; image adjustments (darkness, contrast, background cleanup, sharpness), optimize text/picture (text, mixed, printed picture, photograph); content orientation; scan mode (book, 2-sided ID); erase edges; job build; image preview; blank page suppression; automatically straighten; embedded OCR; Optional, 33.6 kbps (fax modern max speed) Fax memory: Up to 500 pages; Fax resolution: Standard: 20 destinations); Telecom compliance: Optional telecom kit (BC (CANADA); ETSI ES 203 021-1 V2.11; ETSI ES 203 021-2 V2.	(; Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; dor page, barcode); watermark; stamps edia size (ADF): 68 x 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan to to LAN fax; scan to Internet Fax; local address book; Sont compression PDF; image adjustments (darkness, contr mixed, printed picture, photograph); content orientation build; image preview; blank page suppression; automat scan to multi-destination; automatic tone; auto orienta auto paper color removal; job separation (blank page, b Yes, 33.6 kbps (fax modem max speed) 13 x 98 dpi; Fine: 203 x 196 dpi; Superfine: Up to 300 x 30 SIBI-B14-00 / B0ISB-1814-01); TIA-968-B-3; FCC Part 1.2; EFSI ES 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.2; EFSI ES 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.2; EFSI ES 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.2; EFSI ES 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.2; EFSI ESI 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so	ngle pass duplex scanning; Optical scan resolution : Up to 600 × /picture (auto); scan to multi-destination; automatic tone; auto :ument editing; auto paper color removal; job separation (blank : 297 x 420 mm DSB drive; scan to SharePoint; scan to FTP; scan to sFTP; scan TP over SSL; automatically detect color/monochrome; high sst, background (eanup, sharpness); optimize text/picture (tex ; scan mode (book, 2-sided ID); erase edges; auto page rop; ji cially straighten; embedded OCR; optimize text/picture (auto); ion; multi-feed detertion; reverse and retry. document edition	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending Tax Tax Tax Specifications Processor speed	USB; Scan to Job Storage; Open Extensibility Platform (OXP, 600 dpi Embedded OCR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m 24-bit / 256 Standard: Scan to Email; scan to network folder; scan to USB drive; scan to SharePoint; scan to FTP; scan to sFTP; scan to LAN fax; scan to Internet Fax; local address book; SMTP over SSL; automatically detect color/monochrome; high compression PDF; image adjustments (darkness, contrast, background cleanup, sharpness); optimize text/picture (text, mixed, printed picture, photograph); content orientation; scan mode (book, 2-sided ID); erase edges; job build; image preview; blank page suppression; automatically straighten; embedded OCR; Optional, 33.6 kbps (fax modem max speed) Fax memory: Up to 500 pages; Fax resolution: Standard: 2C destinations); Telecom compliance: Optional telecom kit (BC (CANADA); ETSI ES 203 021-1 V2.11; ETSI ES 203 021-2 V2. Zealand), Other Telecom approvals as required by individua 1.6 GHz (Quad Core), 1.4 GHz (Dual Core)	(; Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; dor page, barcode); watermark; stamps edia size (ADF): 68 x 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan to to LAN fax; scan to Internet Fax; local address book; Sont compression PDF; image adjustments (darkness, contr mixed, printed picture, photograph); content orientation build; image preview; blank page suppression; automat scan to multi-destination; automatic tone; auto orienta auto paper color removal; job separation (blank page, b Yes, 33.6 kbps (fax modem max speed) 13 x 98 dpi; Fine: 203 x 196 dpi; Superfine: Up to 300 x 30 SIBI-B14-00 / B0ISB-1814-01); TIA-968-B-3; FCC Part 1.2; EFSI ES 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.2; EFSI ES 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.2; EFSI ES 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.2; EFSI ES 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.2; EFSI ESI 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so	ngle pass duplex scanning; Optical scan resolution : Up to 600 : /picture (auto); scan to multi-destination; automatic tone; auto :ument editing; auto paper color removal; job separation (bland : 297 x 420 mm) USB drive; scan to SharePoint; scan to FTP; scan to sFTP; scan P over SSL; automatically detect color/monochrome; high sst, background cleanup, sharpness); optimize text/picture (text ; scan mode (book, 2-sided ID); erase edges; auto page crop; j cically straighten; embedded OCR; optimize text/picture (auto; ically straighten; ically straig	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending Fax	USB; Scan to Job Storage; Open Extensibility Platform (OXP, 600 dpi Embedded OCR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m 24-bit / 256 Standard: Scan to Email; scan to network folder; scan to USB drive; scan to SharePoint; scan to FTP; scan to LAN fax; scan to Internet Fax; local address book; SMTP over SSL; automatically detect color/monochrome; high compression PDF; image adjustments (darkness, contrast, background cleanup, sharpness), optimize text/picture (text, mixed, printed picture, photograph); content orientation; scan mode (book, 2-sided ID); erase edges; job build; image preview; blank page suppression; automatically straighten; embedded OCR; Optional, 33.6 kbps (fax modern max speed) Fax memory: Up to 500 pages; Fax resolution: Standard: 20 destinations); Telecom compliance: Optional telecom kit (BC (CANADA); ETSI ES 203 021-1 V2.11; ETSI ES 203 021-2 V2.	(; Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; dor page, barcode); watermark; stamps edia size (ADF): 68 x 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan to to LAN fax; scan to Internet Fax; local address book; Sont compression PDF; image adjustments (darkness, contr mixed, printed picture, photograph); content orientation build; image preview; blank page suppression; automat scan to multi-destination; automatic tone; auto orienta auto paper color removal; job separation (blank page, b Yes, 33.6 kbps (fax modem max speed) 13 x 98 dpi; Fine: 203 x 196 dpi; Superfine: Up to 300 x 30 SIBI-B14-00 / B0ISB-1814-01); TIA-968-B-3; FCC Part 1.2; EFSI ES 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.2; EFSI ES 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.2; EFSI ES 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.2; EFSI ES 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.2; EFSI ESI 203 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 2.12 (EU); TE-001 Issue 25 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so 1.3; EFSI ESI 201 201 -3 V 201 201 -3 V 201 (so	ngle pass duplex scanning; Optical scan resolution : Up to 600 : /picture (auto); scan to multi-destination; automatic tone; auto rument editing; auto paper color removal; job separation (blan : 297 x 420 mm DSB drive; scan to SharePoint; scan to FTP; scan to SFTP; scan TP over SSL; automatically detect color/monochrome; high sst, background cleanup, sharpness); optimize text/picture (text; ; scan mode (book, 2-sided ID); erase edges; auto page crop; ically straighten; embedded OCR; optimize text/picture (lauto; ically straighten; ically straigh	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending Fax	USB; Scan to Job Storage; Open Extensibility Platform (OXP, 600 dpi Embedded OCR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m 24-bit / 256 Standard: Scan to Email; scan to network folder; scan to USB drive; scan to SharePoint; scan to TFP; scan to STP; scan to LAN fax; scan to Internet Fax; local address book; SMTP over SSL; automatically detect color/monochrome; high compression PDF; image adjustments (darkness, contrast, background cleanup, sharpness); optimize text/picture (text, mixed, printed picture, photograph); content orientation; scan mode (book, 2-sided ID); erase edges; job build; image preview; blank page suppression; automatically straighten; embedded OCR; Optional, 33.6 kbps (fax modem max speed) Fax memory; Up to 500 pages; Fax resolution: Standard: 2C destinations); Telecom compliance: Optional telecom kit (BC (CANADA); ETSI ES 203 021-1 V2.1.1; ETSI ES 203 021-2 V2 Zealand), Other Telecom approvals as required by individua 1.6 GHz (Quad Core), 1.4 GHz (Dual Core) 256 GB SSD	(; Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; dor page, barcode); watermark; stamps eedia size (ADF): 68 × 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan tr to LAN fax; scan to Internet Fax; local address book; SM compression PDF; image adjustments (darkness, contr mixed, printed picture, photograph); content orientation build; image preview; blank page suppression; automat scan to multi-destination; automatic tone; auto orienta auto paper color removal; job separation (blank page, b SIB-1814-00 / BOISB-1814-01); TIA-968-B-3; FCC Part 1 2.1.2; ETSI ES 203 021-3 V2.1.2 (EU); TE-001 Issue 5 (Sou countries	ngle pass duplex scanning; Optical scan resolution : Up to 600 : /picture (auto); scan to multi-destination; automatic tone; auto : 297 x 420 mm DUSB drive; scan to SharePoint; scan to FTP; scan to SFTP; scan TP over SSL; automatically detect color/monochrome; high st, background cleanup, sharpness); optimize text/picture (text); ically straighten; embedded OCR; optimize text/picture (auto; ically straighten; ically	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending Fax	USB; Scan to Job Storage; Open Extensibility Platform (OXP, 600 dpi Embedded OCR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m 24-bit / 256 Standard: Scan to Email; scan to network folder; scan to USB drive; scan to SharePoint; scan to TFP; scan to STP; scan to LAN fax; scan to Internet Fax; local address book; SMTP over SSL; automatically detect color/monochrome; high compression PDF; image adjustments (darkness, contrast, background cleanup, sharpness); optimize text/picture (text, mixed, printed picture, photograph); content orientation; scan mode (book, 2-sided ID); erase edges; job build; image preview; blank page suppression; automatically straighten; embedded OCR; Optional, 33.6 kbps (fax modem max speed) Fax memory; Up to 500 pages; Fax resolution: Standard: 2C destinations); Telecom compliance: Optional telecom kit (BC (CANADA); ETSI ES 203 021-1 V2.1.1; ETSI ES 203 021-2 V2 Zealand), Other Telecom approvals as required by individua 1.6 GHz (Quad Core), 1.4 GHz (Dual Core) 256 GB SSD); Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; dor page, barcode); watermark; stamps eedia size (ADF): 68 × 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan tr to LAN fax; scan to Internet Fax; local address book; SM compression PDF; image adjustments (darkness, contr mixed, printed picture, photograph); content orientation build; image preview; blank page suppression; automat scan to multi-destination; automatic tone; auto orienta auto paper color removal; job separation (blank page, b SIB-1814-00 / BOISB-1814-01); TIA-968-B-3; FCC Part 1 2.1.2; ETSI ES 203 021-3 V2.1.2 (EU); TE-001 Issue 5 (Sou countries	ngle pass duplex scanning; Optical scan resolution : Up to 600 /picture (auto); scan to multi-destination; automatic tone; auto summent editing; auto paper color removal; job separation (blan : 297 x 420 mm DUSB drive; scan to SharePoint; scan to FTP; scan to sFTP; scan to sci background cleanup, sharpness); optimize text/picture (tex s; background cleanup, sharpness); optimize text/picture (tex s; background cleanup, sharpness); optimize text/picture (tex s; scan mode (book, 2-sided ID); erase edges; auto page crop; ically straighten; embedded OCR; optimize text/picture (tex s; scan mode (book, 2-sided ID); erase edges; auto page crop; ically straighten; embedded OCR; optimize text/picture (tex s; scan mode (book, 2-sided ID); erase edges; auto page crop; ically straighten; embedded OCR; optimize text/picture (auto; ically straighten; embedded OCR; optimize text/picture (auto; arcode); watermark; stamps 0 dpi; Quick dialing ; Up to 1000 numbers (each with 210 58 (USA); IC CS-03 Part I Issue 9, Amendment 5, March 2016 ith Africa); AS/CA S002"2010 (Australia); PTC 200:2006 (New	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending Fax Fax Fax Fax Fax Fax Fax Storage Standard Connectivity Standard	USB; Scan to Job Storage; Open Extensibility Platform (0XP, 600 dpi Embedded 0CR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m 24-bit / 256 Standard: Scan to Email; scan to network folder; scan to USB drive; scan to SharePoint; scan to TP; scan to LAN fax; scan to Internet Fax; local address book; SMTP over SSL; automatically detect color/monochrome; high compression PD; image adjustments (darkness, contrast, background cleanup, sharpness); optimize text/picture (text, mixed, printed picture, photograph); content orientation; scan mode (book, 2-sided ID); erase edges; job build; image preview; blank page suppression; automatically straighten; embedded 0CR; Optional, 33.6 kbps (fax modem max speed) Fax memory. Up to 500 pages; Fax resolution: Standard: 2C destinations); Telecom compliance: Optional telecom kit (BC (CANADA); ETSI ES 203 021-1 V2.1.1; ETSI ES 203 021-2 V Zealand), Other Telecom approvals as required by individua 1.6 GHz (Quad Core), 1.4 GHz (Dual Core) 256 GB SSD); Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; dor page, barcode); watermark; stamps eedia size (ADF): 68 × 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan tr to LAN fax; scan to Internet Fax; local address book; SM compression PDF; image adjustments (darkness, contr mixed, printed picture, photograph); content orientation build; image preview; blank page suppression; automat scan to multi-destination; automatic tone; auto orienta auto paper color removal; job separation (blank page, b SIB-1814-00 / BOISB-1814-01); TIA-968-B-3; FCC Part 1 2.1.2; ETSI ES 203 021-3 V2.1.2 (EU); TE-001 Issue 5 (Sou countries	ngle pass duplex scanning; Optical scan resolution : Up to 600 : /picture (auto); scan to multi-destination; automatic tone; auto sument editing; auto paper color removal; job separation (blan : 297 x 420 mm) USB drive; scan to SharePoint; scan to FTP; scan to sFTP- scan TP over SSL; automatically detect color/monochrome; high st, background cleanup, sharpness); optimize text/picture (text); scan mode (book, 2-sided ID); erase edges; auto page crop; ically straighten; embedded OCR; optimize text/picture (text); icon; multi-feed detection; reverse and retry; document editing arcode); watermark; stamps 0 dpi; Quick dialing ; Up to 1000 numbers (each with 210 58 (USA); IC CS-03 Part I Issue 9, Amendment 5, March 2016 th Africa); AS/CA S002"2010 (Australia); PTC 200:2006 (New	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending Fax Fax Fax Fax specifications Processor speed Storage Standard Connectivity Standard Dptional	USB; Scan to Job Storage; Open Extensibility Platform (OXP, 600 dpi Embedded OCR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m 24-bit / 256 Standard: Scan to Email; scan to network folder; scan to USB drive; scan to SharePoint; scan to FTP; scan to LAN fax; scan to Internet Fax; local address book; SMTP over SSL; automatically detect color/monochrome; high compression PDF; image adjustments (darkness, contrast, background cleanup, sharpness); optimize text/picture (text, mixed, printed picture, photograph); content orientation; scan mode (book, 2-sided ED); erase edges; job build; image preview; blank page suppression; automatically straighten; embedded OCR; Optional, 33.6 kbps (fax modem max speed) Fax memory. Up to 500 pages; Fax resolution: Standard: 2C destinations); Telecom compliance: Optional telecom kit (BC (CANADA); ETSI ES 203 021-1 V2.1.1; ETSI ES 203 021-2 V2. Zealand), Other Telecom approvals as required by individua 1.6 GHz (Quad Core), 1.4 GHz (Dual Core) 256 GB SSD 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Inte (host) HP Jetdirect 3100w BLE/NFC/Wireless Accessory 3JN69A); Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; dor page, barcode); watermark; stamps eedia size (ADF): 68 × 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan tr to LAN fax; scan to Internet Fax; local address book; SM compression PDF; image adjustments (darkness, contr mixed, printed picture, photograph); content orientation build; image preview; blank page suppression; automat scan to multi-destination; automatic tone; auto orienta auto paper color removal; job separation (blank page, b SIB-1814-00 / BOISB-1814-01); TIA-968-B-3; FCC Part 1 2.1.2; ETSI ES 203 021-3 V2.1.2 (EU); TE-001 Issue 5 (Sou countries	ngle pass duplex scanning; Optical scan resolution : Up to 600 : /picture (auto); scan to multi-destination; automatic tone; auto sument editing; auto paper color removal; job separation (blan : 297 x 420 mm) USB drive; scan to SharePoint; scan to FTP; scan to sFTP- scan TP over SSL; automatically detect color/monochrome; high st, background cleanup, sharpness); optimize text/picture (text); scan mode (book, 2-sided ID); erase edges; auto page crop; ically straighten; embedded OCR; optimize text/picture (text); icon; multi-feed detection; reverse and retry; document editing arcode); watermark; stamps 0 dpi; Quick dialing ; Up to 1000 numbers (each with 210 58 (USA); IC CS-03 Part I Issue 9, Amendment 5, March 2016 th Africa); AS/CA S002"2010 (Australia); PTC 200:2006 (New	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending Fax Fax Fax specifications Processor speed Storage Standard Connectivity Standard Optional Wireless	USB; Scan to Job Storage; Open Extensibility Platform (OXP. 600 dpi Embedded OCR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m 24-bit / 256 Standard: Scan to Email; scan to network folder; scan to USB drive; scan to SharePoint; scan to FTP; scan to SFTP; scan to LAN fax; scan to Internet Fax; local address book; SMTP over SSL; automatically detect color/monochrome; high compression PDF; image adjustments (darkness, contrast, background cleanup, sharpness); optimize text/picture (text, mixed, printed plank page suppression; automatically straighten; embedded OCR; Optional, 33.6 kbps (fax modern max speed) Fax memory. Up to 500 pages; Fax resolution: Standard: 2C destinations); Telecom compliance: Optional telecom kit (BC (CANADA); ETSI ES 203 021-1 V2.1.1; ETSI ES 203 021-2 V3 Zealand), Other Telecom approvals as required by individua 1.6 GHz (Quad Core), 1.4 GHz (Dual Core) 256 GB SSD 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Inte (host) HP Jetdirect 3100w BLE/NFC/Wireless Accessory 3JN69A Optional, enabled with purchase of a hardware accessory	(; Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; do page, barcode); watermark; stamps eedia size (ADF): 68 × 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan to to LAN fax; scan to Internet Fax; local address book; SM compression PDF; image adjustments (darkness, contri- mixed, printed picture, photograph); content orientation build; image preview; blank page suppression; automat scan to multi-destination; automatic tone; auto orienta auto paper color removal; job separation (blank page, b Yes, 33.6 kbps (fax modem max speed) 33 × 98 dpi; Fine; 203 × 196 dpi; Superfine: Up to 300 × 30 SIB-1814-00 / BOISB-1814-01); TIA-968-B-3; FCC Part 1 2.1.2; ETSI ES 203 021-3 V2.1.2 (EU); TE-001 Issue 5 (So Lountries)	ngle pass duplex scanning; Optical scan resolution : Up to 600 : /picture (auto); scan to multi-destination; automatic tone; auto sument editing; auto paper color removal; job separation (blan : 297 x 420 mm) USB drive; scan to SharePoint; scan to FTP; scan to sFTP- scan TP over SSL; automatically detect color/monochrome; high st, background cleanup, sharpness); optimize text/picture (text); scan mode (book, 2-sided ID); erase edges; auto page crop; ically straighten; embedded OCR; optimize text/picture (text); icon; multi-feed detection; reverse and retry; document editing arcode); watermark; stamps 0 dpi; Quick dialing ; Up to 1000 numbers (each with 210 58 (USA); IC CS-03 Part I Issue 9, Amendment 5, March 2016 th Africa); AS/CA S002"2010 (Australia); PTC 200:2006 (New	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending Fax Fax Fax specifications Processor speed Storage Standard Connectivity Standard Optional Wireless	USB; Scan to Job Storage; Open Extensibility Platform (OXP. 600 dpi Embedded OCR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m 24-bit / 256 Standard: Scan to Email; scan to network folder; scan to USB drive; scan to SharePoint; scan to FTP; scan to LAN fax; scan to Internet Fax; local address book; SMTP over SSL; automatically detect color/monochrome; high compression PD; image adjustments (darkness, contrast, background cleanup, sharpness); optimize text/picture (text, mixed, printed point, scan to Funk page suppression; automatically straighten; embedded OCR; Optional, 33.6 kbps (fax modern max speed) Fax memory; Up to 500 page; Fax resolution: Standard: 2C destinations); Telecom compliance: Optional telecom kit (BC (CANADA); ETSI ES 203 021-1 V2.1.1; ETSI ES 203 021-2 V2 Zealand), Other Telecom approvals as required by individua 1.6 GHz (Quad Core), 1.4 GHz (Dual Core) 256 GB SSD 1 (Gigabit Ethernet 10/100/1000T network; 1 Hardware Inter (host) HP Jetdirect 3100w BLE/NFC/Wireless Accessory 3JN69A Optional, enabled with purchase of a hardware accessory Apple AirPrint™; Mopria™ Certified; Wi-Fi® Direct Printing; P	(; Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; do page, barcode); watermark; stamps eedia size (ADF): 68 × 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan to to LAN fax; scan to Internet Fax; local address book; SM compression PDF; image adjustments (darkness, contr: mixed, printed picture, photograph); content orientation build; image preview; blank page suppression; automat scan to multi-destination; automatic tone; auto orienta auto paper color removal; job separation (blank page, b 3 x 98 dpi; Fine: 203 x 196 dpi; Superfine: Up to 300 x 30 SIB-1814-00 / BOISE-1814-01); TH-968-B-3; FCC Part 2.1.2; ETSI ES 203 021-3 V2.1.2 (EU); TE-001 Issue 5 (So I countries	ngle pass duplex scanning; Optical scan resolution : Up to 600 : /picture (auto); scan to multi-destination; automatic tone; auto rument editing; auto paper color removal; job separation (bland : 297 x 420 mm : 297 x 420 mm : USB drive; scan to SharePoint; scan to FTP; scan to SFTP; scan TP over SSL; automatically detect color/monochrome; high sst, background cleanup, sharpness); optimize text/picture (text); scan mode (book, 2-sided ID); erase edges; auto page crop; ji cally straighten; embedded OCR; optimize text/picture (text); ition; multi-feed detection; reverse and retry; document editing arcode); watermark; stamps 0 dpi; Quick dialing : Up to 1000 numbers (each with 210 S8 (USA); IC CS-03 Part I Issue 9, Amendment 5, March 2016 th Africa); AS/CA S002*2010 (Australia); PTC 200:2006 (New 0 (host); 1 SuperSpeed USB 3.0 (device); 1 SuperSpeed USB 3.	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending Fax Fax Fax Fax specifications Processor speed Storage Standard Connectivity Standard Optional	USB; Scan to Job Storage; Open Extensibility Platform (OXP. 600 dpi Embedded OCR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m 24-bit / 256 Standard: Scan to Email; scan to network folder; scan to USB drive; scan to SharePoint; scan to FTP; scan to LAN fax; scan to Internet Fax; local address book; SMTP over SSL; automatically detect color/monochrome; high compression PD; image adjustments (darkness, contrast, background cleanup, sharpness); optimize text/picture (text, mixed, printed point, scan to Funk page suppression; automatically straighten; embedded OCR; Optional, 33.6 kbps (fax modern max speed) Fax memory; Up to 500 page; Fax resolution: Standard: 2C destinations); Telecom compliance: Optional telecom kit (BC (CANADA); ETSI ES 203 021-1 V2.1.1; ETSI ES 203 021-2 V2 Zealand), Other Telecom approvals as required by individua 1.6 GHz (Quad Core), 1.4 GHz (Dual Core) 256 GB SSD 1 (Gigabit Ethernet 10/100/1000T network; 1 Hardware Inter (host) HP Jetdirect 3100w BLE/NFC/Wireless Accessory 3JN69A Optional, enabled with purchase of a hardware accessory Apple AirPrint™; Mopria™ Certified; Wi-Fi® Direct Printing; P	(; Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; do page, barcode); watermark; stamps eedia size (ADF): 68 × 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan to to LAN fax; scan to Internet Fax; local address book; SM compression PDF; image adjustments (darkness, contr: mixed, printed picture, photograph); content orientation build; image preview; blank page suppression; automat scan to multi-destination; automatic tone; auto orienta auto paper color removal; job separation (blank page, b 3 x 98 dpi; Fine: 203 x 196 dpi; Superfine: Up to 300 x 30 SIB-1814-00 / BOISE-1814-01); TH-968-B-3; FCC Part 2.1.2; ETSI ES 203 021-3 V2.1.2 (EU); TE-001 Issue 5 (So I countries	ngle pass duplex scanning; Optical scan resolution : Up to 600 : /picture (auto); scan to multi-destination; automatic tone; auto rument editing; auto paper color removal; job separation (bland : 297 x 420 mm : 297 x 420 mm : USB drive; scan to SharePoint; scan to FTP; scan to SFTP; scan TP over SSL; automatically detect color/monochrome; high sst, background cleanup, sharpness); optimize text/picture (text); scan mode (book, 2-sided ID); erase edges; auto page crop; ji cally straighten; embedded OCR; optimize text/picture (text); ition; multi-feed detection; reverse and retry; document editing arcode); watermark; stamps 0 dpi; Quick dialing : Up to 1000 numbers (each with 210 S8 (USA); IC CS-03 Part I Issue 9, Amendment 5, March 2016 th Africa); AS/CA S002*2010 (Australia); PTC 200:2006 (New 0 (host); 1 SuperSpeed USB 3.0 (device); 1 SuperSpeed USB 3.	
Scanner advanced features Scannable area Bit depth/ Grey scale levels Digital sending Fax Fax Fax Fax Fax Fax Fax Forcessor speed Storage Standard Connectivity Standard Optional Wireless Mobile printing capability	USB; Scan to Job Storage; Open Extensibility Platform (OXP. 600 dpi Embedded OCR; Automatically straighten Maximum media size (flatbed): 297 x 432 mm; Minimum m 24-bit / 256 Standard: Scan to Email; scan to network folder; scan to USB drive; scan to SharePoint; scan to FTP; scan to LAN fax; scan to Internet Fax; local address book; SMTP over SSL; automatically detect color/monochrome; high compression PD; image adjustments (darkness, contrast, background cleanup, sharpness); optimize text/picture (text, mixed, printed point, scan to Funk page suppression; automatically straighten; embedded OCR; Optional, 33.6 kbps (fax modern max speed) Fax memory; Up to 500 page; Fax resolution: Standard: 2C destinations); Telecom compliance: Optional telecom kit (BC (CANADA); ETSI ES 203 021-1 V2.1.1; ETSI ES 203 021-2 V2 Zealand), Other Telecom approvals as required by individua 1.6 GHz (Quad Core), 1.4 GHz (Dual Core) 256 GB SSD 1 (Gigabit Ethernet 10/100/1000T network; 1 Hardware Inter (host) HP Jetdirect 3100w BLE/NFC/Wireless Accessory 3JN69A Optional, enabled with purchase of a hardware accessory Apple AirPrint™; Mopria™ Certified; Wi-Fi® Direct Printing; P	(; Twain version: Version 2.4; Duplex ADF scanning: Yes, si Embedded OCR; automatically straighten; optimize text orientation; multi-feed detection; reverse and retry; do page, barcode); watermark; stamps eedia size (ADF): 68 × 127 mm Maximum media size (ADF) Standard: Scan to Email; scan to network folder; scan to to LAN fax; scan to Internet Fax; local address book; SM compression PDF; image adjustments (darkness, contr: mixed, printed picture, photograph); content orientation build; image preview; blank page suppression; automat scan to multi-destination; automatic tone; auto orienta auto paper color removal; job separation (blank page, b 3 x 98 dpi; Fine: 203 x 196 dpi; Superfine: Up to 300 x 30 SIB-1814-00 / BOISE-1814-01); TH-968-B-3; FCC Part 2.1.2; ETSI ES 203 021-3 V2.1.2 (EU); TE-001 Issue 5 (So I countries	ngle pass duplex scanning; Optical scan resolution : Up to 600 : /picture (auto); scan to multi-destination; automatic tone; auto rument editing; auto paper color removal; job separation (blank : 297 x 420 mm DSB drive; scan to SharePoint; scan to FTP; scan to sFTP; scan TP over SSL; automatically detect color/monochrome; high sst, background cleanup, sharpness); optimize text/picture (text; ; scan mode (book, 2-sided ID); erase edges; auto page crop; j cially straighten; embedded OCR; optimize text/picture (auto; icially straighten; icially s	

	HP Color LaserJet Enterprise MFP 8801dn	HP Color LaserJet Enterprise Flow MFP 8801z	HP Color LaserJet Enterprise Flow MFP 8801z+		
Product number	9S184A	9S183A	AQ1E2A		
Media handling	-		-		
Number of paper trays	Standard: 5 ; Maximum: 5				
Media types	Plain, HP EcoEFICIENT, HP Matte 90 g, Light 60-74 g, Bond, Recycled, HP Matte 105 g, HP Matte 120 g, HP Soft Gloss 120 g, HP Glossy 120 g, Mid-Weight 96-110 g, Heavy 111-130 g, MP Matte 150 g, HP Glossy 150 g, Extra Heavy 131-175 g, XHvyGlossy 131-175 g, HP Matte 200 g, HP Glossy 200 g, Card-sto 176-220 g, Card Glossy 176-220 g, Light Paperboard 221-255 g, Paperboard 256-300 g, Heavy Paperboard, Color Transparency, Labels, Letterhead, Envelope, Heavy Envelope, Preprinted, Pre-punched, Colored				
Media size	Custom (metric): Tray 1: 98 x 139.7 to 320 x 457.2 mm; Tray 2: 98 x 139.7 to 297 x 241.5 mm; Tray 3: 140 x 182 to 320 x 457.2 mm; Tray 4: 140 x 182 to 320 x 457.2 mm; Supported (metric): Tray 1: A3, A4, A4R, A5, A5R, A6, RA3, SRA3, RA4, SRA4, SRA4, SRA4, SB (UIS), B5 (UIS), B6 (UIS), 10 x 15 cm, Oficio, 8K, 16k, Postcard (UIS), Postcard (UIS), Envelope E5, Envelope C6, Envelope DL; Tray 2: A4, A4R, A5, A5R, A6, RA4, RA4, SA4, A64, RA5, B5 (UIS), B6 (UIS), Oficio, 8K, 16k, Envelope B5, Envelope C6, Envelope DL; Tray 2: A4, A4R, A5, A5R, A6, RA4, RA4, B4 (UIS), B5 (UIS), 06(UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), B6 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), B6 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, B4 (UIS), B5 (UIS), Oficio, 8K, 16k; Tray 5: A3, A4, A4R, A5, RA3, RA4, A5, RA3, RA				
Media handling ³	Standard input: 100-sheet multi-purpose tray, 4 x 520- sheet input tray Standard output: Up to 500 sheets ADF: Standard, 200 sheets	Standard input: 100-sheet multi-purpose tray, 4 x 520- sheet input tray Standard output: Up to 500 sheets ADF: Standard, 300 sheets	Standard input: 100-sheet multi-purpose tray, 4 x 520- sheet input tray Standard output: Up to 3,250 sheets ADF: Standard, 300 sheets		
Media weight	Tray 1, 2, 3: 60 to 325 g/m ² ; Tray 4, 5: 60 to 300 g/m ² ; ADF: 45 to 199 g/m ²	Tray 1, 2, 3: 60 to 325 g/m² ; Tray 4, 5: 60 to 300 g/m²; AD	F : 45 to 255 g/m ²		
Input capacity	Standard: 100-sheet multi-purpose tray, 4 x 520-sheet input tray Up to 2,180 sheets (Tray 1: up to 100 sheets; Tray 2: up to 520 sheets; Tray 3: up to 520 sheets; Tray 4: sheets; Tray 5: up to 520 sheets) Up to 50 envelopes ; Maximum: Up to 2,180 sheets				
Output capacity	Standard: Up to 500 sheets Envelopes: Up to 40 envelopes Transparencies: Up to 100 sheets Maximum: Up to 500 sheets		Standard: Up to 3,250 sheets Envelopes: Up to 40 envelopes Transparencies: Up to 100 sheets Maximum: Up to 3,250 sheets		
Compatible operating systems	Windows 11; Windows 10; Windows Client OS; Android; iOS	; Mobile OS; macOS 13 Ventura; MacOS v14 Sonoma; macOS	12 Monterey; Windows 8.1		
Compatible network operating systems	Windows Server; Linux; Citrix				
Minimum system requirements	Windows: 2 GB available hard disk space, Internet connection, or USB port, Internet browser. For additional OS hardware requirements see microsoft.com; Mac: 2 GB available hard drive space; Internet connection or USB port; Internet browser. For additional OS hardware requirements see apple.com				
Software included	No software solutions are included in the Box only on http:/	//hp.com, https://support.hp.com/			
Security management	Identity management: Kerberos authentication, LDAP authentication, 1000 user PIN codes, Optional HP and 3rd party advanced authentication solutions (e.g., badge readers): Network: IPsec/firewall with Certificate/Pre-shared Key authentication, Supports WJA-10 IPsec configuration Plug-in, 802.1X authentication (EAP-PEAP; EAP-TLS), SNMPv3, HTTPS Certificates; Data: Storage Encryption, Encrypted PDF & Email, SSL/TLS (HTTPS), Encrypted Credentials; Device: HP Sure Start Secure Boot (BIOS Integrity Checking with Self-healing capability), Intrusion Detection (Constant in-device monitoring for attacks), Whitelisting (loads only known good code), HP Memory Shield [™] , Embedded Trusted Platform Module, H Connection Inspector, Security lock slot, USB port disablement; Security management: Compatible with HP Security Manager, Device Security Syslog Messages processed and accessible in Arcsight and Splunk SIEMs				
Printer management	HP Web JetAdmin Software, HP Security Manager, HP SNMF Resource Kit for HP Universal Print Driver (Driver Configurat	P Proxy Agent (Part of HP WebJetAdmin), HP WS Pro Proxy Ag ion, Utility - Driver, Deployment Utility - Managed Printing Ad	ient (Part of HP WebJetAdmin), Printer Administrator ministrator)		
Dimensions and weight					
Printer dimensions (W × D × H)	Minimum 585 x 695 x 1158 mm; Maximum: 1083.5 x 1308.1 x 1486.7 mm	Minimum 585 x 695 x 1189 mm; Maximum: 1083.5 x 1308.1 x 1500.5 mm	Minimum 1293 x 695 x 1189 mm; Maximum : 1677.2 x 1308.1 x 1500.5 mm		
Package dimensions (W x D x H)	890 x 972 x 1364 mm	890 x 972 x 1394 mm	1,565 x 972 x 1,418 mm		
	890 x 972 x 1364 mm 127.61 kg	131.41 kg	171.63 kg		
Printer weight ⁹ Package weight	127.61 kg 167.11 kg				
Printer weight ⁹ Package weight Operating environment	127.61 kg 167.11 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH	131.41 kg	171.63 kg		
Printer weight ⁹ Package weight Operating environment	127.61 kg 167.11 kg	131.41 kg	171.63 kg 237.73 kg		
Package dimensions (W x D x H) Printer weight ⁹ Package weight Operating environment Storage conditions Acoustics ⁸	127.61 kg 167.11 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH	131.41 kg 170.91 kg	171.63 kg		
Printer weight ⁹ Package weight Operating environment Storage conditions Acoustics ⁸	127.61 kg 167.11 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 6.9 B(A) (printing color simplex A (printing color simplex A4 at 60 ppm) Requirements: Input voltage: 110 to 127 VAC (+/-10%), 50/ dual voltage, power supply varies by part number with # 0	131.41 kg 170.91 kg 44 at 60 ppm); Acoustic pressure emissions : 54 dB(A) /60 Hz (+/-3 Hz), 12.0 A 220 to 240 VAC (+/-10%), 50/60 Hz	171.63 kg 237.73 kg Acoustic power emissions: 7.2 B(A) (printing color simplex A4 at 60 ppm); Acoustic pressure emissions: 57 dB(A) (printing color simplex A4 at 60 ppm) (+/-3 Hz), 7.0 A 100 VAC (+/-10%), 50/60 Hz (+/-3 Hz), (Not		
Printer weight ⁹ Package weight Operating environment Storage conditions	127.61 kg 167.11 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 6.9 B(A) (printing color simplex A (printing color simplex A4 at 60 ppm) Requirements: Input voltage: 110 to 127 VAC (+/-10%), 50, dual voltage, power supply varies by part number with # 0r Consumption: 1,013.14 watts (printing), 36.29 watts (read, Typical Electricity Consumption (TEC): 0.901 KW/Week; 1	131.41 kg 170.91 kg A4 at 60 ppm); Acoustic pressure emissions : 54 dB(A) /60 Hz (+/-3 Hz), 12.0 A 220 to 240 VAC (+/-10%), 50/60 Hz stion code identifier) ;	171.63 kg 237.73 kg Acoustic power emissions: 7.2 B(A) (printing color simplex A4 at 60 ppm); Acoustic pressure emissions: 57 dB(A) (printing color simplex A4 at 60 ppm) (+/-3 Hz), 7.0 A 100 VAC (+/-10%), 50/60 Hz (+/-3 Hz), (Not		
Printer weight ⁹ Package weight Operating environment Storage conditions Acoustics ⁸ Power	127.61 kg 167.11 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 6.9 B(A) (printing color simplex Af (printing color simplex A4 at 60 ppm) Requirements: Input voltage: 110 to 127 VAC (+/-10%), 50/ dual voltage, power supply varies by part number with # 0 Consumption: 1,013.14 watts (printing), 36.29 watts (read) Typical Electricity Consumption (TEC): 0.901 kWh/Week ; Power supply type: Internal (Built-in) power supply Power save CISPR 22:2008 (International) - Class A, CISPR 32:2015 (Int	131.41 kg 170.91 kg 44 at 60 ppm); Acoustic pressure emissions: 54 dB(A) /60 Hz (+/-3 Hz), 12.0 A 220 to 240 VAC (+/-10%), 50/60 Hz ation code identifier) ; y), 0.74 watts (sleep), 0.12 watts (auto-off), 0.12 watts (manu ernational) - Class A, EN 55032: 2015 (EU) - Class A, CISPR 1 017+A11:2020, EN60601-1-2:2015, EMC Directive 2014/30, STAR® certified	171.63 kg 237.73 kg Acoustic power emissions: 7.2 B(A) (printing color simplex A4 at 60 ppm); Acoustic pressure emissions: 57 dB(A) (printing color simplex A4 at 60 ppm) (+/-3 Hz), 7.0 A 100 VAC (+/-10%), 50/60 Hz (+/-3 Hz), (Not Jal-off); 1:2016, EN 55011:2016, EN 61000-3-2: 2019, EN 61000-3-		
Printer weight ⁹ Package weight Operating environment Storage conditions Acoustics ⁸ Power Energy savings feature technology Certifications	127.61 kg 167.11 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 6.9 B(A) (printing color simplex A (printing color simplex A4 at 60 ppm) Requirements: Input voltage: 110 to 127 VAC (+/-10%), 50/ dual voltage, power supply varies by part number with # 0p Consumption: 1,013.14 watts (printing), 36.29 watts (ready Typical Electricity Consumption (TEC): 0.901 kWh/Week ; Power supply type: Internal (Built-in) power supply Power save CISPR 22:2008 (International) - Class A, CISPR 32:2015 (Int 3: 2013+A1:2019, EN 55024: 2010+A1:2015, EN 55035:20 Class A, Other EMC approvals as required by individual coun IT ECD Declaration; Blue Angel; EPAT® registered; ENERGY	131.41 kg 170.91 kg 170.91 kg 44 at 60 ppm); Acoustic pressure emissions: 54 dB(A) /60 Hz (+/-3 Hz), 12.0 A 220 to 240 VAC (+/-10%), 50/60 Hz yition code identifien ; y), 0.74 watts (sleep), 0.12 watts (auto-off), 0.12 watts (manu remational) - Class A, EN 55032: 2015 (EU) - Class A, CISPR 1 017+A11:2020, EN60601-1-2:2015, EMC Directive 2014/30, STAR® certified sured when using Original HP supplies	171.63 kg 237.73 kg Acoustic power emissions: 7.2 B(A) (printing color simplex A4 at 60 ppm); Acoustic pressure emissions: 57 dB(A) (printing color simplex A4 at 60 ppm) (+/-3 Hz), 7.0 A 100 VAC (+/-10%), 50/60 Hz (+/-3 Hz), (Not Jal-off); 1:2016, EN 55011:2016, EN 61000-3-2: 2019, EN 61000-3		
Printer weight ⁹ Package weight Operating environment Storage conditions Acoustics ⁸ Power Energy savings feature technology Certifications Sustainable impact specifications	127.61 kg 167.11 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 6.9 B(A) (printing color simplex A (printing color simplex A4 at 60 ppm) Requirements: Input voltage: 110 to 127 VAC (+/-10%), 50, dual voltage, power supply varies by part number with # 0p Consumption: 1,013.14 watts (printing), 36.29 watts (ready Typical Electricity Consumption (TEC): 0.901 Kwh/Week ; Power supply type: Internal (Built-in) power supply Power save CISPR 22:2008 (International) - Class A, CISPR 32:2015 (Int 3: 2013+A1:2019, EN 55024: 2010+A1:2015, EN 55035:20 (class A, Other EMC approvals as required by individual coun T ECO Declaration; Blue Angel DE-HTa* Pergistered; LENERGY Blue Angel compliant Yes, Blue Angel DE-UZ 219—only ens FSC Certified Packaging; 10% post-consumer recycled plast	131.41 kg 170.91 kg 170.91 kg A4 at 60 ppm); Acoustic pressure emissions: 54 dB(A) /60 Hz (+/-3 Hz), 12.0 A 220 to 240 VAC (+/-10%), 50/60 Hz obtion code identifier); y), 0.74 watts (sleep), 0.12 watts (auto-off), 0.12 watts (manufilm), 0.74 watts (sleep), 0.12 watts (auto-off), 0.12 watts (manufilm) ernational) - Class A, EN 55032: 2015 (EU) - Class A, CISPR 1 017+A11:2020, EN60601-1-2:2015, EMC Directive 2014/30, STAR® certified sured when using Original HP supplies tic 0); HP 225A Cyan LJ Toner Cartridge W2251A (ISO Yield 40,0	171.63 kg 237.73 kg Acoustic power emissions: 7.2 B(A) (printing color simplex A4 ta 60 ppm); Acoustic pressure emissions: 57 dB(A) (printing color simplex A4 at 60 ppm) (+/-3 Hz), 7.0 A 100 VAC (+/-10%), 50/60 Hz (+/-3 Hz), (Not Jal-off); 1:2016, EN 55011:2016, EN 61000-3-2: 2019, EN 61000-3-2: 2019, EN 61000-3-2: 2020 FCC CFR 47 Part 15 Class A / ICES-003, Issue 7:2020		
Printer weight ⁹ Package weight Operating environment Storage conditions Acoustics ⁸ Power Energy savings feature technology	127.61 kg 167.11 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 6.9 B(A) (printing color simplex A (printing color simplex A4 at 60 ppm) Requirements: Input voltage: 110 to 127 VAC (+/-10%), 50/ dual voltage, power supply varies by part number with # 0 Consumption: 1,013.14 watts (printing), 36.29 watts (read) Typical Electricity Consumption (TEC): 0.901 kWh/Week ; Power supply type: Internal (Built-in) power supply Power save CISPR 22:2008 (International) - Class A, CISPR 32:2015 (Int 3: 2013+A1:2019, EN 55024: 2010+A1:2015, EN 55035:21 Class A, Other EMC approvals as required by individual coun IT ECO Declaration; Blue Angel; EPEAT® registered; ENERGY Blue Angel compliant Yes, Blue Angel DE-UZ 219—only ens FSC Certified Packaging; 10% post-consumer recycled plast HP 225A Black LJ Toner Cartridge W2250A (ISO Yield 45,00 40,000); HP 225A Magenta LJ Toner Cartridge W2253A (ISC) Installation guide; regulatory flyer; power cords; keyboard/c	131.41 kg 170.91 kg 170.91 kg 14 at 60 ppm); Acoustic pressure emissions: 54 dB(A) /60 Hz (+/-3 Hz), 12.0 A 220 to 240 VAC (+/-10%), 50/60 Hz vition code identifier); /), 0.74 watts (sleep), 0.12 watts (auto-off), 0.12 watts (manufacture); ernational) - Class A, EN 55032: 2015 (EU) - Class A, CISPR 1 1017+A11:2020, EN60601-1-2:2015, EMC Directive 2014/30, strifes STAR® certified sured when using Original HP supplies tic 0); HP 225A Cyan LJ Toner Cartridge W2251A (ISO Yield 40,00) sverlay for z/z+; manual	171.63 kg 237.73 kg Acoustic power emissions: 7.2 B(A) (printing color simplex A4 at 60 ppm); Acoustic pressure emissions: 57 dB(A) (printing color simplex A4 at 60 ppm) (+/-3 Hz), 7.0 A 100 VAC (+/-10%), 50/60 Hz (+/-3 Hz), (Not Jal-off); 1:2016, EN 55011:2016, EN 61000-3-2: 2019, EN 61000-3 /EU, FCC CFR 47 Part 15 Class A / ICES-003, Issue 7:2020 000); HP 225A Yellow LJ Toner Cartridge W2252A (ISO Yield		
Printer weight ⁹ Package weight Operating environment Storage conditions Acoustics ⁸ Power Energy savings feature technology Certifications Sustainable impact specifications Replacement cartridges ⁷	127.61 kg 167.11 kg Temperature: 15 to 30°C; Humidity: 20 to 80% RH Temperature: -10 to 40°C Acoustic power emissions: 6.9 B(A) (printing color simplex A (printing color simplex A4 at 60 ppm) Requirements: Input voltage: 110 to 127 VAC (+/-10%), 50/ dual voltage, power supply varies by part number with # 0 Consumption: 1,013.14 watts (printing), 36.29 watts (read) Typical Electricity Consumption (TEC): 0.901 kWh/Week ; Power supply type: Internal (Built-in) power supply Power save CISPR 22:2008 (International) - Class A, CISPR 32:2015 (Int 3: 2013+A1:2019, EN 55024: 2010+A1:2015, EN 55035:21 Class A, Other EMC approvals as required by individual coun IT ECO Declaration; Blue Angel; EPEAT® registered; ENERGY Blue Angel compliant Yes, Blue Angel DE-UZ 219—only ens FSC Certified Packaging; 10% post-consumer recycled plast HP 225A Black LJ Toner Cartridge W2250A (ISO Yield 45,00 40,000); HP 225A Magenta LJ Toner Cartridge W2253A (ISC) Installation guide; regulatory flyer; power cords; keyboard/c	131.41 kg 170.91 kg 170.91 kg 44 at 60 ppm); Acoustic pressure emissions: 54 dB(A) /60 Hz (+/-3 Hz), 12.0 A 220 to 240 VAC (+/-10%), 50/60 Hz stion code identifier); y), 0.74 watts (sleep), 0.12 watts (auto-off), 0.12 watts (manu ernational) - Class A, EN 55032: 2015 (EU) - Class A, CISPR 1 017+A11:2020, EN60601-1-2:2015, EMC Directive 2014/30, STAR® certified sured when using Original HP supplies tic 0); HP 225A Cyan LJ Toner Cartridge W2251A (ISO Yield 40,0 20) verlay for z/z+; manual W2250AS, HP 225A Cyan LJ Starter Toner Cartridge (ISO Yiel	171.63 kg 237.73 kg Acoustic power emissions: 7.2 B(A) (printing color simplex A4 at 60 ppm); Acoustic pressure emissions: 57 dB(A) (printing color simplex A4 at 60 ppm) (+/-3 Hz), 7.0 A 100 VAC (+/-10%), 50/60 Hz (+/-3 Hz), (Not Jal-off); 1:2016, EN 55011:2016, EN 61000-3-2: 2019, EN 61000-3 /EU, FCC CFR 47 Part 15 Class A / ICES-003, Issue 7:2020 000); HP 225A Yellow LJ Toner Cartridge W2252A (ISO Yield		

Footnotes

¹ The HP Laser Jet Enterprise 8801/8601/8501 printer series is the top-tier model in our HP Enterprise portfolio, featuring the highest print and scan speeds, along with advanced printing solutions for easy print management. ² Only available on z, z+.

³ Some features enabled by future HP FutureSmart firmware upgrades may not be available on older devices, if for example, physical product characteristics limit the functionality of the new feature.

⁴ Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.

⁵ Measured using ISO/IEC 24734, excludes first set of test documents. For more information, see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

⁶ HP Security is now HP Wolf Security. Security features vary by platform, please see product data sheet for details. HP's most advanced embedded security features are available on HP Managed and Enterprise devices with HP FuturesMart firmware 4.5 or above. Claim based on HP review of 2024 published features of competitive in-class printers. Only HP offers multiple security features that automatically detect, stop, and recover from attacks with a self-healing reboot in alignment with NIST SP 800-193 guidelines for device cyber resiliency. For a list of compatible products, visit: hp.com/go/PrintersThatProtect. For more information, visit: hp.com/go/PrintersCurityClaims. HP Security Manager must be purchased separately. To learn more, please visit hp.com/go/securitymanager. Post Quantum Cryptography (PQC): Based on HP's internal analysis of business Printers with preinstalled encryption, authentication, malware protection, and BIOS-level protection with automatic self-healing recovery finding that no other in-class Printers implement a quantum-resistant cryptographic scheme to protect the integrity of the BIOS as of 2025. PQC will be available in Fall'25 with Firmware 25.9.2.2+.

⁷ Use of the HP Trusted Platform Module may require a firmware upgrade.

⁸ HP voluntarily designs and tests its printing systems to prevent emissions that exceed Blue Angel and EPEAT eco-label guidelines. Based on US, Canada, India, and Australia EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit www.epeat.net for more information. ENERGY STAR and the ENERGY STAR logo are registered U.S. marks. HP printer, HP paper and Original HP supply - Blue Angel DE-UZ 219 Emissions Criteria.

⁹ Program availability varies. For more information, visit hp.com/hprecycle.

¹⁰ HP works collaboratively with our partners including WWF and Conservation International to manage, restore, and protect forests in many countries around the world. With HP, every print—regardless of paper brand—is addressed through HP's Forest Positive Framework to counteract risks of deforestation. To learn more visit hp.com/forestfirst.

¹¹ HP Web Jetadmin is free and available for download at hp.com/go/webjetadmin.

¹² See hp.com/go/TonerRecycledContent for list. Post-consumer recycled is based on the definition set in the EPEAT standard for imaging equipment, and is expressed as percent of total weight of plastic.

Technical specifications disclaimers

¹ Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software

² Based on HP internal evaluation measuring the time beginning from scan start to print page exit. Exact speed varies depending on the system configuration, software application, driver, and document complexity. Additionally, for information of First Copy Out measured using ISO/IEC 29183, see http://www.hp.com/go/printerclaims.

³ ADF Capacity is defined based on 75 g/m² paper.

⁴ For Scan software, we support PDF, JPEG, PNG, BMP, TIF, Text(.txt), Rich Text(.txt), Searchable PDF(.pdf), PDF/A(.pdf), Word(*.doc), Word(*.doc), Excel(.xlsx), Excel(.xlsx), CSV(.csv), XML(.xml)

⁵ Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

⁶ Based on HP internal evaluation measuring the time from print initiation to page exit. Exact speed varies depending on the system configuration, software application, driver, and document complexity. Additionally, for

information of First Page Out measured using ISO/IEC 17629, see hp.com/go/printer claims. ⁷ Approximate average yield based on ISO/IEC 19798. Actual yield varies considerably based on content of printed pages and other factors. For details, see http://www.hp.com/go/learnaboutsupplies.

⁸ Acoustic values are subject to change. For current information see http://www.hp.com/support

⁹ Including Starter toner cartridge weight



The product could differ from the images shown. © 2014 Hewlett-Packard Development Company, L.P. The Information contained herein is subject to change without notice. Warranties for HP products and services are set out in the express warranty statements accompanying such products and services. In addition, our products and services come with guarantees that cannot be excluded under the Australian Consumer Law. Subject to the foregoing, nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.