



34” curved ultra-wide screen with 15cm height adjustable stand

The ProLite XCB3494WQSU is a 34-inch curved monitor with a VA panel, delivering high contrast, deep blacks, and wide viewing angles for consistent image quality from any perspective. UWQHD (Ultra-Wide QHD) resolution provides an ultra-wide (21:9) viewable area. The large amount of screen space and good pixel density make it very suitable for those who want to use side-by-side applications, watch widescreen content or enhance their gaming experience.

For added comfort and flexibility, the 150mm height-adjustable stand allows you to adjust the screen position to your preference. Additionally, flicker-free technology and a blue light reducer function reduces eye fatigue.



VA

VA panel technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.



KRYTÝ NÁVRH 1500R

01 CHARAKTERISTIKA OBRAZU

Design	curved
Úhlopříčka monitoru	34", 86.7cm
Panel	VA panel, matte finish
Zakřivení	1500R
Nativní rozlišení	3440 x 1440 @120Hz (4.9 megapixel UWQHD, DisplayPort)
Formát obrazu	21:9
Jas	350 cd/m²
Kontrast	3000:1
Pokročilý kontrast	80M:1
Čas rekace (MPRT)	0.4ms
Úhel sledování	horizontální/vertikální: 178°/178°, na parvo/na lefo: 89°/89°, nahoru/dolů: 89°/89°
Barevná podpora	16.7mln (sRGB: 99%; NTSC: 93%)
Horizontalfrequenz	30 - 180kHz
Arbeitsfläche H x B	797.2 x 333.7mm, 31.3 x 13.1"
Velikost bodů	0.232mm
Barva rámu	matná, černá

02 ROZHRANÍ / KONEKTORY / OVLÁDÁNÍ

Vstupní porty	HDMI x2 (1x v.2.0 and 1x v. 1.4, 3440x1440 @100Hz, 2560x1440 @120Hz) DisplayPort x1 (v.1.4, 3440 x 1440 @120Hz)
USB HUB	x4 (2x Type A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type C (5Gbps, 7.5W))
HDCP	ano
Konektor pro sluchátka	ano

03 VLASTNOSTI

Redukce modrého světla	ano
Flicker Free LED	ano
Adaptive Sync support	FreeSync Premium - HDMI: 2560 x 1440 @48-120Hz, DP: 3440 x 1440 @48-120Hz
Extra	i-Style Colour
Jazyky OSD	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Kontrolní tlačítka	Joystick: Power/Menu (Centre), Forward/Signal Select, Backward, Left/i-Style colour/ECO/BlueLigt Reducer, Right/Volume
Nastavitelné parametry	picture adjust (brightness, contrast, Eco, ACR, OD, AdaptiveSync, motion blur reduction, X-Res technology, black tuner), colour settings (6-axis, i-Style colour, blue light reducer, gamma, RGB range, colour temp.,), OSD (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI control, display information), language, miscellaneous (sharpness, video mode adjust, opening logo, power LED, USB charge, USB C speed), input select, audio settings (volume, mute audio), recall
Reproduktory	2 x 5W
Výhoda	Kensington-lock™ připraven, DDC2B

04 MECHANICKÉ ČÁSTI

Úpravy polohy	výška, swivel, náklon
Výškově nastavitelné	150mm
Úhel otočení	90°; 45° na lefo; 45° na parvo

Úhel náklonu	23° nahoru; 5° dolů
VESA	100 x 100mm
Systém správy kabelů	ano

05 ZAHRNUTÉ PŘÍSLUŠENSTVÍ

Kabely	napájecí, USB, HDMI, DP
Ostatní	uživatelský manuál, instrukce bezpečnosti

06 POWER-MANAGEMENT

Napájecí zdroj:	interní
Napájení	AC 100 - 240V, 50/60Hz
Odběr energie	32W default , 0.5W odpočinek, 0.3W vypnutý
Odběr energie:	0.5W odpočinek

07 UDRŽITELNOST

Předpisy	TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
Energetická třída (Regulation (EU) 2017/1369)	F
EPEAT Silver	*registration varies by country, go to www.epeat.net for details

08 ROZMĚRY / HMOTNOST

Rozměry výrobku Š x V x D	807 x 426 (576) x 245.5mm
Rozměry balení Š x V x D	928 x 480 x 186mm
Váha (bez balení)	9.7kg
Váha (s balením)	13.8kg
EAN code	4948570125135



Všechny ochranné známky jsou registrovány a chráněny. Vyhrazené právo na změny. Veškeré ploché panely LCD splňují normu ISO-9241-307:2008 v oblasti počtu vadných pixelů.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED