HP ZBook Fury G1i 16 inch Mobile Workstation PC



Left

1	ACS & ALS Sensor	9	Security lock slot (Integrated)
2	Microphone (2)	10	RJ45 Ethernet port (standard)
3	IR Camera (optional)	11	USB Type-A 10Gbps signaling rate
4	Webcam	12	Thunderbolt™ 4 with USB Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1)*
5	Camera Shutter		
6	IR LEDS (optional)	13	Headphone/mic combo jack
7	Webcam LED	14	Smart Card Reader
8	Fingerprint reader / Power button	15	3-button Touchpad

*Actual throughout may vary.



Right

1	Power Indicator LED	4	HDMI 2.1
2	Power connector	5	SD Card Reader
3	2 Thunderbolt™ 5 with USB Type-C® 80Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1)* *Actual throughout may vary.		

PRODUCT NAME

HP ZBook Fury G1i 16 inch Mobile Workstation PC

OPERATING SYSTEM

Preinstalled OS

FreeDOS

Ubuntu Linux 24.04

Windows 11 Pro[1]

Windows 11 Home - HP recommends Windows 11 Pro for business[1]

Windows 11 Home Single Language - HP recommends Windows 11 Pro for business[1]

Windows 11 Pro (Windows 11 Enterprise available with a Volume Licensing Agreement)[1]

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See http://www.windows.com

NOTE: Your product does not support Windows 8 or Windows 7. In accordance with Microsoft's support policy, HP does not support the Windows® 8 or Windows 7 operating system on products configured with Intel® and AMD® 7th generation and forward processors or provide any Windows® 8 or Windows 7 drivers on http://www.support.hp.com. A full list of HP products and the Windows 10 versions tested is available on the HP support website. https://support.hp.com/us-en/document/c05195282

PROCESSOR

Intel® Core™ Ultra 9 Processor 285HX with Intel® Graphics and Intel® AI Boost (13 NPU TOPS), (2.1 GHz E-core base frequency, 2.8 GHz P-core base frequency, up to 4.6 GHz E-core Max Turbo frequency, up to 5.5 GHz P-core Max Turbo frequency, 36MB Cache, 8 P-cores and 16 E-cores, 24 threads), supports Intel vPro® Enterprise [1,2,3,4,5,6]

Intel® Core™ Ultra 7 Processor 265HX with Intel® Graphics and Intel® AI Boost (13 NPU TOPS),(2.3 GHz E-core base frequency, 2.6 GHz P-core base frequency, up to 4.6 GHz E-core Max Turbo frequency, up to 5.3 GHz P-core Max Turbo frequency, 30MB Cache, 8 P-cores and 12 E-cores, 20 threads), supports Intel vPro® Enterprise [1,2,3,4,5,6]

Intel® Core™ Ultra 7 Processor 255HX with Intel® Graphics and Intel® AI Boost (13 NPU TOPS), (1.8 GHz E-core base frequency, 2.4 GHz P-core base frequency, up to 4.5 GHz E-core Max Turbo frequency, up to 5.2 GHz P-core Max Turbo frequency, 30MB Cache, 8 P-cores and 12 E-cores, 20 threads) [1,2,3,4,5,6]

Intel® Core™ Ultra 5 Processor 245HX with Intel® Graphics and Intel® AI Boost (13 NPU TOPS),(2.6 GHz E-core base frequency, 3.1 GHz P-core base frequency, up to 4.5 GHz E-core Max Turbo frequency, up to 5.1 GHz P-core Max Turbo frequency, 24MB Cache, 6 P-cores and 8 E-cores, 14 threads), supports Intel vPro® Enterprise [1,2,3,4,5,6]

Intel® Core™ Ultra 9 290HX Plus (up to 5.5 GHz with Intel® Turbo Boost Technology, 36 MB L3 cache, 24 cores, 24 threads) with Intel® Graphics and Intel® AI Boost (13 NPU TOPS) [1,2,3,4,5,6]

Intel® Core™ Ultra 7 270HX Plus (up to 5.3 GHz with Intel® Turbo Boost Technology, 30 MB L3 cache, 20 cores, 20 threads) with Intel® Graphics and Intel® AI Boost (13 NPU TOPS) [1,2,3,4,5,6]

1. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.
2. Intel Turbo Boost performance varies depending on hardware, software and overall system configuration. See http://www.intel.com/technology/turboboost for more information.
3. Intel vPro® requires Windows 10 Pro 64 bit or higher, a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN and/or Wi-Fi 6E WLAN and TPM 2.0. Some functionality requires additional 3rd party software in order to run. Features of vPro® Essentials and Enterprise vary. See http://intel.com/vpro
4. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on http://www.support.hp.com .
5. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.
6. Features and software that require a NPU may require software purchase, subscription or enablement by a software or platform provider, and third-party software may have specific configuration or compatibility requirements. Performance varies by use, configuration, and other factors.

GRAPHICS

Integrated

Intel® Graphics

Discrete

NVIDIA RTX PRO 5000 Blackwell Generation Laptop GPU (24 GB GDDR7 dedicated);
NVIDIA RTX PRO 4000 Blackwell Generation Laptop GPU (16 GB GDDR7 dedicated);
NVIDIA RTX PRO 3000 Blackwell Generation Laptop GPU (12 GB GDDR7 dedicated);
NVIDIA RTX PRO 2000 Blackwell Generation Laptop GPU (8 GB GDDR7 dedicated);
NVIDIA RTX PRO 1000 Blackwell Generation Laptop GPU (8 GB GDDR7 dedicated);

Supports

RTX PRO 5000 / RTX PRO 4000 / RTX PRO 3000 Support Memory ECC
DP 2.1, HDMI 2.1b
Supports CUDA, Dynamic Boost

DISPLAY

Non-Touch

40.6 cm (16") diagonal, (2560 x 1600), 120 Hz, UWVA, anti-glare, Low Blue Light, 400 nits, 100% sRGB

40.6 cm (16") diagonal, WQUXGA, (3840 x 2400), 120 Hz, UWVA, anti-glare, 500 nits, 100% DCI-P3

40.6 cm (16") diagonal, WUXGA (1920 x 1200), UWVA, anti-glare, Low Blue Light, 800 nits, 100% sRGB, HP Sure View integrated privacy screen

40.6 cm (16") diagonal, WUXGA (1920 x 1200), UWVA, anti-glare, Low Blue Light, 400 nits, low power, 100% sRGB

Touch

40.6 cm (16") diagonal, WUXGA (1920 x 1200), touch, UWVA, BrightView, Low Blue Light, 400 nits, low power, 100% sRGB

40.6 cm (16") diagonal, WQUXGA (3840 x 2400), OLED, touch, BrightView, eDP + PSR, micro-edge, Low Blue Light,400 nits, 100% DCI-P31,3,4,5

Displays support

Supports up to 4 displays through the HP Thunderbolt 280W G4 Dock

Display Size

16.0"

40.64 cm (16")

DOCKING (Sold Separately)

Docking station model #1	HP Thunderbolt 4 Ultra 180W G6 Dock
Total number of supported displays (incl.the notebook)	4
Max.resolutions supported	(4) 4K @60Hz* (2) 4K @ 120Hz* (3) QHD @ 120Hz* (1) QHD @ 360Hz*
Dock Connectors	1x HDMI 2.1, 2x DisplayPort 1.4, 1x Thunderbolt 4, 1x USB-C 3.2 Gen 2 DisplayPort
HP Quick Connect Support	Yes
Extended Power Range Support	Yes
Technical limitations	Requires DisplayPort 1.4 support with Display Stream Compression (DSC). Bluetooth required for HP Quick Connect. HP Quick Connect available on select HP notebooks. Maximum resolution and display support is dependent on the maximum capability of the notebook.
Thunderbolt Hosts	Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host. Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz
Non-Thunderbolt hosts	The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is (1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.
Docking station model #2	HP Thunderbolt™ 120W G4 Dock
Total number of supported displays (incl.the notebook)	4
Max.resolutions supported	Quad 4K @60Hz

	Dual 8K single cable@30 for Thunderbolt hosts or USB-C hosts DisplayPort 1.4 with Display Stream Compression in High-Resolution Mode
Dock Connectors	2x HDMI 2.0, 2x DisplayPort 1.4, 1x Thunderbolt 4, 1x USB-C 3.2 Gen 2 DisplayPort
Technical limitations	Maximum resolution and display support is dependent on the maximum capability of the notebook. Thunderbolt Hosts: Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host. Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz Non-Thunderbolt hosts: The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is (1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.

STORAGE AND DRIVES

Maximum Storage

16TB

Primary M.2 Storage

1 TB PCIe® Gen5x4 NVMe™ M.2 SSD

2 TB PCIe® Gen5x4 NVMe™ M.2 SSD

4 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC

2 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC

2 TB PCIe® Gen4x4 NVMe™ SED SSD

1 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC

1 TB PCIe® Gen4x4 NVMe™ SED SSD

512 GB PCIe® Gen4x4 NVMe™ M.2 SSD TLC

2 TB Citadel PCIe-3x4 NVMe™ M.2 2280 TLC SED OPAL2 FIPS SSD

1 TB Citadel PCIe-3x4 NVMe™ M.2 2280 TLC SED OPAL2 FIPS SSD

512GB Citadel PCIe-3x4 NVMe™ M.2 2280 TLC SED OPAL2 FIPS SSD

Storage Slots

4 M.2 Solid State Drive

Drive Controllers

M.2 Storage Bay (PCIe NVMe) : PCIe® Gen4 x4 lanes NVMe™ Solid State Drive

* For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 35GB of disk is reserved for system recovery software.

DRIVE CONTROLLERS

M.2 Storage Bay (PCIe NVMe):	PCIe® Gen4 x4 lanes NVMe™ Solid State Drive
RAID:	Supported RAID 0, RAID 1*, RAID 5 and RAID 10**

*RAID 0, RAID 1 not supported on Opal SSD

**RAID 5 and RAID 10 are not available out of factory but can be configured by the end-user. RAID 5 RAID 10 not supported on Opal SSD.

MEMORY

Maximum Memory

128 GB DDR5-5600 MT/s ECC

192 GB DDR5-5600 MT/s non-ECC

Memory

16GB (1x16GB) DDR5 5600 SODIMM Memory

32GB (1x32GB) DDR5 5600 SODIMM Memory

32GB (2x16GB) DDR5 5600 SODIMM Memory

64GB (2x32GB) DDR5 5600 SODIMM Memory

64GB (4x16GB) DDR5 5600 SODIMM Memory

128GB (4x32GB) DDR5 5600 SODIMM Memory

192GB (2x32GB + 2x64GB) DDR5 5600 SODIMM Memory*

32GB (1x32GB) DDR5 5600 SODIMM ECC Memory

32GB (2x16GB) DDR5 5600 SODIMM ECC Memory

64GB (2x32GB) DDR5 5600 SODIMM ECC Memory

128GB (4x32GB) DDR5 5600 SODIMM ECC Memory

128GB (2x64GB) DDR5 6400 CSODIMM NECC Memory

64GB (1x64GB) DDR5 6400 CSODIMM Memory

64GB (2x32GB) DDR5 6400 CSODIMM Memory

32GB (1x32GB) DDR5 6400 CSODIMM Memory

Memory Speed

Memory DDR5 6400 CSODIMM

Memory DDR5 5600 SODIMM

Intel 15th Gen Core HX-Series Processors: Memory transfer speed will be 4000 MT/s or 4400 MT/s under identical DIMM conditions

Current identical DIMM conditions:

- 2 DIMM Per channel (with 2 Rank DDR5 module): 4000 MT/s
- 2 DIMM Per channel (with 1 Rank DDR5 module): 4400 MT/s
- 1 DIMM per channel (with either 1 Rank or 2 Rank DDR module): 4400 MT/s

Note: DIMM per Channel is DPC

Note: 16GB DIMM is 1 Rank module

Note: 32GB and 64GB DIMM are 2 Rank module

DIMM1	DIMM2	DIMM3	DIMM4	MEM Speed	DIMM/Channel
V				1 Rank: 4400 MT/s 2 Rank: 4400 MT/s	1 DPC
V	V			1 Rank: 4400 MT/s 2 Rank: 4400 MT/s	1 DPC
V	V	V		1 Rank: 4400 MT/s 2 Rank: 4000 MT/s	2 DPC
V	V	V	V	1 Rank: 4400 MT/s 2 Rank: 4000 MT/s	2 DPC

Mixing Memory DIMM Vendors/Suppliers

Mixing memory DIMM suppliers and / or capacity may cause a downgrade in memory speed. signal integrity or functional issues

Mixing memory Rank (1 Rank and 2 Rank from table above) in the same channel will cause the memory speed to drop to 3200 MHz and could encounter an unstable condition

Recommendation: Do not install different Rank memory modules in the same channel

Memory Installation Sequence

Intel 15th Gen Core HX-Series Processors have specific population (installation sequence) rules. To Avoid a no-boot issue.

There is/are DIMM population installation sequence requirements for cases where only one DIMM is populated per channel.

Then the furthest memory connectors from the CPU should be populated first

*Available Q4 2025

Note: Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

NETWORKING /COMMUNICATIONS

WLAN

Intel® Wi-Fi 7 BE200 (2x2) and Bluetooth® 5.4 WLAN, vPro®[1,2]

Intel® Wi-Fi 7 BE200 (2x2) and Bluetooth® 5.4 WLAN, non-vPro®[1,2]

WWAN

HP R15 5G Solution WWAN[3]

WLPWAN

Qualcomm 9205 LTE-M (CAT-M1 fSVC)[4]

NFC

WNC XRAV-1 NFC

Ethernet

Intel I226-LM 2.5GbE Ethernet Controller

Intel I226-V 2.5GbE Ethernet Controller

1. Wi-Fi 7: Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 7 (802.11BE) functionality requires compatible Windows 11 OS, compatible processor, and separately purchased Wi-Fi 7 router to support backwards compatibility with prior 802.11 specs. Available in countries where Wi-Fi 7 is supported. The specification for 802.11BE is a draft specification and is not final. If the final specification differs from the draft specification, it may affect the ability of the device to communicate with other 802.11BE devices.

2. Intel vPro® requires Windows 10 Pro 64 bit or higher, a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN and/or Wi-Fi 6E WLAN and TPM 2.0. Some functionality requires additional 3rd party software in order to run. Features of vPro® Essentials and Enterprise vary. See http://intel.com/vpro

3. 5G module is optional and must be configured at the factory. Module designed for 5G NR NSA (non-standalone) networks as carriers deploy Evolved-Universal Terrestrial Radio Access New Radio Dual Connectivity (ENDC) with both 100Mhz of 5G NR and LTE channel bandwidth, using 256QAM 4x4 as defined by 3GPP. Module requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Data connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. Backwards compatible to 4G LTE and 3G HSPA technologies. 5G module planned to be available in select platforms and select countries, where carrier supported.

4. LPWAN (also called Mobile Narrowband) support HP Protect & Trace with Wolf Connect service through the subscription term, but do not support mobile broadband use.

AUDIO/MULTIMEDIA

Audio

Audio by Poly Studio,

4 integrated stereo speakers; discrete amplifiers

2 integrated dual array digital microphones

Speaker Power

(1W/8 ohm per speaker),

Camera

5MP Camera; IR Camera (optional)

Webcam

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

HP Premium Quiet Keyboard – spill-resistant, full-size, backlit keyboard and DuraKeys

HP Lumen RGB Z Keyboard – Full-size, per-key RGB backlit keyboard

Pointing Device

Clickpad with multi-touch gesture support, taps enabled as default

Function Keys

ESC: system information

F1 - Display Switching

F2 - Night Mode / Sure View LED: On = White; Off = Not illuminated

F3 - Brightness Down

F4 - Brightness Up

F5 - Audio Mute LED: On = Amber; Off = not illuminated

F6 - Volume Down

F7 - Volume Up

F8 - Mic Mute On = Amber; Off = not illuminated

F9 - Keyboard Backlight

F10 - Insert

F11 - Airplane Mode

F12 - Command center

> Print Screen

> Power On/Off On = White; Off = not illuminated

> Delete

> Fn key lock

> Microsoft Copilot[1]

Hidden Keys

home

end

Fn+R = Break

Fn+S = Sys Rq

Fn+C = Scroll Lock

Fn+W = Pause

1. Copilot in Windows requires Windows 11. Some features require an NPU. Timing of feature delivery and availability varies by market and device. Requires Microsoft account to log in. Where Microsoft in Windows is not available, the Copilot key will lead to the Bing search engine. Use of Recall requires customer authentication using Windows Hello Enhanced Sign in Security (ESS) which requires a fingerprint reader or facial recognition camera and may not be supported on all platforms. See http://aka.ms/WindowsAIFeatures

SOFTWARE AND SECURITY

Software

Buy Microsoft Office (Sold Separately)

CoPilot in Windows with CoPilot Key [1]

Edge Customization

HP Connection Optimizer

HP Hotkey Support

HP Mac Address Manager

HP Notifications

HP PC Hardware Diagnostics UEFI

HP PC Hardware Diagnostics Windows

HP Privacy Settings

HP Services Scan [2]

HP Smart Support [3]

HP Support Assistant [4]

HSA Fusion for Commercial

HSA Telemetry for Commercial

myHP [5]

Poly Camera Pro

Poly Lens [6]

HP IQ [7]

Manageability Features

HP Client Catalog (download) [8]

HP Client Management Script Library (download) [9]

HP Cloud Recovery [10]

HP Connect for Microsoft Endpoint Manager [11]

HP Driver Packs (download) [12]

HP Image Assistant (download) [13]

HP Manageability Integration Kit (download) [14]

HP Power Manager with Battery Health Manager (download) [15]

Security Management

Secured-Core PC Enable [16]

Windows Hello Enhanced Sign-In Security (ESS)

HP Wolf Security for Business which includes: [17]

HP Sure Admin [18]

HP Sure Click [19]

HP Sure Recover [20]

HP Sure Run [21]

HP Sure Sense [22]

HP Sure Start [23]

HP Tamper Lock[24]

BIOS

Absolute Persistence Module [25]

Audio Permanent Disable

BIOS Update via Network

HP BIOS Recovery

HP BIOSphere [26]

HP DriveLock & Automatic DriveLock

HP Fingerprint Sensor [27]

HP Secure Erase [28]

HP Wake on WLAN

UEFI version: v2.9

Security

TPM

Model: Nuvoton NPCT760HAEYX 7.2.4.1

FIPS 140-3 Compliant: Yes

Model: STMicroelectronics ST33KTPM2X32CKE2

FIPS 140-3 Compliant: Yes

1. Copilot key is available on select Windows 11 PCs. Where Microsoft Copilot is not available, the Copilot key will lead to the Bing search engine. Copilot key feature availability varies by market, see aka.ms/keysupport. Copilot is NOT available in China, Russia, Belarus, and embargoed regions Cuba, Iran, North Korea, Crimea.
2. HP Services Scan is preinstalled and/or provided thru Windows Update and checks for service entitlement on each hardware device and downloads the applicable software agent automatically. To disable this feature, please follow the instructions at http://www.hpdaas.com/requirements. The HP Insights agent is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access with connection to the HP Insights agent is required. For full system requirements, please visit http://www.hpdaas.com/requirements. Not available in China.
3. HP Smart Support requires the HP Insights agent to be installed. For more information about how to enable or to download HP Smart Support, please visit http://www.hp.com/smart-support. HP Services Scan is preinstalled and/or provided thru Windows Update and will check entitlement on each hardware device to determine if an HP Insights agent-enabled service has been purchased, and will download applicable software automatically. HP Insights agent is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access is required. For full system requirements or to disable this feature, please visit https://www.hpdaas.com/requirements.
4. HP Support Assistant is available on Windows. For more information, please visit www.support.hp.com/help/hp-support-assistant.
5. MyHP requires Windows 10 or higher OS.
6. Poly Lens Desktop requires a Windows OS.
7. HP IQ delivery app is preloaded on select HP PCs; it will be automatically updated to the future featured HP IQ application if you have auto updates enabled in Windows or will be available for download from the Microsoft Store. The future featured HP IQ app uses artificial intelligence. Features vary by configuration. For complete details see https://support.hp.com/us-en/document/ish_13696672-13696717-16
8. HP Client Catalog not preinstalled, however available for download at (https://www.hp.com/us-en/solutions/client-management-solutions.html)
9. HP Client Management Script Library (https://www.hp.com/us-sen/solutions/client-management-solutions.html#tab=manageability-tools).
10. HP Cloud Recovery is available for Z by HP, HP Elite and Pro desktops and laptops PCs with Intel® or AMD processors and requires an open, network connection. Note: You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Detail please refer to: https://support.hp.com/us-en/computer.
11. HP Connect for Microsoft Endpoint Manager is available from the Azure Market Place for HP Pro, Elite, Z and Point-of-Sale PCs managed with Microsoft Endpoint Manager. Subscription to Microsoft Endpoint Manager required and sold separately. Network connection required.

12. HP Driver Packs not preinstalled, however available for download at http://www.hp.com/go/clientmanagement.
13. HP Image Assistant not preinstalled, however available for download at (https://ftp.ext.hp.com/pub/caps-softpaq/cmit/HPIA.html),
14. HP Manageability Integration Kit not presintalled, however available for downloaded from https://www.hp.com/us-en/solutions/client-management-solutions.html#tab=manageability-tools.
15. HP Power Manager with Battery Health can be downloaded by entering your system information here: https://support.hp.com/in-en/document/ish_4449597-3519507-16.
16. Secured-Core PC Enable requires an Intel® vPro®, AMD Ryzen™ Pro processor or Qualcomm® processor with SD850 or higher and requires 8 GB or more system memory. Secured-core PC is enabled from the factory.
17. HP Wolf Security for Business requires Windows 10 or 11 Pro or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features.
18. HP Sure Admin requires HP G8 or newer platforms, Windows 10 or higher, HP BIOS, HP Manageability Kit or KMS Service from http://www.hp.com/go/clientmanagement and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store.
19. HP Sure Click requires Windows 10 and higher. See https://bit.ly/2PrLT6A_SureClick for complete details.
20. HP Sure Recover is available on select HP PCs and requires Windows 10 or 11 and an open network connection. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data. HP Sure Recover Gen6 with Embedded Reimaging is an optional feature on select HP PCs which requires Windows 10 or 11 must be configured at purchase. You must back up important files, data, photos, videos, etc. before use to avoid loss of data.
21. HP Sure Run is available on select HP PCs and requires Windows 10 and higher.
22. HP Sure Sense requires Windows 10 and higher. See product specifications for availability. On units with WWAN shipping to China, HP Sure Sense is only available via Softpaq download.
23. HP Sure Start is available on select HP PCs and requires Windows 10 and higher.
24. HP Tamper Lock must be enabled by the customer or your administrator.
25. Absolute Persistence firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit: https://www.absolute.com/about/legal/agreements/absolute/.
26. HP BIOSphere features may vary depending on the platform and configuration.
27. HP Fingerprint Reader is an optional feature that requires Windows 10 or 11 and must be configured at purchase.
28. HP Secure Erase implements the methods outlined in the National Institute of Standards and Technology Special Publication 800-88r "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.

POWER

Power Supply

HP 150W Slim 4.5 mm PFC Right Angle Smart (3-pin) AC Power Adapter;

HP 200W Slim 4.5 mm PFC Right Angle Smart (3-pin) AC Power Adapter;

HP 280W Slim 4.5 mm PFC Right Angle Smart (3-pin) AC Power Adapter;

Not Included AC Adapter

Battery

HP 99 Wh Long Life Polymer Fast Charge 8 cell Battery

Power Cord

C13 1.83m Paper Sticker Flange Premium CWP Black Straight Halogen Free Power Cord

C13 1.83m Paper Sticker Flange Premium CWP Black Straight Power Cord

C5 1.0m Sticker Conventional Halogen Free Straight Power Cord

C5 1.0m Sticker Premium Power Cord

Not Included Power Cord

Battery life

UMA

Up to 17:55 hrs

DIS

Up to 10:11 hrs

WEIGHT & DIMENSIONS

Weight

Starting at 5.36 lb;

(Weight varies by configuration and components.)

Starting at 2.43 kg;

(Weight varies by configuration and components.)

Product Dimensions (w x d x h)

14.16 x 9.81 x 1.09 in;

(Dimensions vary by configuration)

35.9 x 24.9 x 2.7 cm;

(Dimensions vary by configuration)

PORTS/SLOTS

Left side:

1 power connector

2 Thunderbolt™ 5 with USB Type-C® 80 Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1)*

1 HDMI 2.1

SD 7.0 Media Card Reader

Right side:

1 Thunderbolt™ 4 with USB Type-C® 40 Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1)*

1 USB Type-A 10Gbps signaling rate

1 headphone/microphone combo

1 RJ-45

1 nano security lock slot

1 smart card reader

Expansion Slots

SD 7.0 Media Card Reader

*Actual throughout may vary.

SERVICE AND SUPPORT

1-year warranty and 90 day software limited warranty options depending on country. HP Worldwide Limited Warranty for the battery is aligned with the warranty period of the HP Hardware Product. Refer to http://www.hp.com/support/batterywarranty/ for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: http://www.hp.com/go/cpc.

Certification and Compliance

ENERGY STAR® certified

EPEAT® registered configurations available

Low halogen

Sustainable Impact Specifications

40% post-consumer recycled plastic

Bulk packaging available

External power supply 90% efficiency;

Molded paper pulp cushion inside box is 100% sustainably sourced and recyclable;

Outside box and corrugated cushions are 100% sustainably sourced and recyclable

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)	
Nominal Operating Voltage	19.5v
Average Operating Power	
Integrated graphics	CPU < 55W
Discrete Graphics	NVIDIA RTX PRO 5000 Blackwell 115W NVIDIA RTX PRO 4000 Blackwell 115W NVIDIA RTX PRO 3000 Blackwell 105W NVIDIA RTX PRO 2000 Blackwell 60W NVIDIA RTX PRO 1000 Blackwell 60W
Max Operating Power	<280W
Temperature	
Operating	32° to 95° F (0° to 35° C), System performance may be reduced above 32°C (89.6°F). No sustained direct exposure to sunlight.
Non-operating	-4-140°F (-20 - 60°C)
Relative Humidity	
Operating	10% to 90%, non-condensing
Non-operating	5% to 95%; 38.7C (101.6F) maximum wet bulb tempera-ture; non-condensing.
Shock	
Operating	40 G, 2 ms, half-sine
Non-operating	240G, 2ms, half sine
Random Vibration	
Operating	0.079 ~ 1.043 grams
Non-operating	3.5 grams
Altitude (unpressurized)	
Operating	3048m (10,000ft)
Non-operating	12192m (40,000ft)
Planned Industry Standard Certifications	
Regulatory Model Number	HSN-I64C-6
UL	Yes
CSA	Yes

FCC Compliance	Yes
ENERGY STAR®	Yes
EPEAT	Gold
ICES	Yes
Australia /	Yes
NZ A-Tick Compliance	Yes
CCC	Yes
Japan VCCI Compliance	Yes
KC	Yes
BSMI	Yes
CE Marking Compliance	Yes
BNCI or BELUS	No
CIT	
EAC	Yes
SASO	Yes
SABS	Yes
UKRSERTCOMPUTER	

DISPLAYS

Actual brightness will be lower with touchscreen or HP Sure View.

Availability may vary by country

16.0 in 2.5K (2560 x 1600) Anti-Glare UWVA WLED+LBL AD-100 400 eDP 1.4+PSR2 120Hz bent LCD Panel	**Outline Dimensions (W x H)**	349.98 x 224.82 (max)
	Active Area	344.6784x215.424 (typ)
	Weight	280 (max)
	Diagonal Size	16
	Thickness	2.3 / 4.1 (max)
	Interface	eDP1.4
	Surface Treatment	Anti-Glare
	Touch Enabled	No
	Contrast Ratio	2000:1 (typ)
	Refresh Rate	120 (typ)
	Brightness	400 (typ)
	Pixel Resolution - Format	2560 x 1600 (2.5K)
	Backlight	WLED
	Pixel Resolution	RGB
	Color Gamut Coverage	Adobe RGB 100% + DCI-P3 100%
	Color Depth	8
	Viewing Angle	UWVA 89/89/89/89
	Low Blue Light	Yes
	Power Consumption (W, EBL@ 150nits max/ 200nits max)	2.5 (max)/ 3.0 (max)

16.0 in WQUXGA DRM (3840 x 2400) Anti-Glare UWVA LED DCI-P3 100 NB2Y 500 eDP 1.4+PSR 120Hz bent LCD Panel	**Outline Dimensions (W x H)**	349.980 x 225.420 (max)
	Active Area	344.680 x 215.420 (typ)
	Weight	300 (max)
	Diagonal Size	16
	Thickness	2.3 / 4.1(max)
	Interface	eDP1.4
	Surface Treatment	Anti-Glare

	Touch Enabled	No
	Contrast Ratio	1200:1 (typ)
	Refresh Rate	120 Hz(typ)
	Brightness	500 (typ)
	Pixel Resolution - Format	3840 x 2400 (WQUXGA)
	Backlight	WLED
	Pixel Resolution	RGB
	Color Gamut Coverage	DCI-P3 100%
	Color Depth	8
	Viewing Angle	UWVA 89/89/89/89
	Low Blue Light	No
	Power Consumption (W, EBL@ 150nits max/ 200nits max)	4.98 (max)/ 5.84 (max)
16.0 in WUXGA (1920 x 1200) Anti-Glare UWVA Low Blue Light sRGB 100 800 eDP 1.4+PSR+IOL Sure View 5 bent LCD Panel	**Outline Dimensions (W x H)**	349.980 x224.82 (max)
	Active Area	344.680 x215.420 (typ)
	Weight	310 (max)
	Diagonal Size	16
	Thickness	2.3/4.1 (max)
	Interface	eDP1.4
	Surface Treatment	Anti-Glare
	Touch Enabled	No
	Contrast Ratio	1500 : 1 (typ)
	Refresh Rate	60Hz(typ)
	Brightness	800 (typ)
	Pixel Resolution - Format	1920 x 1200 (WUXGA)
	Backlight	WLED
	Pixel Resolution	
	Color Gamut Coverage	sRGB 100%
	Color Depth	8
	Viewing Angle	UWVA 89/89/89/89
	Low Blue Light	Yes

	Power Consumption (W, EBL@ 150nits max/ 200nits max)	1.93(max)/2.38(max)
16.0 in WUXGA (1920 x 1200) Anti-Glare UWVA WLED+LBL sRGB NB2Y 400 eDP 1.4+PSR2 Low-Power 100 bent LCD Panel	**Outline Dimensions (W x H x D)**	350.680 x 226.470 (max)
	Active Area	344.678 x 215.424 (typ)
	Weight	330 (max)
	Diagonal Size	16
	Thickness	2.6 / 4.6 (max)
	Interface	eDP1.4
	Surface Treatment	Anti-Glare (non-touch); Bright View (touch)
	Touch Enabled	Yes
	Contrast Ratio	1000 : 1 (typ)
	Refresh Rate	60Hz(typ)
	Brightness	400 (typ)
	Pixel Resolution - Format	1920 x 1200 (WUXGA)
	Backlight	WLED
	Pixel Resolution	RGB
	Color Gamut Coverage	sRGB 100%
	Color Depth	8
	Viewing Angle	UWVA 89/89/89/89
	Low Blue Light	Yes
	Power Consumption (W, EBL@ 150nits max/ 200nits max)	1.60 (max)/ 1.95 (max)
16.0 in WQUXGA (3840 x 2400) BrightView UWVA DCI-P3 NBZ2 400 eDP 1.4+PSR 100 bent OLED Panel	**Active Area (W x H, mm)**	344.448 x 215.280 (typ)
	Dimensions (W x H, mm)	348.578 x 224.310 (max)
	Diagonal Size (inch)	16
	Thickness (body/PCB, mm)	1.242 / 3.143 (max)
	Weight (g)	230 (max)
	Interface	eDP1.4

Surface Treatment	Bright View
Contrast Ratio	100,000:1 (typ)
Refresh Rate (Hz)	60 (typ)
Brightness	400 (typ)
P.P.I.	283
Pixel Resolution - Format	3840 x 2400 (WQUXGA)
Pixel Resolution - Configuration	RGB
Backlight	OLED
Color Gamut Coverage	DCI-P3 100%
Color Depth (bit)	8
Viewing Angle	UWVA 85/85/85/85
Power Consumption (W, EBL@ 150nits max /200nits max)	6.10 (max) / 7.40 (max)
Low Blue Light	Yes
Touch Enabled	Yes
Touch Point Supported	10-point multi-touch
Pen Enabled	No

*All specifications represent the typical specifications provided by HP's component manufactures; actual performance may vary either higher or lower.

STORAGE

SSD 512GB 2280 PCIe-4x4 NVMe Three Layer Cell	**Form Factor**	M.2 2280
	Capacity	512GB
	NAND Type	TLC
	Weight	10 g (0.02 lb)
	Interface	PCIe NVMe Gen4X4
	Sequential Read	6400 MB/s ±20%
	Sequential Write	3500 MB/s ±20%
	Logical Blocks	1000215215
	Features	Pyrite 2.0; TRIM; L1.2
SSD 1TB 2280 PCIe-4x4 NVMe Three Layer Cell	**Form Factor**	M.2 2280
	Capacity	1TB
	NAND Type	TLC
	Weight	10 g (0.02 lb)
	Interface	PCIe NVMe Gen4X4
	Sequential Read	6400 MB/s ±20%
	Sequential Write	5000 MB/s ±20%
	Logical Blocks	2000409264
	Features	Pyrite 2.0; TRIM; L1.2
1TB PCIe-4x4 2280 NVME Self Encrypted OPAL2 Three Layer Cell Solid State Drive	**Form Factor**	M.2 2280
	Capacity	1TB
	NAND Type	TLC
	Weight	10 g (0.02 lb)
	Interface	PCIe NVMe Gen4X4
	Sequential Read	6400 MB/s ±20%
	Sequential Write	5000 MB/s ±20%
	Logical Blocks	2000409264
	Features	Pyrite 2.0; TRIM; L1.2

1TB PCIe-5x4 2280 NVMe Solid State Drive	**Form Factor**	M.2 2280
	Capacity	1TB
	NAND Type	TLC
	Weight	10 g (0.02 lb)
	Interface	PCIe NVMe Gen5X4
	Sequential Read	13000 MB/s ±20%
	Sequential Write	9000 MB/s ±20%
	Logical Blocks	
	Features	Pyrite 2.0; TRIM; L1.2
2TB PCIe-4x4 2280 NVMe Three Layer Cell Solid State Drive	**Form Factor**	M.2 2280
	Capacity	2TB
	NAND Type	TLC
	Weight	10 g (0.02 lb)
	Interface	PCIe NVMe Gen4X4
	Sequential Read	6400 MB/s ±20%
	Sequential Write	5000 MB/s ±20%
	Logical Blocks	4000797360
	Features	Pyrite 2.0; TRIM; L1.2
2TB PCIe-4x4 2280 NVME Self Encrypted OPAL2 Three Layer Cell Solid State Drive	**Form Factor**	M.2 2280
	Capacity	2TB
	NAND Type	TLC
	Weight	10 g (0.02 lb)
	Interface	PCIe NVMe Gen4X4
	Sequential Read	6400 MB/s ±20%
	Sequential Write	5000 MB/s ±20%
	Logical Blocks	4000797360
	Features	Pyrite 2.0; TRIM; L1.2
2TB PCIe-5x4 2280 NVMe Solid State Drive	**Form Factor**	M.2 2280
	Capacity	2TB
	NAND Type	TLC

	Weight	10 g (0.02 lb)
	Interface	PCIe NVMe Gen5X4
	Sequential Read	13500 MB/s ±20%
	Sequential Write	10000 MB/s ±20%
	Logical Blocks	
	Features	Pyrite 2.0; TRIM; L1.2
4TB PCIe-4x4 2280 NVMe Three Layer Cell double-sided M.2 Solid State Drive	**Form Factor**	M.2 2280
	Capacity	4TB
	NAND Type	TLC
	Weight	15 g
	Interface	PCIe NVMe Gen4X4
	Sequential Read	6400 MB/s ±20%
	Sequential Write	5000 MB/s ±20%
	Logical Blocks	8001573552
	Features	Pyrite 2.0; TRIM; L1.2

NETWORKING / COMMUNICATION

Intel BE200 Wi-Fi 7 +BT 5.4 M.2 320MHz PCIe World-wide WLAN vPro [1]	**Wireless LAN Standards**	IEEE 802.11a
		IEEE 802.11b
		IEEE 802.11g
		IEEE 802.11n
		IEEE 802.11ac
		IEEE 802.11ax
		IEEE 802.11be
		IEEE 802.11d
		IEEE 802.11e
		IEEE 802.11h
		IEEE 802.11i
		IEEE 802.11k
		IEEE 802.11r
		IEEE 802.11v
	Interoperability	Wi-Fi certified
	Frequency Band	802.11b/g/n/ax/be
		2.402 - 2.482 GHz
		802.11a/n/ac/ax/be
		4.9 - 4.95 GHz (Japan)
		5.15 - 5.25 GHz
		5.25 - 5.35 GHz
		5.47 - 5.725 GHz
		5.825 - 5.850 GHz
		5.955 - 6.415 GHz
		6.435 - 6.515 GHz
		6.535 - 6.875 GHz
		6.895 - 7.115 GHz
	Data Rates	802.11b: 1, 2, 5.5, 11 Mbps
		802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
		802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
		802.11n: max 300Mbps

	802.11ac : 1733Mbps
	802.11ax : max 2.4Gbps
	802.11be : max 5.76Gbps
Modulation	Direct Sequence Spread Spectrum
	OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM, 4096QAM
Security[3]	IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only
	AES-CCMP: 128 bit in hardware
	802.1x authentication
	WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.
	WPA2 certification
	WPA3 certification
	IEEE 802.11i
	WAPI
Network Architecture	Ad-hoc (Peer to Peer)
Models	
	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power[2]	802.11b, 1Mbps : +17dBm minimum
	802.11g, 6Mpbs : +16dBm minimum
	802.11a, 6Mbps : +17dBm minimum
	802.11n, MCS7(HT20) : +14dBm minimum
	802.11n, MCS7(HT40) : +13.5dBm minimu
	802.11ac MCS9(VHT20) : 13.5dBm minimum
	802.11ac MCS9(VHT40) : +13.5dBm minimum
	802.11ac MCS9(VHT80) : +12.5dBm minimum
	802.11ac MCS9(VHT160) : +10.5dBm minimum
	802.11ax MCS11(HE20)(6GHz) : +11.5dBm minimum
	802.11ax MCS11(HE40)(6GHz) : +7.5dBm minimum
	802.11ax MCS11(HE80)(6GHz) : +7.5dBm minimum
	802.11ax MCS11(HE160)(6GHz) : +7.5dBm minimum
	802.11be MCS13(EHT20)(6GHz) : 11.5dBm

	802.11be MCS13(EHT40)(6GHz) : 7.5dBm
	802.11be MCS13(EHT80)(6GHz) : 7.5dBm
	802.11be MCS13(EHT160)(6GHz) : 6.5dBm
	802.11be MCS13(EHT320)(6GHz) : 4.5dBm
Power Consumption	Transmit mode 3.1 W
	Receive mode 1.8 W
	Idle mode (PSP) 180 mW (WLAN Associated)
	Idle mode 50 mW (WLAN unassociated)
	Connected Standby 10mW
	Radio disabled 8 mW
Power Management	ACPI and PCI Express compliant power management
	802.11 compliant power saving mode
Receiver Sensitivity[3]	802.11b, 1Mbps : -93.5dBm maximum
	802.11b, 11Mbps : -85dBm maximum
	802.11a/g, 6Mbps : -90.5dBm maximum
	802.11a/g, 54Mbps : -72.5dBm maximum
	802.11n, MCS0(HT20) : -90dBm maximum
	802.11n, MCS7(HT20) : -71.5dBm maximum
	802.11n, MCS0(HT40) : -88.5dBm maximum
	802.11n, MCS7(HT40) : -68.5dBm maximum
	802.11ac, MCS9(VHT20) : -88.5dBm maximum
	802.11ac, MCS9(VHT40) : -65.5dBm maximum
	802.11ac, MCS9(VHT80) : -60.5dBm maximum
	802.11ac, MCS9(VHT160) : -58.5dBm maximum
	802.11ax, MCS11(HE20)(6GHz) : -59.5dBm maximum
	802.11ax, MCS11(HE40)(6GHz) : -56.5dBm maximum
	802.11ax, MCS11(HE80)(6GHz) : -53.5dBm maximum
	802.11ax, MCS11(HE160)(6GHz) : -51.5dBm maximum
	802.11be, MCS13(EHT20)(6GHz) : -55.5dBm maximum
	802.11be, MCS13(EHT40)(6GHz) : -53.5dBm maximum
	802.11be, MCS13(EHT80)(6GHz) : -51.5dBm maximum
	802.11be, MCS13(EHT160)(6GHz) : -48.5dBm maximum
	802.11be, MCS13(EHT320)(6GHz) : -45.5dBm maximum

Antenna type	High efficiency antenna with spatial diversity Two embedded tri-band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	1. Type 2230 : 2.8g 2. Type 1216: 1.3g
Operating Voltage	3.3v +/- 9%
Temperature	Operating: 14° to 158° F (-10° to 70° C) Non-operating: -40° to 176° F (-40° to 80° C)
Humidity	Operating: 10% to 90% (non-condensing) Non-operating: 5% to 95% (non-condensing)
Altitude	Operating: 0 to 10,000 ft (3,048 m) Non-operating: 0 to 50,000 ft (15,240 m)
LED Activity	LED Amber - Radio OFF; LED OFF - Radio ON
Subtitle	HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4 Wireless Technology
Bluetooth Specification	4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class I Bluetooth device with a maximum transmit power of +15.5 dBm for BR and +13dBm for EDR.

Power Consumption	Peak (Tx): 330 mW
	Peak (Rx): 230 mW
	Selective Suspend: 17 mW
Bluetooth Software Supported	1. Microsoft Windows Bluetooth Software
	2. Linux/Chrome OS Bluetooth Software.
Link Topology	
Power Management	ACPI and PCI Express compliant power management
	802.11 compliant power saving mode
Certifications	FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407
	ETSI 300 328, ETSI 301 893, ETSI 303 687
Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance
	LE Link Layer Ping
	LE Dual Mode
	LE Link Layer
	LE Low Duty Cycle Directed Advertising
	LE L2CAP Connection Oriented Channels
	Train Nudging & Interlaced Scan
	BT4.2 ESR08 Compliance
	LE Secure Connection- Basic/Full
	LE Privacy 1.2 -Link Layer Privacy
	LE Privacy 1.2 -Extended Scanner Filter Policies
	LE Data Packet Length Extension
	FAX Profile (FAX)
	Basic Imaging Profile (BIP)2
	Headset Profile (HSP)
	Hands Free Profile (HFP)
	Advanced Audio Distribution Profile (A2DP)
	BT5.2
	ESR9/10 Compliance
	LE Advertisement Extensions
	Channel Selection Algo

		Limited High Duty Cycle Non-Connectable Advertising 2Mbps LE LE Long Range BT5.3 Host to Controller Encryption Key Control Enhancements Compliance to the latest Errata Section 12.3 of BT 5.3 specification

1.Wi-Fi 7 requires a Wi-Fi 7 router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 7 is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 7 is supported. Wi-Fi 7 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.

2. Check latest software/driver release for updates on supported security features.

3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.

4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Intel BE200 Wi-Fi 7 +BT 5.4 M.2 320MHz PCIe World-wide WLAN non-vPro [1]	**Wireless LAN Standards**	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11ax IEEE 802.11be IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
	Interoperability	Wi-Fi certified

Frequency Band	802.11b/g/n/ax/be 2.402 - 2.482 GHz 802.11a/n/ac/ax/be 4.9 - 4.95 GHz (Japan) 5.15 - 5.25 GHz 5.25 - 5.35 GHz 5.47 - 5.725 GHz 5.825 - 5.850 GHz 5.955 - 6.415 GHz 6.435 - 6.515 GHz 6.535 - 6.875 GHz 6.895 - 7.115 GHz
Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: max 300Mbps 802.11ac : 1733Mbps 802.11ax : max 2.4Gbps 802.11be : max 5.76Gbps
Modulation	Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM, 4096QAM
Security[3]	IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only AES-CCMP: 128 bit in hardware 802.1x authentication WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification WPA3 certification IEEE 802.11i WAPI

Network Architecture	Ad-hoc (Peer to Peer)
Models	
	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power[2]	802.11b, 1Mbps : +17dBm minimum
	802.11g, 6Mpbs : +16dBm minimum
	802.11a, 6Mbps : +17dBm minimum
	802.11n, MCS7(HT20) : +14dBm minimum
	802.11n, MCS7(HT40) : +13.5dBm minimu
	802.11ac MCS9(VHT20) : 13.5dBm minimum
	802.11ac MCS9(VHT40) : +13.5dBm minimum
	802.11ac MCS9(VHT80) : +12.5dBm minimum
	802.11ac MCS9(VHT160) : +10.5dBm minimum
	802.11ax MCS11(HE20)(6GHz) : +11.5dBm minimum
	802.11ax MCS11(HE40)(6GHz) : +7.5dBm minimum
	802.11ax MCS11(HE80)(6GHz) : +7.5dBm minimum
	802.11ax MCS11(HE160)(6GHz) : +7.5dBm minimum
	802.11be MCS13(EHT20)(6GHz) : 11.5dBm
	802.11be MCS13(EHT40)(6GHz) : 7.5dBm
	802.11be MCS13(EHT80)(6GHz) : 7.5dBm
	802.11be MCS13(EHT160)(6GHz) : 6.5dBm
	802.11be MCS13(EHT320)(6GHz) : 4.5dBm
Power Consumption	Transmit mode 3.1 W
	Receive mode 1.8 W
	Idle mode (PSP) 180 mW (WLAN Associated)
	Idle mode 50 mW (WLAN unassociated)
	Connected Standby 10mW
	Radio disabled 8 mW
Power Management	ACPI and PCI Express compliant power management
	802.11 compliant power saving mode
Receiver Sensitivity[3]	802.11b, 1Mbps : -93.5dBm maximum
	802.11b, 11Mbps : -85dBm maximum
	802.11a/g, 6Mbps : -90.5dBm maximum

	802.11a/g, 54Mbps : -72.5dBm maximum 802.11n, MCS0(HT20) : -90dBm maximum 802.11n, MCS7(HT20) : -71.5dBm maximum 802.11n, MCS0(HT40) : -88.5dBm maximum 802.11n, MCS7(HT40) : -68.5dBm maximum 802.11ac, MCS9(VHT20) : -88.5dBm maximum 802.11ac, MCS9(VHT40) : -65.5dBm maximum 802.11ac, MCS9(VHT80) : -60.5dBm maximum 802.11ac, MCS9(VHT160) : -58.5dBm maximum 802.11ax, MCS11(HE20)(6GHz) : -59.5dBm maximum 802.11ax, MCS11(HE40)(6GHz) : -56.5dBm maximum 802.11ax, MCS11(HE80)(6GHz) : -53.5dBm maximum 802.11ax, MCS11(HE160)(6GHz) : -51.5dBm maximum 802.11be, MCS13(EHT20)(6GHz) : -55.5dBm maximum 802.11be, MCS13(EHT40)(6GHz) : -53.5dBm maximum 802.11be, MCS13(EHT80)(6GHz) : -51.5dBm maximum 802.11be, MCS13(EHT160)(6GHz) : -48.5dBm maximum 802.11be, MCS13(EHT320)(6GHz) : -45.5dBm maximum
Antenna type	High efficiency antenna with spatial diversity Two embedded tri-band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	1. Type 2230 : 2.8g 2. Type 1216: 1.3g
Operating Voltage	3.3v +/- 9%
Temperature	Operating: 14° to 158° F (-10° to 70° C) Non-operating: -40° to 176° F (-40° to 80° C)
Humidity	Operating: 10% to 90% (non-condensing) Non-operating: 5% to 95% (non-condensing)
Altitude	Operating: 0 to 10,000 ft (3,048 m)

	Non-operating: 0 to 50,000 ft (15,240 m)
LED Activity	LED Amber – Radio OFF; LED OFF – Radio ON
Subtitle	HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4 Wireless Technology
Bluetooth Specification	4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class I Bluetooth device with a maximum transmit power of +15.5 dBm for BR and +13dBm for EDR.
Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
Bluetooth Software Supported	1. Microsoft Windows Bluetooth Software 2. Linux/Chrome OS Bluetooth Software.
Link Topology	
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Certifications	FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407 ETSI 300 328, ETSI 301 893, ETSI 303 687
Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode

LE Link Layer
LE Low Duty Cycle Directed Advertising
LE L2CAP Connection Oriented Channels
Train Nudging & Interlaced Scan
BT4.2 ESR08 Compliance
LE Secure Connection- Basic/Full
LE Privacy 1.2 -Link Layer Privacy
LE Privacy 1.2 -Extended Scanner Filter Policies
LE Data Packet Length Extension
FAX Profile (FAX)
Basic Imaging Profile (BIP)2
Headset Profile (HSP)
Hands Free Profile (HFP)
Advanced Audio Distribution Profile (A2DP)
BT5.2
ESR9/10 Compliance
LE Advertisement Extensions
Channel Selection Algo
Limited High Duty Cycle Non-Connectable Advertising
2Mbps LE
LE Long Range
BT5.3
Host to Controller Encryption Key Control Enhancements
Compliance to the latest Errata Section 12.3 of BT 5.3 specification

1. Wi-Fi 7 requires a Wi-Fi 7 router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 7 is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 7 is supported. Wi-Fi 7 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.

4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

HP 5G Sub-6 Cat 19	**Technology/Operating bands**	WCDMA/HSPA+ operating bands: Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL) Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL) Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL) Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL) Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL) LTE FDD/TDD operating bands: Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL) Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL) Band 3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL) Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL) Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL) Band 7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL) Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL) Band 12: 699 to 716 MHz (UL), 729 to 746 MHz (DL) Band 13: 777 to 787 MHz (UL), 746 to 756 MHz (DL) Band 14: 788 to 798 MHz (UL), 758 to 768 MHz (DL) Band 17: 704 to 716 MHz (UL), 734 to 746 MHz (DL) Band 18: 815 to 830 MHz (UL), 860 to 875 MHz (DL) Band 19: 830 to 845 MHz (UL), 875 to 890 MHz (DL) Band 20: 832 to 862 MHz (UL), 791 to 821 MHz (DL) Band 25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL) Band 26: 814 to 849 MHz (UL), 859 to 894 MHz (DL) Band 28: 703 to 748 MHz (UL), 758 to 803 MHz (DL) Band 29: 717 to 728 MHz (DL) Band 30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL) Band 32: 1452 to 1496 MHz (DL) Band 34: 2010 to 2025 MHz (UL/DL) Band 38: 2570 to 2620 MHz (UL/DL) Band 39: 1880 to 1920 MHz (UL/DL)

	Band 40: 2300 to 2400 MHz (UL/DL) Band 41: 2496 to 2690 MHz (UL/DL) Band 42: 3400 to 3600 MHZ (UL/DL) Band 43: 3400 to 3800 MHZ (UL/DL) Band 46: 5150 to 5925 MHZ (DL) Band 48: 3550 to 3700 MHZ (UL/DL) Band 66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL) Band 71: 663 to 698 MHz (UL), 617 to 652 MHz (DL) 5GNR Sub 6GHZ n1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL) n2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL) n3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL) n5: 824 to 849 MHz (UL), 869 to 894 MHz (DL) n7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL) n8: 880 to 915 MHz (UL), 925 to 960 MHz (DL) n20: 832 to 862 MHz (UL), 791 to 821 MHz (DL) n25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL) n28: 703 to 748 MHz (UL), 758 to 803 MHz (DL) n30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL) n38: 2570 to 2620 MHz (UL/DL) n40: 2300 to 2400 MHz (UL/DL) n41: 2496 to 2690 MHz (UL/DL) n48: 3550 to 3700 MHZ (UL/DL) n66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL) n71: 663 to 698 MHz (UL), 617 to 652 MHz (DL) n77: 3300 to 4200 MHz (UL/DL) n78: 3300 to 3800 MHz (UL/DL) n79: 4400 to 5000 MHz (UL/DL)
Wireless protocol standards	NR Sub6G rel15 200MHz 2 DLCA, 256 QAM 200MHz 2 ULCA, 256 QAM 15KHz/30KHz SCS for FDD/TDD LTE Rel15

	100MHz 5 DLCA, 256 QAM 40MHz 2 ULCA, 256 QAM UMTS Rel8
GPS	GPS only support L1 C/A
GPS bands	GPS: L1 (1575.42MHz) GLONASS: L1 (1602MHz) BeidouB1(1561.098MHz) Galileo E1 (1575.42) QZSS(1575.42 MHz)
Maximum data rates	Sub-6 SA Peak DL 4.67Gbps/UL 1.25Gbps Sub-6 NSA Peak DL 3.74Gbps/UL 835Mbps LTE Peak DL 1.6Gbps (CAT19)/UL 211Mbps (CAT18) UMTS/HSPA+ DL DC-HSPA+: 42 Mbps (CAT24)/UL 11.5 Mbps (CAT7)
Maximum output power	NR： 23 dBm in all band except (n30 = 22dBm & n48=21dBm & n77=25dBm & n41/n77/n78 = 26dBm) LTE: 23 dBm in all band except (B30 = 22dBm & B48=21dBm & B41=26dBm) UMTS: 23.5 dBm
Maximum power consumption	3500 mA (peak); 1674mA (average)
Form Factor	M.2, 3052-S3 Key B
Weight	8.7g
Dimensions (Length x Width x Thickness)	52 mm × 30 mm × 2.3 mm
embedded eSIM	Support

1. 5G module is optional and must be configured at the factory. Module designed for 5G NR NSA (non-standalone) networks as carriers deploy Evolved-Universal Terrestrial Radio Access New Radio Dual Connectivity (ENDC) with both 100Mhz of 5G NR and LTE channel bandwidth, using 256QAM 4x4 as defined by 3GPP. Module requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Data connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. Backwards compatible to 4G LTE and 3G HSPA technologies. 5G module planned to be available in select platforms and select countries, where carrier supported.

Qualcomm 9205	**Technology/Operating bands**	FDD LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3), 1700/2100 (Band 4), 850 (Band 5), 900 (Band 8), 700 (Band 12 lower), 700 (Band 13 upper), 700 (Band 14 upper), 850 (Band 18 lower), 850 (Band 19 upper), 800 (Band 20), 1900 (Band 25), 850 (Band 26), 800 (Band 27), 700 (Band 28), 1700/2100 (Band 66), 700 (band 85) MHz. GSM/GPRS/EGPRS: 850, 900, 1800, 1900MHz.
	Wireless protocol standards	l 3GPP TS 51.010-1 V10.5.0: Mobile Station (MS) conformance specification; Part 1: Conformance specification l 3GPP TS 36.521-1 V14.3.0: User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Conformance testing l 3GPP TS 21.111 V10.0.0: USIM and IC card requirements l 3GPP TS 51.011 V4.15.0: Specification of the Subscriber Identity Module -Mobile Equipment (SIM-ME) interface l 3GPP TS 31.102 V10.11.0: Characteristics of the Universal Subscriber Identity Module (USIM) application l 3GPP TS 31.11 V10.16.0: Universal Subscriber Identity Module (USIM) Application Toolkit (USAT) l 3GPP TS 36.124 V10.3.0: Electro Magnetic Compatibility (EMC) requirements for mobile terminals and ancillary equipment l 3GPP TS 27.007 V10.0.8: AT command set for User Equipment (UE) l 3GPP TS 27.005 V10.0.1: Use of Data Terminal Equipment - Data Circuit terminating Equipment (DTE - DCE) interface for Short Message Service (SMS) and Cell Broadcast Service (CBS)

	GPS	Standalone GPS/Beidou/Glonass, A-GPS(XTRA)
	GPS bands	1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz, Beidou 1561.098 MHz
	Maximum data rates	LTE FDD: 375 Kbps (Download), 1119 Kbps (Upload) GSM: - GPRS: 107 Kbps (Download), 85.6 Kbps (Upload) - EGPRS: 296 Kbps (Download), 236.8 Kbps (Upload)
	Maximum output power	LTE: 21.5 dBm in all band GSM:34dBm
	Maximum power consumption	LTE: 147 mA(peak), 18 mA(average)
	Form Factor	M.2
	Weight	4 g
	Dimensions (Length x Width x Thickness)	22 x 42 x 2.3 mm
	embedded eSIM	Support
NFC NXP NPC300	**Dimensions (L x W x H)**	17 x 10 x 2.0 mm
	Chipset	NPC300
	System interface	I2C
	NFC RF standards	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 ISO/IEC 18092 ECMA-340 NFCIP-1 Target and Initiator ECMA-320 NFCIP-2
	NFC Forum Support	Tag Type 1, Type 2, Type3 and Type 4, NFCIP-1 and NFCIP-2
	Reader (PCD-VCD) Mode(1)	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 MIFARE 1K MIFARE 4K MIFARE DESFire

	FeliCa
	Jewel and Topaz cards
Card Emulation (PICC-VICC) Mode(1)	ISO/IEC 14443 A
	ISO/IEC 14443 B and B'
	MIFARE
	FeliCa
Frequency	13.56 MHz
NFC Modes Supported	Reader/Writer, Peer-to-Peer
Raw RF Data Rates	106, 212, 424, 848 kbps
Operating temperature	Operating: 0 °C to 70 °C (32 °F to 158 °F)
Storage temperature	Storage: -20 °C to 125 °C (-4 °F to 257 °F)
Humidity	10-90% operating
	5-95% non-operating
Supply Operating voltage	4.35 to 5.25 Volts
I/O Voltage	1.8V or 3.3V
Power Consumption (Booster enable, VBAT= 3.3V, VCC_BOOST = 5V)	(Booster enable, VBAT= 3.3V, VCC_BOOST = 5V)
Mode	Power Consumption, Typical
Polling	7.3 mA
Detected Test Tag Type 1	Total 283.8 mA
	Net Module 236.8 mA
Detected Test Tag Type 2	Total 288.8 mA
	Net Module 241.8 mA
Detected Test Tag Type 3	Total 287.7 mA
	Net Module 240.7 mA
Detected Test Tag Type 4	Total 282.3 mA
	Net Module 235.3 mA
Antenna	Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module.

Intel® I226-LM 2.5 Gigabit Network Connection LOM (vPro)	**Connector**	RJ-45
	System Interface	PCI(Intel proprietary) + SMBus
	Data rates supported	1. 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 2. 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 3. 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 802.3 clauses 40) 4. 2.5 Gbit/s operation (2.5GBASE-T; IEEE 802.3bz Clause 126) 5. Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 & 100 Mbit/s
	IEEE Compliance	IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet) IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BAE-T IEEE 802.3bz 2.5GBASE-T
	Performance	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling(Hash Mode Only) Jumbo Frame 9K
	Power consumption	Cable Disconnection: 25mW 100Mbps Full Run: 450mW 1000Mbp Full Run: 1000mW 2500Mbp Full Run: 4500mW WoL Enable(S3/S4): 50mW WoL Disable(S3/S4): 25mW
	Power	ACPI compliant – multiple power modes

	Management	Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
	Management Interface	Auto MDI/MDIX Crossover cable detection
	IT Manageability	Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status
	Security & Manageability	Intel® vPro™ support with appropriate Intel® chipset components
Intel® I226V 2.5 Gigabit Network Connection LOM (non-vPro)	**Connector**	RJ-45
	System Interface	PCI (Intel proprietary) + SMBus
	Data rates supported	1. 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 2. 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 3. 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 802.3 clauses 40) 4. 2.5 Gbit/s operation (2.5GBASE-T; IEEE 802.3bz Clause 126) 5. Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10& 100 Mbit/s
	IEEE Compliance	IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet) IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BAE-T

	IEEE 802.3bz 2.5GBASE-T
Performance	TCP/IP/UDP Checksum Offload (configurable)
	Protocol Offload (ARP & NS)
	Large send offload and Giant send offload
	Receiving Side Scaling (Hash Mode Only)
	Jumbo Frame 9K
Power consumption	Cable Disconnection: 25mW
	100Mbps Full Run: 450mW
	1000Mbp Full Run: 1000mW
	2500Mbp Full Run: 4500mW
	WoL Enable(S3/S4): 50mW
	WoL Disable(S3/S4): 25mW
Power	ACPI compliant - multiple power modes
Management	Situation-sensitive features reduce power consumption
	Advanced link down power saving for reducing link down power consumption
Management Interface	Auto MDI/MDIX Crossover cable detection
IT Manageability	Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame)
	PXE 2.1 Remote Boot
	Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30))
	Comprehensive diagnostic and configuration software suite
	Virtual Cable Doctor for Ethernet cable status
Security & Manageability	Intel® non-vPro™ support with appropriate Intel® chipset components

POWER

Power supply availability may vary by country.

HP 150W Slim 4.5 mm PFC Right Angle Smart (3-pin) AC Power Adapter Vesta II	**Dimensions**	5.43 x 2.59 x 0.39 in (13.8x6.6x2.2cm)
	Weight	330g(+/-10g) (Not including power cord. Power cord varies by country.)
	Input Voltage	100-240Vac
	Input Efficiency	88 % at 115 Vac and 89 % at 230Vac
	Input frequency range	47-63 Hz
	Input AC current	Max. 2.7 A at 90 Vac
	Output	
	Output power	150W
	DC output	19.5V
	Hold-up time	100% load 5ms at 115 Vac input
	Output Over Current Protection	< 16.0A
	Connector	C6
	Connector	4.5mm Barrel Type
	Environmental Design	
	Operating temperature	32°F to 95°F (0° to 35°C)
	Non-operating (storage) Temperature	-4°F to 185°F (-20° to 85°C)
	Altitude	0 to 16,400 ft (0 to 5000m)
	Humidity	20% to 95%
	Storage Humidity	10% to 95%
	EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC), NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC

HP 200W Slim 4.5 mm PFC Right Angle Smart (3-pin) AC Power Adapter Eris+	**Dimensions**	6.496 x 3.11 x 1.0 in (16.5x7.9x2.54cm)
	Weight	530g(+/-10g) (Not including power cord. Power cord varies by country.)
	Input Voltage	100-240Vac
	Input Efficiency	88 % at 115 Vac and 89 % at 230Vac
	Input frequency range	47-63 Hz
	Input AC current	Max. 3.0 A at 90 Vac
	Output	
	Output power	200W
	DC output	19.5V
	Hold-up time	100% load 5ms at 115 Vac input
	Output Over Current Protection	< 21.0A
	Connector	C14
	Connector	4.5mm Barrel Type
	Environmental Design	
	Operating temperature	32°F to 95°F (0° to 35°C)
	Non-operating (storage) temperature	-4°F to 185°F (-20° to 85°C)
	Altitude	0 to 16,400 ft (0 to 5000m)
	Humidity	20% to 95%
	Storage Humidity	10% to 95%
	EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC), NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC

HP 280W Standard 4.5 mm Right Angle Smart (3-pin) AC Power Adapter Bowser+	**Dimensions**	7.087 x 3.465 x 1.0 in (18.0x8.8x2.54cm)
	Weight	730g(+/-10g) (Not including power cord. Power cord varies by country.)
	Input Voltage	100-240Vac
	Input Efficiency	89 % at 115Vac/230Vac
	Input frequency range	47-63 Hz
	Input AC current	Max. 4.0 A at 90 Vac
	Output	
	Output power	280W
	DC output	20.0V
	Hold-up time	100% load 10ms at 115 Vac input
	Output Over Current Protection	< 28.0A
	Connector	C14
	Connector	4.5mm Barrel Type
	Environmental Design	
	Operating temperature	32°F to 95°F (0° to 35°C)
	Non-operating (storage) temperature	-4°F to 185°F (-20° to 85°C)
	Altitude	0 to 16,400 ft (0 to 5000m)
	Humidity	20% to 95%
	Storage Humidity	10% to 95%
	EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1, IEC 62368-1:2014 and IEC62368-1 : 2018, EN62368-1:2020+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, CU(EAC), KCC(Safety+EMC), NOM-001 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC

GT 99Whr Long Life Polymer Fast Charge 8 cell Battery	**Weight**	0.39 kg +/- 10g(0.86 lb)
	Cells/Type	8cell Lithium-Ion Polymer cell /574269
	Energy	
	Voltage	15.56V
	Amp-hour capacity	6.37Ah
	Watt-hour capacity	99Wh
	Temperature	
	Operating (Charging)	0˚ to 45˚ C (32˚ to 113˚ F)
	Operating (Discharging)	-10~65 ˚ C (14˚ to 149˚ F)

AUDIO

HD Stereo Codec	Realtek ALC3315
Audio I/O Ports	Support 3.5mm Headset: CTIA only and Headphone-out
Internal Speaker Amplifier	Texas Instruments digital input Class-D smart audio amplifiers
Multi-streaming Capable	Playback multi-streaming can be enabled in the audio control panel to allow independent audio. Following MSFT Behaviour
Sampling	DAC:48kHz 16bits~24bits ADC:44.1k~48kHz 16bits~24bits
Wavetable Syntheses	
Analog Audio	Support 3.5mm Headset: CTIA only and Headphone-out
Internal Speaker	Yes

FINGERPRINT READER

Sensor vendor	Synaptics FS7614
Sensor type	Capacitive
DPI resolution	363 DPI
Scan area	104 x 86 pixels
False Rejection Rate	<3%
False Acceptance Rate	< 0.001%
Mobile Voltage Operation	3.0V to 3.6V
Operating Temperature	0°~60°C
Current Consumption Image	100mA max
Low Latency Wait For Finger	260uA
Capture Rate	Image transmitter output frequency 9.6MHz
ESD Resistance	IEC 61000-4-2 4B (+15KV)
Detection Matrix	363 dpi / 7.4x6mm sensor area

ENVIRONMENTAL DATA

Eco-Label Certifications & declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR®
- US Federal Energy Management Program (FEMP)
- EPEAT® Gold registered in the United States. See http://www.epeat.net for registration status in your country.
- TCO Certified
- China Energy Conservation Program (CECP)
- China State Environmental Protection Administration (SEPA)
- Taiwan Green Mark
- Korea Eco-label
- Japan PC Green label*

Sustainable Impact Specifications

- Product Carbon Footprint
- At least 30% ocean bound plastic in the speaker[1]
- At least 30% post-consumer recycled plastic[2]
- At least 85% recycled metal[3]
- Low Halogen[4]
- 100% of HP paper-based packaging is from recycled or certified sustainable sources[5]
- Bulk packaging available

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".

Energy Consumption (in accordance with US ENERGY STAR® test method)	**115VAC, 60Hz**	**230VAC, 50Hz**	**100VAC, 50Hz**
Normal Operation (Short idle)	9.09 W	9.10 W	9.09 W
Normal Operation (Long idle)	N/A	N/A	N/A
Sleep	1.93 W	1.98 W	2.02 W
Off	0.46 W	0.45 W	0.45 W

NOTE:

Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Heat Dissipation*	**115VAC, 60Hz**	**230VAC, 50Hz**	**100VAC, 50Hz**
Normal Operation (Short idle)	31 BTU/hr	31 BTU/hr	31 BTU/hr
Normal Operation (Long idle)	N/A	N/A	N/A
Sleep	6.6 BTU/hr	7 BTU/hr	6.9 BTU/hr
Off	1.6 BTU/hr	2 BTU/hr	1.5 BTU/hr

***NOTE:** Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (L_{Wad}, bels)	Sound Pressure (L_{pAm}, decibels)
Typically Configured – Idle	3.2	22.3
Fixed Disk – Random writes	3.4	24.0
Optical Drive – Sequential reads	4.8	37.9

Longevity and Upgrading

This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the

Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product is 98.1% recycle-able when properly disposed of at end of life.

Packaging Materials

External:	PAPER/Corrugated	367 g
	PAPER/Molded Pulp	175 g
	PAPER/Paper	28 g

The plastic packaging material contains at least 0.0% recycled content.

The corrugated paper packaging materials contains at least 59% recycled content.

RoHS Compliance

HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.

We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.

We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve.

To obtain a copy of the HP RoHS Compliance Statement, see HP RoHS position statement.

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c05998906):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Bis(2-Ethylhexyl) phthalate (DEHP)
- Benzyl butyl phthalate (BBP)
- Dibutyl phthalate (DBP)
- Diisobutyl phthalate (DIBP)
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: https://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c05403198 or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: HP Product Disassembly Instruction Website. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

HP Inc. Corporate Environmental Information

For more information about HP's commitment to the environment:

- Sustainable Impact Report
  - https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c06040843
- Eco-label certifications
  - https://www.hp.com/us-en/sustainable-impact/document-reports.html#filters_documents_reports-=document_type-type_energy_star,type_epeat,type_tcoISO
- ISO 14001 certificates
  - https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c04777932

Footnotes

1. Percentage of ocean-bound plastic contained in each component varies by product. Ocean Bound plastic is expressed as a percentage of the total weight plastic. Ocean Bound plastic is based on the definition set by the UL2809 standard.
2. Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled is based on the definition set in the EPEAT standard for computers, IEEE 1680.1-2018 standard.
3. Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams.
4. External power supplies, WWAN modules, power cords, cables and peripherals excluded. Service parts obtained after purchase may not be Low Halogen.
5. HP paper and fiber-based packaging for PCs, displays, home and office print, and supplies is reported by suppliers as recycled or certified, with a minimum of 97% by volume verified by HP. Packaging is the box that comes with the product and all paper-based materials inside the box. Packaging for personal systems accessories and spare parts is not included. Plastic cushions are made from >90% recycled plastic.

OPTIONS

Type	Description	Part Number
Bags	HP Renew Business 17.3 Laptop Backpack	3E2U5UT
	HP Renew Business 17.3 Laptop Bag	3E2U6AA
	HP Renew Business 17.3 Laptop Backpack (Bulk Qty. 6)	3E2U5A6
	HP Renew Executive 16 Laptop Backpack	6B8Y1UT
	HP Renew Executive 16 Laptop Bag	6B8Y2AA
	HP Campus XL Marble Stone Backpack	7J592AA
	HP Campus XL Marble Stone Backpack	7K0E2AA
	HP Campus XL Tie Dye Backpack	7J593AA
	HP Campus XL Tie Dye Backpack	7K0E3AA
	HP Convertible Laptop Stand	9C2H2AA
	HP Everyday 16 Odyssey Gray Laptop Briefcase	A08JTAA
	HP Everyday 16 Odyssey Gray Laptop Briefcase	A08KHUT
	HP Everyday 16 Odyssey Gray Laptop Bag	A08JWAA
	HP Everyday 16 Odyssey Gray Laptop Bag	A08KKAA
	HP Everyday 16 Odyssey Gray Laptop Backpack	A08JXAA
	HP Everyday 16 Odyssey Gray Laptop Backpack	A08KLUT
	HP Everyday 16 Odyssey Gray Laptop Backpack (Bulk Qty.10)	A08KLA6
	HP Everyday 16 Odyssey Gray Laptop Bag (Bulk Qty.15)	A08KKA6
	HP Travel Plus 30 Liter 17 Laptop Backpack	A2CC9AA
	HP Travel Plus 30 Liter 17 Laptop Backpack	A2CE0AA
	HP Travel Plus 22 Liter 16 Laptop Bag	A2CD0AA
	HP Travel Plus 22 Liter 16 Laptop Bag	A2CE1AA
Docking	HP Thunderbolt 4 Ultra 280W G6 Dock	AW5M5UT
	HP Thunderbolt 280W G4 Dock w/Combo Cable	4J0G4AA
	HP Thunderbolt 280W G4 Dock w/Combo Cable	4J0G4ET

	HP Thunderbolt 280W TAA G4 Dock w/Combo Cable	4J0J9AA
Input/Output	HP USB-C to USB-C 100W Cable	5AR72AA
Keyboard/Mouse	HP 320K Wired Keyboard	9SR37AA
	HP 975 USB+BT Dual-Mode Wireless Keyboard	3Z726AA
	HP 455 Programmable Wireless Keyboard	4R177AA
	HP 455 Programmable USB Wireless Keyboard (Bulk Qty.12)	4R177A6
	HP 965 BLK Ergonomic Wireless Keyboard	7E756AA
	HP 475 Dual-Mode Wireless Keyboard	7N7B9AA
	HP 475 Dual-Mode Wireless Keyboard	7N7B9UT
	HP 405 Multi-Device Backlit Wired Keyboard	7N7C1AA
	HP 405 Multi-Device Backlit Wired Keyboard	7N7C1UT
	HP 435 Programmable Bluetooth Wireless Keypad	7N7C3AA
	HP Wired Desktop 320MK Mouse and Keyboard	9SR36AA
	HP 655 Wireless Keyboard and Mouse Combo	4R009AA
	HP 655 Wireless Keyboard and Mouse Combo (Blk Qty.10)	4R009A6
	HP Wired 320M Mouse	9VA80AA
	HP Multi-Device 635 Black Wireless Mouse	1D0K2AA
	HP Creator 935 Black Wireless Mouse	1D0K8AA
	HP 235 Slim Wireless Mouse	4E407AA
	HP 235 Slim Wireless Mouse	4E407UT
	HP 435 Multi-Device Wireless Mouse	3B4Q5UT
	HP 715 Rechargeable Multi-Device Bluetooth Mouse	6E6F0AA
	HP 925 Ergonomic Vertical Wireless Mouse	6H1A5AA
	HP 695 Qi-Charging Wireless Mouse	8F1Y4AA
	HP Tilt Ergonomic Mouse 725M	BH0Z5AA
Hub	HP USB-C to USB-A Hub	Z6A00AA

	HP Portable USB-C Hub	B8SU8UT
	HP Portable USB-C Hub	B8SV8AA
Audio	HP USB G2 Stereo Headset	428H5AA
	HP USB G2 Stereo Headset	428K6AA
	HP USB G2 Stereo Headset	428K6PT
Power	HP 330W Smart AC Adapter	BF7A6AA
	HP 330W Smart AC Adapter	BF7C7AA
Security	HP Nano Keyed Cable Lock	1AJ39AA
	HP Nano Master Keyed Cable Lock	1AJ40AA
	HP Sure Key Cable Lock	6UW42AA
	HP Nano Combination Cable Lock	63B28AA
	HP Essential Nano Combination Cable Lock	63B31AA
	HP 16 Widescreen Laptop Privacy Filter	BH0M5AA

Date of change	Version History		Description of change
June 2, 2025	From v1 to v2	Changed	Format
June 5, 2025	From v2 to v3	Added	Environmental Data Section
July 23, 2025	From v3 to v4	Changed	Power, Memory, Docking (Sold Separately) Sections
August 4, 2025	From v4 to v5	Changed	Software And Security Section
August 20, 2025	From v5 to v6	Changed	Format Page 1
September 4, 2025	From v6 to v7	Changed	Storage And Drives Section
October 1, 2025	From v7 to v8	Changed	Memory Section
November 11, 2025	From v8 to v9	Changed	Software And Security Section
December 5, 2025	From v9 to v10	Added	Displays Section
December 17, 2025	From v10 to v11	Addition	CSODIMM NECC and CSODIMM Memory cards added
April 27, 2025	From v11 to v12	Updated	Processor Section
April 29, 2025	From v12 to v13	Updated	Memory Section
May 25, 2026	From v13 to v14	Updated	Software and Security Section
September 16, 2026	From V14 to V15	Updated	Software Section
November 10, 2026	From V15 to V16	Updated	Intel® I226-LM 2.5 (vPro) and (non-vPro), Power consumption and IT manageability sections updated

© Copyright 2026 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core, Thunderbolt and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.