

Siemens
EcoTech



AS-Interface module, 2 safe inputs, black, 4-pole connector with screw terminal and 4-pole connector with spring-type terminal, for front plate mounting



product brand name	SIRIUS ACT
product designation	AS-Interface module
product type designation	3SU1
General technical data	
product function	2F-DI
degree of pollution	3
type of voltage	
• of the operating voltage	DC
• of the input voltage	DC
consumed current maximum	60 mA
protection class IP	IP20, clamping screw tightened
shock resistance for railway applications according to EN 61373	Category 1, Class B
vibration resistance for railway applications according to EN 61373	Category 1, Class B
reference code according to IEC 81346-2	K
Substance Prohibitation (Date)	10/01/2014
SVHC substance name	Lead - 7439-92-1 Lead monoxide (lead oxide) - 1317-36-8 Diboron trioxide - 1303-86-2
design of the slave type	2 F-DI
AS-Interface slave profile	S-0.B.F
ID1 code	0...F
number of AS-i slaves	1
operating voltage rated value	26.5 ... 31.6 V
operating voltage 1 at DC rated value	30 V
Communication/ Protocol	
protocol is supported	
• AS-Interface protocol	Yes
• ASIsafe (Safety at work) protocol	Yes
Inputs/ Outputs	
number of digital inputs	
• safety-related	2
Connections/ Terminals	
type of electrical connection	Screw connection + spring-type terminal
type of connectable conductor cross-sections	
• solid without core end processing	1x (0.2 ... 2.5 mm²)
• finely stranded with core end processing	1x (0.25 ... 2.5 mm²)
• finely stranded without core end processing	1x (0.2 ... 2.5 mm²)

• for AWG cables	1x (30 ... 12)
tightening torque with screw-type terminals	0.5 ... 0.6 N·m
Product Function	
suitability for use safety-related circuits	Yes
Safety related data	
product function suitable for safety function	Yes
category according to EN 954-1	4
average diagnostic coverage level (DCavg)	99 %
IEC 62061	
SIL Claim Limit (subsystem) according to EN 62061	SILCL 3
Safety Integrity Level (SIL) according to IEC 62061	3
ISO 13849	
performance level (PL) according to ISO 13849-1	e
IEC 61508	
Safety Integrity Level (SIL)	
• according to IEC 61508	3
PFHD with high demand rate according to IEC 61508	4.5E-9 1/h
PFDavg with low demand rate according to IEC 61508	5E-6
Safe failure fraction (SFF)	99 %
Ambient conditions	
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3 (without salt spray), 3K6 (with relative humidity of 10 ... 95%, no condensation in operation permitted)
Environmental footprint	
Environmental Product Declaration (EPD)	Yes
Global Warming Potential [CO2 eq] total	0.787 kg
Global Warming Potential [CO2 eq] during manufacturing	0.566 kg
Global Warming Potential [CO2 eq] during operation	0.235 kg
Global Warming Potential [CO2 eq] after end of life	-0.015 kg
Siemens Eco Profile (SEP)	Siemens EcoTech
Installation/ mounting/ dimensions	
fastening method	
• of modules and accessories	Front plate mounting
• of AS-i slaves	Frontplattenbefestigung
height	42 mm
width	30 mm
depth	65.5 mm
Approvals Certificates	
General Product Approval	
EMV	

[Confirmation](#)



Functional Safety	Test Certificates	other	Environment
	Special Test Certificate	Type Test Certificates/Test Report	Confirmation
Environment		Industrial Communication	
Environmental Confirmations			

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1400-1EA10-2AA0>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1400-1EA10-2AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1400-1EA10-2AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1400-1EA10-2AA0&lang=en



-K1

AS-i Bus:
Slave:




☐ F-IN1

☐ F-IN2

☐ AS-i Fault

Logic



1 ASI+

2 ASI-

3 ASI+

4 ASI-

ADDR

last modified:

3/11/2024