

SCALANCE XR326-8; managed layer 2; IE switch, 19" rack; 24x 100/1000 Mbps RJ45 port; 2x 1G/2.5G/5G/10 Gbps RJ45 8x 1G/10G SFP+ port; LED diagnostics; error signaling contact; select/set button; PROFINET IO device; network management; integrated redundancy manager; office features (RSTP, VLAN, IGMP,...); CLP included in scope of supply; power supply 230 V AC;



product type designation	
product brand name	SCALANCE
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 2.5 Gbit/s, 5 Gbit/s, 10 Gbit/s
interfaces / for communication / integrated	
number of electrical connections	
• for network components or terminal equipment	26; RJ45
number of 10/100/1000 Mbit/s RJ45 ports	
• with securing collar	26
number of 1000/2500/5000/10000 Mbps RJ45 ports / with securing collar	2
number of electrical connections	
• for SFP+	8; 1000 Mbps and 10000 Mbps SFP usable
interfaces / other	
number of electrical connections	
• for operator console	1
• for signaling contact	1
• for power supply	1
type of electrical connection	
• for operator console	USB (2.0 Port, Type B, serial via USB)
• for signaling contact	2-pole terminal block
• for power supply	IEC plug C14 AC supply or 2-pole terminal block for DC supply
design of the removable storage	
• CLP	Yes
operating voltage / of the signaling contacts	
• at AC / rated value	24 V
• at DC / rated value	24 V
operational current / of the signaling contacts	
• at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	No
type of voltage supply / redundant power supply unit	No
type of voltage / 1 / of the supply voltage	
• supply voltage / 1 / rated value	DC
• power loss [W] / 1 / rated value	100V ... 250V DC
• supply voltage / 1 / rated value	99 W
• consumed current / 1 / maximum	77 ... 300 V
• type of electrical connection / 1 / for power supply	0.8 A
• product component / 1 / fusing at power supply input	2-pole terminal block
• fuse protection type / 1 / at input for supply voltage	Yes
	F 4A / 250 V

type of voltage / 2 / of the supply voltage		AC (50 / 60Hz) 240 V; 100V ... 240V AC 99 W 85 ... 264 V 0.8 A C14, IEC plug F 4A / 250 V
ambient conditions		
ambient temperature / in horizontal mounting position / during operation		-25 ... +60 °C; Starting at -25 °C; The maximum ambient temperature during operation depends on the operating height and the plug-in transceivers, see also manual.
installation altitude / at height above sea level / maximum		3000 m
relative humidity		
• at 25 °C / without condensation / during operation / maximum		95 %
operating condition / fanless operation		Yes
protection class IP		IP20
design, dimensions and weights		
design	19" rack	
number of modular height units / relating to 19-inch cabinet	1	
width	446 mm	
height	43.6 mm	
depth	374.8 mm	
net weight	8.2 kg	
material / of the enclosure	metal	
fastening method		
• 19-inch installation	Yes	
product features, product functions, product components / general		
cascading in the case of a redundant ring / at reconfiguration time of <~0.3\~s	50	
cascading in cases of star topology	any (depending only on signal propagation time)	
number of automatically learnable MAC addresses	16382	
number of QoS queues / per port	8	
product function		
• QoS according to IEEE 802.1Q	Yes	
product feature		
• Store & Forward switching method	Yes	
product functions / management, configuration, engineering		
product function		
• CLI	Yes	
• web-based management	Yes	
• MIB support	Yes	
• TRAPs via email	Yes	
• configuration with STEP 7	Yes	
• RMON	Yes	
• SMTP server	No	
• port mirroring	Yes	
• multiport mirroring	Yes	
• Encapsulated Remote Traffic Mirroring (ERTM)	Yes	
• CoS	Yes	
• PROFINET IO diagnosis	Yes	
• switch-managed	Yes	
PROFINET conformity class	B	
network load class / according to PROFINET	3	
telegram length / for Ethernet / maximum	9194 byte	
protocol / is supported		
• Telnet	Yes	
• HTTP	Yes	
• HTTPS	Yes	
• TFTP	Yes	
• FTP	Yes	
• SFTP	Yes	

• BOOTP	Yes
• NETCONF	Yes
• GMRP	Yes
• DCP	Yes
• LLDP	Yes
• EtherNet/IP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	Yes
identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 - higher level designation/location designation	Yes
product functions / diagnostics	
product function	
• port diagnostics	Yes
• statistics Packet Size	Yes
• statistics packet type	Yes
• error statistics	Yes
• SysLog	Yes
product functions / VLAN	
product function	
• VLAN - port based	Yes
• VLAN - protocol-based	No
• VLAN - IP-based	No
number of VLANs / maximum	257
number of VLANs - dynamic / maximum	257
number of VLANs / at ring redundancy (HRP; MRP; standby link)	257
product functions / DHCP	
product function	
• DHCP server	Yes
• DHCP client	Yes
• DHCP Option 82	Yes
• DHCP Option 66	Yes
• DHCP Option 67	Yes
product functions / redundancy	
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
• media redundancy protocol (MRP) with redundancy manager	Yes
• Media Redundancy Protocol Interconnection (MRP-I)	Yes
• of the PROFINET IO device / is supported / H-Sync forwarding	Yes
• of the PROFINET IO device / is supported / PROFINET system redundancy	Yes
• ring redundancy	Yes
• high speed redundancy protocol (HRP) with redundancy manager	Yes
• high speed redundancy protocol (HRP) with standby redundancy	Yes
• redundancy procedure STP	Yes
• redundancy procedure RSTP	Yes
• redundancy procedure RSTP+	Yes
• redundancy procedure MSTP	Yes
• High-availability Seamless Redundancy (HSR)	Yes
• Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	Yes
• passive listening	Yes
protocol / is supported	
• STP/RSTP	Yes

• STP	Yes
• RSTP	Yes
• MSTP	No
• RSTP big network support	Yes
• LACP	Yes
system modification during operation	
product function / configuration in RUN via CiR/H-CiR	Yes
product functions / security	
product function	
• IEEE 802.1x (radius)	Yes
• broadcast/multicast/unicast limiter	Yes
• broadcast blocking	Yes
protocol / is supported	
• SSH	Yes
• SSL	Yes
product functions / time	
product function	
• SICLOCK support	Yes
• NTP-client	Yes
• SNTP client	Yes
• IEEE 1588 v2 transparent forwarding	Yes
protocol / is supported	
• NTP	Yes
• SNTP	Yes
• IEEE 1588 profile default	No
accuracy / at IEEE 1588 v2	
• not less than	100 µs
• typical	50 ns
standards, specifications, approvals	
certificate of suitability	
• CE marking	Yes
• UKCA marking	Yes
• cULus approval	Yes
• KC approval	Yes
• Regulatory Compliance Mark (RCM)	Yes
product conformity / according to EMC-guideline	2014/30/EU
standard	
• for EMC interference emission	EN 61000-6-4
• for immunity to EMC	EN 61000-6-2
standards, specifications, approvals / other	
certificate of suitability	
• railway application in accordance with EN 50121-4	Yes; use only in areas not accessible to the public
• railway application in accordance with EN 50125-3	Yes
IT security for industrial automation systems / according to IEC 62443-4-2:2019	Yes
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
Global Warming Potential [CO2 eq]	
• total	1274.81 kg
• during manufacturing	225.96 kg
• during operation	1048 kg
• after end of life	0.85 kg
product functions / general	
MTBF	8.3 a
reference temperature / for MTBF determination	40 °C
reference code	
• according to IEC 81346-2	KF
• according to IEC 81346-2:2019	KFE
Warranty period	5 a
further information / internet links	

internet link

- to website: Selection guide for cables and connectors
- to web page: selection aid TIA Selection Tool
- to website: Industrial communication
- to web page: SiePortal
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<https://support.industry.siemens.com/cs/ww/en/view/109766358>
<https://www.siemens.com/tstcloud>
<https://www.siemens.com/simatic-net>
<https://sieportal.siemens.com/>
<https://www.automation.siemens.com/bilddb>
<https://www.siemens.com/cax>
<https://support.industry.siemens.com>

security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under [https://www.siemens.com/cert. \(V4.7\)](https://www.siemens.com/cert. (V4.7))

Approvals / Certificates

General Product Approval



[Type Test Certificates/Test Report](#)

PROFINET

last modified:

8/16/2024