


# Product datasheet

Specifications



## APC NetShelter SX Advanced Rack, 48U 750mm 1470mm, without shock package, Black

AR9657B2

### Main

|                           |   |
|---------------------------|---|
| Product or component type | Rack enclosure  |
| Number of rack unit       | 48U   |
| Provided equipment        | Baying hardware<br>Key(s)<br>Leveling feet<br>Mounting hardware<br>Pre-installed casters<br>Side panels |

### Physical

|                            |   |
|----------------------------|---|
| Height                     | 2256 mm   |
| Width                      | 750 mm  |
| Depth                      | 1470 mm   |
| Product weight             | 288 kg  |
| Colour                     | Black   |
| Mounting preference        | No preference   |
| Mounting mode              | Not rack-mountable  |
| Maximum mounting depth     | 1320.8 mm   |
| Minimum mounting depth     | 292 mm  |
| Rack width                 | 19"   |
| Marking                    | 12 gauge EIA mounting rail<br>16 gauge front door<br>16 gauge post<br>18 gauge rear door<br>18 gauge roof<br>18 gauge side panels |
| Permanent permissible load | 1927.8 kg static<br>1587.6 kg dynamic   |

### Conformance

|           |                     |
|-----------|---------------------|
| Standards | EIA-310E<br>UL 2416 |
|-----------|---------------------|

### Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 239.17 cm |
| Package 1 Width              | 90 cm     |

---

|                  |           |
|------------------|-----------|
| Package 1 Length | 159.08 cm |
|------------------|-----------|

---

|                  |        |
|------------------|--------|
| Package 1 Weight | 320 kg |
|------------------|--------|

## Contractual warranty

---

|                      |    |
|----------------------|----|
| Warranty (in months) | 60 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|  |   |
|--|---|
| Total lifecycle Carbon footprint                       | 1 168 kg CO2 eq.                              |
| Carbon footprint of the manufacturing phase [A1 to A3] | 1 709 kg CO2 eq.                              |
| Carbon footprint of the distribution phase [A4]        | 95 kg CO2 eq.                                 |
| Carbon footprint of the installation phase [A5]        | 37 kg CO2 eq.                                 |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 0 kg CO2 eq.                                  |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 767 kg CO2 eq.                                |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|  |   |
|--|---|
| Average percentage of recycled plastic content | 1 %   |
| Packaging made with recycled cardboard         | Yes   |
| Packaging without single use plastic           | Yes   |
| EU RoHS Directive                              | <a href="#">Compliant</a>   |
| REACH Regulation                               | <a href="#">Free of Substances of Very High Concern above the threshold</a> |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                               |    |
|-------------------------------|----|
| Recyclability potential, in % | 97 |
| Take-back                     | No |

Image of product / Alternate images

Alternative

---

