

Statement of Volatility

Dell Pro P 27 USB-C Hub Webcam Monitor P2726DEV

⚠ CAUTION: A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

The Dell P2726DEV monitor contains both volatile and non-volatile components. Volatile components erase their data immediately after power is removed from the component. Non-volatile components continue to retain their data even after power is removed from the component. The following non-volatile components are present on the Dell P2726DEV monitor system board.

Table 1. List of Non-Volatile components on System Board

Description	Reference Designator	Volatility Description	User Accessible for external data	Remedial Action (Action necessary to prevent loss of data)
Serial Flash ROM MX25L3233FM2I-08G	U302	Non-volatile Flash memory, 32M bit. To store scaler firmware.	No	The part is installed on the Interface Board and is configured with both hardware and software-level write protection.
EEPROM P24C128F-SSH-MIR	U303	Non-volatile memory, 128K bit. To store scaler data.	No	The part is installed on the Interface Board and is configured with both hardware and software-level write protection.
Serial Flash ROM MX25V80066M1I02	U1303	Non-volatile Flash memory, 8M bit. To store PD firmware.	No	The part is installed on the Interface Board and is configured with both hardware and software-level write protection.
Serial Flash ROM W25X40CLSNIG	U1903	Non-volatile Flash memory, 4M bit. To store HUB1 firmware.	No	The part is installed on the Interface Board and is configured with both hardware and software-level write protection.
Serial Flash ROM W25X40CLSNIG	U1906	Non-volatile Flash memory, 4M bit. To store HUB2 firmware.	No	The part is installed on the Interface Board and is configured with both hardware and software-level write protection.

⚠ CAUTION: All other components on the system board lose data if power is removed from the computer. Primary power loss (unplugging the power cable and removing the battery) destroys all user data on the memory. Secondary power loss (removing the on-board coin-cell battery) destroys system data on the system configuration and time-of-day information.