

# Product datasheet

Specifications



APC NetShelter SX, Server Rack Enclosure Gen 2, Shock Packaging, 2500 lbs, Black, 48U x 600W x 1200D

AR3307SPB2

EAN Code: 3606487836605

## Main

|                           |                          |
|---------------------------|--------------------------|
| Product or component type | Rack enclosure           |
| Number of rack unit       | 48U                      |
| Provided equipment        | Baying hardware          |
| Range of product          | NetShelter SX Enclosures |

## Physical

|                            |                            |
|----------------------------|----------------------------|
| Height                     | 2258 mm                    |
| Width                      | 600 mm                     |
| Depth                      | 1200 mm                    |
| Product weight             | 146.2 kg                   |
| Colour                     | Black                      |
| Mounting preference        | No preference              |
| Mounting mode              | Not rack-mountable         |
| Maximum mounting depth     | 1048 mm                    |
| Minimum mounting depth     | 190.5 mm                   |
| Rack width                 | 19"                        |
| Marking                    | 14 gauge EIA mounting rail |
| Permanent permissible load | 1020.6 kg dynamic          |

## Conformance

|           |         |
|-----------|---------|
| Standards | UL 2416 |
|-----------|---------|

## Packing Units

|                              |                     |
|------------------------------|---------------------|
| Unit Type of Package 1       | PCE                 |
| Number of Units in Package 1 | 1                   |
| Package 1 Height             | 246.9 cm            |
| Package 1 Width              | 112.5 cm            |
| Package 1 Length             | 136.1 cm            |
| Package 1 Weight             | 248.835812857143 kg |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 60 |
|----------------------|----|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 2 864 ton CO2 eq.                             |
| Carbon footprint of the manufacturing phase [A1 to A3] | 1 876 ton CO2 eq.                             |
| Carbon footprint of the distribution phase [A4]        | 104 ton CO2 eq.                               |
| Carbon footprint of the installation phase [A5]        | 40 789 kg CO2 eq.                             |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 0 kg CO2 eq.                                  |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 842 ton CO2 eq.                               |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                                |                                                                                                                                       |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Average percentage of recycled plastic content | 50 %                                                                                                                                  |
| Average percentage of recycled metal content   | 70 %                                                                                                                                  |
| Packaging made with recycled cardboard         | Yes                                                                                                                                   |
| Packaging without single use plastic           | No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards |
| EU RoHS Directive                              | <a href="#">Compliant By Exemption</a>                                                                                                |
| REACH Regulation                               | <a href="#">Reference contains Substances of Very High Concern above the threshold</a>                                                |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                                 |                                          |
|---------------------------------|------------------------------------------|
| Recyclability potential, in %   | 97                                       |
| End of life manual availability | No need of specific recycling operations |
| Removable battery               | No                                       |
| Take-back                       | No                                       |

Image of product / Alternate images

Alternative

---







