






11-in-1 DockingStation for 2 screens with Power Delivery
11-in-1 DockingStation für 2 Bildschirme mit Power Delivery
Station d'accueil 11-en-1 pour 2 écrans avec Power Delivery
Stacja dokująca 11-w-1 do 2 ekranów z Power Delivery




1x









1x



1x




1x





Legacy USB standards	Current USB standards	Data transfer rate
USB 3.0 = USB 3.1 (Gen 1)	= USB 3.2 Gen 1	= 5 Gbps
USB 3.1 = USB 3.1 (Gen 2)	= USB 3.2 Gen 2	= 10 Gbps
USB 3.2 (Gen 2x2)	= USB 3.2 Gen 2x2	= 20 Gbps
	= USB4® Gen 2x1	= 10 Gbps
	= USB4® Gen 2x2	= 20 Gbps
	= USB4® Gen 3x2	= 40 Gbps



© Copyright 2026 by RaidSonic Technology GmbH. All Rights Reserved.
The information contained in this manual is believed to be accurate and reliable. RaidSonic Technology GmbH assumes no responsibility for any errors contained in this manual. RaidSonic Technology GmbH reserves the right to make changes in the specifications and/or design of the above-mentioned product without prior notice. The diagrams contained in this manual may also not fully represent the product that you are using and are there for illustration purposes only. USB Type-C and USB-C are registered trademarks of USB Implementers Forum. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. RaidSonic Technology GmbH assumes no responsibility for any differences between the product mentioned in this manual and the product you may have.

1



1



2



www.synaptics.com/products/displaylink-graphics/downloads




3



4



2



3

