

Newer version available PEX1P2: 1 Port PCI Express Dual Profile Parallel Adapter Card - SPP/EPP/ECP - 1x DB25 IEEE 1284 PCIe Parallel Card (PEX1P)

**Product ID: PEX1P** 



The PEX1P PCIe Parallel Adapter card can be installed in a PCI Express (PCIe) slot, allowing you to connect EPP/ECP parallel peripherals to any computer system. Relying on a native single-chip design(Oxford OXPCIe952), this adapter harnesses the true capability of PCI Express - ensuring maximum performance and reliability.

This high performance SPP/EPP/ECP parallel card adds one DB25 parallel port, perfect for connecting printers, scanners, CD-R/RW drives, memory card readers, bar code scanners and more. With the added convenience of plug and play capability, installing the parallel adapter card is hassle-free!

The PCIe Parallel Adapter card includes both standard and half-height/low profile mounting brackets and is backed by a StarTech.com two year warranty and free lifetime technical support.

# **Certifications, Reports and Compatibility**

## **Applications**

Connects any parallel peripheral including printers, scanners, CD-R/RWs, Zip drives, and memory card readers.

#### **Features**

- SPP/EPP/ECP Parallel port fully supports existing Centronics interface
- Compliant with PCI Express Base Specification 1.0a
- Includes low profile/half-height mounting bracket
- PCI 2.2 and PCI Power Management 1.0 compliant



| Hardware                 |                               |   |
|--------------------------|-------------------------------|---|
|                          | Warranty                      | 2 Years   |
|                          | Ports                         | 1   |
|                          | Interface                     | Parallel  |
|                          | Bus Type                      | PCI Express   |
|                          | Card Type                     | Standard Profile (LP bracket incl.)   |
|                          | Port Style                    | Integrated on Card  |
|                          | Chipset ID                    | PLX/Oxford - OXPCIe952  |
| Performance              |                               |   |
|                          | Maximum Data Transfer<br>Rate | 2.5 Mbps  |
|                          | MTBF                          | 26,297 Hours  |
| Connector(s)             |                               |   |
|                          | Connector Type(s)             | PCI Express x1  |
|                          | External Ports                | DB-25 (25 pin, D-Sub)   |
| Software                 |                               |   |
|                          | OS Compatibility              | Windows CE 6.0 / 5.0, 95, 98SE, 2000, XP, XP Embedded, Vista, 7, 8, 8.1, 10, 11 |
|                          |                               | Windows Server 2003, 2008 R2, 2012, 2012 R2, 2016, 2019                         |
|                          |                               | Linux 2.4.x to 4.11.x <i>LTS Versions only</i>                                  |
| Physical Characteristics |                               |   |
|                          | Material                      | Steel   |
|                          | Product Length                | 0.8 in [21.0 mm]  |
|                          | Product Width                 | 4.3 in [11.0 cm]  |
|                          | Product Height                | 4.7 in [12.0 cm]  |
|                          | Weight of Product             | 1.5 oz [42.0 g]   |

**Packaging** 



#### Information

Package Length 6.7 in [17.0 cm]

Package Width 5.6 in [14.3 cm]

Package Height 1.2 in [30.0 mm]

Shipping (Package)

Weight

4.7 oz [133.0 g]

### What's in the Box

Included in Package PCI Express Parallel Card

Low Profile Bracket

Driver CD

Instruction Manual

<sup>\*</sup>Product appearance and specifications are subject to change without notice.