HP Color LaserJet Enterprise flow M880 Multifunction Printer series



Top colour performance. Solid value.

This top-of-the-line enterprise MFP helps streamline workflows and accelerate document tasks with advanced finishing options and file sharing. Give users simple, direct access to this MFP through mobile printing and touch-to-print capabilities^{1,2}.





Single-pass 2-sided ADI

Color touchscreen

Wireless direct

settings



Give workgroups the speed they need.

- Let departments scan without worry: HP EveryPage detects potential errors or missed pages on the spot.
- Manage content in a way you never thought possible with HP Flow CM Enterprise³.
- Forget email let employees scan and send documents to Microsoft[®] SharePoint[®] in one step.
- Make it easy to be efficient with an intuitive touchscreen and large pull-out keyboard.

Keep your business moving.

- Save on both sides capture documents faster with two-sided, single-pass scanning.
- Create easily searchable scanned files, using built-in optical character recognition software.
 Save IT time and make printing easy for the entire company by using a single driver for all HP devices⁴.
- Let employees complete big jobs faster, choosing from a range of finishing options⁵.

Be much more efficient with mobile printing.

- Give users simple, direct access through wireless direct printing and touch-to-print technology⁶.
- Mobile printing at a touch enable touch-to-print convenience from mobile devices².
- Let employees print from mobile devices with built-in print capability or HP ePrint app and software¹.
- Give users the power to print wirelessly from an iPad[®], iPhone[®], or iPod touch^{®7}.

Invest once, expand easily and manage efficiently.

- Expand your options: easily upgrade firmware on your schedule, and easily integrate solutions or devices at will.
- Help build business efficiency. Centrally monitor and control printers with HP Web Jetadmin⁸.
- Apply fleet-wide policies to help protect all your HP devices with the HP Imaging and Printing Center⁹.
- Confidently safeguard the sensitive data sent to your MFP with the HP High-Performance Secure Hard Disk.

Product walkaround

HP Color LaserJet Enterprise flow MFP M880z+ shown:

- 1. Intuitive 8-inch (20.3 cm) HP Easy Select pivoting color touchscreen control panel
- 2. 200-sheet automatic document feeder with single pass two-sided scanning, and HP
- EveryPage with ultrasonic double-feed detection 3. Home button (returns to home screen)
- 4. Plate glass color scanner handles sizes up to 11 x 17 in/A3
- 5. Easy-access USB port to save and print files directly
- 6. Hardware integration pocket for solution integration*
- 7.500-sheet output bin
- 8. Front door provides convenient access to HP toner cartridges and drums
- 9. Built-in automatic two-sided printing
- 10. Retractable keyboard for easy, accurate data entry
- 11. 100-sheet multipurpose tray 1 handles heavy custom media up to 58 lb bond (220 $g/m^2)$
- 12. Right-side doors provide access to the fuser and for clearing jams
- 13. 500-sheet input tray supports media up to size 11×17 in/A3
- 14. 3,500-sheet high-capacity input tray supports media sizes letter/A4
- 15. HP Jetdirect Gigabit Ethernet print server
- 16. HP High-Performance Secure Hard Disk
- 17. Access port for optional Kensington-style lock
- 18. Hi-Speed USB 2.0 port (for connecting third-party devices)
- 19. Hi-Speed USB 2.0 printing port
- 20. 800 MHz processor, 2.5 GB (system memory)
- 21. Foreign interface harness (for connecting external devices)
- 22. Two internal host USB 2.0 type ports for third party solutions
- 23. RJ-11 fax port

Series at a glance





Model	HP Color LaserJet Enterprise flow M880z Multifunctio Printer	n HP Color LaserJet Enterprise flow M880z+ Multifunction Printer	
Product number	A2W75A	A2W76A	
100-sheet multipurpose tray 1		Yes	
500-sheet tray 2		Yes	
3x500 sheet input trays	Yes	Not available	
3,500-sheet HCI	Not available	Yes	
Touch-to-print, wireless direct mobile printing	(Optional	



Accessories, Supplies and Support

Supplies **HP Jetdirect	C1N54A HP LaserJet Fuser Kit 110V (130,000 pages)
2800W (J8029A) and HP Jetdirect 2700W (J8026A) accessories cannot be installed at the same time.	C1N58A HP LaserJet Fuser Kit 220V (100,000 pages)
	C1P70A HP Laser Jet ADF Roller Replacement Kit (Average yield: 100,000 pages)
	CF300A HP 827A Black Original LaserJet Toner Cartridge (29,500 pages)
	CF301A HP 827A Cyan Original Laser Jet Toner Cartridge (32,000 pages)
	CF302A HP 827A Yellow Original LaserJet Toner Cartridge (32,000 pages)
	CF303A HP 827A Magenta Original Laser Jet Toner Cartridge (32,000 pages)
	CF358A HP 828A Black LaserJet Image Drum (30,000 pages)
	CF359A HP 828A Cyan LaserJet Image Drum (30,000 pages)
	CF364A HP 828A Yellow LaserJet Image Drum (30,000 pages)
	CF365A HP 828A Magenta Laser Jet Image Drum (30,000 pages)
	D7H14A HP Laser Jet D7H14A Transfer and Roller Kit (150,000 pages)
Service and Support	UBD23E HP 3 year Next Business Day with Defective Media Retention Color LaserJet M880 Multifunction Printer Support UBD17E HP 3 year 4 hour 9x5 Color LaserJet M880 MFP Hardware Support UBD24E HP 4 year Next Business Day with Defective Media Retention Color LaserJet M880 Multifunction Printer Support UBD25E HP 5 year Next Business Day with Defective Media Retention Color LaserJet M880 Multifunction Printer Support UBD24PE HP 1 year Post Warranty Next Business Day with Defective Media Retention Color LaserJet M880 MILtifunction Printer Support UBD42PE HP 1 year Post Warranty A hour 9x5 Color LaserJet M880 MFP Support UBD39E HP 2 year Post Warranty Next Business Day With Defective Media Retention Color LaserJet M880 MFP Hardware Support

Technical specifications

Model	HP Color LaserJet Enterprise flow M880z Multifunction Printer	HP Color LaserJet Enterprise flow M880z+ Multifunction Printer	
Product number	A2W75A	A2W76A	
Functions	Print, copy, scan, fax		
Control panel	20.3 cm colour LCD with capacitive touchscreen; rotating (adjustable angle) display; illuminated capacitive Home button (for quick return to the Home menu); Easy Access USB; Hardware Integration Pocket		
Print	•		
Print technology	Laser		
Print speed ¹	Black (A4, normal) Up to 46 ppm; Colour (A4, normal): Up to 46 ppm; Black (A4, duplex): Up to 43 ipm; Colour (A4, duplex): Up to 43 ipm; Black (A3, normal): Up to 22 ppm; Colour (A3, normal): Up to 22 ppm;		
First page out ²	Black (A4, ready): As fast as 11 sec; Colour (A4, ready): As fast as 11 sec;		
Print resolution	Black (best): Up to 1200 x 1200 dpi; Colour (best): Up to 1200 x 1200 dpi; Technology: HP ImageREt 4800; HP FastRes 1200 (1200 dpi quality), 600 x 600 dpi; HP ProRes 1200 (1200 x 1200 dpi); Pantone© Calibrated;		
Monthly duty cycle	Up to 200,000 pages A4; Recommended monthly page volume: 5000 to 25,000		
Printer smart software features	HP ePrint, Apple AirPrint ^M , Mopria-certified, Open Extensibility Platform, FutureSmart Firmware, Instant-on Technology, HP Auto-On/Auto-Off Technology, HP Easy Color, Pantone© Calibrated, print preview, duplex, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, job separator, staple, offset booklet making, hole punch		
Standard print languages	HP PCL 5e, HP Postscript Level 3 emulation, PDF		
Fonts and typefaces	105 internal True Type fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Anda Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP Laser Jet Fonts an IPDS Emulation available at hp.com/go/laserjetfonts		
Print area	Print margins Top: 2.1 mm, Bottom: 2.1 mm, Left: 2.1 mm, Right: 2.1 mm; Maximum print area: 312 x 457.2 mm		
Duplex printing	Automatic (standard)		
Сору	· · · · · · · · · · · · · · · · · · ·		
Copy speed	Black (A4): Up to 46 cpm; Colour (A4): Up to 46 cpm		
Copier specifications	Sides; Collate; Paper Selection; Colour/Black; Reduce/Enlarge; Image Adjustment; Content Orientation; Maximum number of copies: Up to 9999 copies; Copy resolution: Up to 600 x 600 dpi; Reduce/Enlarge: 25 to 400%;		
Scan	· · · · · · · · · · · · · · · · · · ·		
Scan speed	Normal (A4): Up to 70 ppm (black & white), up to 68 ppm (colour); Duplex (A4): Up to 85 ipm (black & white), up to 63 ipm (colour)		
Scan file format	Digital Send: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A, TEXT (OCR), Unicode TEXT (OCR), RTF (OCR), Searchable PDF (OCR), Searchable PDF/A (OCR), HTML (OCR), CSV (OCR) Scan to easy access USB: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A, TEXT (OCR), Unicode TEXT (OCR), RTF (OCR), Searchable PDF (OCR), Searchable PDF/A (OCR), HTML (OCR CSV (OCR), Print from easy access USB: PDF, PS, Print Ready files (prn, pcl, .cht)		

Data sheet | HP Color LaserJet Enterprise flow M880 Multifunction Printer series

Model	HP Color LaserJet Enterprise flow M880z Multifunction Printer	HP Color LaserJet Enterprise flow M880z+ Multifunction Printer	
Product number	A2W75A	A2W76A	
Scanner specifications	Scanner type: Flatbed, ADF; Scan technology: Charge Coupled Device (CCD); Scan input modes: Copy, scan to e-mail, scan to network folder, scan to USB, save to device; Duplex ADF scanning: Yes, single pass duplexing ADF; Scan size maximum (flatbed): 297 x 432 mm; Optical scan resolution: Up to 600 dpi		
Scanner advanced features	Optimise text/picture; Image adjustments; Job build; Output quality setting; Selectable scan resolution 75 to 600 dpi; Auto detect colour; Edge erase; Auto tone; Auto job notification; Blank page suppression; Auto orientation; Auto page crop; HP Quick Sets		
Recommended monthly scan volume	26,750 to 44,600		
Scannable area	Maximum media size (flatbed): 297 x 432 mm; Minimum media size (ADF): 147 x 68 mm Maximum media size (ADF): 297 x 432 mm		
Bit depth/ Grey scale levels	24-bit / 256		
Digital sending	Standard: Scan to e-mail; Save-to-Network Folder; Scan to SharePoint; Save-to-USB drive; Send to FTP; Send to LAN Fax; Send to Internet Fax; OCR; Local Address Book; SMTP over SSL; Optional: Optional via HP Digital Sending Software (HP DSS); Send to folder; Send-to-workflow; Send-to-printer; Authentication; Digital fax (send to LAN, Internet); OCR; Local Address Book; via HP Embedded Capture; Metadata capture and validation; Data transfer; Scan workflow management		
Fax			
Fax ³	Yes, 33.6 kbps		
Fax specifications	Fax memory: Incoming fax can be stored to disk; Fax resolution: Standard: 100 x 100 dpi; Fine: 200 x 200 dpi, 256 levels of grey; Superfine: 300 x 300 dpi, 256 levels of grey; Quick dialing: Up to 100 (each can contain 100 numbers)		
Fax smart software features	Stored faxes; fax archiving; fax forwarding; scale-to-fit; fax address book; LAN/Internet fax; fax number confirmation; Holiday fax schedule		
Processor speed	800 MHz		
Connectivity			
Standard	2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T Network; 1 Foreign Interface; 1 Hardware Integration Pocket (HIP); 2 Internal USB Host; 1 Fax		
Optional	HP Jetdirect ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2 J8029A	HP Jetdirect ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8026A; HP Jetdirect 2800w NFC & Wireless Direct J8029A	
Wireless	Optional, enabled with purchase of a hardware accessory		
Mobile printing capability	HP ePrint; Apple AirPrint™; Mopria™-certified; Mobile Apps; Wireless Direct pr	inting	
Supported network protocols	IPv4/IPv6: Apple Bonjour Compatible (Mac OS v10.2.4 and later), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, Port 9100, LPD, IPP, Secure-IPP, WS Discovery, IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: Auto-IP, SLP, TFTP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print; Other: IPX/SPX, AppleTalk, NetWare NDS, Binder NDPS, iPrint		
Network capabilities	Yes, via HP Jetdirect Ethernet embedded print server (standard) which suppor 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet Gig Links; IPsec (standard); 802.11b/g/n wireless networking (optional); Touc Print and Wireless Direct (optional). Please note: HP Jetdirect 2800W (J8029/ HP Jetdirect 2700W (J8026A) accessories cannot be installed at the same tin	and 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and to Gig Links; IPsec (standard); 802.11b/g/n wireless networking; Touch to Print and) and Wireless Direct (optional). Please note: IHP Jetdirect 2800W (J8029A) and HP	
Hard disk	Standard, minimum 500 GB HP High-Performance Secure Hard Disk (AES 256 hardware encryption or greater)		
Memory	Standard: 2.5 GB (system memory); Maximum: 2.5 GB (system memory)		
Media handling			
Number of paper trays	Standard: 5 ; Maximum: 5	Standard: 4 ; Maximum: 4	
Media types	Cut sheet paper, labels, transparencies, glossy paper, glossy film, photo medi	a, tough paper, envelopes	
Media size	Custom (metric): Tray 1: 76.2 x 127 to 320 x 457.2 mm; Tray 2: 148 x 210 to x 432 mm; Tray 3, 4, 5: 148 x 210 to 320 x 457 mm; Supported (metric): Tra A3, A4, A4-R, A5, S65 (JIS), B4 (UIS), RA4, SRA4, RA3, SRA3, A6, B6 (JIS), DPost (JIS), Envelopes: B5, C5, C6, DL; Tray 2: A3, A4, A4-R, A5, B5 (JIS), B4 (JIS), RA4, SRA4; Tray 3, 4, 5: A3, A4, A4-R, A5, B5 (JIS), B4 (JIS), RA4, SRA4; A5, B4, 55 (JIS), B4 (JIS), RA4, SRA4, A5, B5 (JIS), B4 (JIS), RA4, SRA4, A5, B4, A5, B4, B5 (JIS), B4 (JIS), RA4, SRA4, RA3, SRA4, RA3, SRA4, RA3, SRA4, RA3, SRA4, RA4, RA5, B4 (JIS), B4 (JIS), B4 (JIS), RA4, SRA4, RA3, SRA4, RA3, SRA4, RA3, SRA4, RA4, RA5, B4 (JIS), B	 Custom (hend), Hay 1, 76, 2x H1 (52, 2x 47, 25, 24), Hay 2, Hay 2,	

Model	HP Color LaserJet Enterprise flow M880z Multifunction Printer	HP Color LaserJet Enterprise flow M880z+ Multifunction Printer	
Product number	A2W75A	A2W76A	
Media handling	Standard input: 100-sheet multipurpose tray, 4 x 500-sheet input tray Standard output: 500-sheet face-down bin ADF: Standard, 200 sheets (75 g/m ²)	Standard input: 100-sheet multipurpose tray, 500-sheet input tray, 1500-sheet input tray, 2000-sheet input tray. Standard output: 500-sheet face-down bin ADF: Standard, 200 sheets (75 g/m ²)	
Media weight	Tray 1-5: 60 to 220 g/m ² ; ADF : 45 to 199 g/m ²	Tray 1, 2: 60 to 220 g/m ² ; Tray 3, 4: 60 to 120 g/m ² ; ADF : 45 to 199 g/m ²	
Input capacity	Tray 1: sheets: 100; envelopes: 10 Tray 2: sheets: 500 Tray 3: Tray 3, 4, 5: Sheets: 500 Maximum: Up to 2100 sheets (75 g/m ² media) ADF: Standard, 200 sheets (75 g/m ²)	Tray 1: sheets: 100; envelopes: 10 Tray 2: sheets: 500 Tray 3: Tray 3: sheets: 1500; Tray 4: sheets: 2000 Maximum: Up to 4100 sheets (75 g/m ² media) ADF: Standard, 200 sheets (75 g/m ²)	
Output capacity	Standard: Up to 500 sheets (75 g/m ² media) Envelopes: Up to 60 envelopes Transparencies: Up to 100 sheets Maximum: Up to 3000 sheets (75 g/m ² media) with an optional output device.		
Compatible operating systems	Windows 10 (32-bit/64-bit), Windows 8 (32-bit/64-bit), Windows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows Server 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2003 (SP) or higher) (32-bit/64-bit); Mac 05 X version 10.6.8, 10.7.5 Lion, 10.8 Mountain Lion; For the latest operating system support see: Air Print (http://suport.apple.com/kl/H4356), Android (http://www.ahg.com/g/olupd), HP ePrint Software Driver (http://www.hp.com/go/eprintsoftware), Linux (http://www.hplp.net), Novell (http://www.hp.com/go/eprintsoftware), Linux (http://www.hplp.net), Novell (http://www.hp.com/go/eprintsoftware), SAP Print (http://www.hp.com/go/sap/print), UNIX (http://www.hp.com/go/eprintsoftware) (http://www.hp.com/go/eprint), SAP device types (http://www.hp.com/go/sap/print), UNIX (http://www.hp.com/go/eprintsoftware), SAP Print (http://www.hp.com/go/sap/print), UNIX (http://www.hp.com/go/unix		
Compatible network operating systems	 Windows 8.1 (32-bit/64-bit); Windows 8 Basic (32-bit/64-bit); Windows 8 Pro (32-bit/64-bit); Windows 8 Enterprise RT (32-bit only); Windows 7 (32-bit/64-bit); Windows 8 Enterprise RT (32-bit only); Windows 7 (32-bit/64-bit); Windows 8 Enterprise RT (32-bit only); Windows 7 (32-bit/64-bit); Windows 8 Enterprise RT (32-bit only); Windows 7 (32-bit/64-bit); Windows 5 Server 2012 (No Software Installer support); Windows Server 2012 (No Software Installer support); Windows Server 2008 R2 (SP1); Windows Server 2003 Server Terminal Services (SP1); Windows Server 2003 Server Rev		
Minimum system requirements	 Windows: Windows 10, Windows 7 (SP1 or higher), Windows Vista, Windows Server 2012 (64-bit), Windows Server 2008, Windows Server 2008 kP (64-bit), Windows Server 2003 (SP1 or higher): 200 MB available hard disk space, CD-ROM/DVD drive or Internet connection, dedicated USB 1.1/2.0 or network connection (for OS compatible hardware system requirements see http://www.microsoft.com); Mac: Mac OS X v10.6.8, OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of available hard disk space; CD-ROM or DVD drive, or Internet connection; Dedicated UISB 1.1 or 2.0), or network connection (Operating system compatible hardware system requirements see apple.com) 		
Software included	HP PCL 6 Discrete Printer Driver; Mac Software Link to Web (Mac Installer); Window:	s Installer	
Security management	Identity management: Kerberos authentication, LDAP authentication, 1000 user PIN codes, optional HP and 3rd party advanced authentication solutions (e.g., badge readers); Network: IPsec/firewall with Certificate, Pre-Shared Key, and Kerberos authentication, Supports WJA-10 IPsec configuration Plug-in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPV3, HTTPS, Certificates, Access Control List, Data: Storage Encryption, Encrypted PDF & Email (uses FIPS 140 validated cryptographic libraries from Microsoft), Secure Erase, SSL/TLS (HTTPS), Encrypted Credentials; Device: Security lock slot, USB port disablement, hardware integration pocket for security solutions; Security management: Compatible with HP Imaging and Printing Security Center		
Printer management	HP Web Jetadmin; HP Utility (Mac)		
Dimensions and weight			
Printer dimensions (W x D x H)	Minimum 704 x 635 x 1199 mm; Maximum: 1000 x 800 x 1199 mm;		
Package dimensions (W x D x H)	856 x 790 x 1567 mm		
Printer weight	150.6 kg	152.9 kg	
Package weight	173.33 kg	175.33 kg	
Operating environment	Temperature: 15 to 30°C; Humidity: 10 to 80% RH		
Storage conditions	Temperature: 0 to 35°C; Humidity: 10 to 90% RH		
Acoustics	Acoustic power emissions: 7.0 B(A); Acoustic pressure emissions: 55 dB(A)		
Power	Requirements: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz), 10.5 A; 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 5.5 A (Not dual voltage, power supply varies by part number with # Option code identifier); Consumption: 972 watts (printing), 972 watts (copying), 80 watts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watts (off); Typical Electricity Consumption (TEQ: Energy Star 3.0: 0.734 kWh/Week; Power supply type: Built-in power supply;	Requirements: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz), 10.5 A; 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 5.5 A (Not dual voltage, power supply varies by part number with # Option code identifier). Not dual voltage, power supply varies by part number with # Option code identifier; Consumption: 972 watts (printing), 972 watts (copying), 80 watts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watts (off); Typical Electricity Consumption (TEC): Energy Star 3.0: 0.734 kWh/Week; Power supply type: Built-in power supply;	
Energy savings feature technology	HP Auto-on/Auto-off Technology; Instant-on Technology		
Certifications	CISPR 22:2008 / EN 55022:2010 (Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN 61000-3-3:2008; EN 55024:2010; EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries ENERGY STAR [®] ; EPEAT [®] Silver; CECP Telecom compliance : Fax Telecom: ES 203 021; R&TTE Directive 1999/5/EC (Annex II) with CE Marking (Europe); FCC Part 68; other Telecom approvals as required by individual countries	CISPR 22:2008 / EN 55022:2010 (Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN 61000-3-3:2008; EN 55024:2010; EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries ENERGY STAR® qualified; CECP Telecom compliance: Fax Telecom: ES 203 021; R&TTE Directive 1999/5/EC (Annex II) with CE Marking (Europe); FCC Part 68; other Telecom approvals as required by individual countries	
Blue Angel compliant	No; Please refer to the ECI document		
Country of origin	Made in China		
What's in the box	HP Color LaserJet Enterprise flow MFP M8802; Black, Cyan, Magenta, and Yellow HP Color LaserJet Drums; Black, Cyan, Magenta, and Yellow HP Color LaserJet Toner Cartridges; CD with software drivers and documentation; Documentation (Hardware Install Guide); Power cord; HP Jetdirect Gigabit Ethernet Print Server (embedded); Automatic duplexer (built-in); Encrypted Hard Drive; 100-sheet multipurpose tray; 1 x 500-sheet input tray; 3 x 500-sheet input tray with stand; Fax, Fax cable	HP Color LaserJet Enterprise flow MFP M880z+; Black, Cyan, Magenta, and Yellow HP Color LaserJet Drums; Black, Cyan, Magenta, and Yellow HP Color LaserJet Toner Cartridges; CD with software drivers and documentation; Documentation (Hardware Install Guide); Power cord; HP Jetdirect Gigabit Ethernet Print Server (embedded); Automatic duplexer (built-in); Encrypted Hard Drive; 100-sheet multipurpose tray; 1 x 500-sheet input tray; 1 x 3500-sheet high capacity input tray with stand; Fax, Fax cable	
Warranty*Solutions deployed through the hardware integration pocket may require additional purchase.	One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Go to http://www.hp.com/support to learn about HP award winning service and support options in your region.		

Footnotes

¹ Local printing requires mobile device and printer to be on the same network or have a direct wireless connection to printer. Wireless performance is dependent on physical environment and distance from access point. Wireless operations are compatible with 2.4 GHz operations only. Remote printing requires an Internet connection to an HP web-connected printer. App or software and HP ePrint account registration may also be required. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. See hp.com/go/mobileprinting for more details ² Touch-to-print capability may be added as an option to the HP Color Laser Jet Enterprise flow MFP M880z+ A2W76A and M880z A2W75A. Mobile device must support near-field communications-enabled printing. For a list of supported devices, see hp.com/go/mobileprinting.

³ HP Flow CM is not available in all regions. Network connection is required to upload and download files. Additional software and licenses may be required.

⁴ The HP Universal Print Driver is free and available for download at hp.com/go/upd.

⁵ Paper-handling options must be purchased separately.

⁶ Wireless direct printing may be added as an option to the HP Color Laser Jet Enterprise M880z + A2W76A and M880z A2W75A. Mobile device may require an app or driver. Wireless performance is dependent on physical

environment and distance from the printer. For details, see hp.com/go/wirelessprinting. ⁷ Supports OS X[®] Lion, OS X Mountain Lion, and the following devices running iOS 4.2 or later: iPad[®] (all models), iPhone[®] (3GS or later), and iPod touch[®] (third generation or later). Works with HP's AirPrint-enabled printers and requires the printer be connected to the same network as your OS X or iOS device. Wireless performance is dependent on physical environment and distance from the access point. OS X, iPad, iPhone, and iPod touch are trademarks of Apple® Inc., registered in the United States and other countries. AirPrint™ and the AirPrint logo are trademarks of Apple Inc. ⁸ HP Web Jetadmin is free and available for download at hp.com/go/webjetadmin.

⁹ HP Imaging and Printing Security Center must be purchased separately.

Technical specifications disclaimers

¹ Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

² Exact speed varies depending on the system configuration, software application, driver and document complexity.

³ Based on standard ITU-T test image at standard resolution and MMR encoding, the HP fax device can transmit at 3 sec/page for V.34 and 6 sec/page for V.17

⁴ Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies.

⁵ Average colour composite (C/M/Y) and black declared yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see hp.com/go/learnaboutsupplies.





http://www.hp.com/uk

© Copyright 2021 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.