Data sheet

HP Color LaserJet Enterprise flow M880 Multifunction Printer series

Top colour performance. Solid value.

This top-of-the-line enterprise MFP helps streamline workflows and accelerate document tasks with advanced finishing options and file sharing. Give users simple, direct access to this MFP through mobile printing and touch-to-print capabilities[1,2].



Color touchscreen

Printer security settings

Wireless direct

Single-pass 2-sided ADF

Give workgroups the speed they need.

- Let departments scan without worry: HP EveryPage detects potential errors or missed pages on the spot.
- Manage content in a way you never thought possible with HP Flow CM Enterprise[3].
- Forget email – let employees scan and send documents to Microsoft® SharePoint® in one step.
- Make it easy to be efficient with an intuitive touchscreen and large pull-out keyboard.

Keep your business moving.

- Save on both sides – capture documents faster with two-sided, single-pass scanning.
- Create easily searchable scanned files, using built-in optical character recognition software.
- Save IT time and make printing easy for the entire company by using a single driver for all HP devices[4].
- Let employees complete big jobs faster, choosing from a range of finishing options[5].

Be much more efficient with mobile printing.

- Give users simple, direct access through wireless direct printing and touch-to-print technology[6].
- Mobile printing at a touch – enable touch-to-print convenience from mobile devices[2].
- Let employees print from mobile devices with built-in print capability or HP ePrint app and software[1].
- Give users the power to print wirelessly from an iPad®, iPhone®, or iPod touch®[7].

Invest once, expand easily and manage efficiently.

- Expand your options: easily upgrade firmware on your schedule, and easily integrate solutions or devices at will.
- Help build business efficiency. Centrally monitor and control printers with HP Web Jetadmin[8].
- Apply fleet-wide policies to help protect all your HP devices with the HP Imaging and Printing Center[9].
- Confidently safeguard the sensitive data sent to your MFP with the HP High-Performance Secure Hard Disk.

Product walkaround

HP Color LaserJet Enterprise flow MFP M880z+ shown:

1. Intuitive 8-inch (20.3 cm) HP Easy Select pivoting color touchscreen control panel
2. 200-sheet automatic document feeder with single pass two-sided scanning, and HP EveryPage with ultrasonic double-feed detection
3. Home button (returns to home screen)
4. Plate glass color scanner handles sizes up to 11 x 17 in/A3
5. Easy-access USB port to save and print files directly
6. Hardware integration pocket for solution integration*
7. 500-sheet output bin
8. Front door provides convenient access to HP toner cartridges and drums
9. Built-in automatic two-sided printing
10. Retractable keyboard for easy, accurate data entry
11. 100-sheet multipurpose tray 1 handles heavy custom media up to 58 lb bond (220 g/m^2)
12. Right-side doors provide access to the fuser and for clearing jams
13. 500-sheet input tray supports media up to size 11 x 17 in/A3
14. 3,500-sheet high-capacity input tray supports media sizes letter/A4
15. HP Jetdirect Gigabit Ethernet print server
16. HP High-Performance Secure Hard Disk
17. Access port for optional Kensington-style lock
18. Hi-Speed USB 2.0 port (for connecting third-party devices)
19. Hi-Speed USB 2.0 printing port
20. 800 MHz processor, 2.5 GB (system memory)
21. Foreign interface harness (for connecting external devices)
22. Two internal host USB 2.0 type ports for third party solutions
23. RJ-11 fax port

Front view



Side I/O panel close-up

Series at a glance

Model	HP Color LaserJet Enterprise flow M880z Multifunction Printer	HP Color LaserJet Enterprise flow M880z+ Multifunction Printer
Product number	A2W75A	A2W76A
100-sheet multipurpose tray 1	Yes	
500-sheet tray 2	Yes	
3x500 sheet input trays	Yes	Not available
3,500-sheet HCI	Not available	Yes
Touch-to-print, wireless direct mobile printing	Optional	

Accessories, Supplies and Support

Supplies **HP Jetdirect 2800W (J8029A) and HP Jetdirect 2700W (J8026A) accessories cannot be installed at the same time.	**C1N54A** HP LaserJet Fuser Kit 110V (130,000 pages)
	C1N58A HP LaserJet Fuser Kit 220V (100,000 pages)
	C1P70A HP LaserJet ADF Roller Replacement Kit (Average yield: 100,000 pages)
	CF300A HP 827A Black Original LaserJet Toner Cartridge (29,500 pages)
	CF301A HP 827A Cyan Original LaserJet Toner Cartridge (32,000 pages)
	CF302A HP 827A Yellow Original LaserJet Toner Cartridge (32,000 pages)
	CF303A HP 827A Magenta Original LaserJet Toner Cartridge (32,000 pages)
	CF358A HP 828A Black LaserJet Image Drum (30,000 pages)
	CF359A HP 828A Cyan LaserJet Image Drum (30,000 pages)
	CF364A HP 828A Yellow LaserJet Image Drum (30,000 pages)
	CF365A HP 828A Magenta LaserJet Image Drum (30,000 pages)
	D7H14A HP LaserJet D7H14A Transfer and Roller Kit (150,000 pages)
Service and Support	**U8D23E** HP 3 year Next Business Day with Defective Media Retention Color LaserJet M880 Multifunction Printer Support **U8D17E** HP 3 year 4 hour 9x5 Color LaserJet M880 MFP Hardware Support **U8D24E** HP 4 year Next Business Day with Defective Media Retention Color LaserJet M880 Multifunction Printer Support **U8D25E** HP 5 year Next Business Day with Defective Media Retention Color LaserJet M880 Multifunction Printer Support **U8D42PE** HP 1 year Post Warranty Next Business Day with Defective Media Retention Color LaserJet M880 MFP Hardware Support **U8D40PE** HP 1 year Post Warranty 4 hour 9x5 Color LaserJet M880 MFP Support **U8D39PE** HP 2 year Post Warranty Next Business Day Color LaserJet M880 MFP Hardware Support

Technical specifications

Model	**HP Color LaserJet Enterprise flow M880z Multifunction Printer**	**HP Color LaserJet Enterprise flow M880z+ Multifunction Printer**
Product number	A2W75A	A2W76A
Functions	Print, copy, scan, fax	
Control panel	20.3 cm colour LCD with capacitive touchscreen; rotating (adjustable angle) display; illuminated capacitive Home button (for quick return to the Home menu); Easy Access USB; Hardware Integration Pocket	
Print		
Print technology	Laser	
Print speed[1]	**Black (A4, normal)** Up to 46 ppm; **Colour (A4, normal)**: Up to 46 ppm; **Black (A4, duplex)**: Up to 43 ipm; **Colour (A4, duplex)**: Up to 43 ipm; **Black (A3, normal)**: Up to 22 ppm; **Colour (A3, normal)**: Up to 22 ppm;	
First page out[2]	**Black (A4, ready)**: As fast as 11 sec; **Colour (A4, ready)**: As fast as 11 sec;	
Print resolution	**Black (best)**: Up to 1200 x 1200 dpi; **Colour (best)**: Up to 1200 x 1200 dpi; **Technology**: HP ImageREt 4800; HP FastRes 1200 (1200 dpi quality), 600 x 600 dpi; HP ProRes 1200 (1200 x 1200 dpi); Pantone© Calibrated;	
Monthly duty cycle	Up to 200,000 pages A4; **Recommended monthly page volume**: 5000 to 25,000	
Printer smart software features	HP ePrint, Apple AirPrint™, Mopria-certified, Open Extensibility Platform, FutureSmart Firmware, Instant-on Technology, HP Auto-On/Auto-Off Technology, HP Easy Color, Pantone© Calibrated, print preview, duplex, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, job separator, staple, offset, booklet making, hole punch	
Standard print languages	HP PCL 6, HP PCL 5e, HP Postscript Level 3 emulation, PDF	
Fonts and typefaces	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at hp.com/go/laserjetfonts	
Print area	**Print margins** Top: 2.1 mm, Bottom: 2.1 mm, Left: 2.1 mm, Right: 2.1 mm; Maximum print area: 312 x 457.2 mm	
Duplex printing	Automatic (standard)	
Copy		
Copy speed	**Black (A4)**: Up to 46 cpm; **Colour (A4)**: Up to 46 cpm	
Copier specifications	Sides; Collate; Paper Selection; Colour/Black; Reduce/Enlarge; Image Adjustment; Content Orientation; **Maximum number of copies**: Up to 9999 copies; **Copy resolution**: Up to 600 x 600 dpi; **Reduce/Enlarge**: 25 to 400%;	
Scan		
Scan speed	**Normal (A4)**: Up to 70 ppm (black & white), up to 68 ppm (colour); **Duplex (A4)**: Up to 85 ipm (black & white), up to 63 ipm (colour)	
Scan file format	Digital Send: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A, TEXT (OCR), Unicode TEXT (OCR), RTF (OCR), Searchable PDF (OCR), Searchable PDF/A (OCR), HTML (OCR), CSV (OCR); Scan to easy access USB: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A, TEXT (OCR), Unicode TEXT (OCR), RTF (OCR), Searchable PDF (OCR), Searchable PDF/A (OCR), HTML (OCR), CSV (OCR); Print from easy access USB: PDF, PS, Print Ready files (.prn, .pcl, .cht)	

Model	HP Color LaserJet Enterprise flow M880z Multifunction Printer	HP Color LaserJet Enterprise flow M880z+ Multifunction Printer
Product number	A2W75A	A2W76A
Scanner specifications	**Scanner type**: Flatbed, ADF; **Scan technology**: Charge Coupled Device (CCD); **Scan input modes**: Copy, scan to e-mail, scan to network folder, scan to USB, save to device; **Duplex ADF scanning**: Yes, single pass duplexing ADF; **Scan size maximum (flatbed)**: 297 x 432 mm; **Optical scan resolution**: Up to 600 dpi	
Scanner advanced features	Optimise text/picture; Image adjustments; Job build; Output quality setting; Selectable scan resolution 75 to 600 dpi; Auto detect colour; Edge erase; Auto tone; Auto job notification; Blank page suppression; Auto orientation; Auto page crop; HP Quick Sets	
Recommended monthly scan volume	26,750 to 44,600	
Scannable area	**Maximum media size (flatbed)**: 297 x 432 mm; **Minimum media size (ADF)**: 147 x 68 mm **Maximum media size (ADF)**: 297 x 432 mm	
Bit depth/ Grey scale levels	24-bit / 256	
Digital sending	Standard: Scan to e-mail; Save-to-Network Folder; Scan to SharePoint; Save-to-USB drive; Send to FTP; Send to LAN Fax; Send to Internet Fax; OCR; Local Address Book; SMTP over SSL ; Optional: Optional via HP Digital Sending Software (HP DSS); Send to folder; Send-to-workflow; Send-to-printer; Authentication; Digital fax (send to LAN, Internet); OCR; Local Address Book; via HP Embedded Capture; Metadata capture and validation; Data transfer; Scan workflow management	
Fax		
Fax[3]	Yes, 33.6 kbps	
Fax specifications	**Fax memory**: Incoming fax can be stored to disk; **Fax resolution**: Standard: 100 x 100 dpi; Fine: 200 x 200 dpi, 256 levels of grey; Superfine: 300 x 300 dpi, 256 levels of grey; **Quick dialing**: Up to 100 (each can contain 100 numbers)	
Fax smart software features	Stored faxes; fax archiving; fax forwarding; scale-to-fit; fax address book; LAN/Internet fax; fax number confirmation; Holiday fax schedule	
Processor speed	800 MHz	
Connectivity		
Standard	2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T Network; 1 Foreign Interface; 1 Hardware Integration Pocket (HIP); 2 Internal USB Host; 1 Fax	
Optional	HP Jetdirect ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8026A; HP Jetdirect 2800w NFC & Wireless Direct J8029A	
Wireless	Optional, enabled with purchase of a hardware accessory	
Mobile printing capability	HP ePrint; Apple AirPrint™; Mopria™-certified; Mobile Apps; Wireless Direct printing	
Supported network protocols	IPv4/IPv6: Apple Bonjour Compatible (Mac OS v10.2.4 and later), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, Port 9100, LPD, IPP, Secure-IPP, WS Discovery, IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: Auto-IP, SLP, TFTP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print; Other: IPX/SPX, AppleTalk, NetWare NDS, Bindery, NDPS, iPrint	
Network capabilities	Yes, via HP Jetdirect Ethernet embedded print server (standard) which supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard); 802.11b/g/n wireless networking (optional); Touch to Print and Wireless Direct (optional). Please note: HP Jetdirect 2800W (J8029A) and HP Jetdirect 2700W (J8026A) accessories cannot be installed at the same time.	Yes, via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard); 802.11b/g/n wireless networking; Touch to Print and Wireless Direct (optional). Please note: HP Jetdirect 2800W (J8029A) and HP Jetdirect 2700W (J8026A) accessories cannot be installed at the same time.
Hard disk	Standard, minimum 500 GB HP High-Performance Secure Hard Disk (AES 256 hardware encryption or greater)	
Memory	**Standard**: 2.5 GB (system memory); **Maximum**: 2.5 GB (system memory)	
Media handling		
Number of paper trays	**Standard**: 5 **; Maximum**: 5	**Standard**: 4 **; Maximum**: 4
Media types	Cut sheet paper, labels, transparencies, glossy paper, glossy film, photo media, tough paper, envelopes	
Media size	**Custom (metric)**: Tray 1: 76.2 x 127 to 320 x 457.2 mm; Tray 2: 148 x 210 to 297 x 432 mm; Tray 3, 4, 5: 148 x 210 to 320 x 457 mm **; Supported (metric)**: Tray 1: A3, A4, A4-R, A5, B5 (JIS), B4 (JIS), RA4, SRA4, RA3, SRA3, A6, B6 (JIS), DPostcard (JIS), Envelopes: B5, C5, C6, DL; Tray 2: A3, A4, A4-R, A5, B5 (JIS), B4 (JIS), RA4, SRA4; Tray 3, 4, 5: A3, A4, A4-R, A5, B5 (JIS), B4 (JIS), RA4, SRA4, RA3, SRA3 **; ADF**: A3; A4; A5; B4; B5 (JIS); B6 (JIS)	**Custom (metric)**: Tray 1: 76.2 x 127 to 320 x 457.2 mm; Tray 2: 148 x 210 to 297 x 432 mm; Tray 3, 4: 210 x 297 mm **; Supported (metric)**: Tray 1: A3, A4, A4-R, A5, B5 (JIS), B4 (JIS), RA4, SRA4, RA3, SRA3, A6, B6 (JIS), DPostcard (JIS), Envelopes: B5, C5, C6, DL; Tray 2: A3, A4, A4-R, A5, B5 (JIS), B4 (JIS), RA4, SRA4, Trays 3, 4: A4 **; ADF**: A3; A4; A5; B4; B5 (JIS); B6 (JIS)

Model	HP Color LaserJet Enterprise flow M880z Multifunction Printer	HP Color LaserJet Enterprise flow M880z+ Multifunction Printer
Product number	A2W75A	A2W76A
Media handling	**Standard input**: 100-sheet multipurpose tray, 4 x 500-sheet input tray **Standard output**: 500-sheet face-down bin **ADF**: Standard, 200 sheets (75 g/m²)	**Standard input**: 100-sheet multipurpose tray, 500-sheet input tray, 1500-sheet input tray, 2000-sheet input tray **Standard output**: 500-sheet face-down bin **ADF**: Standard, 200 sheets (75 g/m²)
Media weight	Tray 1–5: 60 to 220 g/m²; **ADF**: 45 to 199 g/m²	Tray 1, 2: 60 to 220 g/m²; Tray 3, 4: 60 to 120 g/m²; **ADF**: 45 to 199 g/m²
Input capacity	**Tray 1**: sheets: 100; envelopes: 10 **Tray 2**: sheets: 500 **Tray 3**: Tray 3, 4, 5: Sheets: 500 **Maximum**: Up to 2100 sheets (75 g/m² media) **ADF**: Standard, 200 sheets (75 g/m²)	**Tray 1**: sheets: 100; envelopes: 10 **Tray 2**: sheets: 500 **Tray 3**: Tray 3: sheets: 1500; Tray 4: sheets: 2000 **Maximum**: Up to 4100 sheets (75 g/m² media) **ADF**: Standard, 200 sheets (75 g/m²)
Output capacity	**Standard**: Up to 500 sheets (75 g/m² media) Envelopes: Up to 60 envelopes Transparencies: Up to 100 sheets **Maximum**: Up to 3000 sheets (75 g/m² media) with an optional output device.	
Compatible operating systems	Windows 10 (32-bit/64-bit), Windows 8 (32-bit/64-bit), Windows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows Server 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit); Mac OS X version 10.6.8, 10.7.5 Lion, 10.8 Mountain Lion; For the latest operating system support see: Air Print (http://support.apple.com/kb/ht4356), Android (http://www.android.com/), Citrix and Windows Terminal Services (http://www.hp.com/go/upd), HP ePrint Software Driver (http://www.hp.com/go/eprintsoftware), Linux (http://www.hplip.net), Novell (http://www.novell.com/iprint), SAP device types (http://www.hp.com/go/sap/drivers), SAP Print (http://www.hp.com/go/sap/print), UNIX (http://www.hp.com/go/unix), UNIX JetDirect (http://www.hp.com/go/jetdirectunix_software)	
Compatible network operating systems	Windows 8.1 (32-bit/64-bit); Windows 8 Basic (32-bit/64-bit); Windows 8 Pro (32-bit/64-bit); Windows 8 Enterprise (32-bit/64-bit); Windows 8 Enterprise N (32-bit/64-bit); Windows 8 Enterprise RT (32-bit only); Windows 7 (32-bit/64-bit) (Including Starter Edition); Windows Vista (32-bit) (Including Starter Edition); Windows Vista (64-bit); Windows XP (SP2 or higher) (32-bit/64-bit); Windows Server 2012 R2; Windows Server 2012 (No Software Installer support); Windows Server Win7/2008 R2 (SP1); Windows Server 2008 (Standard Edition); Windows Server 2008 (Enterprise Edition); Windows Server 2008 (32-bit/64-bit) (SP1); Windows Server 2008 (32-bit/64-bit) (SP2); Windows Server 2008 R2 (32-bit/64-bit) (Standard Edition, Enterprise Edition); Windows Server 2008 Server Terminal Services; Windows Server 2008 Server Terminal Services with Citrix XenApp; Windows Server 2003 (Standard Edition); Windows Server 2003 (Enterprise Edition); Windows Server 2003 (32-bit/64-bit) (SP1); Windows Server 2003 (32-bit/64-bit) (SP2); Windows Server 2003 R2 (32-bit/64-bit) (Standard Edition, Enterprise Edition); Windows Server 2003 Server Terminal Services; Windows Server 2003 Server Terminal Services w/Citrix Metaframe XP with Feature Release 3; Windows Server 2003 Server Terminal Services w/Citrix Presentation Server 4.0; Windows Server 2003 Server Terminal Services with Citrix Presentation Server 4.5; Novell NetWare 6; Novell NetWare 6.5 [SP8 minimum for full Windows Vista, Windows 7 and Windows XP (SP7 if only Windows XP)]; Novell Novell iPrint Client v5.4 for Windows XP, Windows Vista and Windows 7, (x86 and x64); Novell Novell iPrint Support Only; Novell Novell Open Enterprise Server 2 (Linux); Novell Novell Open Enterprise Server 6.5; Other Citrix (Print): Citirx XenApps 6.0, Xen Server 5.6, Xen Desktop 5.5; Other Cluster Support; Mac 10.5; Mac 10.6.8; Mac 10.7.5; Mac 10.8.x; Mac 10.9.x; For Linux OS versions, refer to the HP Linux web site: hplipopensource.com/hplip-web/index.html; Unix HPUX 11i; IBM AIX 3.2.5 or higher; MPE-iX; Citrix MetaFrame Server; Red Hat Linux 7.x or higher; Solaris 2.5 or higher (SPARC systems only); SuSe Linux 8.x or higher. (For Microsoft IPv6 compatibility use Windows 2003, Windows XP Home, Windows XP Professional and Windows Vista)	
Minimum system requirements	**Windows**: Windows 10, Windows 8, Windows 7 (SP1 or higher), Windows Vista, Windows Server 2012 (64-bit), Windows Server 2008, Windows Server 2008 R2 (64-bit), Windows Server 2003 (SP1 or higher): 200 MB available hard disk space, CD-ROM/DVD drive or Internet connection, dedicated USB 1.1/2.0 or network connection (for OS compatible hardware system requirements see http://www.microsoft.com); **Mac**: Mac OS X v10.6.8, OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of available hard disk space; CD-ROM or DVD drive, or Internet connection; Dedicated Universal Serial Bus (USB 1.1 or 2.0), or network connection (Operating system compatible hardware system requirements see apple.com)	
Software included	HP PCL 6 Discrete Printer Driver; Mac Software Link to Web (Mac Installer); Windows Installer	
Security management	Identity management: Kerberos authentication, LDAP authentication, 1000 user PIN codes, optional HP and 3rd party advanced authentication solutions (e.g., badge readers); Network: IPsec/firewall with Certificate, Pre-Shared Key, and Kerberos authentication, Supports WJA-10 IPsec configuration Plug-in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, Certificates, Access Control List; Data: Storage Encryption, Encrypted PDF & Email (uses FIPS 140 validated cryptographic libraries from Microsoft), Secure Erase, SSL/TLS (HTTPS), Encrypted Credentials; Device: Security lock slot, USB port disablement, hardware integration pocket for security solutions; Security management: Compatible with HP Imaging and Printing Security Center	
Printer management	HP Web Jetadmin; HP Utility (Mac)	
Dimensions and weight		
Printer dimensions (W x D x H)	**Minimum** 704 x 635 x 1199 mm; **Maximum**: 1000 x 800 x 1199 mm;	
Package dimensions (W x D x H)	856 x 790 x 1567 mm	
Printer weight	150.6 kg	152.9 kg
Package weight	173.33 kg	175.33 kg
Operating environment	**Temperature**: 15 to 30ºC; **Humidity**: 10 to 80% RH	
Storage conditions	**Temperature**: 0 to 35ºC; **Humidity**: 10 to 90% RH	
Acoustics	**Acoustic power emissions**: 7.0 B(A); **Acoustic pressure emissions**: 55 dB(A)	
Power	**Requirements**: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz), 10.5 A; 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 5.5 A (Not dual voltage, power supply varies by part number with # Option code identifier); **Consumption**: 972 watts (printing), 972 watts (copying), 80 watts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watts (off); **Typical Electricity Consumption (TEC)**: Energy Star 3.0: 0.734 kWh/Week; **Power supply type**: Built-in power supply;	**Requirements**: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz), 10.5 A; 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 5.5 A (Not dual voltage, power supply varies by part number with # Option code identifier). Not dual voltage, power supply varies by part number with # Option code identifier.; **Consumption**: 972 watts (printing), 972 watts (copying), 80 watts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watts (off); **Typical Electricity Consumption (TEC)**: Energy Star 3.0: 0.734 kWh/Week; **Power supply type**: Built-in power supply;
Energy savings feature technology	HP Auto-on/Auto-off Technology; Instant-on Technology	
Certifications	CISPR 22:2008 / EN 55022:2010 (Class A), EN 61000-3-2 :2006 +A1:2009 +A2:2009; EN 61000-3-3 :2008; EN 55024:2010; EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries ENERGY STAR®; EPEAT® Silver; CECP **Telecom compliance**: Fax Telecom: ES 203 021; R&TTE Directive 1999/5/EC (Annex II) with CE Marking (Europe); FCC Part 68; other Telecom approvals as required by individual countries	CISPR 22:2008 / EN 55022:2010 (Class A), EN 61000-3-2 :2006 +A1:2009 +A2:2009; EN 61000-3-3 :2008; EN 55024:2010; EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries ENERGY STAR® qualified; CECP **Telecom compliance**: Fax Telecom: ES 203 021; R&TTE Directive 1999/5/EC (Annex II) with CE Marking (Europe); FCC Part 68; other Telecom approvals as required by individual countries
Blue Angel compliant	No; Please refer to the ECI document	
Country of origin	Made in China	
What's in the box	HP Color LaserJet Enterprise flow MFP M880z; Black, Cyan, Magenta, and Yellow HP Color LaserJet Drums; Black, Cyan, Magenta, and Yellow HP Color LaserJet Toner Cartridges; CD with software drivers and documentation; Documentation (Hardware Install Guide); Power cord; HP Jetdirect Gigabit Ethernet Print Server (embedded); Automatic duplexer (built-in); Encrypted Hard Drive; 100-sheet multipurpose tray; 1 x 500-sheet input tray; 3 x 500-sheet input tray with stand; Fax, Fax cable	HP Color LaserJet Enterprise flow MFP M880z+; Black, Cyan, Magenta, and Yellow HP Color LaserJet Drums; Black, Cyan, Magenta, and Yellow HP Color LaserJet Toner Cartridges; CD with software drivers and documentation; Documentation (Hardware Install Guide); Power cord; HP Jetdirect Gigabit Ethernet Print Server (embedded); Automatic duplexer (built-in); Encrypted Hard Drive; 100-sheet multipurpose tray; 1 x 500-sheet input tray; 1 x 3500-sheet high capacity input tray with stand; Fax, Fax cable
Warranty*Solutions deployed through the hardware integration pocket may require additional purchase.	One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Go to http://www.hp.com/support to learn about HP award winning service and support options in your region.	

Footnotes

[1] Local printing requires mobile device and printer to be on the same network or have a direct wireless connection to printer. Wireless performance is dependent on physical environment and distance from access point. Wireless operations are compatible with 2.4 GHz operations only. Remote printing requires an Internet connection to an HP web-connected printer. App or software and HP ePrint account registration may also be required. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. See hp.com/go/mobileprinting for more details.
[2] Touch-to-print capability may be added as an option to the HP Color LaserJet Enterprise flow MFP M880z+ A2W76A and M880z A2W75A. Mobile device must support near-field communications-enabled printing. For a list of supported devices, see hp.com/go/mobileprinting.
[3] HP Flow CM is not available in all regions. Network connection is required to upload and download files. Additional software and licenses may be required.
[4] The HP Universal Print Driver is free and available for download at hp.com/go/upd.
[5] Paper-handling options must be purchased separately.
[6] Wireless direct printing may be added as an option to the HP Color LaserJet Enterprise M880z+ A2W76A and M880z A2W75A. Mobile device may require an app or driver. Wireless performance is dependent on physical environment and distance from the printer. For details, see hp.com/go/wirelessprinting.
[7] Supports OS X® Lion, OS X Mountain Lion, and the following devices running iOS 4.2 or later: iPad® (all models), iPhone® (3GS or later), and iPod touch® (third generation or later). Works with HP's AirPrint-enabled printers and requires the printer be connected to the same network as your OS X or iOS device. Wireless performance is dependent on physical environment and distance from the access point. OS X, iPad, iPhone, and iPod touch are trademarks of Apple® Inc., registered in the United States and other countries. AirPrint™ and the AirPrint logo are trademarks of Apple Inc.
[8] HP Web Jetadmin is free and available for download at hp.com/go/webjetadmin.
[9] HP Imaging and Printing Security Center must be purchased separately.

Technical specifications disclaimers

[1] Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
[2] Exact speed varies depending on the system configuration, software application, driver and document complexity.
[3] Based on standard ITU-T test image at standard resolution and MMR encoding, the HP fax device can transmit at 3 sec/page for V.34 and 6 sec/page for V.17
[4] Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies.
[5] Average colour composite (C/M/Y) and black declared yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see hp.com/go/learnaboutsupplies.

Windows 10

ENERGY STAR

http://www.hp.com/uk

© Copyright 2021 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA April 2021