



| Components                           | Specification   | Components  | Specification  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
|--------------------------------------|---|---|--|-------------------------|---|--------------------------------------|------------------------------------|----------------------|---|----------------------|---|---|-------------------------|---|--|
| Dimensions                           | 1U rack.<br>Height: 43.5 mm (1.71 in), width: 430 mm (16.9 in), depth: 411 mm (16.2 in)   | Base warranty   | 1 or 3-year limited onsite service with 9x5/NBD.   |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Weight                               | Maximum configuration: 16.2 lb (7.36kg)   | Power supply  | One fixed 300 watts power supply, 80 PLUS Gold qualified   |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Processor                            | Supports one of the following Intel processors (code name: Haswell):<br>• Xeon E3-1200 v3: up to 4C/3.7GHz/8MB/84W/1600MHz<br>• Core i3: up to 2C/3.7GHz/4MB/54W/1600MHz<br>• Pentium: up to 2C/3.4GHz/3MB/53W/1600MHz<br>• Celeron: up to 2C/2.9GHz/2MB/53W/1333MHz<br><i>Note: Supports processors with integrated graphics only.</i>   | Graphics  | Integrated Intel HD Graphics in processor  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Chipset                              | Intel C226 Platform Controller Hub (PCH)  | Front ports   | Two USB 2.0  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Memory DIMMs                         | 4 DIMM sockets, 2-channel capable. UDIMM, DDR3  | Rear ports  | Four USB 3.0, two USB 2.0, one serial (9-pin), two ethernet (RJ-45), one RJ-45 (dedicate/share mgmt), one VGA, one DisplayPort. Optional two serial ports via PCIe adapter   |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Memory capacity                      | 32GB (4 x 8GB)  | Noise emissions   | Operating: < 5.2 Bels. Idle: < 5.0 Bels (Mainstream configuration)   |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Memory protection                    | ECC   | Environmental specification   | <p>RoHS-compliant.</p> <table border="1"> <tr> <td>Temperature - operating</td> <td>50 °F to 95 °F (10 °C to 35 °C)</td> </tr> <tr> <td>Temperature - storage (with package)</td> <td>-40 °C to 70 °C</td> </tr> <tr> <td>Altitude - operating</td> <td>Supported Altitude (unpressurized): 0-10000ft (0-3048m)</td> </tr> <tr> <td>Humidity - operating</td> <td>10%~80%, non-condensing</td> </tr> <tr> <td>Humidity - storage (with package)</td> <td>10%~90%, non-condensing</td> </tr> </table> | Temperature - operating | 50 °F to 95 °F (10 °C to 35 °C)         | Temperature - storage (with package) | -40 °C to 70 °C                    | Altitude - operating | Supported Altitude (unpressurized): 0-10000ft (0-3048m)         | Humidity - operating | 10%~80%, non-condensing                           | Humidity - storage (with package)   | 10%~90%, non-condensing |   |  |
| Temperature - operating              | 50 °F to 95 °F (10 °C to 35 °C)   |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Temperature - storage (with package) | -40 °C to 70 °C   |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Altitude - operating                 | Supported Altitude (unpressurized): 0-10000ft (0-3048m)   |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Humidity - operating                 | 10%~80%, non-condensing   |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Humidity - storage (with package)    | 10%~90%, non-condensing   |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| RAID controller                      | RAID 0, 1, 5, 10 with onboard RAID 100, 6Gb/s SATA. RAID 0, 1, 10 with RAID 500, PCIe adapter, 6Gb/s SAS/SATA, optional key for RAID5. RAID 0, 1, 10, 5, 6 with RAID 700, PCIe adapter, 6Gb/s SAS/SATA, optional Intelligent Battery Backup Unit (iBBU08)<br><i>Note: RAID 5, 6, and 10 needs 4 x 2.5" bays.</i>  | <b>Expansion slots and disk bays</b><br>Supports one PCI-Express slot via riser card, half-length, full-height, PCIe 3.0 x8 |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Disk drive bays                      | Up to 2 3.5" disk bays or up to 4 2.5" disk bays. Direct cabled, non-hot swap. Supports optional external USB RDX tape drive  | HDD 1 (under optical)   | 9.5mm optical  | HDD 0                   | HDD 3/HDD2 (under optical)              | 9.5mm optical                        | HDD 1                              | HDD 0                |   |                      |   |   |                         |   |  |
| Supporting disk drives               | <table border="1"> <tr> <td>For 3.5" bay</td> <td>3.5" SATA HDD 7.2K 6Gbs: 500GB/1TB/2TB/3TB/4TB/6TB</td> </tr> <tr> <td></td> <td>3.5" SAS HDD 7.2K 6Gbs: 1TB/2TB/3TB/4TB</td> </tr> <tr> <td>For 2.5" bay</td> <td>2.5" SATA HDD 7.2K 6Gbs: 500GB/1TB</td> </tr> <tr> <td></td> <td>2.5" SAS HDD 10K 6Gbs: 300GB/600GB/900GB. 15K 6Gbs: 146GB/300GB</td> </tr> <tr> <td></td> <td>2.5" SATA SSD 6Gbs: 120GB/240GB/300GB/480GB/600GB</td> </tr> </table> | For 3.5" bay  | 3.5" SATA HDD 7.2K 6Gbs: 500GB/1TB/2TB/3TB/4TB/6TB   |                         | 3.5" SAS HDD 7.2K 6Gbs: 1TB/2TB/3TB/4TB | For 2.5" bay                         | 2.5" SATA HDD 7.2K 6Gbs: 500GB/1TB |                      | 2.5" SAS HDD 10K 6Gbs: 300GB/600GB/900GB. 15K 6Gbs: 146GB/300GB |                      | 2.5" SATA SSD 6Gbs: 120GB/240GB/300GB/480GB/600GB |  |                         |  |  |
| For 3.5" bay                         | 3.5" SATA HDD 7.2K 6Gbs: 500GB/1TB/2TB/3TB/4TB/6TB  |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
|                                      | 3.5" SAS HDD 7.2K 6Gbs: 1TB/2TB/3TB/4TB   |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| For 2.5" bay                         | 2.5" SATA HDD 7.2K 6Gbs: 500GB/1TB  |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
|                                      | 2.5" SAS HDD 10K 6Gbs: 300GB/600GB/900GB. 15K 6Gbs: 146GB/300GB   |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
|                                      | 2.5" SATA SSD 6Gbs: 120GB/240GB/300GB/480GB/600GB   |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Optical drive                        | Up to one 9.5mm optical. DVD-ROM or DVD±RW  |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Network interfaces                   | Two Gigabit Ethernet ports by Intel I210, on riser card.<br>One Gigabit Ethernet port by Intel I217, dedicate/share management  |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Security features                    | Power-on and administrator password. TPM (TCG 1.2-compliant).   |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Systems management                   | Intel Active Management Technology 9 on models with Xeon processor. Remote presence is supported on models with Xeon processors.<br>Supports ThinkServer EasyStartup/EasyUpdate   |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |
| Operating systems supported          | Microsoft Windows Server 2016/2012 R2/2012/2008 R2. Windows Small Business Server 2011. Red Hat Enterprise Linux 6.5. SUSE Linux Enterprise Server 11 SP3.<br><i>Note: VMware requires add-on network adapter.</i>  |   |  |                         |   |                                      |                                    |                      |   |                      |   |   |                         |   |  |

| <b>Model</b>      |  | <b>70F9001D++</b>                         |
|-------------------|--|---|
| Product           |  | ThinkServer RS140                         |
| Region            |  | EMEA                                      |
| Machine Type      |  | 70F9                                      |
| TopSeller         |  | TopSeller                                 |
| Processor         |  | Pentium G3240 2C/3.1GHz/3MB/53W/DDR3-1333 |
| Memory            |  | 1x4GB UDIMM DDR3-1600 ECC                 |
| RAID Controller   |  | RAID 100                                  |
| Disk Bays         |  | 2x3.5" DC                                 |
| Storage           |  | Open                                      |
| Optical           |  | 9.5mm DVD±RW                              |
| Add-on NIC        |  | None                                      |
| Add-on Ports      |  | None                                      |
| System Management |  | AMT9                                      |
| Operating System  |  | None                                      |
| Warranty          |  | 1-year                                    |
| Power Supply      |  | 300W Gold Fixed                           |
| Ann Date (mm/yy)  |  | 09/14                                     |

