

Travel Docking Station for Laptops - VGA - USB 3.0

Product ID: USB3SMDOCKV



This travel docking station lets you turn your laptop into a mobile workstation. It's a travel-friendly solution that helps you connect extra devices to any computer, even when you're on the move.



The essential stow-away laptop accessory

With a lightweight design, this compact laptop docking station tucks neatly into your travel bag. Now, you can avoid the nuisance of carrying multiple adapters, by consolidating three essential connection ports into one convenient device.

Plus, the portable docking station complements your Ultrabook™ nicely, with an aesthetically matching black and silver housing.

Easy to create a versatile mobile workstation

Providing added distance flexibility via an integrated extended-length (21") USB 3.0 host cable, you can easily connect a VGA monitor as a second display.

The versatile docking station also adds Gigabit Ethernet and a USB 3.0 port to your laptop, letting you set up a multi-functional workstation on the run. Plus, you don't have to worry about sacrificing one of your laptop USB ports.



Quick setup with no external power adapter required

To save you time, setup is seamless and hassle-free. The travel dock automatically downloads the latest driver when connected to a Windows® system with an active network connection.

The universal travel docking station for laptops works with almost any USB 3.0 capable system. It's USB-powered too, so you can get up and running without the aggravation of searching for an available power outlet.

The USB3SMDOCKV is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Work from your Ultrabook or laptop easily, while you're on the run or on the road, by adding essential connectivity options
- Use your laptop as a multi-display workstation, through external monitor support
- Connect to your VGA-equipped projector and display multimedia content in boardrooms
- Connect your laptop to a wired Gigabit network in situations where a WiFi connection isn't available, such as in classrooms, offices, and hotels

Features

- VGA video, USB 3.0 hub port, and GbE through a single USB 3.0 cable
- Compact and lightweight for maximum portability — multiple connection options in a travel-friendly casing
- Built-in, extended-length USB 3.0 cable for convenience and distance flexibility
- USB bus-powered - No external power adapter required (optional auxiliary USB power cable included)
- Hassle-free setup - Latest drivers are automatically downloaded in Windows systems when an active network connection is present
- IEEE 802.3, 802.3u and 802.3ab (10BASE-T, 100BASE-TX, and 1000BASE-T) compatible
- SuperSpeed USB 3.0 (5 Gbps) interface, backward compatible with USB 2.0
- Support for resolutions up to 2048x1152 (QWXGA)
- Choose between Mirrored, Extended or Primary display configurations

Hardware	Warranty	3 Years	
	4K Support	No	
	Bus Type	USB 3.0	
	Chipset ID	DisplayLink - DL-3700	
	Displays Supported	1	
	Fast-Charge Port(s)	No	
	Industry Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab USB 3.0 - Hub port supports USB 2.0/1.1 backward-compatibility	
Performance	Auto MDIX	Yes	
	Compatible Networks	10/100/1000 Mbps	
	Full Duplex Support	Yes	
	Maximum Analog Resolutions	2048x1152 (VGA)	
	Maximum Data Transfer Rate	5 Gbps (USB 3.0) 2 Gbps (Ethernet; Full-Duplex)	
	Type and Rate	USB 3.0 - 5 Gbit/s	
	UASP Support	Yes	
Connector(s)	Connector Type(s)	1 - USB Type-A (9 pin) USB 3.0 Male 1 - VGA (15 pin, High Density D-Sub) Female 1 - RJ-45 Female 1 - USB Type-A (9 pin) USB 3.0 Female 1 - USB Micro-B (5 pin) Female	
	Software	OS Compatibility	Windows® XP SP3 (32-bit), Vista, 7, 8, 8.1, 10 Mac OS® 10.6 to 10.12
	Special Notes / Requirements	Note	Micro USB Port (Auxiliary Power Input Port) If necessary the provided USB power cable may be connected to draw additional power from the host computer in order to sufficiently power all outputs simultaneously
		System and Cable Requirements	USB enabled computer system with available USB 3.0 port
	Indicators	LED Indicators	1 - Power 1 - Link/Activity 1 - Link
Power		Power Source	USB-Powered
Environmental		Humidity	5~85% RH

	Operating Temperature	0°C to 50°C (32°F to 122°F)
	Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Physical Characteristics	Cable Length	21 in [534 mm]
	Color	Black & Silver
	Enclosure Type	Plastic
	Product Height	1 in [25 mm]
	Product Length	4.2 in [106 mm]
	Product Weight	4.4 oz [126 g]
	Product Width	2.7 in [68 mm]
Packaging Information	Shipping (Package) Weight	9.2 oz [260 g]
What's in the Box	Included in Package	1 - USB 3.0 Mini Docking Station
		1 - USB Power Cable
		1 - Driver CD
		1 - Instruction Manual

Product appearance and specifications are subject to change without notice.